Solahart
HOT WATER Free FROM THE SUN®
STREAMLINE SERIES

SOLAHART SPLIT SYSTEM MDV SERIES ELECTRIC BOOSTED

MLV and MCSV Systems							
Model	272 MLV	273 MLV	322 MLV	323 MLV	412 MLV	413 MLV	414 MLV
Tank Model	270MDV		320MDV		410MDV		
Collector	L						
No Of Collector	2	3	2	3	2	3	4

Solar Storage Tank				
Tank Model		270MDV	320MDV	410MDV
Storage Capacity	litres	270	320	410
Boost Capacity	litres	140	170	220
Installation		Indoor / Outdoor		
Solar Controller Kit	PN299280	1	1	1
Weight Empty	kg	78	88	109
	lbs	172	194	241
Weight Full	kg	348	414	525
	lbs	767	912	1158
Height	m	1.395	1.640	1.840
	in	54.9	64.6	72.5
Width	m	0.640	0.640	0.690
	in	25.2	25.2	25.2
Depth	m	0.680	0.680	0.730
	in	26.8	26.8	28.7

Collectors General		L
Aperture (heating) area	m^2	1.87
length	mm	1937 / 1996
width	mm	1022 / 1043
height	mm	77 / 82
Capacity	litres	3
Working Pressure	kPa	1000

Electric Boost Spesifications	
Heating Unit Type	Copper sheath immersion element
Supply Voltage	240V 50Hz

Recovery rate @ 240 V and temperature rise of :				
Rating kW	Current Amps	30°C litres/hours	40°C litres/hours	50°C litres/hours
3.6	15	103	77	62

Water Supply				
TPR valve setting	kPa	1000	psi	145
ECV* setting	kPa	850	psi	125
Max. supply pressure				
with ECV	kPa	680	psi	100
without ECV	kPa	800	psi	115
Min. supply pressure	kPa	200	psi	29
Water Connections	cold	Rp 3/4		
	hot	Rp 3/4		
	solar	DN15 compression fittings (solar hot and solar cold inlets to tank Rp 3/4)		

Collector Installation				
Roof area dimensions		2	3	4
Length*	m	2.0	2.0	2.0
	in	78.8	78.8	78.8
Width*	m	2.3	3.4	4.5
	in	90.6	133.9	177.2
Solar kits - L collector				
Collector kit PN 12104297		1	1	1
Collector add on kit PN 12104405		0	1	2

SPLIT SYSTEM
MDV SERIES ELECTRIC BOOSTED
272 | 273 MLV
322 | 323 MLV
412 | 413 | 414 MLV

KEUNTUNGAN

- HEMAT 55% HINGGA 85% AIR ANDA KONSUMSI ENERGI PEMANAS*
- AIR PANAS DI SEGALA KONDISI CUACA
- MEMENUHI SYARAT BERNILAI UNTUK MENDUKUNG LINGKUNGAN SECARA INSENTIF*
- MENGURANGI PENGGUNAAN ENERGI DAPAT MENGHEMAT HINGGA 1,7 HINGGA 3,1 TON CO2 EMISI PER TAHUN*
- RUANG EFISIEN DAN INSTALASI YANG FLEKSIBEL

BAGAIMANA CARA KERJANYA

01 Panel yang dipasang di atap disebut kolektor dipanaskan oleh matahari.

02 Air bersirkulasi melalui kolektor dan kembali dipanaskan ke tangki penyimpanan yang terletak di atap atau di tanah.

03 Air panas tenaga surya siap digunakan kapan saja, menjadikannya salah satu yang paling banyak solusi penyimpanan energi matahari yang efektif.

04 Penguat listrik memastikan Anda akan selalu tersedia air panas