Singly Linked List (Deletion)

```
#include <stdio.h>
#include <stdlib.h>

struct Node
{
    int data;
    struct Node *next;
};

/* Create Linked List */
struct Node* create(struct Node *head)
{
    int n, i, value;
    struct Node *newnode, *temp;

    printf("Enter number of elements: ");
    scanf("%d", &n);

    for(i = 0; i < n; i++)
    {
        newnode = (struct Node*)malloc(sizeof(struct Node));

        printf("Enter data: ");
        scanf("%d", &value);

        newnode->data = value;
        newnode->next = NULL;

        if(head == NULL)
        {
            head = newnode;
            temp = newnode;
        }
        else
        {
            temp->next = newnode;
            temp = newnode;
        }
    }

    return head;
}

/* Delete at Beginning */
struct Node* deleteBegin(struct Node *head)
{
    struct Node *temp;

    if(head == NULL)
    {
        printf("List is empty\n");
        return head;
```

```
    }

    temp = head;
    head = head->next;
    free(temp);

    printf("Node deleted from beginning\n");

    return head;
}

/* Delete at End */
struct Node* deleteEnd(struct Node *head)
{
    struct Node *temp, *prev;

    if(head == NULL)
    {
        printf("List is empty\n");
        return head;
    }

    if(head->next == NULL)
    {
        free(head);
        head = NULL;
        return head;
    }

    temp = head;

    while(temp->next != NULL)
    {
        prev = temp;
        temp = temp->next;
    }

    prev->next = NULL;
    free(temp);

    printf("Node deleted from end\n");

    return head;
}

/* Delete at Specific Position */
struct Node* deletePosition(struct Node *head)
{
    struct Node *temp, *prev;
    int pos, i;

    printf("Enter position to delete: ");
    scanf("%d", &pos);

    temp = head;
```

```
    if(pos == 1)
    {
        head = temp->next;
        free(temp);
        return head;
    }

    for(i = 1; i < pos; i++)
    {
        prev = temp;
        temp = temp->next;
    }

    prev->next = temp->next;
    free(temp);

    printf("Node deleted from position %d\n", pos);

    return head;
}

/* Display Linked List */
void display(struct Node *head)
{
    struct Node *temp;

    if(head == NULL)
    {
        printf("List is empty\n");
        return;
    }

    temp = head;

    printf("Linked List: ");

    while(temp != NULL)
    {
        printf("%d -> ", temp->data);
        temp = temp->next;
    }

    printf("NULL\n");
}

/* Main Function */
int main()
{
    struct Node *head = NULL;
    int choice;

    while(1)
    {
        printf("\n----- MENU -----\n");
        printf("1. Create\n");
        printf("2. Delete at Beginning\n");
```

```
        printf("3. Delete at End\n");
        printf("4. Delete at Position\n");
        printf("5. Display\n");
        printf("6. Exit\n");

        printf("Enter choice: ");
        scanf("%d", &choice);

        switch(choice)
        {
            case 1:
                head = create(head);
                break;

            case 2:
                head = deleteBegin(head);
                break;

            case 3:
                head = deleteEnd(head);
                break;

            case 4:
                head = deletePosition(head);
                break;

            case 5:
                display(head);
                break;

            case 6:
                exit(0);

            default:
                printf("Invalid choice\n");
        }
    }

    return 0;
}
```

Example Menu

```
----- MENU -----
1. Create
2. Delete at Beginning
3. Delete at End
4. Delete at Position
5. Display
6. Exit
```

Deletion Operations Included

Operation	Description
Delete at Beginning	Removes first node
Delete at End	Removes last node
Delete at Position	Removes node at specific index