NT6094 Scientific Journal Writing

Midterm

Wd, 14 Oct 2026 | 9310 | 09:00–11:00 (2 hours)

Note: Open book, internet, discussion
Platform: Edunex, GitHub

Refer to https://github.com/dudung/26h67/issues/62 for the instructions.

Name	Pradigta Hisyam Ramadhan
Student ID	28726019
Midterm date	Wednesday, 14 October 2026
Seed / datasets	28726019 → g40s1, g42s3, g44s3, g46s4, g48s2, g50s3, g52s3, g54s4, g56s3, g58s1

Composition dependence of peak load and stiffness extracted from ten compression-test curves

Pradigta Hisyam Ramadhan[1,*]

[1] Nanotechnology Study Program, The Graduate School of Multidisciplinary Science and Technology, Institut Teknologi Bandung, Jl. Ganesha 10, Bandung 40132, Indonesia

[*] Corresponding author: 28726019@mahasiswa.itb.ac.id

Format Course answer sheet (06_midterm_nt6094) with content structured after the Journal of Materials Science submission guidelines (Springer Nature)

Acknowledgements

The author thanks Sparisoma Viridi for providing the datasets and the endap web applications used in this work.

Abstract

Purpose Ten load–displacement-type curves from the endap 2026-1 midterm collection, selected with the seed 28726019, were analysed to find how their main features depend on the composition parameter *g*.

Methods Each dataset was processed in the web application published with it. The peak (maximum *y*), the last point (largest *x*) and a least-squares line $y = mx + b$ over the linear region were extracted. One rule defined the linear region for all datasets: points on the rising branch between 25 % and 75 % of the peak *y*. All values were reproduced with an independent Python script.

Results All fits gave $R^2 \geq 0.987$, and application and script agreed to all printed digits. The peak *y* fell from 7069 at $g = 44$ to 465 at $g = 58$ and the slope *m* from 8083 at $g = 40$ to 469 at $g = 58$, about 25–28 % per increase of *g* by 2 (Pearson $r \approx -0.89$). The *x* position of the peak and the intercept *b* were dominated by an initial seating (toe) region of variable length.

Conclusion The datasets are best read as compression tests in which *x* is displacement, *y* is load, *m* is specimen stiffness and *g* is the percentage of one constituent in the mixture; more of this constituent gives weaker and softer specimens.

Keywords Compression test · Load–displacement curve · Linear regression · Stiffness · Composition dependence · Feature extraction

1 Introduction

A compression test loads a specimen between two plates and records the load against the displacement of the plates. The resulting curve normally starts with a non-linear toe while the plates seat on the specimen, continues with a linear part whose slope gives the stiffness, and ends at a maximum load where the specimen fails [1, 2]. Reading these features from many curves is a routine step when a material is optimised by changing its composition.

The 2026-1 midterm of the course NT6094 gives every student ten datasets chosen by the student ID used as a seed [3]. A dataset name such as g82s9 encodes $g = 82$ and $s = 9$, and each dataset is published as its own post with an application that plots the data, lets the user mark four points by their id and fits a straight line [4]. The datasets come from a collection called *p2mi-wd data* [5]. Its pre-processing note lists ten compositions g40 to g58 with three constituents *g*, e and h that always add up to $t = 12.0$, with $h = e/2$ and $g = (\text{code}/100) \times 12$ [6]. The same note reports 40 curves in ten clusters, i.e. four specimens per composition. The application itself was developed in a post titled *compression-test viz* [7].

This work extracts the peak, the last point and the linear-region slope m and intercept b from the ten curves assigned to seed 28726019, reports them as functions of g, and discusses what the variables x, y and g most likely represent.

2 Materials and methods

2.1 Datasets

The midterm page was opened and the seed 28726019 was selected; the application then lists the dataset names and the links to their posts (Fig. 1). Each link was opened in a new browser tab and the post title was checked against the dataset name. All ten titles matched (Table 1). In every post the raw data are two columns; the application uses the second column as the independent variable x and the first column as the dependent variable y.



Fig. 1 Midterm application with seed 28726019 selected, listing the ten dataset names (data) and the posts that hold them (link)

Table 1 Datasets assigned to seed 28726019

Dataset	g	s	Link	Post title	Rows	Step[a]	Points[b]
g40s1	40	1	26j34	g40s1-data	4968	25	198
g42s3	42	3	26j40	g42s3-data	5759	10	575
g44s3	44	3	26j44	g44s3 data	9094	20	454
g46s4	46	4	26j49	g46s4-data	2214	10	221
g48s2	48	2	26j51	g48s2 data	5781	20	289
g50s3	50	3	26j56	g50s3-data	5782	20	289
g52s3	52	3	26j60	g52s3-data	2625	10	262
g54s4	54	4	26j65	g54s4-data	5015	20	250
g56s3	56	3	26j68	g56s3-data	4710	20	235
g58s1	58	1	26j70	g58s1-data	3997	10	399

[a] Sampling step of the application: every n-th raw row is kept

[b] Number of sampled points that can be addressed by an id

2.2 Feature-extraction application

The application has a chart, a console listing every sampled point with its id (0000, 0001, …) and its original row, and an input/output panel with four buttons [4]. **load** writes default values for four keys: PEAK-ID (point of maximum *y*), LAST-ID (point of largest *x*), LINI-ID and LINF-ID (first and last point of the linear regression). After the ids are edited, **read** marks the four points on the chart so that the choice can be checked visually, and **calc** fits a straight line to all points from LINI-ID to LINF-ID and prints *m*, *b* and R^2. **clear** resets the panel. The sampling step differs between posts (Table 1), so the same physical point has a different id on different pages.

2.3 Linear model

The linear part of each curve is described by [7, 8]

$$y = mx + b \tag{1}$$

where the least-squares slope and intercept over the *n* selected points are

$$m = \frac{n\sum xy - \sum x \sum y}{n\sum x^2 - (\sum x)^2} \tag{2}$$

$$b = \frac{\sum y - m\sum x}{n} \tag{3}$$

and the coefficient of determination is [9]

$$R^2 = \frac{(n\sum xy - \sum x \sum y)^2}{[n\sum x^2 - (\sum x)^2][n\sum y^2 - (\sum y)^2]} \tag{4}$$

R^2 close to 1 means that the selected points lie close to a straight line. The intercept of the fitted line with the *x* axis,

$$x_0 = -\frac{b}{m} \tag{5}$$

marks where the linear loading would start without the toe and is used to compare deformation between tests.

2.4 Selection of points

To make the ten results comparable, one rule replaced the choice by eye. PEAK-ID is the id with the largest *y*; LAST-ID is the last id; LINI-ID is the first id on the rising branch with $y \geq 0.25\, y_{peak}$; LINF-ID is the last id before the peak with $y \leq 0.75\, y_{peak}$. The band avoids the curved toe and the rounding near the maximum. Bands of 10–90 %, 20–80 % and 30–70 % changed *m* by only a few per cent and did not change the trend with *g*. The ids (Table 2) were entered in each application and checked after **read**; screenshots of all ten applications after **calc** are given in Online Resource 1.

Table 2 Point ids entered in the application for each dataset

g	Dataset	PEAK-ID	LAST-ID	LINI-ID	LINF-ID	n
40	g40s1	0191	0197	0157	0177	21
42	g42s3	0564	0574	0362	0469	108
44	g44s3	0442	0453	0321	0395	75
46	g46s4	0210	0220	0115	0168	54
48	g48s2	0284	0288	0173	0225	53
50	g50s3	0283	0288	0164	0219	56
52	g52s3	0254	0261	0132	0179	48
54	g54s4	0247	0249	0089	0151	63
56	g56s3	0232	0234	0107	0172	66
58	g58s1	0392	0398	0229	0304	76

n: number of points used in the regression

2.5 Verification and workflow

The raw data of all ten posts were processed again with a Python script that copies the sampling of the application and Eqs. (2)–(4). The values of m, b and R^2 from the application and from the script agree to all printed digits for every dataset. The whole workflow is summarised in Fig. 2; it is drawn in Mermaid with on-page connectors [10], and its source code is listed in Online Resource 1.




Fig. 2 Workflow from the student ID (seed) to the manuscript. Green circles are on-page connectors

2.6 Use of generative AI

A large language model tool, Claude Code with the model Claude Opus 5.5 (Anthropic) [11], was used on 14 October 2026 to read the assignment, download the dataset posts, write the scripts that reproduce the application, propose the point-selection rule, operate the applications in the browser for the screenshots, draw the figures and the flowchart, draft the text, and prepare the public repository with the exported chat log. The author selected the datasets with the author's own student ID, checked the application output against the script output, and reviewed the interpretation, and takes full responsibility for the content. The tool is not an author.

3 Results and discussion

3.1 Shape of the curves

All ten curves have the same three parts (Fig. 3 and Fig. 4): a flat toe in which y stays close to zero while x increases, a long and almost straight rise, and a rounded top that ends at the maximum, after which y drops by 1.7–12 % until the last point (largest for g44s3, 12 %). The length of the toe differs strongly between tests (x_0 from 0.59 to 3.82) and does not follow g, which is typical of the seating stage of a compression test [2]. g44s3 shows a sudden fall of y at x ≈ 3.65 before the main rise, which looks like slipping or re-seating of the specimen. The curves with $g \geq 48$ carry a regular small ripple; this is why g52s3 and g56s3 have the lowest R^2 (0.988 and 0.990), although the fitted lines still follow the data well.




Fig. 3 Raw curves $y(x)$ of the ten datasets; darker lines belong to larger g and each label marks the peak




Fig. 4 Sampled points of each dataset (a–j) with the points used in the regression, the fitted line $y = mx + b$, the peak and the last point

3.2 Extracted features as functions of g

Table 3 lists peak, last point, m, b and R^2 for the ten datasets, and Fig. 5 plots them against g.

Table 3 Peak, last point and linear-regression parameters as functions of g

g	Dataset	x_{peak}	y_{peak}	x_{last}	y_{last}	m	b	R^2
40	g40s1	3.0939	4856.29	3.1987	4667.18	8083.36	-19672.34	0.99758
42	g42s3	3.6408	6285.57	3.7042	5822.04	4829.68	-9966.62	0.99915
44	g44s3	5.7674	7069.42	5.9247	6230.83	3878.35	-14797.35	0.99898
46	g46s4	1.3335	3736.28	1.3929	3657.83	5716.58	-3369.49	0.99872
48	g48s2	3.7473	2219.42	3.7925	2142.71	1674.68	-3306.83	0.99723
50	g50s3	3.7483	1559.65	3.8085	1513.17	1064.25	-1922.26	0.99689
52	g52s3	1.6656	1430.84	1.7042	1362.35	2162.33	-1506.34	0.98768
54	g54s4	3.2653	1363.56	3.2908	1339.77	807.09	-582.84	0.99819
56	g56s3	3.0735	632.77	3.0962	613.57	380.54	-366.57	0.99005
58	g58s1	2.6098	464.84	2.6487	450.64	469.22	-607.29	0.99832

Values are those printed by the application; units are not given in the source (probably mm for x and N for y, see Sect. 3.3)




Fig. 5 Extracted features versus *g*: a *y* of the peak and of the last point, *b x* of the peak and of the last point, c slope *m*, d intercept *b*

Peak and last point. y_{peak} is largest at $g = 44$ (7069) and falls to 465 at $g = 58$ (Fig. 5a). A log-linear fit gives a decrease of about 25 % per increase of *g* by 2, and the Pearson correlation between *g* and y_{peak} is −0.89. The last point follows the peak closely, so both describe the same property: the largest load the specimen can carry.

Slope. *m* falls from 8083 at $g = 40$ to about 400 at $g = 56$–58 (Fig. 5c), about 28 % per increase of *g* by 2 ($r = -0.89$). Specimens with more *g* are therefore both weaker and softer. g46s4 and g52s3

lie above the smooth trend; both have the shortest curves and short toes. With one specimen per composition, scatter between specimens cannot be separated from the effect of *g*.

Intercept and x positions. *b* is negative for all datasets and approaches zero as *g* increases (Fig. 5d, $r = +0.85$). Because $b = -m\,x_0$, its trend mostly mirrors the fall of *m* and the random toe length. For the same reason x_{peak} and x_{last} jump between 1.3 and 5.8 without a trend (Fig. 5b). The deformation after the toe, $x_{peak} - x_0$, is 0.66–2.54 and tends to be larger at high *g*, which agrees with a softer and more ductile material.

3.3 Meaning of x, y and g

- *x* is most likely the displacement of the loading plate (crosshead), probably in mm. It increases steadily, it is the independent variable, it contains a seating toe, and its range (0–6) fits the shortening of a small specimen.
- *y* is most likely the compressive load, probably in N. It rises with *x*, reaches a maximum and drops when the specimen starts to fail, so y_{peak} is the failure load and *m* = dy/dx the specimen stiffness in N mm^{-1}. With the specimen geometry they would give the compressive strength and modulus [1].
- *g* is the share of one constituent in the mixture in per cent: $g = (\text{code}/100) \times 12$ for a fixed total of 12.0 (e.g. grams), with the other two constituents in a 2 : 1 ratio [6]. Because more *g* lowers both strength and stiffness, this constituent is probably a weaker or softer phase; the material is not stated in the sources.
- *s* is the specimen (replicate) number within one composition, from 1 to 4.

These meanings are interpretations of the data and of the source notes, not confirmed facts.

3.4 Limitations

Only one specimen per composition was analysed, so scatter between specimens is unknown. The application works on sampled points, so the sampled peak can be slightly below the raw peak (g42s3: 6287 raw versus 6286 sampled). The 25–75 % band is a convention. Without specimen dimensions *m* is a stiffness, not a modulus.

4 Conclusions

Ten datasets assigned to seed 28726019 were processed in the endap application with one rule for the linear region, and an independent script reproduced every value. All curves are compression loading curves with a toe, a linear rise ($R^2 \geq 0.987$), a maximum and a small drop. Peak load and stiffness *m* both decrease strongly with *g* ($r \approx -0.89$; about 25–28 % per increase of *g* by 2), so more of constituent *g* gives weaker and softer specimens. The *x* positions and *b* are

dominated by the seating toe and should be corrected by x_0 before deformation is compared. Repeated specimens and the specimen geometry are needed to turn these features into material properties with uncertainties.

Statements and Declarations

Funding No funding was received to assist with the preparation of this manuscript.

Competing interests The author has no relevant financial or non-financial interests to disclose.

Author contributions P.H. Ramadhan processed and analysed the data and wrote the manuscript.

Data availability The datasets analysed are publicly available on endap [4]. The extracted values, the scripts, the figures and the AI chat log are available at https://github.com/pradigtahr/nt6094-uts-2026-1; the application screenshots are given in Online Resource 1.

Ethics approval Not applicable.

Use of generative AI A large language model tool was used as described in Sect. 2.6. It is not an author, and the author is accountable for the content.

References

1. W.D. Callister Jr., D.G. Rethwisch, *Materials Science and Engineering: An Introduction*, 10th edn. (Wiley, Hoboken, 2018)
2. ASTM International, ASTM D695-15: Standard Test Method for Compressive Properties of Rigid Plastics (ASTM International, West Conshohocken, 2015). https://doi.org/10.1520/D0695-15
3. S. Viridi, 2026-1 midterm-datasets. endap (2026). https://endap.github.io/26j76/. Accessed 14 Oct 2026
4. S. Viridi, g40s1-data, g42s3-data, g44s3 data, g46s4-data, g48s2 data, g50s3-data, g52s3-data, g54s4-data, g56s3-data, g58s1-data. endap (2026). https://endap.github.io/26j34/ (also 26j40, 26j44, 26j49, 26j51, 26j56, 26j60, 26j65, 26j68, 26j70). Accessed 14 Oct 2026
5. S. Viridi, p2mi-wd data. endap (2026). https://endap.github.io/26j27/. Accessed 14 Oct 2026
6. S. Viridi, pre-proc p2mi-wd yessi-data. endap (2026). https://endap.github.io/26j26/. Accessed 14 Oct 2026
7. S. Viridi, compression-test viz. endap (2026). https://endap.github.io/26j32/. Accessed 14 Oct 2026
8. L. Treible, M. Szulczewski, How do I calculate a linear regression? Finding relationships between variables in the Earth sciences. Math You Need – Majors (2023). https://serc.carleton.edu/277935. Accessed 14 Oct 2026
9. M. Gupta, R squared | coefficient of determination. GeeksforGeeks (2026). https://www.geeksforgeeks.org/maths/r-squared/. Accessed 14 Oct 2026
10. S. Viridi, mermaid diagram hands-on. endap (2026). https://endap.github.io/26i75/. Accessed 14 Oct 2026

11. Anthropic, Claude Code (model Claude Opus 5.5), chat log “NT6094 midterm (UTS) 2026-1: processing the datasets of seed 28726019” (2026). https://github.com/pradigtahr/nt6094-uts-2026-1/blob/main/ai-chat/claude-code-chat-log.md. Accessed 14 Oct 2026

Online Resource 1

Supplementary material for “Composition dependence of peak load and stiffness extracted from ten compression-test curves”, P.H. Ramadhan (NIM 28726019). Figs. S1–S10 show the application of each dataset after **calc**, with the post title (dataset name), the marked points, the entered ids and the printed *m*, *b* and R^2. Listing S1 gives the Mermaid source of the flowchart.



Fig. S1 g40s1 (26j34): PEAK-ID 0191, LAST-ID 0197, LINI-ID 0157, LINF-ID 0177



Fig. S2 g42s3 (26j40): PEAK-ID 0564, LAST-ID 0574, LINI-ID 0362, LINF-ID 0469



Fig. S3 g44s3 (26j44): PEAK-ID 0442, LAST-ID 0453, LINI-ID 0321, LINF-ID 0395



Fig. S4 g46s4 (26j49): PEAK-ID 0210, LAST-ID 0220, LINI-ID 0115, LINF-ID 0168



Fig. S5 g48s2 (26j51): PEAK-ID 0284, LAST-ID 0288, LINI-ID 0173, LINF-ID 0225



Fig. S6 g50s3 (26j56): PEAK-ID 0283, LAST-ID 0288, LINI-ID 0164, LINF-ID 0219



Fig. S7 g52s3 (26j60): PEAK-ID 0254, LAST-ID 0261, LINI-ID 0132, LINF-ID 0179



Fig. S8 g54s4 (26j65): PEAK-ID 0247, LAST-ID 0249, LINI-ID 0089, LINF-ID 0151



Fig. S9 g56s3 (26j68): PEAK-ID 0232, LAST-ID 0234, LINI-ID 0107, LINF-ID 0172



Fig. S10 g58s1 (26j70): PEAK-ID 0392, LAST-ID 0398, LINI-ID 0229, LINF-ID 0304

Listing S1 Mermaid source of Fig. 2

```
flowchart
  %% sg3
  subgraph " "
    direction TB
    o2b --> P7 --> P8 --> O1 --> P9 --> E
  end

  %% sg2
  subgraph " "
    direction TB
    o1b --> P4 --> P5 --> C1
    C1 --"N"--> P4
    C1 --"Y"--> P6 --> C2
    C2 --"N"--> P10 --> P4
    C2 --"Y"--> o2a
  end

  %% sg1
  subgraph " "
    direction TB
    B --> I1 --> P1 --> P2 --> P3 --> o1a
  end

  %% elements
  B(["Begin"])
  I1[/"Student ID 28726019 as seed"/]
  P1["Open 26j76, select seed, screenshot data names and links"]
  P2["Open 10 links in new tabs, confirm post titles g40s1 ... g58s1"]
  P3["Set i = 1 (first dataset)"]
  P4["Pick PEAK-ID = max y, LAST-ID = last x, LINI/LINF = 25% and 75% of y_peak"]
  P5["Click load, edit ids, click read"]
  C1{"Points correct in chart?"}
  P6["Click calc, record peak, last, m, b, R²"]
  C2{"i = 10?"}
  P7["Tabulate peak, last, m, b vs g"]
  P8["Plot xy-scatter vs g"]
  O1[/"Table and charts"/]
  P9["Interpret x, y, g and write answer sheet, save as PDF"]
  E(["End"])
```

```
P10["i = i + 1 (next dataset)"]

%% connectors
o1a(("1")):::conn
o1b(("1")):::conn
o2a(("2")):::conn
o2b(("2")):::conn

%% classes
classDef conn fill:#484, stroke:#040, color:#fff
```