LAB 1

Title: Introduction to DDL and DML statements in SQL

Objective:

- To be familiar with concept of DDL and DML
- To use different DDL and DML statements to perform various operations on database

Theory:

SQL (Structured Query Language)

- SQL stands for Structured Query Language
- SQL let us to access and manipulate databases
- SQL became a standard of the American National Standards Institute (ANSI) in 1986, and of the International Organization for Standardization (ISO) in 1987

DDL (Data Definition Language)

- ✓ DDL or Data Definition Language actually consists of the SQL commands that can be used to define the database schema.
- ✓ It simply deals with descriptions of the database schema and is used to create and modify the structure of database objects in the database.
- ✓ DDL is a set of SQL commands used to create, modify, and delete database structures but not data.

Examples of DDL commands:

CREATE: This command is used to create the database or its objects (like table, views, store procedure and triggers).

DROP: This command is used to delete objects from the database.

ALTER: This is used to alter the structure of the database.

TRUNCATE: This is used to remove all records from a table, including all spaces allocated for the records are removed.

DML (Data Manipulation Language)

The SQL commands that deals with the manipulation of data present in the database belong to DML.

Examples of DML:

INSERT – is used to insert data into a table.

UPDATE – is used to update existing data within a table.

DELETE – is used to delete records from a database table

SELECT- It is used to retrieve data from the database table.

Now let us discuss a detailed description of DDL and DML language and their usage with their syntax.

DDL

CREATE

To Create Database

```
✓ CREATE DATABASE DatabaseName;

      eg: CREATE DATABASE employeedb;
      To Create table
      CREATE TABLE table_name (
           column1 datatype,
           column2 datatype,
           column3 datatype,
           columnn datatype
      );
Example
CREATE TABLE employee_info
(eid int,
name varchar(50),
address varchar(50),
position varchar(50),
salary decimal(10,2)
);
DROP
To Remove Database
DROP DATABASE DatabaseName;
Eg. DROP DATABASE employeedb;
To Remove table
DROP TABLE table_name;
Eg; DROP TABLE employee_info;
TRUNCATE
To remove all rows from table
TRUNCATE TABLE table_name;
Eg. TRUNCATE TABLE employee_info;
```

ALTER

- The ALTER TABLE statement is used to add, delete, or modify columns in an existing table.
- It is also used to add and drop various constraints on an existing table.

To add Column in table

```
ALTER TABLE table_name
ADD column_name datatype;
```

Eg.

ALTER TABLE employee_info

ADD department varchar(30);

To remove column from table

ALTER TABLE table_name
DROP COLUMN column name;

Eg. ALTER TABLE employee_info
DROP COLUMN address;

To rename column of table

```
ALTER TABLE table_name CHANGE COLUMN old_name new_name datatype;
```

Eg. ALTER TABLE employee_info
CHANGE COLUMN address location varchar(30);

(Note: This syntax is for MariaDB and any vary in different DBMS)

To modify data type of any column

```
ALTER TABLE table_name

MODIFY column_name datatype;
```

Eg.

ALTER TABLE employee_info

MODIFY location char(20);

DML

INSERT

```
To Insert data into table
Method-I
INSERT INTO table_name (column1, column2, column3, ...)
VALUES (value1, value2, value3, ...);
Eg.
INSERT INTO employee_info
VALUES(1,'Hari','kathmandu','manager',55625);
Method-II
INSERT INTO table_name
VALUES (value1, value2, value3, ...);
       INSERT INTO employee info(eid,name,address)
Eg.
      VALUES(2,'ram','pokhara');
UPDATE
To update existing data within a table.
UPDATE table_name
SET column1 = value1, column2 = value2, ...
WHERE condition;
Eg.
UPDATE employee_info
SET salary=75000
WHERE position='manager';
DELETE
To delete records from a table
DELETE FROM table_name WHERE condition;
DELETE FROM employee info where address='chitwan';
```

SELECT

To retrieve data from the database table.

```
SELECT column1, column2, ...
FROM table_name
WHERE condition;
```

Eg.

SELECT position, salary from employee_info

where salary >30000;

Some useful commands

✓ To Select Database

USE DatabaseName;

Eq. use employee db;

✓ To Show Databases

show databases;

√ To see which database is selected

select database();

√ To see tables in a selected database

show tables;

Problem:

- 1. Create a database named eemcDB
- 2. Create table named student_info database named eemcDB with following columns and datatypes

Sid	Name	contact	Faculty	College_name
Int	Varchar(50)	char(10)	Varchar(50)	Varchar(50)

- 3. Now add column named address with datatype varchar(30)
- 4. Delete the column named contact
- 5. Rename column named address as location
- 6. Change data type of faculty to char(20)

- 7. Insert minimum 10 information of student into table named student info
 - ✓ Insert 1 information of student whose faculty is not known
 - ✓ Insert 1 information of student whose college name is not known
- 8. Update the information of student whose sid=3 by setting faculty ='civil'
- 9. Update the information of student whose name is 'ram' and location is 'kathmandu' by setting faculty='computer'
- 10. Delete the information of student whose faculty is civil and location is pokhara
- 11. Display all the information of student from table named student info
- 12. Display name and faculty of student whose location is Kathmandu
- 13. Display name and faculty of student whose location is pokhara and college_name is eemc
- 14.Delete all rows from table
- 15. Delete the table named student info
- 16.Delete the database named eemcDB;

Note: Students are suggested insert information of student into table in such a way that above operations can be performed.

Discussion: (This portion is left for student)

Conclusion: (This portion is left for student)

*******THE END******