



JavaScript Beginner Practice Questions (Phase -2) Sheet - 3

JavaScript

1. `forEach()`

Intermediate Question

You are given an array of prices.

Print each price with `"₹"` before it.

```
let prices = [100, 250, 399, 499];
```

Hint

`forEach()` runs once for every element.

You don't return anything here.

Use `console.log()` inside it.

Hard Question

You are given an array of students.

```
let students = [
  { name: "Anubhav", marks: 85 },
  { name: "Rahul", marks: 42 },
  { name: "Aman", marks: 90 },
];
```

Print:

`"Pass"` if marks are greater than 50

`"Fail"` otherwise

Output format:

```
Anubhav - Pass
Rahul - Fail
```

Hint

Loop through objects using `forEach()`

Use condition checking inside loop.

2. `map()`

Intermediate Question

Convert all names into uppercase.

```
let names = ["anubhav", "rahul", "aman"];
```

Expected Output:

```
["ANUBHAV", "RAHUL", "AMAN"]
```

Hint

`map()` creates a new array.
Use `.toUpperCase()`.

Hard Question

You are given products.

```
let products = [  
  { name: "Laptop", price: 50000 },  
  { name: "Phone", price: 20000 },  
];
```

Create a new array where:

Every product has a new property `discountPrice`
Discount is 10%

Expected:

```
[  
  { name: "Laptop", price: 50000, discountPrice: 45000 }  
]
```

Hint

Return a new object from `map()`
Formula:

```
price - (price * 10 / 100)
```

3. filter()

Intermediate Question

Filter all even numbers.

```
let nums = [1,2,3,4,5,6,7,8];
```

Expected Output:

```
[2,4,6,8]
```

Hint

`filter()` keeps elements when condition is `true`.

Hard Question

You are given users.

```
let users = [  
  { name: "Anubhav", active: true },  
  { name: "Rahul", active: false },
```

```
{ name: "Aman", active: true },  
];
```

Return only active users.

Hint

Check `active === true`
Return condition directly.

4. `reduce()`

Intermediate Question

Find total sum of array.

```
let nums = [10,20,30,40];
```

Expected Output:

```
100
```

Hint

`reduce()` needs:
accumulator
current value

Hard Question

Count frequency of elements.

```
let fruits = ["apple", "banana", "apple", "orange", "banana", "apple"];
```

Expected Output:

```
{  
  apple: 3,  
  banana: 2,  
  orange: 1  
}
```

Hint

Create an empty object `{}` as initial value.
Increase count if already exists.

5. `find()`

Intermediate Question

Find first number greater than 50.

```
let nums = [20, 35, 60, 80];
```

Expected Output:

60

Hint

`find()` returns first matching element.

Hard Question

Find a user with username `"admin"`.

```
let users = [
  { username: "rahul" },
  { username: "admin" },
  { username: "aman" }
];
```

Hint

Compare inside callback:

```
user.username === "admin"
```

6. `findIndex()`

Intermediate Question

Find index of number `90`.

```
let nums = [10, 40, 90, 50];
```

Hint

`findIndex()` returns index number.

Hard Question

Find index of first failed student.

```
let students = [
  { name: "A", marks: 90 },
  { name: "B", marks: 30 },
  { name: "C", marks: 70 },
];
```

Condition:

Failed if marks < 40

Hint

Use condition directly inside callback.

7. `some()`

Intermediate Question

Check if any number is negative.

```
let nums = [10, 20, -5, 40];
```

Expected Output:

```
true
```

Hint

`some()` returns true if at least one condition matches.

Hard Question

Check if any product is out of stock.

```
let products = [  
  { name: "Laptop", stock: 5 },  
  { name: "Phone", stock: 0 },  
];
```

Hint

Check:

```
stock === 0
```

8. `every()`

Intermediate Question

Check if all numbers are positive.

```
let nums = [10, 20, 30, 40];
```

Expected Output:

```
true
```

Hint

`every()` checks all elements.

Hard Question

Check if all students passed.

```
let students = [  
  { name: "A", marks: 80 },  
  { name: "B", marks: 45 },  
  { name: "C", marks: 60 },  
];
```

Passing marks:

```
40
```

Hint

Return condition:

```
marks >= 40
```