This is my se lab 4.I want you to analyse the files, This is my github link(https://github.com/SETAPESU26/63_anvil_dodge).help me solve the bugs in the game and also identify the bugs in the codes of every file in order to understand the working of the game and also help me fix it.


# SE Lab 4 — Anvil Dodge: Complete Bug Analysis and Fixing Guide

I've located your GitHub repository: 63_anvil_dodge — Anvil Dodge Repair Lab. The project is a Python game built using Pygame, and its README explicitly identifies a boundary bug and three additional features to implement.

SETAPESU26/63_anvil_dodge · GitHub

We'll approach this as a proper Software Engineering lab: understand the game, identify bugs file by file, fix the code, test the changes, and prepare evidence for submission.

## 1. How the game is supposed to work



The game loop follows this sequence:

1. Initialize the game

Create the display, player, anvil list and timer.

2. Read keyboard input

Move left or right using arrow keys or A/D.

3. Spawn and move anvils

Create hazards at random horizontal positions and move them downward.

4. Check collisions and boundaries

Detect impacts and prevent the player from leaving the screen.

5. Update the screen

Draw the player, hazards, timer and effects.

6. Handle game over and restart

Stop survival-time tracking when hit; press R to start a new run.

The key Software Engineering concept is separation of responsibilities: the player handles movement, anvils handle falling hazards, the game engine coordinates the game, and `main.py` starts the application.

# 2. File-by-file bug analysis

I inspected the repository's `main.py`, `game/player.py`, `game/anvil.py`, `game/game_engine.py`, and `README.md`. The following findings are based on the code currently visible in your repository.


GitHub
+4

1. `main.py`

No confirmed core bug

Purpose: initializes Pygame, creates the display and game engine, processes events, updates the game and redraws each frame.

The basic game loop is correct. It calls `engine.handle_event(event)`, `engine.update()` and `engine.render(screen)` in the expected sequence.

Potential improvement: put `pygame.quit()` in a `try/finally` block so Pygame can shut down cleanly if an unexpected exception occurs.

2. `game/player.py`

Confirmed bug

Purpose: stores the player's position, controls movement and draws the character.

- `move_left()` subtracts speed from `self.x` without checking the left edge.
- `move_right()` adds speed without checking the right edge.
- `update()` contains only `pass`, so the intended boundary correction is missing.

Result: the player can move off-screen and exploit the game to survive indefinitely.

3. `game/anvil.py`

Feature missing

Purpose: generates anvils at random horizontal positions, moves them downward and draws them.

- `self.speed = random.uniform(4.5, 7.0)` correctly gives each anvil a randomized speed.
- `render()` always uses fixed grey colors, so speed is not communicated visually.
- `is_off_screen()` supports cleanup, but the engine does not create an impact effect before removing an anvil.

Result: fast hazards are not visually distinguishable, and ground impacts have no feedback.

4. `game/game_engine.py`

Features missing; edge case to fix

Purpose: manages movement, spawning, collisions, survival time, restarting and rendering.

- `spawn_delay = 700` remains constant, so difficulty never increases.
- There is no particle or impact-effect system.
- The engine relies on the player's missing boundary logic.
- After a collision, the current loop continues processing the remaining anvils for that frame. A collision should end the current update immediately.

What already works: basic spawning, rectangular collision detection, survival-time calculation, game-over display and restart logic.

5. `README.md`

No code bug

It documents the expected behavior and four lab tasks. It is useful as a requirements checklist, not part of the executable game.

Improvement: update the README after fixing the game with the implemented features, run instructions, test results and before/after evidence.

# 3. Fix 1 — Prevent the player from leaving the screen

Open `game/player.py`. Replace the empty `update()` method with:

```
def update(self):    # Keep the player inside the horizontal screen
boundaries.    self.x = max(0, min(self.x, self.screen_width - self.width))
```

The existing movement methods can remain unchanged because `update()` clamps the position every frame.

### How this works

For a 700-pixel-wide window and a 44-pixel-wide player:

- Leftmost valid position: `x = 0`
- Rightmost valid position: `x = 700 - 44 = 656`

The expression `min(self.x, self.screen_width - self.width)` prevents the player from exceeding 656. The outer `max(0, ...)` prevents negative positions.

Important: `GameEngine.update()` already calls `self.player.update()`, so you do not need to change that call.

# 4. Fix 2 — Make the game progressively harder

In `game/game_engine.py`, inside `update()`, find the survival-time calculation:

```
self.survival_time = (pygame.time.get_ticks() - self.start_ticks) // 1000
```

Immediately after it, add:

```
# Reduce the anvil spawn interval as survival time
increases.self.spawn_delay = max(    200,    700 - self.survival_time * 20)
```

This gives you the following difficulty progression:

| Survival time | Spawn interval |
|---|---|
| 0 seconds | 700 ms |
| 5 seconds | 600 ms |
| 10 seconds | 500 ms |
| 20 seconds | 300 ms |
| 25 seconds and above | 200 ms |

The `max(200, ...)` acts as a lower limit. Without it, the interval could eventually become zero or negative, causing excessive spawning.

This approach reuses your existing spawn timer, so no new timer is needed.

# 5. Fix 3 — Give fast anvils warning colors

Open `game/anvil.py`. Replace its existing `render()` method with this version:

```
def render(self, surface):    # Use the falling speed to select a warning color.    if self.speed >= 6.5:        top_color = (255, 70, 50)       # Red: very fast        base_color = (170, 40, 40)    elif self.speed >= 5.5: top_color = (255, 155, 40)      # Orange: fast        base_color = (180, 95, 30)    else:        top_color = (120, 120, 130)     # Grey: normal base_color = (80, 80, 90)    top_rect = pygame.Rect(        int(self.x) + 4, int(self.y),        self.width - 8, 14    )    pygame.draw.rect( surface, top_color, top_rect, border_radius=2    )    base_rect = pygame.Rect(        int(self.x), int(self.y) + 14,        self.width, 18 )    pygame.draw.rect(        surface, base_color, base_rect, border_radius=3    )    pygame.draw.rect(        surface, (200, 200, 210), base_rect, width=1, border_radius=3    )
```

### Why this works

Your constructor already assigns a random falling speed between 4.5 and 7.0. We use that existing value to choose the color.

- Grey: ordinary falling anvil.
- Orange: faster anvil that requires more attention.
- Red: very fast anvil and a stronger visual warning.

No new speed variable or randomization logic is needed. The color is calculated each time the anvil is drawn.

# 6. Fix 4 — Add ground-impact particles

We'll add a small dust effect when an anvil reaches the ground. This is managed by `game_engine.py`, because the engine knows when an anvil should be removed.

### Step A: Add the import

At the top of `game/game_engine.py`, add:

```
import random
```

Keep the existing Pygame, Player and Anvil imports.

### Step B: Initialize the particle list

Inside `GameEngine.__init__()`, immediately after `self.anvils = []`, add:

```
self.particles = []
```

Each particle will store its position, velocity, remaining lifetime and radius.

## Step C: Add a particle-creation method

Add this method inside the `GameEngine` class, at the same indentation level as `update()`, `reset()` and `render()`:

```
def create_impact_effect(self, x, y):    for _ in range(12):
self.particles.append({            "x": float(x),            "y": float(y),
"vx": random.uniform(-2.5, 2.5),           "vy": random.uniform(-4.0, -
1.0),            "life": 20,           "radius": random.randint(2, 4),
})
```

This creates 12 particles that spread outward and upward from the impact location.

## Step D: Update the anvil-processing loop

Inside `GameEngine.update()`, replace the existing loop beginning with `for anvil in self.anvils[:]` with the following. Keep it at the same indentation as your original loop.

```
ground_y = self.height - 20player_rect = self.player.rectfor anvil in
self.anvils[:]:    anvil.update()    # A player collision ends this frame's
game update.    if player_rect.colliderect(anvil.rect):
self.game_state = "GAME_OVER"        return    # Create dust when an anvil
hits the ground.    if anvil.rect.bottom >= ground_y:
self.create_impact_effect(            anvil.x + anvil.width / 2,
ground_y        )        self.anvils.remove(anvil)        continue    #
Safety cleanup for anvils that pass below the screen.    if
anvil.is_off_screen(self.height):        self.anvils.remove(anvil)# Update
existing particles.for particle in self.particles[:]:    particle["x"] +=
particle["vx"]    particle["y"] += particle["vy"]    particle["vy"] += 0.15
particle["life"] -= 1    if particle["life"] <= 0:
self.particles.remove(particle)
```

Notice that this checks player collision before ground impact. An anvil that hits the player triggers game over rather than being treated as harmless ground debris.

## Step E: Draw the particles

In `GameEngine.render()`, immediately after the loop that draws anvils, add:

```
for particle in self.particles:    pygame.draw.circle(        screen,
(190, 175, 145),        (int(particle["x"]), int(particle["y"])),
particle["radius"],    )
```

The particles now appear on the screen, move, and disappear after their lifetime expires.

## Step F: Clear particles on restart

In `GameEngine.reset()`, add this line after `self.anvils.clear()`:

```
self.particles.clear()
```

This prevents dust particles from the previous run appearing in the new game.

# 7. One additional fix — Make game-over handling reliable

The current `GameEngine.update()` starts with:

```
if self.game_state != "PLAYING":    return
```

This is correct: it stops normal game updates after game over. The replacement collision loop above also returns immediately on collision, avoiding unnecessary processing of other anvils during that frame.

Your existing `reset()` method already correctly recreates the player, clears the anvils, resets the timer and restores the `"PLAYING"` state. Preserve that behavior.


GitHub

One further improvement is to make the game engine easier to test by separating game logic from rendering in future iterations. For this lab, the fixes above are sufficient without a major redesign.

# 8. Testing checklist for your SE Lab 4

After saving your changes, open a terminal in the repository root.

# Run the game

Install the dependency if you haven't already.

```
python -m pip install pygame
python main.py
```

### Test each behavior

0 of 9 tested

Reset checklist
☐

Boundary — left

Hold A or Left. The player must stop at the left edge.

☐

Boundary — right

Hold D or Right. The player must stop at the right edge.

Anvil spawning

Wait and confirm that anvils appear at different horizontal positions.

Warning colors

Observe that fast anvils become orange or red.

Difficulty scaling

Survive for 20–30 seconds and check that anvils spawn more frequently.

Ground impact

Let an anvil reach the ground away from the player; dust particles should appear.

Collision

Allow an anvil to hit the player; the game-over overlay should appear.

Timer

Confirm the survival time stops increasing after game over.

Restart

Press R; the player and timer should reset and old anvils and particles should disappear.

# 9. Understanding the important Pygame concepts

| Concept | Where it is used | What it does |
| --- | --- | --- |

| | | |
|---|---|---|
| Class and object | `Player`, `Anvil`, `GameEngine` | Organizes game entities and behavior. |
| Encapsulation | `player.py`, `anvil.py` | Keeps each object's state and related methods together. |
| Randomization | `anvil.py` | Randomizes anvil position and falling speed. |
| Game loop | `main.py` | Repeats input, update and rendering operations. |
| Collision detection | `game_engine.py` | Uses `pygame.Rect.colliderect()` to detect overlap. |
| State management | `game_engine.py` | Separates `"PLAYING"` from `"GAME_OVER"`. |
| Time-based spawning | `game_engine.py` | Uses `pygame.time.get_ticks()` and `spawn_delay`. |
| Particle effects | `game_engine.py` | Updates and renders temporary visual objects. |

# 10. What to submit

Your repository's README lists three required submission items:


GitHub

1. Before video: a 10-second gameplay recording showing the original off-screen boundary bug.
2. After video: a 10-second recording showing the fixed boundaries and new features. Try to include the color warnings and ground-impact effect as well.
3. Chat history link: the link to your debugging conversation, including the reasoning, suggested changes and your testing process.

Keep your original version or a separate Git branch so you can demonstrate the bug before fixing it.

Important: I've inspected the source files and provided the targeted code changes, but I haven't run the modified game in your local environment or committed any changes to GitHub. Run the tests above to verify the fixes.

For a complete line-by-line review, including syntax, logic, edge cases and any further bugs, the next step is to apply these changes and share any terminal errors or unexpected gameplay behavior. I can then help you correct those issues one by one.