

Zsyio Backend API - Localhost URLs

Comprehensive Endpoint Directory & Postman Testing Reference

Base URL:	<code>http://localhost:8000/api/</code> (or <code>http://127.0.0.1:8000/api/</code>)
Databases:	Dual Database: SQLite (relational) + MongoDB Atlas (zsyio_db)
Postman Setup:	Set environment variable <code>base_url</code> = <code>http://localhost:8000</code>
Default Headers:	Content-Type: application/json Authorization: Bearer <code>{{token}}</code> (for protected routes)

System Health & Configuration

Method	Localhost URL (Postman)	Description & Notes
GET	<code>http://localhost:8000/api/db-status/</code>	Check dual database status (SQLite file & MongoDB Atlas connection ping) Auth: None
GET	<code>http://localhost:8000/api/config/</code>	Retrieve global site configuration metadata Auth: None

Authentication (JWT)

Method	Localhost URL (Postman)	Description & Notes
POST	<code>http://localhost:8000/api/token/</code>	Obtain JWT access & refresh tokens (Allowed emails: <code>praful@zsyio.com</code> , etc.) Auth: None Body: { "email": "praful@zsyio.com", "password": "your_password" }
POST	<code>http://localhost:8000/api/token/refresh/</code>	Refresh expired JWT access token Auth: None Body: { "refresh": "" }

Projects Portfolio API

Method	Localhost URL (Postman)	Description & Notes
GET	http://localhost:8000/api/projects/	List all portfolio projects Auth: None
POST	http://localhost:8000/api/projects/	Create a new project record Auth: None / Optional Token Body: { "title": "FinTech Mobile App", "category": "Mobile App", "price": 2500.00, "description": "Secure banking app with biometric auth.", "live_url": "https://example.com", "features": ["Biometrics", "Instant Transfer"], "tech_stack": ["React Native", "Django"] }
GET	http://localhost:8000/api/projects/{id}/	Retrieve project details by numeric ID (e.g. /api/projects/1/) Auth: None
PUT	http://localhost:8000/api/projects/{id}/	Full update of project details by ID Auth: None / Optional Token Body: { "title": "FinTech Mobile App Pro", "category": "Mobile App", "description": "Updated full description" }
PATCH	http://localhost:8000/api/projects/{id}/	Partial update of specific project fields Auth: None / Optional Token Body: { "price": 3000.00 }
DELETE	http://localhost:8000/api/projects/{id}/	Delete project by ID Auth: None / Optional Token

Products API

Method	Localhost URL (Postman)	Description & Notes
GET	http://localhost:8000/api/products/	List all products Auth: None
POST	http://localhost:8000/api/products/	Create a new product record Auth: None / Optional Token Body: { "title": "Cloud Analytics Dashboard", "category": "SaaS Product", "price": 499.00, "description": "Serverless analytics dashboard.", "features": ["Real-time", "Exports"], "solutions": ["AWS", "Django"] }
GET	http://localhost:8000/api/products/{id}/	Retrieve product details by ID Auth: None
PUT	http://localhost:8000/api/products/{id}/	Full update of product by ID Auth: None / Optional Token Body: { "title": "Cloud Analytics Enterprise" }
DELETE	http://localhost:8000/api/products/{id}/	Delete product by ID Auth: None / Optional Token

Services & Technologies API

Method	Localhost URL (Postman)	Description & Notes
GET	http://localhost:8000/api/services/services/	List all offered agency services Auth: None
GET	http://localhost:8000/api/services/services/{slug}/	Retrieve service details by slug (e.g. /api/services/services/web-hosting/) Auth: None
GET	http://localhost:8000/api/services/technologies/	List all technologies and stack categories Auth: None
GET	http://localhost:8000/api/services/technologies/{id}/	Retrieve specific technology details by ID Auth: None

Cart & Checkout API

Method	Localhost URL (Postman)	Description & Notes
GET	http://localhost:8000/api/cart/	List active cart sessions / items Auth: None
POST	http://localhost:8000/api/cart/	Create a new cart instance Auth: None Body: { "session_id": "test-session-123" }
POST	http://localhost:8000/api/cart/{id}/add_item/	Add service item to cart by cart ID Auth: None Body: { "service_slug": "web-hosting", "quantity": 1 }
DELETE	http://localhost:8000/api/cart/{id}/	Delete cart item or session Auth: None

About Us API

Method	Localhost URL (Postman)	Description & Notes
GET	http://localhost:8000/api/about/	Retrieve About Us company information Auth: None
POST	http://localhost:8000/api/about/	Create or populate About Us entry Auth: None / Optional Token Body: { "hero_title": "Pioneering Next-Gen Tech", "company_name": "ZSYIO", "mission": "Empowering businesses with AI-driven web systems." }

Interactive & Inquiries (Chatbot & Contact)

Method	Localhost URL (Postman)	Description & Notes
POST	http://localhost:8000/api/chatbot/	Send prompt message to AI chatbot assistant Auth: None Body: { "message": "What web development services do you offer?" }
POST	http://localhost:8000/api/contact/	Submit customer contact inquiry form Auth: None (skipAuth) Body: { "name": "Alex Smith", "email": "alex@example.com", "phone": "+1234567890", "service": "Web Application", "message": "Looking for custom SaaS platform estimation." }

Postman Execution Quick Guide

- 1. Start the Django Server:** Run `python manage.py runserver 8000` in `/backend`.
- 2. Check Health First:** Send a GET request to `http://localhost:8000/api/db-status/` to confirm both SQLite and MongoDB Atlas are online.
- 3. Authentication:** For protected endpoints, first call POST `http://localhost:8000/api/token/`, copy the access token, and set it as Bearer Token.
- 4. Import Collection:** You can also import `document/postman_collection.json` directly into Postman for pre-configured requests.