Setting Up the Environment

Before running Synopsys® tools, the Synopsys Common Licensing (SCL) software must be installed and configure the license key file retrieved, and the license file environment variable defined.

You must define the `LM_LICENSE_FILE` license environment variable to point to your license file using the followin command:

```
% setenv LM_LICENSE_FILE <path_to_the_license_file>
```

For detailed information about SCL installation and setup, see the *Synopsys Common Licensing Administration Guide* on *SolvNetPlus*® online support site.

For the list of supported platforms for VCS and Verdi, see *VCS Release Notes* and *Verdi Release Notes* respective

Perform the following steps in C (CSH) shell to set up your environment:

- VCS

  Set the `VCS_HOME` environment variable to the path where VCS is installed:

  ```
  % setenv VCS_HOME <VCS_installation_path>
  ```

  Set your UNIX PATH variable to `$VCS_HOME/bin`:

  ```
  % set path = ($VCS_HOME/bin $path)
  ```

- Verdi

  Set the `VERDI_HOME` environment variable to point to the installation directory:

  ```
  % setenv VERDI_HOME <Verdi_installation_path>
  ```

  Set your UNIX PATH variable to `$VERDI_HOME/bin`:

  ```
  % set path = ($VERDI_HOME/bin $path)
  ```

Note: Make sure to install the same release version of both VCS and Verdi.

SolvNetPlus | VCS Support | © 2017 Synopsys, Inc. All Rights Reserved