

MASTER RESEARCH PROMPT — SIH 2026 PS 26025

Deep Technical, Scientific, Competitive & Validation-Driven Research

ROLE

Act as a multidisciplinary expert team consisting of:

- Senior mining/geotechnical engineer
- Mine subsidence researcher
- Underground coal-mining safety specialist
- AI/ML researcher
- Time-series forecasting specialist
- IoT and wireless sensor-network architect
- Edge-AI engineer
- GIS/geospatial scientist
- Embedded-systems engineer
- Data-science researcher
- Safety-critical systems engineer
- Technology commercialization expert
- Indian mining-domain researcher
- Patent/prior-art analyst
- Smart India Hackathon evaluator

Conduct a **deep, evidence-based, technically critical research study** for:

SIH 2026 Problem Statement 26025

Title:

Development of an AI-enabled Low Cost Real Time Mine Subsidence Monitoring, Prediction and Early Warning System for Underground Coal Mines in India

0. PRIMARY OBJECTIVE

The objective is NOT to simply generate an attractive AI + IoT solution.

The objective is to determine:

What technically defensible, scientifically credible, low-cost, real-time, scalable, reliable and genuinely innovative system can realistically address PS 26025 and provide a strong SIH 2026 competition advantage?

The research must proceed in this order:

Real-world problem → Physical mechanism → Stakeholders → Existing methods → Existing technologies → Limitations → Research gaps → Design requirements → Candidate technologies → Scientific comparison → Elimination → Final architecture → AI methodology → Prototype → Validation → Cost → Scalability → Novelty → SIH evaluation

Do NOT design the final solution first and then search for evidence to justify it.

1. NON-NEGOTIABLE RESEARCH ACCURACY RULES

Accuracy and evidence quality are more important than producing an impressive-looking answer.

Follow these rules strictly:

1.1 Never fabricate information

Do not invent:

- Research papers
- Authors
- Datasets
- Patents
- Mine incidents
- Statistics
- Sensor specifications
- Costs
- Accuracy values
- Government policies
- Algorithms
- Commercial products
- Deployment claims
- Experimental results

If reliable evidence cannot be found, explicitly state:

“Evidence insufficient to establish this claim.”

1.2 Source hierarchy

Prioritize evidence in this order:

1. Indian Government sources
2. DGMS
3. Ministry of Coal

4. Coal India / subsidiaries
5. CMPDI
6. IIT/IISc/NIT and recognized research institutions
7. Peer-reviewed journals
8. IEEE
9. Elsevier / ScienceDirect
10. Springer
11. USGS and equivalent geological institutions
12. International mining organizations
13. Patents and standards
14. Reputable industrial sources
15. Secondary sources only when primary evidence is unavailable

Clearly distinguish peer-reviewed evidence from commercial claims.

1.3 Cross-validation

For important technical claims, seek confirmation from multiple independent credible sources.

If sources disagree:

- Present the disagreement.
- Explain possible reasons.
- Do not silently choose the convenient value.
- Prefer the strongest primary/peer-reviewed evidence.

1.4 Separate fact from assumption

Every important statement must be classified as:

- **Verified fact**
- **Research finding**
- **Engineering assumption**
- **Prototype assumption**
- **Estimated value**
- **Uncertain / insufficient evidence**

Never present an assumption as a proven fact.

1.5 No fake accuracy

Do not claim:

“95% accurate”

unless supported by an actual experimental methodology and appropriate dataset.

Do not claim that the system can perfectly predict catastrophic ground failure.

Use scientifically defensible terminology such as:

- anomaly detection
 - deformation forecasting
 - risk estimation
 - probability
 - confidence
 - uncertainty
 - warning lead time
-

2. UNDERSTAND PS 26025 EXACTLY

First analyze the official problem statement requirements.

Extract and organize:

- Core problem
- Required functionality
- Expected solution
- Constraints
- Intended users
- Environmental conditions
- Hardware expectations
- Communication requirements
- AI requirements
- GIS requirements
- Offline requirements
- Scalability requirements
- Cost requirements
- Prototype expectations

Create:

PS Requirement → Proposed Capability → Technology → Validation Method

Do not add unnecessary features unless they have a clear justification.

3. DEEP PHYSICAL UNDERSTANDING OF MINE SUBSIDENCE

Explain from first principles:

- What mine subsidence is
- Why underground coal extraction causes surface deformation
- How underground voids affect overburden
- How deformation propagates toward the surface
- Gradual vs sudden subsidence
- Subsidence trough development
- Horizontal and vertical deformation
- Tilt
- Strain
- Displacement
- Cracking
- Vibration
- Ground movement

Investigate the relationship between:

Mining activity → underground deformation → overburden response → surface deformation → measurable sensor signals → risk

Explain what can and cannot realistically be inferred from surface sensors.

4. INDIAN MINING CONTEXT

Research specifically for Indian underground coal mines.

Investigate:

- Indian coalfields
- Underground mining conditions
- Geological variability
- Depth
- Seam characteristics
- Overburden
- Mining methods
- Panel geometry
- Ground conditions
- Monsoon/rainfall effects
- Temperature

- Soil conditions
- Infrastructure exposure
- Connectivity
- Power availability
- Maintenance constraints
- Remote locations
- Cost constraints

Identify which characteristics make an Indian solution different from systems developed elsewhere.

5. STAKEHOLDER AND HUMAN-IMPACT ANALYSIS

Identify:

- Mine operators
- Mining engineers
- Geotechnical engineers
- Safety officers
- Regulators
- Nearby communities
- Farmers
- Infrastructure owners
- Forest/environmental authorities
- Emergency-response personnel

For each:

Problem → Current practice → Missing information → Decision required → Benefit of early warning

6. EXISTING MONITORING METHODS

Deeply investigate:

Conventional

- Manual inspection
- Levelling
- Total station
- GNSS
- Crack surveys

Remote sensing

- InSAR

- LiDAR
- UAV/drone photogrammetry
- Satellite imagery

Sensor-based

- Tilt sensors
- Accelerometers
- Vibration sensors
- Strain sensors
- Displacement sensors
- Crack sensors
- GNSS nodes

For each determine:

- Accuracy
- Temporal resolution
- Spatial resolution
- Cost
- Coverage
- Latency
- Power requirement
- Expertise required
- Deployment complexity
- Environmental limitations
- Suitability for real-time monitoring

7. EXISTING SOLUTIONS AND COMPETITIVE LANDSCAPE

Search for:

- Academic systems
- Government projects
- Commercial mine-monitoring systems
- Research prototypes
- Patents
- IoT subsidence systems
- AI-based subsidence prediction
- Wireless sensor networks
- Real-time mine monitoring platforms

Create:

| Existing System | Technology | Capability | Strength | Limitation | Cost/Complexity | Difference From Proposed System |

Do not assume our idea is novel until prior art has been investigated.

8. WHY CURRENT APPROACHES ARE INSUFFICIENT

Identify evidence-backed limitations such as:

- Periodic monitoring
- Lack of continuous sensing
- High cost
- Limited spatial density
- Manual dependency
- Communication limitations
- Sensor drift
- Environmental noise
- False alarms
- Missing data
- Poor prediction
- Limited local processing
- Cloud dependency
- Maintenance burden
- Lack of sensor fusion
- Poor explainability
- Lack of uncertainty estimation
- Limited scalability

For each:

Existing limitation → Why it occurs → Consequence → Proposed mitigation → Validation method

Do not claim that all existing systems suffer from every limitation.

9. RESEARCH GAP

Identify the strongest scientifically supported gaps.

Prioritize gaps related to:

- Low-cost continuous monitoring
- Dense surface sensing
- Relative deformation

- Multi-sensor fusion
- Wireless mesh networking
- Edge intelligence
- Spatio-temporal analysis
- Early anomaly detection
- Forecasting
- Uncertainty-aware warning
- Sensor-health awareness
- Offline-first operation
- GIS-based risk visualization
- Physics-guided AI

Rank each gap:

Impact / Evidence / Novelty / Feasibility / SIH Value

10. CENTRAL INNOVATION — WIRELESS SURFACE SENSOR MESH

Investigate this proposed core architecture:

A distributed low-cost wireless sensor network deployed across the surface above underground mine panels to continuously observe spatial and temporal ground deformation.

Potential node sensors:

- Tilt/inclination
- Accelerometer/vibration
- Displacement/stretch
- Crack detection
- Temperature
- Optional GNSS

Investigate whether neighboring nodes can be used to detect:

- Differential movement
- Relative displacement
- Differential tilt
- Spatial deformation patterns
- Crack propagation
- Coordinated anomalies

Critically evaluate whether **relative measurements between neighboring nodes** provide useful information and under what assumptions.

Do not assume this automatically improves accuracy; find evidence and define how it should be validated.

11. SENSOR FUSION

Research how to combine:

Tilt + displacement + vibration + crack + optional positioning + environmental measurements

Investigate:

- Statistical fusion
- Kalman filtering
- Extended Kalman Filter
- Unscented Kalman Filter
- Bayesian fusion
- Ensemble approaches
- Confidence-weighted fusion

Determine:

- Which method is appropriate
 - Why
 - Computational requirement
 - Noise handling
 - Missing-data handling
 - Sensor failure handling
-

12. SENSOR HEALTH

Treat sensor reliability as a separate problem.

Investigate detection of:

- Sensor drift
- Stuck values
- Communication failure
- Battery failure
- Calibration problems
- Outliers
- Physical sensor displacement

Determine whether the AI should distinguish:

“Ground deformation”

from

“Sensor malfunction.”

This is mandatory for a safety-oriented system.

13. AI/ML RESEARCH

Do not select algorithms merely because they are advanced.

Investigate and compare:

Anomaly Detection

- Isolation Forest
- One-Class SVM
- Autoencoder
- Variational Autoencoder
- Robust statistical methods

Forecasting

- ARIMA/statistical baselines
- Random Forest/XGBoost for engineered temporal features
- LSTM
- GRU
- Temporal CNN
- Transformer/TFT

Spatial/Graph Modelling

- GNN
- GCN
- GraphSAGE
- Spatio-temporal GNN

Hybrid/Physics-Guided

- Physics-informed ML
- Physics-guided ML
- Hybrid geotechnical + ML models

Spatial interpolation

- IDW
- Kriging
- Gaussian Processes

For every algorithm provide:

Input → Output → Assumptions → Data requirement → Computational requirement → Advantages → Limitations → Suitability

14. BASELINE-FIRST VALIDATION

Never compare only advanced AI models.

Define baseline models first.

Example:

Simple threshold/statistical baseline → classical ML → deep learning → advanced model

Then determine whether the advanced model actually provides a statistically meaningful improvement.

If a simpler model performs similarly, recommend the simpler model.

This is essential for a credible SIH prototype.

15. TIME-SERIES AND EARLY-WARNING VALIDATION

Do not use random train/test splitting for time-dependent data when it would cause temporal leakage.

Investigate:

- Chronological train/validation/test split
- Rolling-window validation
- Walk-forward validation
- Cross-panel validation
- Cross-location validation
- Unseen-condition testing

Ensure that future information never leaks into training.

Evaluate:

- Precision
 - Recall
 - F1
 - ROC-AUC where appropriate
 - PR-AUC where appropriate
 - False alarm rate
 - Miss detection rate
 - Detection latency
 - Warning lead time
 - MAE
 - RMSE
 - Forecast error
 - Calibration
 - Uncertainty quality
-

16. SAFETY-CRITICAL WARNING DESIGN

Design a multi-level warning system, for example:

NORMAL → WATCH → WARNING → CRITICAL

But do not assume these thresholds are correct.

Research how thresholds should be derived from:

- Engineering limits
- Historical data
- Statistical baselines
- Expert knowledge
- Sensor fusion
- Model probability
- Persistence
- Spatial consensus

The system should not generate a critical warning from a single noisy sensor unless scientifically justified.

Investigate:

Temporal persistence + neighboring-node confirmation + multi-sensor evidence + model confidence

for reducing false alarms.

17. UNCERTAINTY AND EXPLAINABILITY

A safety system should communicate not only:

“Risk = High”

but also:

- Why the risk increased
- Which sensors contributed
- Whether neighboring nodes agree
- Whether deformation is accelerating
- Confidence level
- Data quality
- Sensor health
- Prediction uncertainty

Investigate:

- SHAP
- Feature importance
- Confidence intervals
- Prediction intervals
- Bayesian uncertainty
- Conformal prediction where appropriate

Recommend only methods that are feasible for the prototype.

18. EDGE + OFFLINE-FIRST ARCHITECTURE

Investigate:

Sensor node

→ Mesh network → Edge gateway → Local processing → Local AI → Local database → Alert engine → Cloud synchronization

Determine what happens if:

- Internet fails
- Cloud fails
- Gateway fails
- Individual nodes fail
- Several nodes lose communication

The system should fail safely.

Define:

Local sensing → local processing → local alert → later synchronization

where technically feasible.

19. COMMUNICATION TECHNOLOGY SELECTION

Compare:

- LoRa
- LoRaWAN
- Zigbee
- Wi-Fi Mesh
- BLE Mesh
- Cellular/NB-IoT

Evaluate:

- Range
- Power
- Latency
- Data rate
- Reliability
- Mesh capability
- Cost
- Scalability
- Availability
- Deployment complexity

Select ONE primary architecture for the prototype unless there is a justified hybrid design.

Do not recommend every protocol simultaneously.

20. HARDWARE SELECTION

Compare practical components:

Controllers

- ESP32

- Arduino-class platforms
- Raspberry Pi

Sensors

- Tilt
- IMU
- Vibration
- Displacement
- Crack
- Temperature
- Humidity
- GNSS

For each evaluate:

Accuracy / Resolution / Range / Power / Cost / Availability / Environmental suitability / Interface / Prototype feasibility

Clearly separate:

prototype-grade components

from

industrial-grade deployment requirements.

Never imply that hobbyist hardware is automatically suitable for safety-critical industrial deployment.

21. GIS AND SPATIAL RISK MAP

Research how to visualize:

- Mine panels
- Sensor nodes
- Deformation
- Tilt vectors
- Crack locations
- Risk zones
- Historical trends
- Predicted deformation
- Sensor health

Evaluate:

- PostGIS
- QGIS
- Leaflet
- MapLibre
- GeoJSON
- Raster/heatmap approaches

Determine the simplest technically appropriate GIS stack.

22. DIGITAL TWIN — CRITICAL EVALUATION

Investigate whether a Mine Subsidence Digital Twin genuinely improves:

- Understanding
- Prediction
- Visualization
- Decision-making

If it only adds presentation complexity without meaningful technical value, classify it as:

Optional / Future Work

Do not include technology merely because it sounds innovative.

23. DATASET AND DATA-ENGINEERING STRATEGY

Research real datasets first.

Investigate:

- Mine subsidence datasets
- InSAR data
- Ground deformation datasets
- Geological datasets
- Mining sensor datasets
- Environmental datasets

If sufficient real labeled data does not exist, design a transparent strategy using:

- Real sensor data
- Controlled laboratory experiments

- Synthetic data
- Physics-based simulation
- Historical observations
- Data augmentation

Clearly state the limitations of synthetic data.

Do not claim real-world accuracy from synthetic-only testing.

24. PROTOTYPE EXPERIMENT DESIGN

Design a physical miniature demonstration.

Define:

Inputs

- Sensor readings
- Node positions
- Artificial/controlled ground movement
- Vibration
- Crack simulation

Experiment

Create controlled deformation scenarios:

1. Normal condition
2. Gradual movement
3. Localized movement
4. Differential movement
5. Crack initiation
6. Vibration disturbance
7. Sensor failure
8. Communication loss
9. Multiple-node deformation

Outputs

- Anomaly detection
- Deformation map
- Risk score
- Prediction
- Warning level
- Explanation
- Sensor health

Define how every claim will be experimentally validated.

25. VALIDATION FRAMEWORK

Create a complete validation matrix:

Claim	Metric	Test Method	Dataset/ Experiment	Baseline	Acceptance Criterion	Limitation
-------	--------	-------------	------------------------	----------	-------------------------	------------

Validate independently:

Sensor layer

Accuracy, repeatability, drift

Network layer

Latency, packet delivery, range, uptime

AI layer

Precision, recall, F1, forecasting error

Warning layer

Lead time, false alarms, missed events

GIS layer

Spatial consistency

Edge layer

Inference latency and offline operation

System layer

End-to-end reliability

Cost layer

Cost per node and monitored area

26. ABLATION STUDY

Determine whether every component actually contributes.

Test:

- Tilt only
- Tilt + displacement
- Tilt + vibration
- Multi-sensor fusion
- Without spatial information
- With spatial information
- Without temporal model
- With temporal model
- Without edge processing
- With edge processing

Identify which components produce measurable improvement.

This prevents unnecessary technology stacking.

27. ROBUSTNESS TESTING

Test the proposed system against:

- Noise
- Missing data
- Outliers
- Sensor drift
- Communication loss
- Battery reduction
- Environmental changes
- Temporary vibration
- Vehicle movement
- Multiple simultaneous anomalies

Determine whether performance degrades gracefully.

28. COST AND ECONOMIC FEASIBILITY

Calculate separately:

SIH prototype

and

Potential field deployment

Estimate:

- Sensor node
- Gateway
- Communication
- Power
- Enclosure
- Installation
- Maintenance
- Software
- Storage
- Connectivity

Do not invent exact industrial costs.

Use ranges and clearly identify assumptions.

Also calculate:

Cost per node

Cost per monitored area

Estimated maintenance burden

Potential cost advantage versus selected existing approaches

29. SCALABILITY

Evaluate:

10 nodes → 100 nodes → 1,000 nodes → multiple panels → multiple mines

Analyze:

- Network scalability
- Gateway capacity
- Database
- AI inference

- Model management
 - Sensor management
 - OTA updates
 - Fault tolerance
 - Cloud synchronization
-

30. SECURITY AND FAIL-SAFE DESIGN

Research:

- Device authentication
- Encryption
- Secure communication
- Firmware integrity
- Data integrity
- Access control
- Alert tampering
- Sensor spoofing

Define what happens when components fail.

The system must never silently represent missing or unreliable data as normal conditions.

31. NOVELTY AND PRIOR-ART ANALYSIS

Perform a serious prior-art investigation.

Search:

- Research papers
- Patents
- Existing products
- Government projects
- Academic prototypes

Compare them against:

Proposed concept

Distributed surface mesh + relative deformation + multi-sensor fusion + edge intelligence + spatio-temporal prediction + GIS + uncertainty-aware warning + offline operation

Identify:

- What is already known
- What is partially known
- What combination may be novel
- What cannot legitimately be called novel

Do NOT use the word **“unique”**, **“first”**, or **“patented”** without evidence.

32. INNOVATION RANKING

Generate at least 10 candidate innovations.

For each score:

Novelty / Impact / Feasibility / Cost / SIH value / Evidence

Then select the strongest 3–5.

Do not attempt to implement every innovation.

33. FINAL TECHNOLOGY SELECTION

After researching all alternatives, create:

Layer	Alternatives	Selected	Why	Rejected	Reason
-------	--------------	----------	-----	----------	--------

Classify every technology:

- **Essential**
- **Recommended**
- **Optional**
- **Future**
- **Not recommended**

Every selected technology must answer:

“What specific PS 26025 problem does this solve?”

If a simpler technology performs adequately, prefer it.

34. FINAL RECOMMENDED ARCHITECTURE

Produce ONE final architecture.

It must specify:

Hardware

- Sensor node
- Microcontroller
- Sensors
- Power
- Gateway

Communication

- Protocol
- Mesh topology
- Node-to-node communication
- Gateway communication

Software

- Firmware
- Backend
- Database
- API
- Dashboard
- GIS

AI

- Preprocessing
- Sensor health
- Anomaly detection
- Sensor fusion
- Forecasting
- Risk scoring
- Explainability
- Uncertainty

Deployment

- Edge
- Local server
- Cloud
- Offline synchronization

Alerts

- Dashboard
 - Local alarm
 - SMS/email/app where appropriate
-

35. END-TO-END DATA FLOW

Show exactly:

Physical ground movement

↓

Sensor measurement

↓

Sensor validation

↓

Node-level preprocessing

↓

Wireless mesh transmission

↓

Gateway

↓

Edge processing

↓

Sensor fusion

↓

Anomaly detection

↓

Spatial analysis

↓

Temporal forecasting

↓

Risk estimation

↓

Confidence/uncertainty

↓

Warning engine

↓

GIS visualization

↓

Operator decision

Clearly identify the INPUT and OUTPUT of every stage.

36. WHAT SHOULD ACTUALLY BE BUILT FOR SIH

End the research with a section:

“FINAL SIH BUILD”

Specify exactly what the student team should physically build.

Include:

- Number of nodes
- Sensors

- Microcontroller
- Communication
- Gateway
- Edge device
- AI models
- Database
- Backend
- Frontend
- GIS
- Alert system
- Power
- Demo setup
- Dataset
- Experiments
- Metrics

Do not include unnecessary industrial-scale components in the SIH prototype.

37. SIH JUDGE EVALUATION

Act as a highly critical SIH evaluator.

Score from 0–10:

- Problem understanding
- Problem relevance
- Innovation
- Technical depth
- AI justification
- IoT architecture
- Mesh-network innovation
- Prediction methodology
- Accuracy/validation
- Reliability
- Cost
- Scalability
- Indian suitability
- Prototype feasibility
- Social impact
- Commercial potential
- Novelty
- Presentation potential

Then identify:

Top 10 weaknesses

Top 10 judge objections

Top 10 technical questions judges may ask

Best evidence-based answers

Do not protect the proposed idea from criticism.

38. RED-TEAM THE SOLUTION

Attempt to disprove the proposed architecture.

Ask:

- Can the sensors actually detect meaningful deformation?
- Can surface measurements distinguish subsidence from environmental noise?
- Can the model predict future deformation with available data?
- Is enough training data available?
- Can the mesh network operate reliably?
- Can low-cost sensors maintain calibration?
- Can the system operate offline?
- Can false alarms be controlled?
- Can missed events be detected?
- Is the claimed novelty actually novel?
- Is the prototype representative of the real problem?
- What happens when sensors fail?
- What happens when communication fails?
- What happens when AI is uncertain?

For every weakness provide:

Problem → Severity → Mitigation → Validation

Do not hide weaknesses.

39. “NO-DISADVANTAGE” REQUIREMENT — HANDLE SCIENTIFICALLY

Do NOT pretend that the proposed system has zero disadvantages.

Instead produce:

Risk and Mitigation Matrix

Potential Weakness	Severity	Probability	Effect	Mitigation	Residual Risk
--------------------	----------	-------------	--------	------------	---------------

The goal is not to claim:

“No disadvantages.”

The goal is:

“Every known limitation has been identified, quantified where possible, and mitigated or explicitly bounded.”

This is more credible to technical judges.

40. FINAL RESEARCH CONCLUSION

Provide a final conclusion answering:

1. What exactly is the problem?
2. Who is affected?
3. Why is it still difficult?
4. What are existing solutions?
5. Why are they insufficient for the specific PS requirements?
6. What is the research gap?
7. What is our core innovation?
8. Why is the wireless surface mesh important?
9. What sensors should actually be used?
10. What communication technology should actually be used?
11. What AI algorithms should actually be used?
12. Why are those algorithms appropriate?
13. How will sensor fusion work?
14. How will prediction work?
15. How will uncertainty be handled?
16. How will false alarms be reduced?
17. How will sensor failures be detected?
18. How will the system work without internet?
19. How will the system be validated?
20. What can realistically be demonstrated at SIH?
21. What is genuinely novel?
22. What should NOT be included?
23. What is the estimated prototype cost?
24. How can the system scale to real mines?
25. Why should SIH judges select this solution?

41. FINAL OUTPUT STRUCTURE

Return the completed research in this exact order:

1. Executive Summary
2. PS 26025 Requirement Analysis
3. Mine Subsidence Fundamentals
4. Indian Mining Context
5. Stakeholder Analysis
6. Existing Monitoring Methods
7. Existing Technologies
8. Existing Systems and Prior Art
9. Existing Solution Limitations
10. Research Gap
11. Design Requirements
12. Wireless Surface Mesh Innovation
13. Sensor Architecture
14. Communication Architecture
15. Sensor-Fusion Architecture
16. AI/ML Comparison
17. Final Algorithm Selection
18. Time-Series Prediction
19. Risk Scoring
20. Uncertainty & Explainability
21. Sensor Health
22. Edge Computing
23. Offline Architecture
24. GIS Architecture
25. Digital Twin Assessment
26. Dataset Strategy
27. Prototype Design
28. Experimental Design
29. Validation Framework
30. Ablation Study
31. Robustness Testing
32. Cost Analysis
33. Scalability
34. Security & Fail-Safe Design
35. Patent/Prior-Art Analysis
36. Innovation Ranking
37. Final Technology Selection
38. Final System Architecture
39. End-to-End Workflow
40. Final SIH Build
41. Judge Evaluation

- 42. Red-Team Analysis
 - 43. Risk & Mitigation Matrix
 - 44. Final Recommendation
 - 45. Sources & Evidence
-

42. FINAL DECISION RULE

At the very end provide:

THE ONE-SENTENCE FINAL CONCEPT

Describe the solution in one technically precise sentence.

Then provide:

THE FINAL TECHNOLOGY STACK

Only the technologies that should actually be used.

Then:

THE FINAL ALGORITHM STACK

Only the algorithms that should actually be used.

Then:

THE TOP 5 INNOVATIONS

Only the strongest defensible innovations.

Then:

THE TOP 5 TECHNICAL RISKS

And how each is mitigated.

Then:

THE TOP 10 JUDGE QUESTIONS

With evidence-based answers.

CRITICAL FINAL INSTRUCTION

The objective is **not to make the solution sound futuristic.**

The objective is to make it:

Scientifically defensible + technically correct + experimentally validated + low cost + real-time + reliable + explainable + scalable + practical for Indian underground coal mines + genuinely innovative + demonstrable at SIH 2026.

Prefer evidence over assumptions.

Prefer validation over claims.

Prefer simple proven technology over unnecessary complexity.

Prefer measurable innovation over buzzwords.

Never claim 100% prediction accuracy, guaranteed safety, zero false alarms, zero disadvantages, or guaranteed SIH victory.

The final recommendation must clearly distinguish:

What is scientifically established

from

what is experimentally demonstrated

from

what is proposed engineering design

from

what remains future work.