

# Skill week 5

## Session 9:

### Task 1:

To Change Directories, Validate Paths, Update Working Directory, Handle Errors, Maintain Previous Directory, Test Navigation.

Code:

```
jella_pragathi@LAPTOP-RQQC x + v
GNU nano 8.7.1 session9_cd.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <limits.h>
#include <errno.h>

int main()
{
    char input[PATH_MAX];
    char current_dir[PATH_MAX];
    char previous_dir[PATH_MAX] = "";

    while (1)
    {
        if (getcwd(current_dir, sizeof(current_dir)) == NULL)
        {
            perror("getcwd");
            break;
        }

        printf("shell:%s$ ", current_dir);
        fflush(stdout);

        if (fgets(input, sizeof(input), stdin) == NULL)
        {
            break;
        }

        input[strcspn(input, "\n")] = '\0';

        if (strcmp(input, "exit") == 0)
        {
            break;
        }

        if (strncmp(input, "cd", 2) == 0 &&
```

|         |              |             |          |            |
|---------|--------------|-------------|----------|------------|
| ^G Help | ^O Write Out | ^F Where Is | ^K Cut   | ^T Execute |
| ^X Exit | ^R Read File | ^N Replace  | ^U Paste | ^J Justify |

```
if (strncmp(input, "cd", 2) == 0 &&
    (input[2] == '\\0' || input[2] == ' '))
{
    char *path = input + 2;

    while (*path == ' ')
        path++;

    if (*path == '\\0')
    {
        path = getenv("HOME");
    }
    else if (strcmp(path, "-") == 0)
    {
        if (strlen(previous_dir) == 0)
        {
            printf("cd: OLDPWD not set\n");
            continue;
        }

        char temp[PATH_MAX];
        strcpy(temp, previous_dir);

        strcpy(previous_dir, current_dir);

        if (chdir(temp) == -1)
        {
            perror("cd");
        }
        else
        {
            printf("%s\n", temp);
        }

        continue;
    }
}
```

**^G** Help  
**^X** Exit

**^O** Write Out  
**^R** Read File

**^F** Where Is  
**^\\** Replace

**^K** Cut  
**^U** Paste

**^T** Execute  
**^J** Justify

```

    }

    if (chdir(path) == -1)
    {
        fprintf(stderr, "cd: %s: %s\n", path, strerror(errno));
    }
    else
    {
        strcpy(previous_dir, current_dir);
    }

    continue;
}

printf("Unknown command: %s\n", input);
}

return 0;
}

```

|                |                     |                    |                 |                   |
|----------------|---------------------|--------------------|-----------------|-------------------|
| <b>^G</b> Help | <b>^O</b> Write Out | <b>^F</b> Where Is | <b>^K</b> Cut   | <b>^T</b> Execute |
| <b>^X</b> Exit | <b>^R</b> Read File | <b>^N</b> Replace  | <b>^U</b> Paste | <b>^J</b> Justify |

```

jella_pragathi@LAPTOP-RQQGT555:~$ cd ~/OSSP
nano session9_cd.c
jella_pragathi@LAPTOP-RQQGT555:~/OSSP$ gcc -Wall -Wextra -g session9_cd.c -o
session9_cd
jella_pragathi@LAPTOP-RQQGT555:~/OSSP$ ./session9_cd
shell:/home/jella_pragathi/OSSP$ pwd
Unknown command: pwd
shell:/home/jella_pragathi/OSSP$ cd/tmp
Unknown command: cd/tmp
shell:/home/jella_pragathi/OSSP$ /tmp
Unknown command: /tmp
shell:/home/jella_pragathi/OSSP$ cd /tmp
shell:/tmp$ cd -
/home/jella_pragathi/OSSP
shell:/home/jella_pragathi/OSSP$ cd /wrong/path
cd: /wrong/path: No such file or directory
shell:/home/jella_pragathi/OSSP$ cd /tmp
cd -
cd shell:/tmp$ /home/jella_pragathi/OSSP
shell:/home/jella_pragathi/OSSP$ /home
cd ..
cd ~shell:/home$ shell:/$
cd /wrong/path
cd: ~: No such file or directory
shell:/$ cd: /wrong/path: No such file or directory
shell:/$ exit
jella_pragathi@LAPTOP-RQQGT555:~/OSSP$ |

```

## Task 2:

To Identify Built-ins, Create Dispatch Table, Execute In-Process Commands, Handle Invalid Commands, Maintain State, Test Dispatch Logic.

Code:

```
GNU nano 8.7.1 session9_dispatch.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <limits.h>

void builtin_pwd(char *args[])
{
    char cwd[PATH_MAX];

    if (getcwd(cwd, sizeof(cwd)) != NULL)
        printf("%s\n", cwd);
    else
        perror("pwd");
}

void builtin_cd(char *args[])
{
    if (args[1] == NULL)
    {
        const char *home = getenv("HOME");

        if (home != NULL)
        {
            if (chdir(home) == -1)
                perror("cd");
        }

        return;
    }

    if (chdir(args[1]) == -1)
        perror("cd");
}

void builtin_echo(char *args[])
{
    ^G Help      ^O Write Out  ^F Where Is   ^K Cut        ^T Execute
    ^X Exit      ^R Read File  ^\ Replace    ^U Paste      ^J Justify
```

```
jella_pragathi@LAPTOP-RQQC x + v
GNU nano 8.7.1 session9_dispatch.c *
|  for (int i = 1; args[i] != NULL; i++)
|  {
|      printf("%s", args[i]);
|
|      if (args[i + 1] != NULL)
|          printf(" ");
|  }
|
|  printf("\n");
|  }
void builtin_help(char *args[])
{
    printf("Built-in commands:\n");
    printf("  cd      Change directory\n");
    printf("  pwd     Print working directory\n");
    printf("  echo    Display text\n");
    printf("  help    Display this help\n");
    printf("  exit    Exit shell\n");
}

typedef void (*builtin_func)(char **);

struct builtin
{
    char *name;
    builtin_func function;
};

struct builtin builtins[] =
{
    {"cd", builtin_cd},
    {"pwd", builtin_pwd},
    {"echo", builtin_echo},
    {"help", builtin_help}
};

^G Help      ^O Write Out ^F Where Is  ^K Cut       ^T Execute
^X Exit      ^R Read File ^\ Replace   ^U Paste     ^J Justify
```

```
jella_pragathi@LAPTOP-RQQK: ~$ nano session9_dispatch.c
GNU nano 8.7.1 session9_dispatch.c *

int builtin_count()
{
    return sizeof(builtins) / sizeof(builtins[0]);
}

int main()
{
    char input[1024];

    while (1)
    {
        printf("myshell$ ");
        fflush(stdout);

        if (fgets(input, sizeof(input), stdin) == NULL)
            break;

        input[strcspn(input, "\n")] = '\0';

        if (strcmp(input, "exit") == 0)
            break;

        char *args[100];
        int count = 0;

        char *token = strtok(input, " ");

        while (token != NULL && count < 99)
        {
            args[count++] = token;
            token = strtok(NULL, " ");
        }

        args[count] = NULL;

        if (count == 0)
            continue;
    }
}
```

|                |                     |                    |                 |                   |
|----------------|---------------------|--------------------|-----------------|-------------------|
| <b>^G</b> Help | <b>^O</b> Write Out | <b>^F</b> Where Is | <b>^K</b> Cut   | <b>^T</b> Execute |
| <b>^X</b> Exit | <b>^R</b> Read File | <b>^I</b> Replace  | <b>^U</b> Paste | <b>^J</b> Justify |

```

    if (count == 0)
        continue;

    int found = 0;

    for (int i = 0; i < builtin_count(); i++)
    {
        if (strcmp(args[0], builtins[i].name) == 0)
        {
            builtins[i].function(args);
            found = 1;
            break;
        }
    }

    if (!found)
    {
        printf("Unknown command: %s\n", args[0]);
    }
}

return 0;
}

```

<sup>^</sup>G Help  
<sup>^</sup>X Exit

<sup>^</sup>O Write Out  
<sup>^</sup>R Read File

<sup>^</sup>F Where Is  
<sup>^</sup>\ Replace

<sup>^</sup>K Cut  
<sup>^</sup>U Paste

<sup>^</sup>T Execute  
<sup>^</sup>J Justify

```
jella_pragathi@LAPTOP-RQQT555:~/OSSP$ nano session9_dispatch.c
jella_pragathi@LAPTOP-RQQT555:~/OSSP$ gcc -Wall -Wextra -g session9_dispatch.c -o session9_dispatch
session9_dispatch.c: In function 'builtin_pwd':
session9_dispatch.c:7:24: warning: unused parameter 'args' [-Wunused-parameter]
    7 | void builtin_pwd(char *args[])
      |                      ^~~~~~
session9_dispatch.c: In function 'builtin_help':
session9_dispatch.c:49:25: warning: unused parameter 'args' [-Wunused-parameter]
   49 | void builtin_help(char *args[])
      |                      ^~~~~~
jella_pragathi@LAPTOP-RQQT555:~/OSSP$ ./session9_dispatch
myshell$ help
Built-in commands:
  cd      Change directory
  pwd     Print working directory
  echo    Display text
  help    Display this help
  exit    Exit shell
myshell$ pwd
/home/jella_pragathi/OSSP
myshell$ echo Hello Pragathi
Hello Pragathi
myshell$ cd /tmp
myshell$ pwd
/tmp
myshell$ cd /
myshell$ pwd
/
myshell$ abc
Unknown command: abc
myshell$ exit
jella_pragathi@LAPTOP-RQQT555:~/OSSP$ |
```

## Session 10:

### Task 1:

To Retrieve Current Directory, Display Path, Process Exit Requests, Cleanup Resources, Save State, Verify Correct Behavior.



The screenshot shows a terminal window with a dark background. At the top, the window title is 'jella\_pragathi@LAPTOP-RQQC'. Below the title bar, the nano editor interface is visible, showing the file 'session10\_pwd\_exit.c \*'. The code is written in C and includes standard headers for stdio, stdlib, unistd, limits, and string. It defines a 'show\_pwd()' function that uses 'getcwd()' to retrieve the current directory and 'printf()' to display it. The 'main()' function enters a loop where it prompts the user with 'myshell\$ ' and reads input into a 'command' array. It checks for a null input and breaks the loop if necessary. Finally, it null-terminates the command string. At the bottom of the window, there is a row of keyboard shortcuts for nano editor operations.

```
GNU nano 8.7.1 session10_pwd_exit.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <limits.h>
#include <string.h>

void show_pwd()
{
    char cwd[PATH_MAX];

    if (getcwd(cwd, sizeof(cwd)) != NULL)
    {
        printf("%s\n", cwd);
    }
    else
    {
        perror("pwd");
    }
}

int main()
{
    char command[100];

    while (1)
    {
        printf("myshell$ ");
        fflush(stdout);

        if (fgets(command, sizeof(command), stdin) == NULL)
        {
            printf("\n");
            break;
        }

        command[strcspn(command, "\n")] = '\0';
    }
}
```

^G Help      ^O Write Out      ^F Where Is      ^K Cut      ^T Execute  
^X Exit      ^R Read File      ^\ Replace      ^U Paste      ^J Justify

```

        command[strcspn(command, "\n")] = '\0';

        if (strcmp(command, "pwd") == 0)
        {
            show_pwd();
        }
        else if (strcmp(command, "exit") == 0)
        {
            printf("Exiting shell...\n");
            break;
        }
        else if (strlen(command) == 0)
        {
            continue;
        }
        else
        {
            printf("Unknown command: %s\n", command);
        }
    }

    return 0;
}

```

|                |                     |                    |                 |                   |
|----------------|---------------------|--------------------|-----------------|-------------------|
| <b>^G</b> Help | <b>^O</b> Write Out | <b>^F</b> Where Is | <b>^K</b> Cut   | <b>^T</b> Execute |
| <b>^X</b> Exit | <b>^R</b> Read File | <b>^N</b> Replace  | <b>^U</b> Paste | <b>^J</b> Justify |

```

mysHELL$ exit
jella_pragathi@LAPTOP-RQQT555:~/OSSP$ nano session10_pwd_exit.c
jella_pragathi@LAPTOP-RQQT555:~/OSSP$ gcc -Wall -Wextra -g session10_pwd_ex
it.c -o session10_pwd_exit
jella_pragathi@LAPTOP-RQQT555:~/OSSP$ ./session10_pwd_exit
mysHELL$ pwd
/home/jella_pragathi/OSSP
mysHELL$ exit
Exiting shell...
jella_pragathi@LAPTOP-RQQT555:~/OSSP$ |

```

## Task 2:

To Parse Export Syntax, Update Environment Variables, Validate Names, Handle Existing Variables, Export to Child Processes, Test Functionality.



```
GNU nano 8.7.1 session10_export.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>

int valid_name(const char *name)
{
    if (name == NULL || name[0] == '\0')
        return 0;

    if (!isalpha((unsigned char)name[0]) || name[0] == '_')
        return 0;

    for (int i = 1; name[i] != '\0'; i++)
    {
        if (!isalnum((unsigned char)name[i]) || name[i] == '_')
            return 0;
    }

    return 1;
}

void handle_export(char *command)
{
    char *assignment = command + 7;

    while (*assignment == ' ')
        assignment++;

    if (*assignment == '\0')
    {
        printf("export: missing argument\n");
        return;
    }

    char *equal = strchr(assignment, '=');
```

|      |           |          |       |         |
|------|-----------|----------|-------|---------|
| Help | Write Out | Where Is | Cut   | Execute |
| Exit | Read File | Replace  | Paste | Justify |

```
char *equal = strchr(assignment, '=');

if (equal == NULL)
{
    printf("export: invalid syntax\n");
    printf("Usage: export NAME=value\n");
    return;
}

*equal = '\0';

char *name = assignment;
char *value = equal + 1;

if (!valid_name(name))
{
    printf("export: invalid variable name: %s\n", name);
    return;
}

if (setenv(name, value, 1) == -1)
{
    perror("export");
    return;
}

printf("Exported: %s=%s\n", name, value);
}

int main()
{
    char command[1024];

    while (1)
    {
        printf("myshell$ ");
```

**^G** Help  
**^X** Exit

**^O** Write Out  
**^R** Read File

**^F** Where Is  
**^\_\** Replace

**^K** Cut  
**^U** Paste

**^T** Execute  
**^J** Justify

```
printf("myshell$ ");
fflush(stdout);

if (fgets(command, sizeof(command), stdin) == NULL)
    break;

command[strcspn(command, "\n")] = '\0';

if (strcmp(command, "exit") == 0)
{
    break;
}

if (strcmp(command, "env") == 0)
{
    extern char **environ;

    for (char **env = environ; *env != NULL; env++)
        printf("%s\n", *env);

    continue;
}

if (strncmp(command, "export ", 7) == 0)
{
    handle_export(command);
    continue;
}

if (strlen(command) == 0)
    continue;

printf("Unknown command: %s\n", command);
}

return 0;
}
```

**^G** Help  
**^X** Exit

**^O** Write Out  
**^R** Read File

**^F** Where Is  
**^\_** Replace

**^K** Cut  
**^U** Paste

**^T** Execute  
**^J** Justify

```
jella_pragathi@LAPTOP-RQQK: ~
jella_pragathi@LAPTOP-RQQK$ nano session10_export.c
jella_pragathi@LAPTOP-RQQK$ gcc -Wall -Wextra -g session10_export.c -o session10_export
jella_pragathi@LAPTOP-RQQK$ ./session10_export
myshell$ export NAME=Pragathi
Exported: NAME=Pragathi
myshell$ env
SHELL=/bin/bash
WSL2_GUI_APPS_ENABLED=1
WSL_DISTRO_NAME=Ubuntu
NAME=Pragathi
PWD=/home/jella_pragathi/OSSP
LOGNAME=jella_pragathi
HOME=/home/jella_pragathi
LANG=C.UTF-8
WSL_INTEROP=/run/WSL/339.interop
LS_COLORS=rs=0:di=01;34:ln=01;36:mh=00:pi=40;33:so=01;35:do=01;35:bd=40;33;01:cd=40;33;01:or=40;31;01:mi=00:su=37;41:sg=30;43:ca=00:tw=30;42:ow=34;42:st=37;40:ex=01;32:*.tar=01;31:*.tgz=01;31:*.arc=01;31:*.arj=01;31:*.taz=01;31:*.lha=01;31:*.lz4=01;31:*.lzh=01;31:*.lзма=01;31:*.tlz=01;31:*.txz=01;31:*.tzo=01;31:*.t7z=01;31:*.zip=01;31:*.z=01;31:*.dz=01;31:*.gz=01;31:*.lrz=01;31:*.lz=01;31:*.lzo=01;31:*.xz=01;31:*.zst=01;31:*.tztst=01;31:*.bz2=01;31:*.bz=01;31:*.tbz=01;31:*.tbz2=01;31:*.tz=01;31:*.deb=01;31:*.rpm=01;31:*.jar=01;31:*.war=01;31:*.ear=01;31:*.sar=01;31:*.rar=01;31:*.alz=01;31:*.ace=01;31:*.zoo=01;31:*.cpio=01;31:*.7z=01;31:*.rz=01;31:*.cab=01;31:*.wim=01;31:*.swm=01;31:*.dwm=01;31:*.esd=01;31:*.avif=01;35:*.jpg=01;35:*.jpeg=01;35:*.mjpg=01;35:*.mjpeg=01;35:*.gif=01;35:*.bmp=01;35:*.pbm=01;35:*.pgm=01;35:*.ppm=01;35:*.tga=01;35:*.xbm=01;35:*.xpm=01;35:*.tif=01;35:*.tiff=01;35:*.png=01;35:*.svg=01;35:*.svgz=01;35:*.mng=01;35:*.pcx=01;35:*.mov=01;35:*.mpg=01;35:*.mpeg=01;35:*.m2v=01;35:*.mkv=01;35:*.webm=01;35:*.webp=01;35:*.ogm=01;35:*.mp4=01;35:*.m4v=01;35:*.mp4v=01;35:*.vob=01;35:*.qt=01;35:*.nuv=01;35:*.wmv=01;35:*.asf=01;35:*.rm=01;35:*.rmvb=01;35:*.flc=01;35:*.avi=01;35:*.fli=01;35:*.flv=01;35:*.gl=01;35:*.dl=01;35:*.xcf=01;35:*.xwd=01;35:*.yuv=01;35:*.cgm=01;35:*.emf=01;35:*.ogv=01;35:*.ogx=01;35:*.aac=00;36:*.aue=00;36:*.flac=00;36:*.m4a=00;36:*.mid=00;36:*.midi=00;36:*.mka=00;36:*.mp3=00;36:*.mpc=00;36:*.ogg=00;36:*.ra=00;36:*.wav=00;36:*.oga=00;36:*.opus=00;36:*.spx=00;36:*.xspf=00;36:*.old=00;90:*.orig=00;90:*.part=00;90:*.rej=00;90:*.swp=00;90:*.tmp=00;90:*.dpkg-dist=00;90:*.dpkg-old=00;90:*.ucf-dist=00;90:*.ucf-new=00;90:*.ucf-old=00;90:*.rpmsave=00;90:*.rpmorig=00;90:*.rpmsave=00;90:
WAYLAND_DISPLAY=wayland-0
LESSCLOSE=/usr/bin/lesspipe %s %s
TERM=xterm-256color
LESSOPEN=| /usr/bin/lesspipe %s
USER=jella_pragathi
DISPLAY=:0
SHLVL=1
XDG_RUNTIME_DIR=/run/user/1000
DEBUGINFOD_URLS=https://debuginfod.ubuntu.com
```

```
jella_pragathi@LAPTOP-RQQK: ~
WSLENV=
XDG_DATA_DIRS=/usr/local/share:/usr/share:/var/lib/snapd/desktop
PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/usr/local/games:/usr/lib/wsl/lib:/mnt/c/Program Files/WindowsApps/MicrosoftCorporationII.WindowsSubsystemForLinux.2.7.11.0_x64_8wekyb3d8bbwe:/mnt/c/Program Files/Common Files/Oracle/Java/javapath:/mnt/c/Program Files (x86)/Common Files/Oracle/Java/javapath:/mnt/c/windows/system32:/mnt/c/windows:/mnt/c/windows/System32/Wbem:/mnt/c/windows/System32/WindowsPowerShell/v1.0:/mnt/c/windows/System32/OpenSSH:/mnt/c/Users/jella_pragathi/Downloads/gcc-15.1.0/bin:/mnt/c/Program Files/Git/cmd:/mnt/c/Program Files/nodejs:/mnt/c/Program Files/MySQL/MySQL Shell 8.0/bin:/mnt/c/Users/jella_pragathi/AppData/Local/Programs/Python/Python314/Script s:/mnt/c/Users/jella_pragathi/AppData/Local/Programs/Python/Python314:/mnt/c/Users/jella_pragathi/AppData/Local/Microsoft/WindowsApps:/mnt/c/Users/jella p ragathi/AppData/Local/Programs/Microsoft VS Code/bin:/mnt/c/Users/jella_pragathi/AppData/Roaming/npm:/snap/bin
DBUS_SESSION_BUS_ADDRESS=unix:path=/run/user/1000/bus
HOSTTYPE=x86_64
PULSE_SERVER=unix:/mnt/wslg/PulseServer
OLDPWD=/home/jella_pragathi
./session10_export
myshell$ export COLLEGE=KLU
Exported: COLLEGE=KLU
myshell$ env
SHELL=/bin/bash
WSL2_GUI_APPS_ENABLED=1
WSL_DISTRO_NAME=Ubuntu
NAME=Pragathi
PWD=/home/jella_pragathi/OSSP
LOGNAME=jella_pragathi
HOME=/home/jella_pragathi
LANG=C.UTF-8
WSL_INTEROP=/run/WSL/339.interop
LS_COLORS=rs=0:di=01;34:ln=01;36:mh=00:pi=40;33:so=01;35:do=01;35:bd=40;33;01:cd=40;33;01:or=40;31;01:mi=00:su=37;41:sg=30;43:ca=00:tw=30;42:ow=34;42:st=37;40:ex=01;32:*.tar=01;31:*.tgz=01;31:*.arc=01;31:*.arj=01;31:*.taz=01;31:*.lha=01;31:*.lz4=01;31:*.lzh=01;31:*.lзма=01;31:*.tlz=01;31:*.txz=01;31:*.tzo=01;31:*.t7z=01;31:*.zip=01;31:*.z=01;31:*.dz=01;31:*.gz=01;31:*.lrz=01;31:*.lz=01;31:*.lzo=01;31:*.xz=01;31:*.zst=01;31:*.tztst=01;31:*.bz2=01;31:*.bz=01;31:*.tbz=01;31:*.tbz2=01;31:*.tz=01;31:*.deb=01;31:*.rpm=01;31:*.jar=01;31:*.war=01;31:*.ear=01;31:*.sar=01;31:*.rar=01;31:*.alz=01;31:*.ace=01;31:*.zoo=01;31:*.cpio=01;31:*.7z=01;31:*.rz=01;31:*.cab=01;31:*.wim=01;31:*.swm=01;31:*.dwm=01;31:*.esd=01;31:*.avif=01;35:*.jpg=01;35:*.jpeg=01;35:*.mjpg=01;35:*.mjpeg=01;35:*.gif=01;35:*.bmp=01;35:*.pbm=01;35:*.pgm=01;35:*.ppm=01;35:*.tga=01;35:*.xbm=01;35:*.xpm=01;35:*.tif=01;35:*.tiff=01;35:*.png=01;35:*.svg=01;35:*.svgz=01;35:*.mng=01;35:*.pcx=01;35:*.mov=01;35:*.mpg=01;35:*.mpeg=01;35:*.m2v=01;35:*.mkv=01;35:*.webm=01;35:*.webp=01;35:*.ogm=01;35:*.mp4=01;35:*.m4v=01;35:*.mp4v=01;35:*.vob=01;35:*.qt=01;35:*.nuv=01;35:*.wmv=01;35:*.asf=01;35:*.rm=01;35:*.rmvb=01;35:*.flc=01;35:*.avi=01;35:*.fli=01;35:*.flv=01;35:*.gl=01;35:*.dl=01;35:*.xcf=01;35:*.xwd=01;35:*.yuv=01;35:*.cgm=01;35:*.emf=01;35:*.ogv=01;35:*.ogx=01;35:*.aac=00;36:*.aue=00;36:*.flac=00;36:*.m4a=00;36:*.mid=00;36:*.midi=00;36:*.mka=00;36:*.mp3=00;36:*.mpc=00;36:*.ogg=00;36:*.ra=00;36:*.wav=00;36:*.oga=00;36:*.opus=00;36:*.spx=00;36:*.xspf=00;36:*.old=00;90:*.orig=00;90:*.part=00;90:*.rej=00;90:*.swp=00;90:*.tmp=00;90:*.dpkg-dist=00;90:*.dpkg-old=00;90:*.ucf-dist=00;90:*.ucf-new=00;90:*.ucf-old=00;90:*.rpmsave=00;90:*.rpmorig=00;90:*.rpmsave=00;90:
WAYLAND_DISPLAY=wayland-0
LESSCLOSE=/usr/bin/lesspipe %s %s
TERM=xterm-256color
```

```
LESSOPEN=| /usr/bin/lesspipe %s
USER=jella_pragathi
DISPLAY=:0
SHLVL=1
XDG_RUNTIME_DIR=/run/user/1000
DEBUGINFOD_URLS=https://debuginfod.ubuntu.com
WSLENV=
XDG_DATA_DIRS=/usr/local/share:/usr/share:/var/lib/snapd/desktop
PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/usr/local/games:/usr/lib/wsl/lib:/mnt/c/Program Files/WindowsApps/MicrosoftCorporationII.WindowsSubsystemForLinux.2.7.11.0_x64_8wekyb3d8bbwe:/mnt/c/Program Files/Common Files/Oracle/Java/javapath:/mnt/c/Program Files (x86)/Common Fil es/Oracle/Java/javapath:/mnt/c/Program Files (x86)/Common Files/Oracle/Java/javapath:/mnt/c/windows/system32:/mnt/c/windows:/mnt/c/windows/System32/Wbem:/m nt/c/windows/System32/WindowsPowerShell/v1.0:/mnt/c/windows/System32/OpenSSH:/mnt/c/Users/jella_pragathi/Downloads/gcc-15.1.0/bin:/mnt/c/Program Files/Git /cmd:/mnt/c/Program Files/nodejs:/mnt/c/Program Files/MySQL/MySQL Shell 8.0/bin:/mnt/c/Users/jella_pragathi/AppData/Local/Programs/Python/Python314/Script s:/mnt/c/Users/jella_pragathi/AppData/Local/Programs/Python/Python314:/mnt/c/Users/jella_pragathi/AppData/Local/Microsoft/WindowsApps:/mnt/c/Users/jella p ragathi/AppData/Local/Programs/Microsoft VS Code/bin:/mnt/c/Users/jella_pragathi/AppData/Roaming/npm:/snap/bin
DBUS_SESSION_BUS_ADDRESS=unix:path=/run/user/1000/bus
HOSTTYPE=x86_64
PULSE_SERVER=unix:/mnt/wslg/PulseServer
OLDPWD=/home/jella_pragathi
./session10_export
COLLEGE=KLU
myshell$ export 123NAME=test
export: invalid variable name: 123NAME
myshell$ export NAME
export: invalid syntax
Usage: export NAME=value
myshell$ exit
jella_pragathi@LAPTOP-RQQK$ nano session10_export.c
```