School of Computer Science

UNIVERSITY OF PETROLEUM AND ENERGY STUDIES

DEHRADUN, UTTARAKHAND



System Monitoring and Configuration Management

Lab File

(2024)

for

6th Semester

Submitted To:

Dr. Hitesh Kumar Sharma

Submitted By:


Eksha Malhotra
B. Tech. CSE DevOp
[6^h Semester]
Sap id- 500091532
Batch 1
R2142210300

LAB EXERCISE 11

<u>Aim</u>- Configure Ansible Setup In Linux

Steps

1. Create two Amazon Linux t2.micro instance - Ansible Server & Node



2. Install ansible on Ansible Server

[root@ip-172-31-11-127 ec2-user]# |

```
[ec2-user@ip-172-31-11-127 ~]$ sudo su
[root@ip-172-31-11-127 ec2-user]# ls
[root@ip-172-31-11-127 ec2-user]# cat ansible.sh
wget https://dl.fedoraproject.org/pub/epel/epel-release-latest-7.noarch.rpm
yum install epel-release-latest-7.noarch.rpm
yum update -y
yum install git python python-pip openssl -y
yum install ansib<u>le</u>
[root@ip-172-31-11-127 ec2-user]# ./ansible.sh
--2024-04-20 20:19:47-- https://dl.fedoraproject.org/pub/epel/epel-release-latest-7.noarch.rpm
Resolving dl.fedoraproject.org (dl.fedoraproject.org)... 38.145.60.22, 38.145.60.23, 38.145.60.24
Connecting to dl.fedoraproject.org (dl.fedoraproject.org)|38.145.60.22|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 15608 (15K) [application/x-rpm]
Saving to: 'epel-release-latest-7.noarch.rpm.1'
100%[===================] 15,608
                                                                                           58.6KB/s
                                                                                                     in 0.3s
.....
                                                                                  5.0 MB/s | 17 MB 00:00:03
Total
Running transaction check
Running transaction test
Transaction test succeeded
Running transaction
 Installing: python2-httplib2-0.18.1-3.el7.noarch
                                                                                                            2/4
 Installing : sshpass-1.06-1.el7.x86_64
 Installing: python-paramiko-2.1.1-0.10.el7.noarch
                                                                                                            3/4
 Installing: ansible-2.9.27-1.el7.noarch
                                                                                                            4/4
 Verifying : python-paramiko-2.1.1-0.10.el7.noarch
                                                                                                            1/4
           : sshpass-1.06-1.el7.x86_64
                                                                                                            2/4
 Verifying
           : python2-httplib2-0.18.1-3.el7.noarch
                                                                                                            3/4
 Verifying
 Verifying
           : ansible-2.9.27-1.el7.noarch
                                                                                                            4/4
Installed:
 ansible.noarch 0:2.9.27-1.el7
Dependency Installed:
                                          python2-httplib2.noarch 0:0.18.1-3.el7
 python-paramiko.noarch 0:2.1.1-0.10.el7
                                                                                  sshpass.x86_64 0:1.06-1.el7
```

```
root@ip-172-31-11-127:/home/ec2-user

[root@ip-172-31-11-127 ec2-user]# ansible --version
ansible 2.9.27
config file = /etc/ansible/ansible.cfg
configured module search path = [u'/root/.ansible/plugins/modules', u'/usr/share/ansible/plugins/modules']
ansible python module location = /usr/lib/python2.7/site-packages/ansible
executable location = /bin/ansible
python version = 2.7.18 (default, Dec 18 2023, 22:08:43) [GCC 7.3.1 20180712 (Red Hat 7.3.1-17)]
[root@ip-172-31-11-127 ec2-user]# [
```

3. Add Private IP of node to the Ansible server's inventory file

```
root@ip-172-31-11-127 ec2-user]# ansible --version
ansible 2.9.27
config file = /etc/ansible/ansible.cfg
configured module search path = [u'/root/.ansible/plugins/modules', u'/usr/share/ansible/plugins/modules']
ansible python module location = /usr/tib/python2.7/site-packages/ansible
executable location = /bin/ansible
python version = 2.7.18 (default, Dec 18 2023, 22:08:43) [GCC 7.3.1 20180712 (Red Hat 7.3.1-17)]
[root@ip-172-31-11-127 ec2-user]# vi /etc/ansible/hosts
[root@ip-172-31-11-127 ec2-user]# []

# Here's another example of host ranges, this time there are no
# leading 0s:

## db-[99:101]-node.example.com

[upes]
172.31.5.83

***
```

Create super user in both the machines





5. Give sudo user permissions to both users

```
MACHINE=COMMANDS
##
## The COMMANDS section may have other options added to it.
##
## Allow root to run any commands anywhere
                        ALL
       ALL=(ALL)
root
ansible ALL=(ALL)
                      NOPASSWD: ALL
## Allows members of the 'sys' group to run networking, softwar
## service management apps and more.
# %sys ALL = NETWORKING, SOFTWARE, SERVICES, STORAGE, DELEGATIN
## The COMMANDS section may have other options added to it.
## Allow root to run any commands anywhere
        ALL=(ALL)
                        ALL
root
ansiblenode ALL=(ALL)
                          NOPASSWD: ALL
## Allows members of the 'sys' group to run networking, sof
## service management apps and more.
# %sys ALL = NETWORKING, SOFTWARE, SERVICES, STORAGE, DELEG
```

6. Edit the sshd_config file in the node server

```
Ð
                                    root@ip-172-31-5-83:/home/ec2-user
[root@ip-172-31-5-83 ec2-user]# visudo
[root@ip-172-31-5-83 ec2-user]# nano /etc/ssh/sshd_config
[root@ip-172-31-5-83 ec2-user]# |
#LOGLEVEL INFO
# Authentication:
#LoginGraceTime 2m
PermitRootLogin yes
#StrictModes yes
# Don't read the user's ~/.rhosts and ~/.shosts files
#IgnoreRhosts yes
# To disable tunneled clear text passwords, change to no here!
PasswordAuthentication yes
#PermitEmptyPasswords no
#PasswordAuthentication no
```

```
root@ip-172-31-5-83:/home/ec2-user

[root@ip-172-31-5-83 ec2-user]# visudo
[root@ip-172-31-5-83 ec2-user]# nano /etc/ssh/sshd_config
[root@ip-172-31-5-83 ec2-user]# service sshd restart

Redirecting to /bin/systemctl restart sshd.service
[root@ip-172-31-5-83 ec2-user]# [
```

7. Generate key pair in Ansible server and copy the key to node server

```
Q
 Ξ
                                                                                                               O
                                                ansible@ip-172-31-11-127:~
                                                                                                    Ħ
                                                                                                                    ×
[ansible@ip-172-31-11-127 ~]$ ssh-key
-bash: ssh-key: command not found
[ansible@ip-172-31-11-127 ~]$ ssh-keygen
Generating public/private rsa key pair.
Enter file in which to save the key (/home/ansible/.ssh/id_rsa):
/home/ansible/.ssh/id_rsa already exists.
Overwrite (y/n)? y
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /home/ansible/.ssh/id_rsa.
Your public key has been saved in /home/ansible/.ssh/id_rsa.pub.
The key fingerprint is:
SHA25ó:WciCBF7n9Wn5bE6bw5SX67C7unBGgD+qUFrBy2Zf0XI ansible@ip-172-31-11-127.ap-south-1.compute.internal
The key's randomart image is:
+---[RSA 2048]---
  . + + + + 0
   . + + * E
    . 0 0 0 0 . .
      S.Bo
    В
    * . 0 0 * + .
      о.ов.
           00+0.
 ----[SHA256]----+
[ansible@ip-172-31-11-127 ~]$ ssh-copy-id ansiblenode@172.31.5.83
/usr/bin/ssh-copy-id: INFO: Source of key(s) to be installed: "/home/ansible/.ssh/id_rsa.pub"
/usr/bin/ssh-copy-id: INFO: attempting to log in with the new key(s), to filter out any that are already installed
/usr/bin/ssh-copy-id: INFO: 1 key(s) remain to be installed -- if you are prompted now it is to install the new keys
ansiblenode@172.31.5.83's password:
Number of key(s) added: 1
Now try logging into the machine, with: "ssh 'ansiblenode@172.31.5.83'"
and check to make sure that only the key(s) you wanted were added.
[ansible@ip-172-31-11-127 ~]$
```

8. Connect to node server from ansible server