Unit - 3

1D Array in C

A one-dimensional (1D) array is a collection of elements of the same data type stored in contiguous memory locations. Each element is accessed using an index.

Declaration of 1D Array

Array declaration specifies the data type, array name, and number of elements.

Syntax: data_type array_name[size];

Example: int marks[5];

This declares an integer array named marks that can store five elements.

Array indexing:

Element	Index
First element	0
Second element	1
Third element	2
Fourth element	3
Fifth element	4

In C, array indexing starts from 0 and ends at size - 1.

Input in 1D Array

The scanf() function is used to take input for array elements.

Example:

```
int a[5], i;
for (i = 0; i < 5; i++)
{
   scanf("%d", &a[i]);
}
```

The loop takes input for all five elements, one by one.

Output of 1D Array

The printf() function is used to display array elements.

Example:

```
int a[5] = {10, 20, 30, 40, 50};
int i;
for (i = 0; i < 5; i++)
{
   printf("%d ", a[i]);
}
```

Output: 10 20 30 40 50

Traversal of 1D Array

Array traversal is the process of visiting and accessing each element of an array one by one.

A for loop is commonly used for traversal.

Syntax:

```
for (i = 0; i < size; i++)
{
   // Process array element
}
```

Example:

```
#include <stdio.h>
int main()
{
   int a[5] = {10, 20, 30, 40, 50};
   int i;
   for (i = 0; i < 5; i++)
   {
      printf("a[%d] = %d\n", i, a[i]);
   }
   return 0;
}
```

Output:

a[0] = 10

a[1] = 20

a[2] = 30

a[3] = 40

a[4] = 50

Complete Program: Input, Output and Traversal

```
#include <stdio.h>
int main()
{
   int a[5], i;
   printf("Enter 5 elements:\n");
   for (i = 0; i < 5; i++)
   {
      scanf("%d", &a[i]);
   }
   printf("Array elements are:\n");
   for (i = 0; i < 5; i++)
   {
      printf("%d ", a[i]);
   }
   return 0;
}
```

Input:

10 20 30 40 50

Output:

Array elements are:

10 20 30 40 50

1. Find Maximum Element in a 1D Array

```
#include <stdio.h>

int main()

{

int a[5] = {10, 25, 5, 40, 15};

int i, max = a[0];

for (i = 1; i < 5; i++)

{

if (a[i] > max)

max = a[i];

}

printf("Maximum = %d", max);

return 0;

}
```

Output:

Maximum = 40

2. Find Minimum Element in a 1D Array

```
#include <stdio.h>

int main()

{

int a[5] = {10, 25, 5, 40, 15};

int i, min = a[0];

for (i = 1; i < 5; i++)

{
```

```
if (a[i] < min)

min = a[i];

}

printf("Minimum = %d", min);

return 0;

}
```

Output:

Minimum = 5

3. Find Sum of Elements in a 1D Array

```
#include <stdio.h>

int main()

{

int a[5] = {10, 20, 30, 40, 50};

int i, sum = 0;

for (i = 0; i < 5; i++)

{

sum = sum + a[i];

}

printf("Sum = %d", sum);

return 0;

}
```

Output:

Sum = 150

4. Find Average of Elements in a 1D Array

```
#include <stdio.h>

int main()

{

int a[5] = {10, 20, 30, 40, 50};

int i, sum = 0;

float avg;

for (i = 0; i < 5; i++)

{

sum = sum + a[i];

}

avg = (float)sum / 5;

printf("Average = %.2f", avg);

return 0;

}
```

Output:

Average = 30.00

ASCII values

In C, every character has a numerical value called an ASCII value. ASCII value is a number assigned to a character so that a computer can represent and process it.

ASCII values of characters

In C, every character has a numerical value called an ASCII value. In Program 19, these values are used to store the frequency of each character.

ASCII values of characters

Capital letters (A–Z)

Character	ASCII value
A	65
B	66
C	67
D	68
E	69
F	70
G	71
H	72
I	73
J	74
K	75
L	76
M	77
N	78
O	79
P	80
Q	81
R	82
S	83
T	84
U	85
V	86
W	87
X	88
Y	89
Z	90

Small letters (a–z)

Character	ASCII value
a	97
b	98
c	99
d	100
e	101
f	102
g	103
h	104
i	105
j	106
k	107
l	108
m	109
n	110
o	111
p	112
q	113
r	114
s	115
t	116
u	117
v	118
w	119
x	120
y	121
z	122

Digits (0–9)

Character	ASCII value
'0'	48
'1'	49
'2'	50
'3'	51
'4'	52
'5'	53
'6'	54
'7'	55
'8'	56
'9'	57

Program to print ASCII values

```
#include <stdio.h>

int main()

{

    char ch;

    printf("Enter a character: ");

    scanf("%c", &ch);

    printf("Character = %c\n", ch);

    printf("ASCII value = %d", ch);

    return 0;

}
```

Output:

```
Enter a character: A

Character = A

ASCII value = 65
```

Strings in C

A string in C is a sequence of characters terminated by the null character '\0'. Strings are stored in character arrays.

Example:

char str[20] = "Hello";

Header file required for string functions:

#include <string.h>

Example: -

```
#include <stdio.h>

int main()

{

   char str[100];

   printf("Enter a string: ");

   scanf("%s", str);

   printf("String = %s", str);

   return 0;

}
```

Output

Enter a string: Hello

String = Hello

In C, an array name automatically behaves like a pointer to its first element in most expressions. This is called array-to-pointer conversion.

1. Understand with an example

char str[5] = {'H', 'e', 'l', 'l', 'o'};

The array name str refers to the beginning of this array in most expressions.

- str points to the first character, H.
- &str[0] is the address of the first character.
- str[0] is the character H.

For a char array, str and &str[0] represent the same starting address when used in this context.

2. Why does scanf() need str, not &str?

scanf("%s", str);

scanf() needs the address where it should store the characters.

When you pass str, C automatically converts the array name to a pointer to its first element.

This is effectively equivalent to:

scanf("%s", &str[0]);

But &str is different: it represents the address of the entire array, with type char (*)[5] in this example, rather than a pointer to its first character.

3. Remember this rule

Expression	**Meaning**
str	Converts to a pointer to the first character in most expressions
str[0]	First character
&str[0]	Address of the first character
&str	Address of the entire array

In C, an array name is automatically converted into a pointer to its first element in most expressions. Therefore, scanf("%s", str) is correct because scanf() receives the address of the first character where it can store the input string.

1. gets() and puts()

gets() is used to read a string from the keyboard, including spaces. However, it is unsafe because it does not check the array size and has been removed from the C11 standard. Use fgets() instead.

Syntax:

fgets(str, sizeof(str), stdin);

puts() is used to display a string on the screen and automatically adds a newline.

Syntax:

puts(str);

Example:

```
#include <stdio.h>

int main()

{

   char str[50];

   printf("Enter a string: ");

   fgets(str, sizeof(str), stdin);

   puts(str);

   return 0;

}
```

Output:

Enter a string: Hello World

Hello World

Program: Read and Print a String with Spaces

```
#include <stdio.h>

int main()

{

   char str[100];
```

```
    printf("Enter a string: ");
    fgets(str, sizeof(str), stdin);
    printf("String = %s", str);
    return 0;
}
```

Output:

Enter a string: Hello World

String = Hello World

2. strlen()

The strlen() function returns the length of a string, excluding the null character '\0'.

Syntax: strlen(string);

Example:

```
#include <stdio.h>
#include <string.h>
int main()
{
    char str[] = "Hello";
    printf("Length = %d", (int)strlen(str));
    return 0;
}
```

Output:

Length = 5

3. strcpy()

The strcpy() function copies the source string into the destination string, including the terminating null character.

Syntax:

strcpy(destination, source);

Example:

```
#include <stdio.h>
#include <string.h>
int main()
{
    char source[] = "Hello";
    char destination[20];
    strcpy(destination, source);
    printf("%s", destination);
    return 0;
}
```

Output:

Hello

Program: Copy a String Without Using strcpy()

```
#include <stdio.h>
int main()
{
    char str1[100], str2[100];
    int i = 0;
    printf("Enter a string: ");
    scanf("%s", str1);
    while (str1[i] != '\0')
```

```
    {
        str2[i] = str1[i];
        i++;
    }
    str2[i] = '\0';
    printf("Copied string = %s", str2);
    return 0;
}
```

Output:

Enter a string: Hello

Copied string = Hello

Explanation:

- The loop copies each character of str1 into str2.
- The loop stops when it reaches '\0'.
- str2[i] = '\0' adds the string terminator to the copied string.
- str2 can then be printed using %s.

4. strcmp()

The strcmp() function compares two strings lexicographically, character by character.

Syntax:

strcmp(string1, string2);

Return values:

- 0 — both strings are equal.
- Negative value — the first string is smaller.
- Positive value — the first string is greater.

Example:

```
#include <stdio.h>
#include <string.h>
int main() {
   char str1[100], str2[100];
   int result;
   printf("Enter first string: ");
   scanf("%s", str1);
   printf("Enter second string: ");
   scanf("%s", str2);
   result = strcmp(str1, str2);
   if (result == 0)
      printf("Strings are equal");
   else if (result < 0)
      printf("%s is smaller than %s", str1, str2);
   else
      printf("%s is greater than %s", str1, str2);
   return 0;
}
```

Input

```
Enter first string: android
Enter second string: ankit
```

Output

```
android is smaller than ankit
```

Explanation

The strcmp() function compares two strings character by character using their ASCII values.

Position	First string	ASCII	Second string	ASCII
1	a	97	a	97
2	n	110	n	110
3	d	100	k	107

1). Position 1: a = 97 and a = 97. Both characters are equal, so comparison continues.

2). Position 2: n = 110 and n = 110. Both characters are equal, so comparison continues.

3). Position 3: d = 100 and k = 107. The characters are different.

Since 100 < 107, the comparison result is negative. Therefore, android is smaller than ankit.

Important: As soon as strcmp() finds the first different characters, it determines the result and stops comparing further characters. It does not compare the remaining characters.

For example, it does not need to compare roid with it because the difference has already been found at position 3.

- result == 0 → Strings are equal.
- result < 0 → First string is smaller.
- result > 0 → First string is greater.

Difference Between String Functions

Function	Purpose
fgets()	Reads a string safely with a specified size limit.
puts()	Displays a string followed by a newline.
strlen()	Calculates the length of a string.
strcpy()	Copies one string into another.
strcmp()	Compares two strings.

Program: Concatenate Two Strings Using strcat()

```
#include <stdio.h>

#include <string.h>

int main()

{

   char str1[200], str2[100];

   printf("Enter first string: ");

   scanf("%s", str1);

   printf("Enter second string: ");

   scanf("%s", str2);

   strcat(str1, str2);

   printf("Concatenated string = %s", str1);

   return 0;

}
```

Output:

Enter first string: Hello

Enter second string: World

Concatenated string = HelloWorld

Explanation:

- Concatenation means joining two strings.
- strcat(str1, str2) appends str2 to the end of str1.
- The destination array str1 must have enough space for both strings and the terminating '\0'.

Program: Count Alphabets, Digits and Special Characters

```
#include <stdio.h>

int main()

{

   char str[100];

   int i = 0, alphabets = 0, digits = 0, special = 0;

   printf("Enter a string: ");

   scanf("%s", str);

   while (str[i] != '\0')

   {

      if ((str[i] >= 'A' && str[i] <= 'Z') ||

         (str[i] >= 'a' && str[i] <= 'z'))

         alphabets++;

      else if (str[i] >= '0' && str[i] <= '9')

         digits++;

      else

         special++;


      i++;

   }

   printf("Alphabets = %d\n", alphabets);

   printf("Digits = %d\n", digits);

   printf("Special characters = %d", special);

   return 0;
```

}

Output:

Enter a string: Abc123@

Alphabets = 3

Digits = 3

Special characters = 1

Explanation:

- The first condition checks whether a character is an uppercase or lowercase English letter.
- The second condition checks whether it is a digit from 0 to 9.
- Any remaining character is counted as a special character.
- Because scanf("%s", str) stops at whitespace, spaces are not included in this input.