VARDHAMAN
COLLEGE OF ENGINEERING
(AUTONOMOUS)
Affiliated to JNTUH, Approved by AICTE, Accredited by NAAC with A++ Grade, ISO 9001:2015 Certified
Kacharam, Shamshabad, Hyderabad – 501218, Telangana,
India DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING (AI&ML)

Literature Survey Summary

Recent advancements in artificial intelligence have significantly influenced symbolic music generation by adapting sequence-learning and language modeling techniques to musical data. Researchers increasingly treat music as a structured sequence similar to language, enabling deep learning models to learn temporal and stylistic relationships from symbolic representations such as MIDI.

Mon [1] explored LSTM-based music generation approaches, demonstrating how recurrent neural networks effectively capture temporal dependencies required for coherent musical composition. The study highlighted LSTM models as suitable for sequential creative tasks due to their memory mechanisms.

Wang and Gong [2] introduced heterogeneous AI frameworks that combine multiple learning strategies to improve controllability in music generation systems. Their work emphasized fine-grained control over musical attributes during synthesis.

Huo et al. [3] proposed an LSTM framework designed specifically for soundtrack synthesis, showing that recurrent architectures can generate structured musical sequences while maintaining stylistic consistency across compositions.

Mitra and Zuakerman [4] conducted a systematic review of deep learning and generative AI techniques in music generation, identifying neural sequence models as a dominant approach for symbolic composition tasks.

Mangal et al. [5] developed an LSTM-based music generation system using encoded MIDI sequences, demonstrating that sequential training enables prediction of musically meaningful note progressions.

Zhao et al. [6] surveyed text-to-music generation frameworks and highlighted the growing integration of natural language processing with music synthesis pipelines, motivating systems that translate textual intent into musical output.

Eck and Schmidhuber [7] presented one of the earliest applications of LSTM networks for blues improvisation, proving that recurrent models can learn long-term musical structure and stylistic continuity.

Boulanger-Lewandowski et al. [8] investigated temporal dependency modeling in polyphonic music generation, showing how neural networks can represent complex multi-note relationships within high-dimensional sequences.

Hadjeres et al. [9] introduced DeepBach, a controllable generative model capable of producing stylistically accurate chorale compositions, demonstrating the importance of structured learning in symbolic music synthesis.

Huang et al. [10] proposed the Music Transformer architecture, illustrating how attention mechanisms improve long-term structural modeling in music generation compared to traditional recurrent networks.

Oore et al. [11] focused on expressive musical performance modeling, showing that neural networks can learn timing and dynamics beyond symbolic notation to produce more human-like outputs.

Dong et al. [12] introduced MuseGAN, a generative adversarial network designed for multi-track symbolic music creation, enabling coordinated generation across multiple instruments.

Roberts et al. [13] proposed hierarchical latent vector models to capture long-range musical structure, emphasizing the importance of multi-level representation learning for coherent compositions.

Briot et al. [14] provided a comprehensive survey of deep learning techniques in music generation, outlining challenges related to evaluation, representation, and creativity in AI-generated music.

Ji et al. [15] reviewed deep music generation methods across multiple representation levels, highlighting sequence modeling as a core component for learning musical patterns.

Additional supporting literature [16] discusses symbolic music representation and NLP–music integration, reinforcing the idea that token-based representations enable effective modeling of musical sequences using deep learning.

Overall, prior research demonstrates that sequence-based neural architectures play a central role in modern music generation systems. Building upon these findings, the present work employs an LSTM-based framework combined with text-driven genre prediction to generate stylistically guided MIDI compositions efficiently.

References:

[1] Y. J. Mon, "LSTM-Based Music Generation Technologies," *Computers*, vol. 14, no. 6, p. 229, 2025.

[2] H. Wang and L. Gong, "Heterogeneous AI Music Generation Technology Integrating Fine-Grained Control," *IEEE Access*, 2025.

[3] Y. Huo, M. Jin, and S. You, "LSTM-Based Framework for the Synthesis of Original Soundtracks," *IEEE Access*, vol. 12, pp. 33832–33842, 2024.

[4] R. Mitra and I. Zualkernan, "Music Generation Using Deep Learning and Generative AI: A Systematic Review," *IEEE Access*, 2025.

[5] S. Mangal, R. Modak, and P. Joshi, "LSTM Based Music Generation System," *arXiv preprint arXiv:1908.01080*, 2019.

[6] Y. Zhao et al., "AI-Enabled Text-to-Music Generation: A Comprehensive Review of Methods, Frameworks, and Future Directions," *Electronics*, vol. 14, no. 6, p. 1197, 2025.

[7] D. Eck and J. Schmidhuber, "Finding Temporal Structure in Music: Blues Improvisation with LSTM Recurrent Networks," in *Proceedings of the IEEE Workshop on Neural Networks for Signal Processing*, 2002, pp. 747–756.

[8] N. Boulanger-Lewandowski, Y. Bengio, and P. Vincent, "Modeling Temporal Dependencies in High-Dimensional Sequences: Application to Polyphonic Music Generation," in *Proceedings of the 29th International Conference on Machine Learning (ICML)*, 2012.

[9] G. Hadjeres, F. Pachet, and F. Nielsen, "DeepBach: A Steerable Model for Bach Chorales Generation," in *Proceedings of the 34th International Conference on Machine Learning (ICML)*, 2017.

[10] C.-A. Huang et al., "Music Transformer: Generating Music with Long-Term Structure," in *Proceedings of the International Conference on Learning Representations (ICLR)*, 2018.

[11] S. Oore, I. Simon, S. Dieleman, and D. Eck, "This Time with Feeling: Learning Expressive Musical Performance," *Neural Computing and Applications*, vol. 32, no. 4, pp. 955–967, 2020.

[12] H.-W. Dong, W.-Y. Hsiao, L.-C. Yang, and Y.-H. Yang, "MuseGAN: Multi-Track Sequential Generative Adversarial Networks for Symbolic Music Generation," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 32, no. 1, 2018.

[13] A. Roberts, J. Engel, C. Raffel, C. Hawthorne, and D. Eck, "A Hierarchical Latent Vector Model for Learning Long-Term Structure in Music," in *Proceedings of the 35th International Conference on Machine Learning (ICML)*, 2018.

[14] J.-P. Briot, G. Hadjeres, and F. Pachet, "Deep Learning Techniques for Music Generation: A Survey," *IEEE Transactions on Emerging Topics in Computational Intelligence*, vol. 4, no. 1, pp. 43–58, 2020.

[15] S. Ji, J. Luo, and X. Yang, "A Comprehensive Survey on Deep Music Generation: Multi-Level Representations, Algorithms, Evaluations, and Future Directions," *arXiv preprint arXiv:2011.06801*, 2019.

[16] Additional supporting literature on symbolic music representation, NLP–music integration, and sequence modeling aligned with recent AI music generation research.

Signature of the Supervisor **Signature of Coordinator** **Signature of HOD**