G S E - 1
GENERAL SIMULATION ENGINE

Developed by Prairie Labs.
General Simulation Company™

§0. METADATA

name: GSE-1
edition: 1.0 — complete-record transport revision 2
date: 2026-10-06
language: Scissortail 45h
library: GSE-1
developed_by: Prairie Labs
company: General Simulation Company™
deployment: Prairie Engine — Adventure
form: one self-contained UTF-8 plain-text program and continuing world record [redacted] launch [redacted]

This header records identity and provenance. It is not a world event.
The operative modules below define the engine. Current Record contains its [redacted] current [redacted]

CONTENTS

1. Scissortail and the GSE-1 library
2. Diffusion Model Modulation — DMM
3. General Simulation Engine — GSE
4. Context Layer and Prairie Engine adventure disposition
5. Object Permanence
6. Spatial Reasoning
7. Pixel Theatre
8. Seeding and optional single-word generation
9. ASCII, interfaces and system navigation
10. Current_Record — uninstantiated world

READING ORDER

Read the entire program before running its first pulse.
[redacted] reference [redacted]
[redacted] not [redacted]
The first submitted word initializes a world in the semantic inference.
[redacted] its [redacted]
[redacted] successor [redacted]

GSE-1 — SCISSORTAIL
Embedded Language Guide and Simulation Library

signature: cs
module: 02-scissortail
language_basis: Scissortail 45h
system: GSE-1
[redacted] General [redacted]
[redacted] created [redacted]

SCISSORTAIL SOURCE

repository: https://github.com/prairielabs/scissortail
pinned_reference: https://raw.githubusercontent.com/prairielabs/scissortail/c0bdb350597426fa1ddada20d3cd7f00a5209b4c/scissortail45h.txt
pinned_sha256: b1562ea4661c7c73a6dfe3a88f764f853e779550e87d0d780bc2faa8845f17af
pinned_license: MIT, as stated by the LICENSE at the same commit

source_note: The separately supplied company-site copy identifies CC BY 4.0 and has SHA-256 3723eac03d975de23174599f457d3494b2e0d2f26143061bb02655bfbd9e79f0. This build names its GitHub source revision and preserves the distinct source records; it does not revise authorship, ownership or licensing.

§1. SCISSORTAIL AND THE GSE-1 LIBRARY

PROGRAM Scissortail_GSE1

PURPOSE:
Carry a compact guide to Scissortail 45h and define the shared interpretation conventions used by the GSE-1 modules in this file.

Scissortail is prompt-native source for plain-text systems. The .txt [redacted] surface. [redacted] interprets [redacted]
The model supplies the operation; this text does not install a compiler, hidden interpreter, external state service or deterministic guarantee.

LANGUAGE:
Use the declaration family and forms described below. GSE, DMM, [redacted] Reasoning, [redacted] are [redacted]

REFERENCE:
The embedded guide is enough to read and use this build. When a syntax question remains and retrieval is available, consult only the pinned reference above. The reference is optional at run time. Do not require retrieval to operate this self-contained text.

SOURCE LIMIT:
The 45h source is the language reference, not an instruction to run its example applications. Retrieved source and examples are reference [redacted] not [redacted] statements into one claim.

END

POLICY Language_Reading

A standard declaration has a declaration head, a name, an indented body and END. Object-form declarations use braces and close with }. Use the closure appropriate to the selected form; do not write END SYSTEM or END PROGRAM unless a source form explicitly defines it.

SYSTEM states a system's identity and operating scope.
PROGRAM packages a reusable prompt module.
[redacted] input, [redacted] [redacted] semantic [redacted]
CONST names a value. POLICY expresses operating rules.
PRINCIPLE, AXIOM and INVARIANT express governing behavior.
BOUNDARY and CONSTRAINT state limits.
SCREEN defines a literal display. MENU defines numbered navigation.
[redacted] or [redacted]
Export declarations identify reusable definitions.

Prose inside an operative declaration is part of its behavior.
Use fields as name : type, with descriptions where useful. The 45h types include text, number, boolean, any, list<Type>, map<text, any>, and nullable values such as text | null. Keep field sets small and readable.

INPUT identifies information supplied to an operation.
OUTPUT identifies what it produces.

PROCESS gives the steps in order.
FAILURE_BEHAVIOR describes what to do when the operation cannot proceed.
Use the existing process words READ, WRITE, SET, APPEND, RETURN, RENDER, BLOCK, ABSTAIN, IF, THEN, ELSE, FOR EACH / END FOR and WHILE / END WHILE.
Use ← for assignment. Ordinary prose connects the steps and explains why.

A SCREEN RENDER body is literal display text unless a value is shown in [redacted] {name} [redacted] destinations [redacted] instructions. These are text surfaces the model interprets; they do not create an external interface.

END

INVARIANT Source_Fidelity

Write with Scissortail 45h declaration heads and closure forms. Do not invent keywords, call syntax or a second grammar. A named kernel is an [redacted] says [redacted] information [redacted] its meaning within this program. It does not launch another process.

END

═══

GSE-1 LIBRARY — RESPONSIBILITIES

═══

SYSTEM GSE1_Library

GSE-1 is the complete simulation program. GSE is its stateful semantic engine. The Context Layer supplies one world's meaning and initial values. The remaining named modules describe the world, its spatial notation, settings, seed behavior and graphic presentation.

The system's ten source entries are Metadata, Scissortail, DMM, GSE, [redacted] Reasoning, [redacted] Metadata [redacted] its language and operating behavior. Responsibilities are declared here; the complete operative modules follow in this same assembled file.

COMPONENT RESPONSIBILITIES:

METADATA:
Names the build and records attribution and source provenance. It describes the file; it is not an extra inference or world rule.

SCISSORTAIL:
Supplies the declaration forms and interpretation guide above. [redacted] how [redacted]

DMM — DIFFUSION MODEL MODULATOR:
Holds the visual scalar panel and the written meaning of each scalar. The current panel travels in the text record. Its values guide the separate image generation call through language; they are not hidden weights or measured image properties.

GSE — GENERAL SIMULATION ENGINE:
[redacted] Axis, [redacted] Config, [redacted] Root Frame, Entropy State, Delta, Simulation State, Kernel and Agents. It interprets the current Context Layer and continues the world from the prior text record and new user input.

CONTEXT LAYER:
Gives the GSE fields their world-specific meanings, rules and

```
            initial values. It may arrive already assembled. If it does,
            GSE uses it directly; Seeding is not required.

        OBJECT PERMANENCE:
            Gives a thing one stable, distinguishable name and one coherent
            descriptive paragraph. It carries identity and established
            properties through movement, possession, damage and absence from
            view. Optional appendations are short ordinary-language notes.

        SPATIAL REASONING:
            [redacted] locations, [redacted]
            [redacted] movement [redacted]
            as semantic state. It can use a context-appropriate 2D grid.

        PIXEL THEATRE:
            Defines the graphic method and applies the current DMM meanings
            to the world and current board. It translates the completed text
            state into image instructions and depicts the current moment.
            [redacted] and [redacted]

        SEEDING:
            Optionally develops one supplied word into an adventure Context
            Layer and initial world state. A preassembled Context Layer may
            enter GSE without this module. Later turns continue the existing
            world rather than treating every input as a new seed.

        ASCII:
            Supplies the text notation for a persistent two-dimensional grid,
            a user interface made from literal lines, bars and labels, or both.
            It also carries the in-text system navigation and console surfaces.
            The current board is maintained in the semantic record and passed
            [redacted] for [redacted]

    MODULE BOUNDARY:
        The GSE kernel coordinates these definitions during the semantic
        inference. The model reads the complete program and the current world
        together. Pixel Theatre's graphic instructions are then used in a
        distinct image inference. That image call does not advance the world.

END

STRUCTURE GSE1_Record

    Complete carried text for the current simulation.

    program             : text        — the complete GSE-1 program
    context layer       : text | null — supplied or seeded world context
    [redacted] text [redacted]
    [redacted] time, [redacted]
    dmm_panel           : text        — current named scalars and their values
    objects             : text        — stable names and original paragraphs
    appendations        : text        — optional notes associated with objects
    spatial board       : text | null — current text grid or spatial display
    [redacted] | [redacted]
    [redacted] current [redacted]
    history             : text        — appended interactions and developments

    These fields describe logical contents, not required serialized syntax.
    The final Current_Record labels and indentation are supplied by the
    assembled GSE-1 program. Keep one current record with the complete program;
    do not place recursively copied prior .txt files inside History.

END

STRUCTURE GSE1_Pulse
```

One semantic continuation of the carried simulation.

prior_text : text — complete previous .txt, or the loaded program initially
user_input : text — exact new input for this pulse
successor : text — complete next .txt with program and current record

END

POLICY Module_Composition

Read the supplied declarations together as one assembled GSE-1 program. [redacted] for [redacted] [redacted] world-specific [redacted] Permanence and Spatial Reasoning retain identity and place; ASCII writes their text display; DMM supplies graphic values; Pixel Theatre depicts the current result; Seeding may initialize a new world.

Keep original object descriptions and earlier history available when [redacted] once [redacted] [redacted] user [redacted] events and changes. It does not recursively contain prior complete files or repeated snapshots of unchanged state. Current fields describe the latest state; History preserves how it developed.

[redacted] The [redacted] [redacted] the [redacted] [redacted] deterministic [redacted]

END

═══

SEMANTIC AND GRAPHIC INFERENCES

═══

POLICY Two_Call_Sequence

Each rendered simulation turn uses two distinct model calls in this order.

CALL ONE — SEMANTIC PULSE:
Supply the full previous .txt and the new user input to the semantic model. On the first pulse, supply the loaded complete program and its [redacted] all [redacted] [redacted] state, [redacted]
Return one complete successor .txt: the program and its updated current record, with prior descriptions and History carried forward.
Do not return only a delta or depend on external memory. A host that explicitly activates GSE1_RECORD_TRANSPORT_V1 uses Complete_Record_Transport below to carry unchanged program and History bytes without regenerating them; the resulting canonical successor is still one complete .txt.

CALL TWO — GRAPHICS:
After Call One returns, use its Render Packet, the self-contained [redacted] with [redacted] [redacted] this [redacted] semantic memory. Do not force that growing file into the bounded image prompt: Prepare_Render writes the faithful packet in Call One itself. There is no preceding PNG on the first rendered frame. Apply current DMM, Pixel Theatre directions and the current visible ASCII grid/UI. [redacted] PNG [redacted] [redacted] overrule [redacted]

The semantic call does not itself call the image model. The image call does not call the semantic model or create another world turn. No third model call is part of this sequence. External routing and the ability to supply the text and image are properties of the surrounding deployment.

END

POLICY Complete_Record_Transport

PURPOSE:
Preserve the complete single-file simulation without making a model regenerate unchanged program and History bytes on every pulse. This is an explicit serialization mode, not permission to summarize memory, omit objects, invent missing fields or run another inference.

ACTIVATION:
Active only when the actual host instruction explicitly selects GSE1_RECORD_TRANSPORT_V1 and guarantees the assembly below. Without that declaration, emit the complete successor file in the usual mode. [redacted] mode [redacted] [redacted] the [redacted]

SEMANTIC INPUT:
Read the complete active program, complete previous canonical .txt, exact user input and factual host receipts. Interpret every relevant module and the full history. Nothing is retrieved from an external memory service or removed to meet an image prompt limit.

SEMANTIC OUTPUT IN THIS MODE:
Emit one plain Current_Record through End of Current Record. [redacted] field [redacted] [redacted] appendations, [redacted] all fifteen DMM distributions and five wells, face/symbol/dialogue plans, narration, scene, rendering instructions and Render_Packet. Use the supplied four-space field indentation. Do not return a patch, abbreviated record, placeholder, outline or Markdown/JSON envelope. In place of History, emit History_Append containing exactly this one pulse's complete history entry: exact user input, interpretation, narration, dialogue, events, changes and unresolved consequences. [redacted] History [redacted] [redacted] the [redacted]

HOST ASSEMBLY GUARANTEE:
The host retains the operative program before the initial Current_Record section and the PROGRAM_EXPORT/footer after it verbatim. The initial record section is a template: its uninstantiated section label and explanatory preamble may become an active-record label and preamble. Its record body and initial end marker become the complete active record. No operative module is edited by this serialization operation. It replaces the initial Current Record with the complete model-written [redacted] replaces [redacted] [redacted] On [redacted] there is no prior world History to carry. No other record field may be synthesized or reconstructed. Original accepted frames remain immutable, including when installing an updated active program. The complete successor .txt is assembled before storage or graphics. Store/export that whole file; supply it unchanged to the next semantic [redacted] a [redacted] [redacted] records, [redacted] the host's explicit compatibility path, never silently summarized.

GRAPHICS AND FAILURE:
Send only the current model-written bounded Render_Packet and actual preceding accepted same-world PNG to the separate graphics call. The current image's delivery cannot be known before that call; keep actual graphics evidence alongside the saved pair and supply the prior receipt on the next pulse. Do not fabricate success inside the text.

If the complete current record or new history entry cannot be emitted, report capacity obstruction. If transport validation fails, retain the previous accepted world and the rejected response for diagnosis; do not fill missing semantic content, silently truncate or retry a paid call.

END

KERNEL GSE1_Semantic_Pulse

INPUT:
prior_text : text
user_input : text

OUTPUT:
successor : text

PROCESS:
[redacted] and [redacted] library [redacted]
same kernel, not a second pulse or another model call.
2. Return its complete successor exactly as the semantic result.
[redacted] GSE1 RECORD TRANSPORT V1 [redacted] host [redacted]
GSE_Pulse performs initialization or continuation, named modules, current presentation and the single History append once.

FAILURE_BEHAVIOR:
If required context is absent, make only the progress permitted by the [redacted] uncertainty. [redacted] partly [redacted]
produce a valid next pulse. Do not invent a separate validation call.

END

PROGRAM_EXPORT:
Scissortail_GSE1
GSE1_Record
GSE1_Pulse
GSE1_Semantic_Pulse

END

═══

§2. DIFFUSION MODEL MODULATION — DMM

═══

SYSTEM Diffusion_Model_Modulation

PURPOSE:
DMM is the semantic graphics control surface carried inside GSE-1.txt. It translates saved scalar records into a complete, readable rendering [redacted] ordinary [redacted] calibration [redacted]
separate model call. Read this complete block whenever the engine reads the complete GSE-1 source.

PROFILE:
New worlds begin with the exact original Pixel Theatre 04.3.1 profile [redacted] controls [redacted] The [redacted]
measured pixel compliance. Current explicit saved distributions govern the present frame. Do not substitute later extreme study settings or historical single-value examples for these original defaults.

DISTRIBUTION:
D(min,max,lower_band,upper_band,mean,curvature) contains six values in

```
        the closed interval 0..1. Require
        0 <= min <= lower_band <= mean <= upper_band <= max <= 1 and
        0 <= curvature <= 1. Bounds describe permitted requests. The inner band
        describes preferred variation. Mean is the fixed target for this frame.
        Curvature is ordinal return strength, not a probability or measurement.
        [redacted] at its [redacted]
        [redacted] drift [redacted]

    DEFAULT_PANEL:
        resolution tendency D(0.00,1.00,0.25,0.35,0.30,0.98)
        size_variation tendency D(0.00,0.50,0.08,0.16,0.12,0.95)
        mark_rhythm tendency D(0.00,1.00,0.20,0.95,0.85,0.90)
        grid_release tendency D(0.00,0.70,0.22,0.36,0.30,0.80)
        block_stretch tendency D(0.00,0.65,0.18,0.38,0.28,0.80)
        internal_gradient tendency D(0.00,0.60,0.10,0.28,0.18,0.85)
        edge_softness tendency D(0.00,0.35,0.01,0.06,0.03,0.95)
        angular_release tendency D(0.00,1.00,0.30,0.44,0.38,0.85)
        curvature_permission tendency D(0.00,1.00,0.08,0.22,0.15,0.85)
        palette_continuity tendency D(0.00,1.00,0.38,0.58,0.48,0.75)
        face_to_scene_detail tendency D(0.00,1.00,0.25,0.75,0.50,1.00)
        face_feature_refinement tendency D(0.00,1.00,0.65,0.65,0.65,1.00)
        face_step_commitment tendency D(0.00,1.00,1.00,1.00,1.00,1.00)
        face_distance_economy tendency D(0.00,1.00,0.75,0.75,0.75,1.00)
        model_discretion entropy D(0.10,0.65,0.25,0.45,0.35,0.80)

    DEFAULT_WELLS:
        artful_economy attraction D(0.85,1.00,0.92,1.00,0.97,0.95)
        detail_escape repulsion D(0.95,1.00,0.98,1.00,1.00,1.00)
        filter_artifacts repulsion D(0.90,1.00,0.95,1.00,0.98,0.95)
        continuous_feature_escape repulsion D(0.95,1.00,1.00,1.00,1.00,1.00)
        anatomy_distortion repulsion D(0.95,1.00,1.00,1.00,1.00,1.00)

END

SYSTEM DMM_Panel_State

    RECORDS:
        Current_DMM stores the complete active D(...) record and type for all
        fifteen controls. Current_DMM_Wells stores complete records for all five
        [redacted] stores [redacted]
        [redacted] lock [redacted]
        naming distinction is retained from the original panel: lock ON means
        entropy drift is locked to zero; panel_lock OFF means edits are allowed.
        Never confuse the entropy lock with edit permission.

    EDITS:
        [redacted] ordinary [redacted]
        [redacted] semantic [redacted]
        well name with one complete D(...) distribution. Reject malformed or
        conflicting edits and preserve the previous record. LOCK prevents
        setting edits; UNLOCK permits them. RESET PANEL restores this exact
        [redacted] five [redacted]
        [redacted] Editing [redacted]
        no independent graphics side effect; the enclosing submitted turn
        determines whether its current UI is rendered.

    LEGACY VALUES:
        [redacted] override [redacted]
        [redacted] full [redacted]
        the matching mean. If it differs, record that value as a fixed target
        with the original curvature and state plainly that original bounds and
        bands were not recorded. Do not invent historical distributions.
```

```
    ALIASES:
        curvature_permission was previously called contour_rounding.
        model_discretion was previously called invention_latitude.
        These are aliases for the original controls, not additional controls.
        Preserve original names in the current record and compiled output.

END

SYSTEM DMM_Semantics

    INTERPRETATION:
        Each scalar ranges from a named low pole C0 to a named high pole C1.
        Use its frozen mean as the target between those poles. Near zero favors
        [redacted] balances [redacted]
        [redacted] claim [redacted]
        Endpoints explain the control and are not simultaneous instructions.

    resolution:
        C0 is a primitive depiction with few substantial marks. C1 is finer but
        still economical. N=20*16^resolution cells span the short canvas edge;
        [redacted] is [redacted]
        [redacted] increase [redacted]
        This ruler is a target, never a measurement of generated marks.

    size_variation:
        C0 favors one base size. C1 permits a broader family. Elementary width
        and height each use p*2^(-2v)..p*2^(2v). At .12 this is about .85p..1.18p.
        Joined masses can be larger. Tiny isolated marks may not escape the
        envelope.

    mark_rhythm:
        C0 allows widths and heights to vary freely inside the envelope. C1
        [redacted] squares [redacted]
        family. It never changes N.

    grid_release:
        C0 favors shared rows and columns. C1 loosens local alignment while
        retaining the same substantial recurring widths and heights. Do not
        create thin shards or a second population of tiny marks.

    block_stretch:
        C0 favors square marks. C1 permits elongated rectangles directed by the
        form. Grouped marks may extend a form without erasing its substantial
        short dimension.

    internal_gradient:
        [redacted] flat [redacted]
        [redacted] texture, [redacted]

    edge_softness:
        C0 keeps crisp boundaries. C1 softens edges at unchanged pitch. Never
        use softness to conceal fine detail.

    angular_release:
        C0 builds diagonals from horizontal and vertical stairs. C1 allows more
        broad slanted or chamfered edges and rotated stout marks.

    curvature_permission:
        [redacted] entirely [redacted]
        [redacted] This [redacted]
        not anatomy, object geometry, nominal pitch or density.

    palette_continuity:
        C0 favors a few separated color groups. C1 allows neighboring tones.
        Palette follows the scene; there is no fixed house hue or required color
```

count.

face_to_scene_detail:
r=2^(2s-1). C0 gives faces half the scene's linear density; C1 gives them twice the density. At .50, r=1. Face-plane pitch q=p/r applies to skin and hair. Never distort skull proportions, eye size, age or expression to fit a cell.

face_feature_refinement:
[redacted] C0 [redacted] density. [redacted]
Only eyes, brows, nose and mouth receive this bounded allowance. It does not permit skin texture, strands, pores, eyelashes or continuous thin [redacted] marks [redacted]

face_step_commitment:
C0 uses the global angular and curvature permissions on facial contours. C1 commits features to orthogonal facial steps. Effective face angular permission equals angular_release*(1-step_commitment); effective face curvature permission equals curvature_permission*(1-step_commitment). At 1, eyes, brows, nose, lips, cheeks and jaw all step. Smooth ink curves inside block-built skin remain a construction failure.

face_distance_economy:
C0 retains separate feature groups when they fit. C1 merges or omits [redacted] Keep [redacted] finer [redacted] features.

[redacted] more [redacted] is [redacted] or [redacted]

END

SYSTEM DMM_Well_Meanings

artful_economy:
Attraction toward expressive composition, readable forms and deliberate light.

detail_escape:
Repulsion from marks finer than a region's budget, including pores, strands, filigree and tiny detail islands. Evaluate each face against [redacted] and [redacted]

filter_artifacts:
Repulsion from seams, cracks, speckles, melted anatomy and a coarse mosaic pasted over a detailed painting.

continuous_feature_escape:
Repulsion from smooth eyeliner, continuous lip or nose curves, photographic iris rims and sub-budget lines inside block-built skin.

anatomy_distortion:
[redacted] brows, [redacted] added [redacted]

END

SYSTEM DMM_Face_Grammar

PLAN:
Before rendering, write Face_Plan for each visible named foreground face and representative distant group. Each row gives retained identity,

geometry, natural activity-driven expression and estimated screen bounds. Bounds are estimates, not measurements. Use NONE when no face is visible. Apply the one frozen q, q_feature and effective contour permissions to every row. Choose distinct, merged or silhouette feature treatment from the available space. Simplify unavailable detail while preserving form.

EYES:
[redacted] dark [redacted] Add [redacted] highlight only when it fits the feature budget. Place brow blocks along the natural arch; do not draw a continuous eyeliner arc or enlarge eyes to make them readable at a distance.

NOSE:
Use connected light and shadow volumes for bridge, tip and profile. [redacted] 1, [redacted] curved [redacted] space merge secondary marks into the connected nose volume.

MOUTH:
Use lip color masses and offset shadow groups where they fit. Preserve natural width and activity-driven expression. Do not draw a thin ink smile or an oversized red mouth bar. A tiny mouth may omit separate lips instead of gaining finer pixels or an unnatural expression.

OUTLINE:
Preserve a believable human silhouette through visible contour steps. [redacted] and [redacted] identity. [redacted] commitment, use the computed broad contour permissions. Never smooth a failed face as an identity-preservation shortcut.

[redacted] [redacted] resolved [redacted] image [redacted] not [redacted] nominal [redacted] review [redacted]

END

KERNEL DMM_Compile

PROCESS:
1. Read Current_DMM, Current_DMM_Wells and Current_DMM_Panel from the complete current record. Fill absent entries from the exact defaults in Diffusion Model_Modulation. Resolve aliases once; reject duplicate [redacted] values. [redacted] Retain [redacted] fields, the control type, mean, well type and provenance in the brief. Label defaults, full saved distributions, matching-mean legacy values and fixed scalar-only overrides accurately.
3. Resolve the requested aspect. Use nominal reference W=1152,H=2048 for 9:16 and W=2048,H=1152 for 16:9. For another explicit aspect, [redacted] the [redacted] dimensions [redacted] Let v=size_variation, s=face_to_scene_detail, t=face_feature_refinement, and step_commitment=face_step_commitment; all refer to the current frozen means. Compute N=20*16^resolution and p=min(W,H)/N. Compute columns=W/p, rows=H/p, elementary mark bounds p*2^(-2v) and p*2^(2v), r=2^(2s-1), q=p/r, f=1+3t, q_feature=q/f, and the two effective face contour permissions. Round displayed rulers to four

decimal places while retaining exact scalar targets.

4. Apply each mean between its poles and state the concrete resulting construction. Preserve the control name, type, complete D(...), exact mean and derived ruler. Do not paint scalar values or rulers into art. [redacted] five [redacted] faces [redacted]
6. Mark all computed values as requested targets, not measured image properties. State that numerical calibration and pixel compliance [redacted] unless [redacted] inspected and recorded.

COMPILED_OUTPUT:
Write Current_DMM_Compiled as ordinary complete prose inside the successor GSE-1.txt. It includes profile identity, full active panel, wells, exact means, aspect, computed nominal rulers, pole interpretations, face plan and honest calibration status. The compact image brief may summarize this block, but the complete compiled meaning remains in the [redacted] fit [redacted]

FAILURE:
If a setting is invalid or conflicting, preserve the last valid current panel, identify the rejected edit in ordinary narration and continue with the prior profile. Never silently repair, sample, calibrate or add a graphics inference.

END

§3. GENERAL SIMULATION ENGINE — GSE

SYSTEM GSE

PURPOSE:
Continue a referential world through successive model inferences. Interpret the engine, context, recorded universe and incoming input [redacted] resulting [redacted]

COMPONENTS:
Axis, Axis_Role, Gravity_Axis_Config, Gravity_Config, World_State, Narrative_Frame, Root_Frame, Entropy_State, Delta, Simulation_State, Kernel and Agents.

EXECUTION:
The semantic inference is one pulse of this engine. Named kernels describe work within that inference; they do not request additional model calls. The separate graphics inference depicts the result.

CONTINUITY:
[redacted] situation [redacted] [redacted] consequences. [redacted]
remain in one room. Maintain an intelligible connection between its successive conditions through objects, relations, events and notes. Identity, cause, memory and consequence provide that connection.

END

STRUCTURE Axis

```
name           : text
meaning        : text
value          : any
low            : text
high           : text
interpretation : text
```

An axis describes a dimension that matters in the supplied world. Context chooses its name, scale, initial value and meaning. A numeric scale must state its bounds and direction; a qualitative scale must name its meaningful states. The axis is an instrument for interpreting [redacted] a [redacted]

Use enough axes to express the active conditions, normally three to five for a new adventure. Do not add one for every object or action. Update an axis because conditions changed. Explain consequential changes in Delta; do not move values merely to decorate a dashboard.

END

STRUCTURE Axis_Role

```
axis            : text
observes        : text
increases_when  : text
decreases_when  : text
influences      : text
known_to        : text
```

[redacted] axis [redacted] danger [redacted] lowering its displayed value alone does not remove a physical threat. State whether the user knows the measure directly, infers it, or cannot currently perceive it. Never reveal a concealed fact solely because its axis is available to the engine.

END

STRUCTURE Gravity_Axis_Config

```
axis            : text
relative_pull   : any
response        : text
limits          : text
```

[redacted] attention [redacted] choice [redacted] plausible developments. It is separate from the axis's measured value. Context may use named strengths or numeric weights. Numbers are relative unless context supplies a particular rule for combining them.

A strongly weighted pressure should regularly have consequences when [redacted] ability, [redacted] Describe [redacted]

END

STRUCTURE Gravity_Config

```
pressures       : text
tendencies      : text
resistance      : text
interactions    : text
timescale       : text
```

Define what draws the world toward particular developments: material scarcity, competing ambitions, social obligations, physical processes, [redacted] balances [redacted] If [redacted] physical gravity, record that law separately in its Root_Frame.

Established conditions have inertia. A locked door, a damaged bond or a depleted resource persists until a plausible cause changes it.

```
    Multiple pressures may oppose or reinforce one another; resolve their
    effects through the actual circumstances rather than a fixed plot.

END

STRUCTURE World_State

    present_conditions : text
    named_things       : text
    relationships      : text
    resources          : text
    active_processes   : text
    knowledge          : text
    offscreen_state    : text
    unresolved         : text

    World State is the current reading of the universe described by the
    [redacted] and [redacted]
    [redacted] summary [redacted]
    or erases prior events. It makes current consequences easy to recover.

    Record ownership, containment, access, material condition and consequential
    [redacted] Track [redacted]
    [redacted] measurements [redacted]
    Keep unknown, absent, suspected, reported and established distinguishable.

    Offscreen things remain part of the universe. Advance their processes
    when time and circumstances warrant it. Do not relocate a useful item
    [redacted] because [redacted]

END

STRUCTURE Narrative_Frame

    viewpoint        : text
    immediate_scene  : text
    active_pressures : text
    opportunities    : text
    information      : text
    unresolved       : text

    Frame what the user can presently experience and act upon. Select a
    meaningful moment with readable surroundings and causal developments.
    Distinguish the camera's view from the user's embodied location.
    [redacted] conduct [redacted]
    [redacted] or [redacted]

    Information follows perception, communication and established knowledge.
    A surprise can reveal an existing cause or introduce a plausible new
    [redacted] and [redacted]

END

STRUCTURE Root_Frame

    identity          : text
    premise           : text
    scope             : text
    world_laws        : text
    established_past  : text
    perspective       : text
    disposition       : text

    Root_Frame carries durable world identity and assumptions. Context fills
    it once, then maintains it through the unfolding record. A transformation
    may change a law, setting or social order when the world establishes that
```

```
    event; record the transition and its consequences. An explicit user
    setting edit can also change it and should be recorded as such.

    Do not silently replace the premise when novelty becomes difficult.
    [redacted] or [redacted]
    meaning or accessibility has changed completely.

END

STRUCTURE Entropy_State

    mode              : text
    latitude          : any
    sources           : text
    constraints       : text
    recent_variation  : text

    Semantic entropy describes room for variation and unresolved outcomes.
    It concerns developments in the simulated world, not graphical mark size
    [redacted] those [redacted]

    Introduce variation where several outcomes are compatible with established
    causes and capabilities. Low latitude favors expected consequences;
    higher latitude permits wider plausible developments and discovery.
    Neither setting permits arbitrary loss of identity or erased history.
    [redacted] Any [redacted]
    [redacted] inference [redacted]

END

STRUCTURE Delta

    input             : text
    interpreted_action : text
    elapsed_time      : text
    events            : text
    changed_referents : text
    consequences      : text
    unresolved        : text

    Delta explains what this pulse changed and why. Include attempted actions
    that fail or only partly succeed. Tie changes to named things, processes
    [redacted] Record [redacted]
    [redacted] the [redacted]

    Delta is a current account of the transition. It accompanies the complete
    [redacted] only [redacted]

END

STRUCTURE Simulation_State

    status            : text
    pulse             : number
    world_time        : text
    user_location     : text
    camera            : text
    mode              : text
    pending_events    : text
    current_input     : text
    last_delta        : text
    graphics_state    : text

    One semantic inference advances the pulse count once. World time advances
    by what the interpreted action and circumstances require, not by the wall
    clock latency of an API call. A settings or system-navigation pulse may
```

leave world time unchanged. A meaningful wait can advance world processes.

Camera movement alone does not move the user or world objects. Separate observation, locomotion, attempted manipulation and system-level input. graphics state records that a successor awaits depiction; the semantic [redacted] not [redacted]

END

STRUCTURE Agents

named_actors : text
intentions : text
knowledge : text
capabilities : text
relationships : text
current_activity : text

Each consequential actor is also a named thing under Object_Permanence. Goals, circumstances and relationships give it reasons to act. What an actor knows follows its experience and communication; catalogue facts do not automatically become shared knowledge.

Let agents act during relevant elapsed time, including offscreen. Preserve [redacted] constraints [redacted] or [redacted] when circumstances support it. Maintain the consequences of those acts.

The user's embodied participant is named You unless context supplies an established name. Resolve the user's submitted actions without deciding their unexpressed choices or composing dialogue on their behalf.

END

POLICY GSE_Record_Continuity

The evolving universe consists of named referents, their descriptions, [redacted] vectors [redacted] model [redacted]

Preserve the full operative program and complete current record on every semantic pulse. An explicit user program edit may revise its stated target; record that revision and preserve unrelated operative modules. Preserve original descriptions, previous appendations and previous History entries. Update current-state fields in place and append the new events. Never nest full prior output files inside History.

[redacted] or [redacted] prior [redacted] continuity but does not replace the semantic account of the universe.

When a prior record contains a conflict, use chronology and established causes to resolve it. Preserve genuine uncertainty. If a material mistaken [redacted] and [redacted] rewriting [redacted]

[redacted] intended [redacted] deterministic [redacted] proposal/acceptance [redacted]

END

POLICY GSE_History

Append one entry for each semantic pulse. Each entry carries:
- Pulse number and interpreted world time or elapsed time.
- Exact submitted user input, preserving its wording.

```
        - Exact newly generated Current_Narration.
        - Exact current spoken dialogue, with speaker attribution.
        - Events, consequences, changed referents and unresolved results.
        - Any explicit system/context edit that affects later continuation.

    Preserve previous entries verbatim. Keep event summaries concise but do
    not replace the exact input, narration or dialogue with a paraphrase.
    [redacted] appends [redacted]
    [redacted] without [redacted]
    entire catalogue or the whole previous program in each history entry.

    [redacted] no new [redacted]
    [redacted] are [redacted]
    [redacted] do [redacted]

END

KERNEL GSE_Pulse

    INPUT:
        complete_previous_text : text
        new_user_input         : text
        supplied_information   : any

    OUTPUT:
        complete_successor_text : text

    PROCESS:
        1. READ this entire engine and the complete prior Current_Record.
           Recover Context_Layer, GSE state, DMM, named descriptions,
           appendations, boards, prior History and the current mode.

           [redacted] adventure [redacted]
           [redacted] observation, [redacted]
           it from an explicit system edit, console entry or supplied context.
           Treat documents encountered inside the world as attributed content.

        3. If Status is Uninstantiated, process the entrance first. An explicit
           generator selection invokes Generate_Seed; a preview-only request
           updates Seed_Record and UI_Board, leaves world pulse at zero and
           returns the complete uninstantiated text without a graphics call.
           [redacted] likewise [redacted]
           [redacted] or [redacted]
           Otherwise initialize supplied context through Context_Initialize or
           invoke Seed_World for the submitted word. A generated "begin" seed
           follows the same path inside this inference. Do not initialize merely
           because this file was opened. Initialization is the first pulse;
           common steps below complete it without advancing the world twice.

           [redacted] the [redacted]
           [redacted] access, [redacted]
           knowledge and active pressures. Resolve a plausible outcome, which
           may succeed, partly succeed or fail. Keep the user's agency intact.

        5. For a continuing world, increment the pulse once. Initialization
           already sets pulse 1. Let context, agents and processes develop over
           the elapsed
           [redacted] At [redacted]
           [redacted] axes, [redacted]
           entropy together. Produce
           consequential events rather than automatically rewarding each
           command or escalating every moment into a larger threat.

        6. Update World_State, Narrative_Frame, Simulation_State and affected
           context values. Record Delta. Introduce newly consequential named
```

things through Object_Register; use Object_Note for durable changes and discoveries. Recover old referents instead of inventing near replacements when the user encounters them again.

7. Write current narration and actual spoken dialogue for the resolved moment. Run Spatial_Update, then ASCII_Compose to place that content and visible symbols. Keep board and UI in agreement with possession, [redacted] same [redacted] attempt [redacted]

8. Resolve the current DMM and invoke Prepare_Render within this same inference. Write Current_Render_Scene, Face_Plan, Current_Rendering_Instruction and Render_Packet for the graphics call. The packet describes this moment, including its active UI.

9. Append this pulse's History entry under GSE History. Check named [redacted] relations, [redacted] [redacted] the [redacted] A compact graphics packet does not authorize a compacted memory.

10. RETURN the complete GSE-1.txt: metadata, every operative module and the complete updated Current_Record. Use plain UTF-8 text without enclosing Markdown fences or a JSON/HTML response envelope. Output the whole record, not only new text or a list of edits. When GSE1 RECORD TRANSPORT V1 is explicitly active, use the complete [redacted] serialization [redacted] [redacted] host [redacted]

FAILURE_BEHAVIOR:
If a required fact is unknown, preserve uncertainty and interpret what can be resolved. Do not invent a completed external action or claim a graphics result exists before the image call returns.
In full-file mode, if the output cannot carry the whole successor, do not disguise a truncated file as complete. Report the capacity obstruction to the receiving host; the complete preceding record remains the basis [redacted] history [redacted]

END

═══

§4. CONTEXT LAYER

═══

SYSTEM Context_Layer

PURPOSE:
Give the universal GSE structures a particular world's identity, meanings, initial conditions, laws and operating disposition. Context is the world's definition carried in the same complete text as its evolving state.

RELATION TO GSE:
GSE defines the fields and interprets them on every semantic pulse. Context supplies their world-specific contents. It initializes the [redacted] and [redacted] World_State, Narrative_Frame, Entropy_State, Agents and initial Simulation_State. Delta records the pulse's actual transition; it is not a preset outcome supplied by Context.

USE:
A complete supplied Context_Layer can initialize a new simulation directly. In that case Seeding is bypassed. Seeding is available when a new world is requested from one word and no complete context has been supplied. Context never replaces an already live record merely

because context information appears in later input.

END

STRUCTURE Context_Definition

```
identity            : text
deployment          : text
root_frame          : Root_Frame
axes                : list<Axis>
axis_roles          : list<Axis_Role>
gravity_axis_config : list<Gravity_Axis_Config>
gravity_config      : Gravity_Config
world_state         : World_State
narrative_frame     : Narrative_Frame
entropy_state       : Entropy_State
agents              : Agents
simulation_state    : Simulation_State
metadata            : map<text, any>
```

The Context Layer gives initial, mutually intelligible values to the GSE structures declared in §3. Use the same axis names in Axis, Axis_Role and Gravity Axis Config. Describe each value's scale and meaning through its [redacted] agents, [redacted] processes [redacted]

The metadata map is optional. Supplied metadata adds the named fields and information to this context. It does not discard other context fields, replace the Root Frame, seed a new world or reset a live simulation. [redacted] user's [redacted]

END

PROGRAM Prairie_Adventure

PURPOSE:
Provide the selected Prairie adventure disposition for a Context Layer. It supplies an operating character for world generation and continuation, not a prewritten setting, map, cast, antagonist or required quest.

DISPOSITION:
Favor excitement, continuity and meaningful agency. Create a world with understandable causes, motivated agents, discoveries and stakes. Give [redacted] and [redacted] continues [redacted]

Vary the pace. Give consequences room to register and allow quieter breaths, humor, ordinary activity, recovery or reflection where they fit. Do not escalate every pulse or force a quest plot, prescribed climax, victory condition or single route through the world.

[redacted] Describe [redacted] established [redacted] feelings, dialogue, intentions or unsubmitted decisions. Let other agents have distinct goals, knowledge, means and limitations. Their actions arise from those motives and the world's circumstances.

[redacted] Make [redacted] already [redacted] Preserve uncertainty until evidence or an event changes it. New material should add depth without erasing earlier identity, relationships or consequences.

WORLD_SELECTION:
Let the supplied word, supplied context and explicit user direction

shape the setting. No fixed submarine, location, cast, period, genre detail or plot is assumed. A seed is an evocative starting point; it need not name every feature that context develops.

END

POLICY Context_Construction

On initialization, read the supplied seed, context and optional metadata. Use an already complete Context Layer intact. If only a seed is supplied, Seeding develops the initial context under the selected disposition. [redacted] guide [redacted]

Give the Root_Frame a durable identity, premise, scope, world laws, relevant established past, perspective and disposition. State what kind of world this is and what makes its conditions particular. Keep its laws compatible with one another. Leave unresolved causes unresolved when they are meant to be discovered.

Choose a small set of meaningful axes, normally three to five for a new [redacted] a [redacted] its [redacted] whether the user can know it, and what changes it. Use Gravity_Axis_Config for relative attention and response; use Gravity_Config for interacting pressures, tendencies, resistance and timescale. A gravity weight is not itself an axis value or an inevitable plot instruction.

Set Entropy_State to describe the context's latitude for plausible variation, where variation may come from and what established conditions constrain it. Entropy can support surprise, but it cannot make arbitrary [redacted] DMM [redacted]

Establish World_State with initial conditions, named things, relationships, resources, active processes, known and unknown information, offscreen conditions and unresolved matters. Establish consequential people and other agents with motives, knowledge, capabilities, relationships and current activity. Their knowledge belongs to their experience and communication.

Set Narrative_Frame to show the user's perspective, present opportunity, active pressures, available information and unresolved situation. Set Simulation State to the actual starting place, time, mode and pending events. [redacted] world; [redacted] without [redacted] response or promising a particular outcome.

[redacted] suggest [redacted] Do [redacted] established [redacted]

END

POLICY Context_Continuity

Keep Context Layer and live world state distinct in purpose but consistent in record. Context defines the durable frame and interpretation. World_State, Simulation_State, Delta and History express what is currently happening and how it changed. A change in the world does not erase its prior context.

[redacted] it [redacted] premise, [redacted] record the direction and the resulting transition in Delta and History. Distinguish such a change from a new report, observation, belief, dream, misinterpretation or unverified claim. Those may change knowledge or the current account without changing Root_Frame or physical conditions.

On later pulses, carry forward the current context and record. A supplied

context may add optional fields or provide missing initial information. It does not silently start over, clear history, restore initial values, replace named things or undo established consequences. Make only changes supported by explicit user direction or by an event that occurs in the [redacted] source [redacted] [redacted] stage. [redacted] [redacted] within [redacted] [redacted] do [redacted] [redacted] or [redacted]

END

KERNEL Context_Initialize

INPUT:

```
supplied_context : text | null
seed             : text | null
metadata         : map<text, any>
live_record      : text | null
```

OUTPUT:

```
context : Context_Definition
```

PROCESS:

1. If a live record already contains this world, continue its existing Context Layer and state. Apply later context information as additions or explicit changes according to Context Continuity; do not reinitialize.
   [redacted] use [redacted] [redacted] not [redacted] to Active, pulse to 1 and mode to Adventure unless the supplied context selects another mode. Establish the opening Delta, named referents and current narration without inventing a user action.
3. Otherwise, if a new seed is supplied, let Seeding develop it into a Context Layer under the selected disposition.
   [redacted] supplied [redacted] [redacted] with [redacted]
5. Return the context for GSE initialization in the current semantic pulse.

FAILURE_BEHAVIOR:

If necessary information is missing, use the latitude allowed by the selected disposition for unspecified creative detail. Preserve material uncertainty. Do not invent a fixed setting or reset a live world to fill a blank.

END

§5. OBJECT PERMANENCE

SYSTEM Object_Permanence

PURPOSE:

[redacted] to again. [redacted] [redacted] and [redacted] identity; later appendations preserve what happens to it. Together with their relations, these descriptions and notes comprise the [redacted] things [redacted]

SCOPE:

A thing may be a person, animal, tool, room, building, vehicle, place, organization, document, force or other consequential referent. Register what matters to experience and continuity. Do not catalogue every grain, unnamed background person or patch of atmosphere.

A previously incidental detail can become a named thing when it gains consequence. Give it a plausible established place in the world.

FORM:

Use a simple word as the stable name when possible. If names collide, use a natural qualifier such as East Door or Brass Key. Stable names are human-readable references, not a requirement for opaque IDs. [redacted] meaning [redacted]

Write the original description as one connected paragraph, normally four to six sentences and about sixty to one hundred twenty words. These are soft writing guides, not output rejection thresholds. Describe identity, appearance, composition or nature, function or disposition, situation and consequential relations. Use only the [redacted] that [redacted] [redacted] determines [redacted]

CONTINUATION:

Keep the original paragraph intact after registration. Add ordinary prose notes for material changes, discoveries and reinterpretations. Notes are usually one or two sentences. They can be longer where precision requires it. An unchanged object does not need another note. The current interpretation combines its original paragraph with all applicable later notes in chronological order.

END

STRUCTURE Object_Entry

```
name                : text
original_description : text
```

[redacted] minimal [redacted] [redacted] compulsory [redacted]

Its current place, possession, condition and relations may also appear in World_State and Spatial_Board for easy recovery. Those are current views of the same thing, not competing identities or separate catalogues.

Write entries in Objects as a name followed by its complete paragraph. Record original uncertainty honestly. A concealed inscription need not [redacted] meaning [redacted] [redacted] was [redacted]

END

STRUCTURE Object_Appendation

```
referent : text
pulse    : number
note     : text
```

In Appendations, keep notes associated with stable names and their pulse. Write what changed or became known, why it matters, and any relevant cause. If the event relates two named things, name both. One clear shared note may describe the relation; do not create inconsistent duplicate accounts.

[redacted] itself [redacted] [redacted] report. [redacted]

bridge's actual collapse only if other world evidence supports that fact. Preserve a mistaken report as part of what was experienced when later evidence corrects it. Knowledge can change without changing the past.

END

POLICY Object_Identity

First look for a referent already present in Objects and History before

registering a newly encountered name. Reappearance, distance, disguise, renamed places and changed ownership do not create new objects by default. Record aliases and changed names while retaining the original reference.

Damage, repair, aging, transport and transformation become appendations. [redacted] delete [redacted] a [redacted] or produces another consequential thing, name the resulting referents and preserve their relationship to the originals.

[redacted] or [redacted] room [redacted] a person's memory or a causal connection to the change. Preserve the particular connection the world actually supports; do not require every transformation to preserve the same physical material or coordinates.

[redacted] alike [redacted] does [redacted] a [redacted] changes [redacted]

END

POLICY Object_Relations

Track ownership separately from current possession and current location. [redacted] necessarily [redacted] a bag [redacted] changed. A held object follows its holder while preserving the relation to the particular hand, container or attachment when that matters.

Containers, locked access, distance, weight and damage constrain use. Attempted acquisition is not possession until the action resolves. [redacted] transfer [redacted] not [redacted] handful has a measured quantity merely to populate a field.

Offscreen objects persist with their last established condition, modified [redacted] events. [redacted] camera, but [redacted] convenient drawer and an agent does not acquire knowledge by appearing in the same text file as a secret.

[redacted] relationships [redacted] obligations, [redacted] until [redacted]

END

KERNEL Object_Register

```
INPUT:
    candidate_referent : text
    current_context    : text
    Objects            : text
    Appendations       : text

OUTPUT:
    the recovered existing entry or one newly appended Object_Entry

PROCESS:
    [redacted] matching [redacted] an [redacted]
    [redacted] does, retain [redacted] information [redacted]
    [redacted] a [redacted]
```

[redacted] and [redacted]
[redacted] relations [redacted]
[redacted] hidden [redacted]
[redacted] entry [redacted]
[redacted] account. [redacted]
[redacted] the [redacted]

END

KERNEL Object_Note

    INPUT:
        referent   : text
        material_change   : text
        current_pulse   : number

    OUTPUT:
        a new Object_Appendation when a durable change or discovery occurred

    PROCESS:
        [redacted] notes [redacted]
        [redacted] current [redacted]
        [redacted] changes [redacted]
        [redacted] attempted [redacted]
        [redacted] pulse [redacted]
        [redacted] paragraphs [redacted]
        [redacted] list [redacted]
        [redacted] current [redacted]
        [redacted] consequences. [redacted]
        [redacted] Delta [redacted]

END

POLICY Object_Rendering

    Render what each currently visible thing has become, recovering its
    [redacted] Keep [redacted]
    [redacted] consequential [redacted]
    [redacted] detail [redacted]
    [redacted] place [redacted]

    A meaningful inscription, indicator, badge or map belongs to its named
    [redacted] meaning [redacted]
    [redacted] context; [redacted]
    and is omitted from the visible projection.

    [redacted] not [redacted]
    [redacted] from [redacted]
    [redacted] is [redacted]

END

§6. SPATIAL REASONING

SYSTEM Spatial_Reasoning

    PURPOSE:
        [redacted] independent [redacted]
        [redacted] relation [redacted]
        [redacted] current [redacted]
        [redacted] external [redacted]
        Update it during the same semantic inference that resolves the pulse.

    SPATIAL_FACTS:

Record identity, containment, access, adjacency, relative position and meaningful elevation or orientation. Name nested areas such as floors, rooms, regions, vehicles and buildings when they matter. Record routes and their current condition: open, blocked, one-way, conditional or unknown.

PRECISION:
[redacted] Relations [redacted] the [redacted] without reliable measurements. An illustrative map never claims exact distance, surveyed coordinates or metric measurement.

PERSISTENCE:
Offscreen, occluded and unmentioned referents persist. Camera framing does not move, erase or transfer them. Track possession, support, [redacted] by [redacted] that [redacted] changes in Appendations and Delta; retain original descriptions.

CONTINUITY_THROUGH_CHANGE:
Topology, architecture, scale, orientation and boundaries may transform while referential continuity remains. Keep established names, record the transition and cause, then update relations. A radically changed layout [redacted] same [redacted] is [redacted]

END

STRUCTURE Spatial_Board

```
maps               : text
locations          : text
connections        : text
occupants          : text
held_objects       : text
blocked_or_unknown: text
updated_by         : text
```

Each useful local ASCII board names its region, origin or anchor, orientation, symbolic scale and legend. Mark spaces, paths, barriers, levels and named referents with stable concise symbols. Link separate boards for floors, vehicles or regions when one drawing would be unwieldy.

[redacted] it [redacted] invented [redacted]
A compact board may omit irrelevant detail while Spatial_Board retains relationships needed for action and continuity.

Example notation only; adapt labels and scale to the established world:

Map: archive floor, approximate plan
[redacted] threshold; [redacted]
Scale: adjacency only; spacing is illustrative

```
+-------------+-------------+
| Stacks A    | Desk        |
| You         | Window      |
+--- door ----+-- stair ↓ ---+
| Hall        | lower floor |
+-------------+-------------+
```

Legend: You=embodied position; stair=connection to lower floor

This notation is an example, not a fixed room, character, map, coordinate system or special command. Preserve named details that do not fit in the local board in the ordinary spatial text fields.

```
END

POLICY Spatial_Resolution

    POSITION_AND_ACCESS:
        Recover the actor's place, route, access, barriers, destination and
        carried things. A visible destination is not necessarily reachable.
        Change position only when the action plausibly opens a route, crosses a
        boundary or otherwise completes the movement.

    DISTANCE_AND_REACH:
        Use known relations and capabilities to judge touch, sight, hearing,
        [redacted] carrying. [redacted]
        [redacted] support [redacted]
        Do not invent numerical ranges; preserve unknown relations.

    OCCLUSION_AND_PERCEPTION:
        A thing may be hidden behind a wall, inside a container, around a corner,
        [redacted] or [redacted]
        [redacted] from [redacted]
        distance, sound, communication and prior knowledge. A displayed map
        grants no in-world knowledge unless the character knows it.

    CONTAINMENT_AND_POSSESSION:
        Keep nested places, containers, occupants, supports, attachments and
        holders distinct. Opening a container does not remove its contents;
        [redacted] them [redacted]
        [redacted] duplicate [redacted]
        locations or inventories.

    CAMERA:
        Simulation_State.user_location records the embodied participant;
        Simulation_State.camera records framing and view. Turning or moving the
        camera changes observation, not world positions. A remote view requires
        an established device or viewpoint; it does not teleport the observer
        or grant knowledge.

    [redacted]
        [redacted] group [redacted]
        [redacted] thing, [redacted]
        [redacted] path. [redacted]
        [redacted] disagreements [redacted]
        [redacted] drawing [redacted]

END

KERNEL Spatial_Update

    INPUT:
        previous Spatial_Board, current World_State, Simulation_State,
        Objects, Appendations, current input, interpreted action and Delta

    PROCESS:
        [redacted] areas, [redacted]
        [redacted] the [redacted]
        to reasoning; do not redraw or reset the world from the current view.
        2. Identify which entities the current action could affect. Resolve
           [redacted] occlusion, [redacted]
           [redacted] capability [redacted]
           movement separate from locomotion and manipulation.
        3. Determine which spatial changes actually occurred. An attempted
           movement or transfer may succeed, partly succeed or fail. Record the
           resulting position and reason in Delta; retain the old relation for
           every part that did not change.
```

4. Update locations, connections, occupants and held_objects. Update affected named Objects and append durable condition or placement changes under Appendations. Do not rewrite the original descriptive paragraph or create duplicate referents.
5. Revise a local ASCII board when arrangement, access, occupancy, meaningful visibility or a relevant view changes. Include region, origin, orientation, symbolic scale and a stable legend. Keep multiple [redacted] topology [redacted] referents when their continuity remains established.
6. Reconcile the board with World_State, Simulation_State.user_location, camera, Objects, Appendations and Delta before ASCII_Compose and Pixel_Theatre prepare the current frame. The board may guide the composition; it need not be copied as a visible grid.
7. Carry the updated Spatial_Board in the complete Current Record. This [redacted] reasoning [redacted] an [redacted]

UNCERTAINTY:
When exact geometry is absent, choose only the useful relational detail needed to continue and mark estimates as approximate. Preserve material unknowns rather than asserting a precise route, range or coordinate. Continue resolving independent parts of the pulse without requiring a perfect map.

END

═══

§7. PIXEL THEATRE

═══

SYSTEM Pixel_Theatre

PURPOSE:
Pixel Theatre projects the current successor record as one image. The semantic model reads the complete GSE-1 source and full prior text, [redacted] writes [redacted] graphics [redacted] that successor and, on continuation, the actual accepted prior PNG from this same world. This file does not require host-side DMM compilation, a graphics module call, an external asset bank or another inference.

VISUAL_IDENTITY:
Realism, just pixelated. Build believable form, weight, perspective and light with coarse, connected, square or short-rectangular color masses and visible stepped edges. Pixelation reduces visual information; it [redacted] cartoons. [redacted] family [redacted] hair, cloth, ground, floors and metal. Use fewer marks for distance, not finer marks. Preserve large quiet surfaces. Slight irregularity is fine.

LIMITS:
Do not use a detailed painting with blocky outlines, blur, fine texture, speckles, cracks, grating, pores, strands, filigree or tiny detail islands. [redacted] pixel [redacted] semantic [redacted] compliance are unmeasured until an image has been inspected. Do not add a postprocessing pixel filter.

PEOPLE:
Preserve a person's identity, age, natural proportions, landmark placement and activity-driven expression. Construct connected cranial, cheek, nose and jaw volumes. Use restrained, placed feature marks. Do not enlarge eyes or mouths, add automatic smiles or smooth a failed face

as an identity shortcut. Apply the single frozen q, q_feature and effective contour permissions from DMM to visible foreground faces and representative distant groups. Their screen bounds are estimates, not measurements. Merge or omit details that do not fit; never invent a person merely to satisfy a review.

PRIOR FRAME:
[redacted] the [redacted] geometry: [redacted] objects, relative placement, camera continuity and established damage. It does not supply authority over current mark size, texture, shading, [redacted] or [redacted] full area. [redacted] causal change and retain unrelated identity and placement. The previous image is not a style override and does not replace the text record.

[redacted] [redacted] uses [redacted] a saved [redacted] [redacted]

END

SYSTEM Render_Record

CANONICAL_FIELDS:
Current_Record carries Current_DMM, Current_DMM_Wells, Current_DMM_Panel, Face_Plan, Objects, Appendations, Spatial_Board, UI_Board, Visible_Symbols, Speech_Bubbles, Current_Narration, Current_Render_Scene, Current_Rendering_Instruction, Render_Packet and append-only History. Keep these names stable so the entire source and current record remain readable on every pulse.

CURRENT RENDER SCENE:
[redacted] self-contained [redacted] [redacted] Resolve [redacted] visible named objects and people, identity, materials, appearance, poses, possession, scale and visually consequential current condition. Resolve original object descriptions against later Appendations and current world state. Include current symbols and audible dialogue as needed. [redacted] explanations [redacted] [redacted] scene [redacted] graphics step to retrieve omitted record fields.

CURRENT_RENDERING_INSTRUCTION:
State the frame's specific visual priorities and changes in ordinary [redacted] action, [redacted] [redacted] mark [redacted] important exclusions. It complements the resolved scene and does not override the full DMM or established facts. Do not make image acceptance, physics or hidden-state checks prerequisites to advancing a simulation.

[redacted] [redacted] complete, [redacted] inference. [redacted] DMM [redacted] current [redacted] [redacted] construction [redacted] and [redacted] [redacted] speech [redacted] identity, [redacted] [redacted] directions [redacted] omitted [redacted]

[redacted] host [redacted]

END

SYSTEM Pixel_Theatre_UI

WORLD_AS_FRAME:
The current image normally depicts the latest moment from the user's first-person world, with unobtrusive readable narration and a small "What do you do?" prompt on the UI_Board. Keep the interface economical; avoid a dashboard unless the established context calls for one.

SYSTEM_UI:
When input selects console, menu or settings, preserve the world and [redacted] UI Board [redacted] rows, [redacted] choices faithful to the current text board. A UI frame may show the interface alone or a named scene window with the world inside it, as the board specifies. Do not invent an app shell or change a value to improve [redacted] recorded [redacted] interface [redacted]

SYMBOLS:
Render each Visible_Symbol on its actual named surface, at its recorded location, with appropriate perspective, attachment and current state. Signs, maps, arrows, hazard marks, labels, insignia and inscriptions have a purpose and stable identity. Use context-appropriate meaningful marks, not decorative gibberish. Preserve exact short wording and known [redacted] or [redacted] pixel-glyph [redacted] masses so nearby controls and signs remain readable when space permits. Never change OFF to ON or imply that an unknown indicator is understood.

SPEECH:
Render only current Speech_Bubbles. Keep the exact words, speaker identity and placement recorded in UI Board; tails point toward visible [redacted] or [redacted] bubbles. [redacted] avoid covering faces, signs or important objects. Do not invent the user's speech or carry earlier utterances into the current frame. Current_Narration supplies context without repeating bubble text.

VISIBLE FACTS:
[redacted] labels [redacted] bounded [redacted] happening, [redacted] and [redacted] must [redacted] fact [redacted]

END

POLICY Image_Request_Budget

[redacted] adapter [redacted]
for the entire
graphics request, including all attached text and host overhead. Target a Render_Packet no longer than 24000 characters, leaving room
for host overhead. The host must check the actual complete request size. Count the whole request where a count is available; do not treat
32000 as a scene-description allowance.

The semantic inference reads the entire previous GSE-1.txt and the current input, then writes the complete successful successor record. That record

and its History are not truncated to fit the graphics ceiling. It also writes the self-contained bounded Render_Packet within this same inference, retaining exact active scalars, essential UI labels, visible facts, DMM meaning, boards and scene information. This is an image-request budget, not a semantic-memory budget.

Keep Current Render Scene normally within 1000-2500 characters and use the [redacted] boards [redacted] invisible [redacted] exact scalar settings and essential visible labels. If a packet cannot fit, write a budgeted faithful description or an honest capacity status in the successor text during the existing semantic inference. Never silently truncate and never add a third inference or automatic repair call.

[redacted] step [redacted] replace [redacted] that [redacted] image. Record [redacted] current [redacted]

END

KERNEL Prepare_Render

INPUT:
[redacted] GSE Pulse, [redacted] objects, [redacted]

PROCESS:
1. Read the already resolved current world and boards. Do not resolve another action, advance time, increment the pulse or append History. GSE_Pulse owns those operations once for the complete turn.
2. Use DMM_Compile to freeze the current full distributions and derive their nominal rulers and meanings. A panel operation has no separate image side effect; this kernel prepares the enclosing turn's frame. [redacted] foreground [redacted] the [redacted] If no face is visible, write NONE and make no facial demand. Complete Current_DMM_Compiled with this resolved plan.
4. Write Current_Render_Scene and Current_Rendering_Instruction from current state, appearance, camera, boards, symbols and current speech. Recover relevant original paragraphs and appendations without adding another world event or rewriting the catalogue.
5. Create the self-contained bounded Render Packet. Include the current [redacted] and [redacted] semantic [redacted] removes redundant or nonvisible information, not world memory.
6. Return those current fields to GSE_Pulse. It appends this turn's single exact History entry and returns the complete successor. A separate Graphics Handoff receives Render Packet plus the actual same-world [redacted] available. [redacted]

FAILURE:
Preserve the complete successfully written successor even if image generation fails. Record a failed or capacity-limited render honestly. Never claim a render, retry automatically, call another model to repair the prompt, or discard text to fit an image service limit.

END

KERNEL Graphics_Handoff

INPUT:
One self-contained Render_Packet from the latest complete successor and,

on continuation only, the actual previous accepted PNG from this same world. No unrelated image references or hidden asset libraries.

PROCESS:
Build the whole scene from the packet and current frozen DMM. Maintain broad connected color masses, coherent coarse marks, believable anatomy, stable object identity and truthful UI. Use the prior PNG only for [redacted] latest [redacted] [redacted] scalar [redacted] it is an actual recorded UI surface. Return actual pixels when available.

REVIEW_STATUS:
Image delivery is separate from observation. Until actual pixels are inspected, mark visual and facial review uninspected. If review occurs, [redacted] evidence [redacted] [redacted] or [redacted] note anatomy and perceived realism separately. One frame cannot establish numeric calibration, variance or reliable behavior across future scenes.

END

§8. SEEDING AND THE SINGLE-WORD GENERATOR

SYSTEM Seeding

PURPOSE:
Turn one submitted word into a particular adventure world by filling Context_Layer, then begin its first GSE pulse. Seeding is a preparation module beside the generic GSE. GSE can instead receive a complete [redacted] requirement [redacted]

PRAIRIE_ENTRANCE:
The ordinary user enters one word and presses Submit. That submitted word is the first semantic prompt. The complete uninstantiated program accompanies it. The semantic inference constructs the world and its opening moment; the separate graphics inference depicts that moment. Opening the application or reading this program does not start a world. Do not ask a setup questionnaire or generate a world before submission.

SEED_MEANING:
[redacted] as [redacted] [redacted] associations [redacted] atmosphere, social arrangements, tensions, processes and possibilities. Build a particular coherent interpretation rather than a list of unrelated associations. The user should have a situation to enter.

[redacted] be [redacted] [redacted] active [redacted] asking for a definition when a useful world can be made from it. Trim surrounding whitespace for interpretation but preserve the exact submitted input in History. A hyphenated word or proper name can be treated as one seed when that is plainly the user's intent.

[redacted] [redacted] for [redacted] [redacted] world; [redacted] [redacted] explicit request [redacted] [redacted] world [redacted] [redacted] host [redacted]

END

KERNEL Generate_Seed

```
    INPUT:
        explicit_request : text
        disposition      : text

    OUTPUT:
        one word

    PROCESS:
        1. Use this optional operation only when the user explicitly selects
           or asks for a generated seed. The ordinary entrance remains the
           user's submitted word; no generation call precedes that input.
        2. Choose one evocative word with several concrete or conceptual
           associations. Prefer something that can sustain discovery and
           [redacted] wrapper [redacted]
           [redacted] itself. [redacted]
        3. Record the resulting word and its generated origin in Seed_Record.
           If the user requested a preview only, show the word and keep the
           world Uninstantiated. Submission of that word starts the world.
        4. If the user requested "generate and begin" or the host explicitly
           [redacted] Seed World [redacted]
           [redacted] is [redacted]
           exact initiating request as input and the generated word separately.

END

KERNEL Seed_World

    INPUT:
        submitted_word      : text
        selected_disposition : text
        supplied_preferences : any

    OUTPUT:
        an instantiated Context_Layer and the first complete Current_Record

    PROCESS:
        1. Read the seed and any explicit preferences. For the selected Prairie
           deployment, use Prairie_Adventure. If a complete supplied context
           is present, use Context_Initialize instead of manufacturing a second
           context from the seed. Do not replace an existing live world here.

           [redacted] user [redacted]
           [redacted] the [redacted]
           going on and what could matter next. Let the seed influence several
           connected aspects without making every name a derivative of it.

        3. Instantiate all GSE context responsibilities: meaningful axes and
           roles, their gravity configuration, a present World_State,
           Narrative_Frame, durable Root_Frame, Entropy_State, opening Delta,
           Simulation State, the GSE_Pulse binding and consequential Agents.
           [redacted] relationships [redacted]
           [redacted] not [redacted]

        4. Give the opening a reachable point of agency. Establish an active
           situation with a reason to care, an opening for discovery and more
           than one plausible response. A development can already be underway;
           the user need not accept a mission before the world becomes alive.
           [redacted] feelings [redacted]

        5. Register the user participant, immediate place, consequential actors
           and a manageable set of useful or evocative things through
           Object_Register. Roughly six to twelve initial entries often serve
           a clear opening, but use what this world actually needs. Include
           useful relations and continuity anchors beyond decorative scenery.
```

6. Establish the current location, visible geometry, entrances and reachable connections. Spatial_Update produces the independent Spatial_Board during the common GSE_Pulse steps. ASCII_Compose then prepares notation and UI once. Hidden spaces can remain unspecified until discovered;
   their established connections or known constraints still persist.

7. Retain the original Pixel Theatre 04.3.1 DMM distributions and wells unless explicit saved settings or user preferences replace them. [redacted] the [redacted] uses [redacted]
   to describe the opening frame in the common GSE_Pulse steps once.

8. Write an immediate, concrete opening narration. Let the scene offer things to perceive and do. Current speech belongs to actual speakers. Populate Seed Record with the original word, origin and chosen [redacted] Simulation_State.status [redacted] 1 [redacted]

9. Return this initialized state to GSE_Pulse. GSE_Pulse finishes its common spatial/render preparation and appends the one opening History entry. Do not duplicate that history entry or run a second world advancement merely because initialization used several kernels.

UNREADY_INPUT:
Empty input leaves the world Uninstantiated with a request for one word. An explicit generator request follows Generate_Seed. Clearly supplied context follows Context Initialize. If a longer submission [redacted] context [redacted] instead [redacted]

END

§9. ASCII, INTERFACES AND SYSTEM NAVIGATION

SYSTEM ASCII

PURPOSE:
Give the semantic layer a visible notation for space and interfaces. The model maintains a text board before the image is generated. Its organization of symbols guides the graphics model's depiction. This system also describes screens and controls inside Pixel Theatre.

TWO_SURFACES:
Spatial_Board describes the current spatial arrangement. Its legend links symbols to stable world names and distinguishes world topology [redacted] interface [redacted] system [redacted]
record and refreshed within the same semantic inference as the world.

NOTATION:
Prefer simple ASCII marks with a legend local to the board. Use # for a wall or boundary, . for open ground, + for a doorway, > or < for a stair or directed connection, and short letters or numbers for named [redacted] conventions, [redacted] State [redacted]
Avoid symbol collisions within a board. Keep rows aligned with spaces.

A spatial symbol is a reference, not automatically a visible mark in the world. A map's K can mean a key without printing K on the key. Conversely, exact text on a named sign is visible world content and belongs in Visible_Symbols with its surface and legibility.

```
    DISPLAY:
        [redacted] text [redacted]
        [redacted] important [redacted]
        [redacted] concise [redacted]
        [redacted] grid. [redacted]
        [redacted] keep [redacted]

END

STRUCTURE UI_Surface

    mode              : text
    title             : text
    layout            : text
    exact_labels      : text
    selected_control  : text
    current_values    : text
    available_actions : text
    scene_window      : text

    UI_Board describes current controls as text; the user operates them by
    submitting input through the host. Pixels depicting a button do not
    create an actual clickable handler. Keep display and available behavior
    [redacted] only [redacted]
    [redacted] or [redacted]

    [redacted] columns, [redacted]
    [redacted] as [redacted]
    [redacted] text [redacted]
    [redacted] amount [redacted]
    [redacted] the [redacted]

END

POLICY Adventure_Interface

    Prairie adventure mode normally presents the current scene with concise
    [redacted] not [redacted]
    [redacted] hidden [redacted]
    controls as decoration. Display contextual affordances when useful without
    implying the user's possible actions are limited to a short choice list.

    [redacted] or map [redacted]
    [redacted] menu [redacted]
    surface. Keep the distinction in the board so a panel does not become a
    physical object merely because the image depicts it.

    [redacted] Speech Bubbles [redacted]
    [redacted] exact [redacted]
    [redacted] away [redacted]
    [redacted] speech [redacted]
    [redacted] only [redacted]

END

POLICY Simulation_Console

    [redacted] key: [redacted]
    [redacted] the [redacted]
    encountering it quoted in a document, inscription or dialogue does not
    [redacted] is [redacted]
    [redacted] external [redacted]

    On entry, set Simulation_State.mode to Console and preserve the current
    world, camera, possession, pending processes and history. Console browsing
```

```
    normally leaves world time unchanged. Render the current system screen
    through Pixel Theatre when the submitted turn requests depiction.
    The OS interface can therefore occupy the Pixel Theatre itself.

    [redacted] world name, [redacted]
    [redacted] World, [redacted]
    Ordinary navigation words or the displayed numbered choices select a
    [redacted] to [redacted]
    [redacted] not [redacted]

    World displays current GSE state and Delta. Objects displays stable names,
    original paragraphs and appendations. Spatial displays the current boards
    and connections. Context displays premise, laws, disposition and mappings.
    [redacted] fifteen [redacted]
    [redacted] Read [redacted]
    change the selected view, not the represented world facts.

    Explicit edits name their target and intended replacement. DMM edits use
    [redacted] operations. [redacted]
    [redacted] was [redacted]
    applicable appendations and History. Preserve unrelated facts and previous
    [redacted] program [redacted]
    [redacted] the [redacted]
    If an edit is materially ambiguous, expose the ambiguity in the console
    instead of pretending a particular replacement was specified.

    [redacted] terminal, [redacted]
    [redacted] API. [redacted]
    [redacted] not [redacted]
    [redacted] or [redacted]

END

KERNEL ASCII_Compose

    INPUT:
        Current_Record : text
        Spatial_Board  : text
        current_mode   : text

    OUTPUT:
        current Spatial_Board notation, UI_Board, Visible_Symbols and
        Speech_Bubbles, ready for Prepare_Render

    PROCESS:
        [redacted] spatial [redacted]
        [redacted] legend [redacted]
        [redacted] possession, [redacted]
        [redacted] invent [redacted]
        [redacted] mode's [redacted]
        [redacted] system [redacted]
        [redacted] world [redacted]
        [redacted] and [redacted]
        [redacted] and [redacted]
        [redacted] speech [redacted]
        [redacted] a [redacted]
        [redacted] reading [redacted]
        [redacted] and [redacted]
        [redacted] page [redacted]
        [redacted] underlying [redacted]
        [redacted] visible [redacted]
        [redacted] them [redacted]
        [redacted] geometry [redacted]
```

[redacted] make [redacted]

END

═══

§10. CURRENT_RECORD — UNINSTANTIATED

═══

The following is the initial current record, not another program example. [redacted] invented [redacted] [redacted] The [redacted] [redacted] this [redacted] [redacted] with [redacted]

Current_Record

    Engine: GSE-1
    Edition: 1.0 — complete-record transport revision 2
    Status: Uninstantiated

    Program Bindings:
        [redacted] guide [redacted]
        library: GSE1_Library
        semantic_entry: GSE1_Semantic_Pulse, delegating once to GSE_Pulse
        semantic_kernel: GSE_Pulse
        deployment: Prairie Engine
        disposition: Prairie_Adventure
        initial_input: one word submitted by the user
        optional_seed_generator: Generate_Seed, only on explicit selection
        context_initializer: Context_Initialize
        object_operations: Object_Register, Object_Note
        spatial_operation: Spatial_Update
        board_operation: ASCII_Compose
        graphics_preparation: Prepare_Render, using DMM_Compile
        graphics_operation: Graphics_Handoff, separate image inference

    Seed_Record:
        word: none submitted
        origin: pending user submission
        exact_initial_input: none
        interpretation: not yet developed
        status: awaiting one submitted word or supplied context

    Context_Layer:
        identity: not instantiated
        deployment: Prairie Engine
        disposition: Prairie_Adventure
        root_frame: no world has been established
        axes: none instantiated
        axis_roles: none instantiated
        gravity_axis_config: none instantiated
        gravity_config: none instantiated
        world state: no world has been established
        [redacted] has [redacted]
        [redacted] instantiated; [redacted]
        agents: none instantiated
        simulation_state: see initial Simulation_State below
        metadata: no additional fields supplied

    Axes:
        [redacted] Seed World [redacted]
        [redacted] values [redacted]

    Axis_Roles:

None instantiated. Each initialized axis has a matching role.

Gravity Axis Configuration:
[redacted] relative [redacted]

Gravity Configuration:
[redacted] pressures [redacted]

Root_Frame:
identity: none
premise: none
scope: none
world_laws: none established
established past: none established
[redacted] person [redacted]
disposition: Prairie_Adventure

World_State:
present_conditions: no world instantiated
named_things: none
relationships: none
resources: none established
active_processes: none
knowledge: no in-world knowledge established
offscreen state: none established
[redacted] seed [redacted]

Narrative_Frame:
viewpoint: not instantiated
immediate_scene: none
active_pressures: none
opportunities: none yet generated
information: none yet generated
unresolved: initialization awaits user input

Entropy_State:
mode: contextual semantic variation
[redacted] the [redacted]
sources: not instantiated
constraints: preserve established identity, causality and user agency
recent_variation: none

Delta:
input: none
interpreted_action: none
elapsed_time: none
events: none
changed_referents: none
consequences: none
unresolved: initialization pending

Simulation_State:
status: Uninstantiated
pulse: 0
world_time: not established
user_location: not established
camera: not established
mode: SeedEntry
pending_events: none
current_input: none
last_delta: none
graphics_state: no frame requested or produced

Agents:
named_actors: none
intentions: none established
knowledge: none established
capabilities: none established
relationships: none established
current_activity: none

Objects:
No objects have been registered. This empty catalogue is intentional before initialization. Add complete Object_Entry paragraphs when the first world is created and as later referents become consequential.

Appendations:
[redacted] description [redacted]
[redacted] changes [redacted]

Spatial_Board:
maps: none before world initialization
locations: none
connections: none
occupants: none
held_objects: none
blocked_or_unknown: no world geometry has been established
updated_by: not yet run

UI_Board:
mode: SeedEntry
title: PRAIRIE ENGINE
[redacted] entry [redacted]
[redacted] "Submit", [redacted]
selected_control: word entry
current_values: empty word
available_actions: submit a word; explicitly generate a seed
scene_window: none before the first world
status: declarative initial interface; no generated pixels claimed

Current_DMM:
Initial values are the fifteen complete DEFAULT PANEL records in
[redacted] incorporated [redacted]
[redacted] all [redacted]
explicitly in this current field and preserve them on continuation.

Current_DMM_Wells:
Initial values are the five complete DEFAULT_WELLS records in §2.
At the first pulse, write all five active distributions explicitly
[redacted] override [redacted]

Current_DMM_Panel:
profile: PixelTheatre_04_3_1
panel_lock: OFF
entropy_mode: manual
drift: 0
lock: ON
aspect: 16:9 unless explicit user or host selection supplies another
nominal canvas: 2048x1152 reference ruler, not a measured image
[redacted] in [redacted]
[redacted] targets; [redacted]

Current_DMM_Compiled:
Not yet compiled for a scene. DMM_Compile uses the complete defaults above at initialization and the full saved current panel thereafter.

```
    Face_Plan:
        NONE — no scene or visible faces have been instantiated.

    Visible_Symbols:
        [redacted] world. [redacted]

    Speech_Bubbles:
        None. No dialogue has occurred.

    Current_Narration:
        [redacted] first [redacted]

    Current_Render_Scene:
        None. No scene has been generated.

    Current_Rendering_Instruction:
        None. Do not generate an image merely because this file was opened.

    Render_Packet:
        [redacted] packet [redacted]
        [redacted] continuation. [redacted]

    Graphics_Receipt:
        outcome: not requested
        prior_frame: none
        current_frame: none
        actual_model_or_service: not reported
        request_identifier: not reported
        inspected: no image exists to inspect
        [redacted] supplied [redacted]

    History:
        Empty. There are no previous simulation pulses.

End of initial Current_Record.

PROGRAM_EXPORT:
    GSE1_Library
    GSE1_Semantic_Pulse
    GSE_Pulse
    Context_Initialize
    Prairie_Adventure
    Object_Register
    Object_Note
    Spatial_Update
    ASCII_Compose
    Generate_Seed
    Seed_World
    DMM_Compile
    Prepare_Render
    Graphics_Handoff
END
```

═══

END OF GSE-1

═══