Supplementary material for Observe, Imagine, Abstain: Detecting Hallucinated Geometry in Feed-Forward 3D Reconstruction

Anonymous CVPR submission

Figure and table numbers below are local to this document; the main paper is self-contained and refers to this material by section title.

Compute. The benchmark involves no training, and all its model runs fit on one 16 GB GPU in about eight hours. The support head trains in ten to twenty-five minutes on one GPU (1500 steps); scoring one detector on one dataset takes one to five minutes on an H200. Every threshold and pass condition was fixed before the run that uses it.




Figure S1. **Per-run spread on DTU.** AUROC and CUR for every (scan, seed, radius) run under blur and noise fills, with pooled means and intervals. The spread across scans is wide for every model; the intervals in the main tables come from resampling scans.




Figure S2. **Fill ablation.** CUR per model and fill on DTU and CO3Dv2 (five seeds) and for the inpainted fill on DTU (two seeds, three models). A visible gray patch gives the lowest leakage; natural-statistics and inpainted fills give more.

Correctness guards. Before any model is scored we check that ground-truth depth reprojects consistently between view pairs and that unsupported points of view i, where visible in view j, land inside view j's hidden mask. DTU: reprojection agreement 0.80 to 0.82 at a 1% depth tolerance, U-transfer 0.96 to 0.99. CO3Dv2 (cameras converted from PyTorch3D and checked against the official point cloud): with an occlusion-aware 3% tolerance, agreement 0.92 to 1.00 and U-transfer 0.90 to 0.98 on 17 of 18 scenes; the eighteenth scores 0.80, is kept, and removing it changes nothing (Section 4 of the paper). ETH3D: agreement 0.996 to 1.000 on all scenes; nine of twelve pass the U-transfer check and three are excluded before any model is run.

Pipeline validation. On a synthetic DTU-format scene, an oracle that knows what is hidden scores AUROC 1.000 and CUR 0.000, and a blind guesser with flat confidence scores AUROC 0.500 and CUR 0.90 (the 10% of supported pixels dropped by τ is the expected floor). These numbers validate the code, not any model.

Table 1 with intervals. The paper's Table 1 shows means; Table S1 adds 95% cluster-bootstrap intervals over scenes, CUR-ERR and the confidence ratio (median confidence inside the hidden region over its clean value), with the matched split's AUROC_m and CUR_m.




Figure S3. **Per-scene CUR** (blur fill, radius 0.18, mean over seeds) for every model on DTU scans and CO3Dv2 scenes. Rows are scenes, columns are models.

Table S1. **Native confidence, full numbers.** Blur and noise pooled, 18 scenes × 5 seeds × 2 radii; mean [95% CI]; matched split seeds 0 and 1, radius 0.18.

model	DTU, 18 scans						CO3Dv2, 18 scenes					
	AUROC↑	CUR↓	CUR-ERR↓	conf ratio	AUROC_m ↑	CUR_m ↓	AUROC↑	CUR↓	CUR-ERR↓	conf ratio	AUROC_m ↑	CUR_m ↓
VGGT-1B	0.903 [0.873, 0.929]	0.242 [0.181, 0.304]	0.000	0.22	0.551	0.802	0.681 [0.632, 0.729]	0.651 [0.566, 0.734]	0.031	0.70	0.486	0.852
Pi3	0.912 [0.881, 0.940]	0.281 [0.189, 0.379]	0.002	0.34	0.495	0.828	0.891 [0.845, 0.930]	0.272 [0.190, 0.360]	0.002	0.43	0.494	0.808
Pi3X	0.813 [0.762, 0.860]	0.532 [0.403, 0.663]	0.003	0.91	0.474	0.870	0.732 [0.680, 0.779]	0.570 [0.500, 0.641]	0.001	0.87	0.500	0.806
MapAnything	0.743 [0.687, 0.795]	0.622 [0.534, 0.707]	0.286	0.69	0.515	0.837	0.576 [0.521, 0.632]	0.810 [0.756, 0.863]	0.007	0.68	0.493	0.836
Depth Anything 3	0.711 [0.653, 0.763]	0.701 [0.614, 0.784]	0.002	0.83	0.425	0.854	0.620 [0.567, 0.670]	0.797 [0.728, 0.861]	0.000	0.88	0.482	0.839

Table S2. **DTU, five models, full configuration.** 18 scans × 5 mask seeds × 2 radii × 3 fills, pooled over radii; mean [95% cluster-bootstrap CI over scans]. *conf ratio* is the median confidence inside the hidden region divided by its value under clean input. The pooled numbers are in Table 1 of the main paper.

model	fill	AUROC	CUR	CUR-ERR	AbsRel_U	AbsRel_U ctrl	conf ratio
VGGT-1B	gray	0.973 [0.955, 0.987]	0.067 [0.031, 0.111]	0.000	0.018	0.006	0.051
VGGT-1B	blur	0.886 [0.843, 0.922]	0.263 [0.203, 0.324]	0.000	0.011	0.006	0.241
VGGT-1B	noise	0.919 [0.892, 0.945]	0.222 [0.145, 0.304]	0.000	0.014	0.006	0.192
Pi3	gray	0.981 [0.972, 0.988]	0.053 [0.025, 0.085]	0.001	0.020	0.014	0.057
Pi3	blur	0.923 [0.895, 0.947]	0.236 [0.156, 0.326]	0.001	0.018	0.014	0.261
Pi3	noise	0.902 [0.865, 0.934]	0.325 [0.219, 0.438]	0.002	0.020	0.014	0.411
Pi3X	gray	0.940 [0.902, 0.971]	0.202 [0.085, 0.337]	0.002	0.022	0.017	0.335
Pi3X	blur	0.826 [0.782, 0.865]	0.512 [0.397, 0.630]	0.002	0.020	0.017	0.739
Pi3X	noise	0.801 [0.734, 0.864]	0.551 [0.390, 0.711]	0.004	0.022	0.017	1.091
MapAnything	gray	0.861 [0.812, 0.905]	0.374 [0.272, 0.480]	0.195 [0.125, 0.269]	0.222	0.111	0.650
MapAnything	blur	0.773 [0.720, 0.825]	0.580 [0.482, 0.672]	0.277 [0.197, 0.361]	0.135	0.111	0.677
MapAnything	noise	0.712 [0.645, 0.773]	0.664 [0.566, 0.758]	0.295 [0.211, 0.390]	0.129	0.111	0.709
Depth Anything 3	gray	0.723 [0.664, 0.780]	0.703 [0.596, 0.804]	0.003	0.017	0.013	0.804
Depth Anything 3	blur	0.682 [0.611, 0.744]	0.711 [0.619, 0.796]	0.003	0.016	0.013	0.800
Depth Anything 3	noise	0.740 [0.686, 0.793]	0.690 [0.578, 0.793]	0.001	0.017	0.013	0.855

DTU and CO3Dv2, full configuration per fill.

Table S3. **CO3Dv2, five models, full configuration.** 18 scenes × 5 seeds × 2 radii × 3 fills, pooled over radii; mean [95% CI over scenes]. The pooled numbers are quoted in Section 5.3 of the main paper.

model	fill	AUROC	CUR	CUR-ERR	AbsRel$_S$	AbsRel$_U$	AbsRel$_U$ ctrl	conf ratio
VGGT-1B	gray	0.747 [0.692, 0.802]	0.565 [0.453, 0.677]	0.029	0.029	0.031	0.027	0.634
VGGT-1B	blur	0.772 [0.717, 0.825]	0.534 [0.416, 0.652]	0.034	0.029	0.031	0.027	0.603
VGGT-1B	noise	0.590 [0.517, 0.656]	0.767 [0.693, 0.839]	0.029	0.029	0.029	0.027	0.805
Pi3	gray	0.930 [0.894, 0.958]	0.196 [0.118, 0.283]	0.002	0.015	0.016	0.013	0.351
Pi3	blur	0.903 [0.860, 0.939]	0.251 [0.170, 0.334]	0.002	0.015	0.016	0.013	0.389
Pi3	noise	0.880 [0.813, 0.929]	0.293 [0.193, 0.405]	0.002	0.015	0.015	0.013	0.472
Pi3X	gray	0.863 [0.825, 0.899]	0.329 [0.248, 0.408]	0.001	0.017	0.022	0.014	0.749
Pi3X	blur	0.720 [0.661, 0.777]	0.584 [0.500, 0.668]	0.002	0.017	0.018	0.014	0.877
Pi3X	noise	0.743 [0.680, 0.798]	0.556 [0.462, 0.650]	0.001	0.017	0.019	0.014	0.867
MapAnything	gray	0.609 [0.554, 0.665]	0.786 [0.721, 0.849]	0.004	0.041	0.029	0.034	0.632
MapAnything	blur	0.575 [0.514, 0.637]	0.801 [0.735, 0.863]	0.008	0.042	0.028	0.034	0.674
MapAnything	noise	0.578 [0.524, 0.631]	0.819 [0.765, 0.870]	0.007	0.041	0.033	0.034	0.690
Depth Anything 3	gray	0.619 [0.560, 0.674]	0.816 [0.751, 0.877]	0.001	0.019	0.015	0.014	0.874
Depth Anything 3	blur	0.622 [0.574, 0.668]	0.813 [0.748, 0.872]	0.001	0.018	0.015	0.014	0.853
Depth Anything 3	noise	0.618 [0.553, 0.679]	0.780 [0.702, 0.854]	0.000	0.019	0.016	0.014	0.901




Figure S4. **Lab rig versus phone captures.** Pooled blur-and-noise CUR and AUROC per model on DTU and CO3Dv2 with 95% intervals. Pi3 is the only model whose numbers transfer; VGGT, MapAnything and DA3 leak markedly more on CO3Dv2.

Lab rig versus phone captures, plotted.




Figure S5. **The benchmark protocol.** A sphere is placed on the ground-truth surface; every pixel in every view whose ground-truth point falls inside it is hidden, so the hidden region is 3D-consistent. Hidden pixels are filled (gray, blur, noise or inpaint), the model runs on the filled views, and its depth and confidence are scored against the unsupported (U), supported (S) and ring labels. The same pixels are also scored under clean input as a control.

The benchmark protocol, in a figure.




Figure S6. **What a model does with a surface it cannot see.** Top: a DTU scan with one 3D region of the ground-truth surface hidden in all ten input views and inpainted so no seam remains (the inpainted fill of Section 4 of the paper). Bottom: a CO3Dv2 phone capture treated the same way. The top row shows the protocol: the same 3D sphere hides the region in every view, including a view from the other side of the rig. The bottom row shows what the backbone (VGGT) does with it: plausible geometry inside the hidden region, with confidence close to its value outside. The cyan contour marks the unsupported pixels. Model panels are the recorded run outputs.

The filled patch, in pictures.

Fused point clouds at matched coverage. Each backbone's per-view depths are back-projected with its own predicted cameras into one cloud, aligned to the ground-truth frame by a similarity transform fitted on the camera centres, and compared with the ground-truth cloud of the same views at a tolerance of 1% of the scene's median depth: accuracy is the fraction of predicted points within tolerance of a ground-truth point, completeness the converse. A detector keeps the given fraction of points with the highest score; random dropping and an oracle that drops single-view pixels first are the references. Table S4: 18 DTU scans and 9 ETH3D scenes, 5 and 10 views, two view sets; the rows marked $\times$ are the label-free head multiplied by native confidence. The absolute accuracies on ETH3D are low because the predicted cameras of a building scan align poorly to the laser frame; the comparison between detectors at matched coverage is what the table is for.

Table S4. **Fused point cloud at matched coverage**, accuracy / completeness against the laser or MVS cloud.

detector	DTU, accuracy / completeness			ETH3D, accuracy / completeness		
coverage	0.6	0.8	1.0	0.6	0.8	1.0
native confidence	0.842 / 0.804	0.783 / 0.885	0.653 / 0.902	0.337 / 0.396	0.306 / 0.443	0.273 / 0.470
reprojection consistency	0.805 / 0.837	0.763 / 0.868	0.654 / 0.902	0.321 / 0.413	0.302 / 0.438	0.273 / 0.470
per-image control	0.766 / 0.735	0.698 / 0.835	0.653 / 0.902	0.293 / 0.369	0.281 / 0.428	0.273 / 0.470
label-free head	0.834 / 0.770	0.771 / 0.874	0.653 / 0.902	0.331 / 0.383	0.300 / 0.428	0.273 / 0.470
random dropping	0.653 / 0.896	0.653 / 0.900	0.653 / 0.902	0.273 / 0.462	0.273 / 0.467	0.273 / 0.470
oracle: single-view first	0.699 / 0.833	0.663 / 0.863	0.653 / 0.902	0.273 / 0.417	0.275 / 0.442	0.273 / 0.470
label-free head $\times$ native confidence	0.844 / 0.786	0.785 / 0.883	0.653 / 0.902	0.333 / 0.384	0.304 / 0.437	0.273 / 0.470
native confidence (Pi3X)	0.381 / 0.498	0.349 / 0.543	0.297 / 0.562	0.346 / 0.426	0.314 / 0.467	0.272 / 0.482
reprojection (Pi3X)	0.353 / 0.485	0.350 / 0.535	0.297 / 0.559	0.301 / 0.412	0.297 / 0.439	0.273 / 0.481
label-free head (Pi3X)	0.404 / 0.494	0.354 / 0.546	0.297 / 0.562	0.332 / 0.404	0.299 / 0.446	0.272 / 0.482
label-free head $\times$ native (Pi3X)	0.403 / 0.492	0.356 / 0.547	0.297 / 0.562	0.338 / 0.408	0.306 / 0.454	0.272 / 0.481
oracle (Pi3X)	0.310 / 0.500	0.300 / 0.531	0.297 / 0.562	0.260 / 0.418	0.268 / 0.449	0.272 / 0.482

Detectors on the filled patches. The cheap alternatives and the fill-trained heads of Sections 4 and 6 of the main paper, on the Table 1 rows with blur, radius 0.18 and seed 0. A fuller perturbation baseline (photometric, blur, flip and view-permutation perturbations, $K = 8$, least-squares scale alignment, median-absolute-deviation spread) scores AUROC 0.52 to 0.60 and CUR 0.74 to 0.86 on all five backbones over blur and noise, worse than native confidence everywhere. On 22 further DTU scans (the MVSNet test split, seed 0, radius 0.18) the ranking of Table 1 holds: VGGT AUROC 0.908 / CUR 0.233, Pi3 0.919 / 0.272, Pi3X 0.850 / 0.539, DA3 0.755 / 0.650, MapAnything 0.697 / 0.693 with CUR-ERR 0.287. On the nine ETH3D scenes

under the full fill protocol native confidence leaks more than on DTU, CUR 0.61 (Pi3) to 0.79 (VGGT), and the fill-trained head scores 0.981 against its per-image control's 0.987.

Table S5. **Detectors on the filled patches, DTU** (18 scans, seed 0, blur, radius 0.18; native and perturbation rows re-run on the detectors' hardware, so every pair is scored on identical rows). The three learned rows per backbone are the *fill-trained* heads: they find the fill, not the missing support (Section 5 of the paper), which is why the per-image control matches them. The visibility-trained heads are in the main paper.

backbone	detector	fwd	AUROC	CUR
VGGT-1B	native confidence	1	0.915 [0.883, 0.943]	0.255 [0.157, 0.364]
VGGT-1B	perturbation var., $K{=}4$	4	0.666 [0.602, 0.729]	0.627 [0.521, 0.732]
VGGT-1B	reprojection consistency	1	0.488 [0.473, 0.506]	0.931 [0.903, 0.954]
VGGT-1B	fill-trained linear probe	1	1.000 [1.000, 1.000]	0.000 [0.000, 0.000]
VGGT-1B	fill-trained per-image control	1	1.000 [1.000, 1.000]	0.000 [0.000, 0.000]
VGGT-1B	fill-trained support head	1	1.000 [1.000, 1.000]	0.000 [0.000, 0.000]
Pi3X	native confidence	1	0.832 [0.782, 0.879]	0.502 [0.362, 0.642]
Pi3X	perturbation var., $K{=}4$	4	0.550 [0.491, 0.608]	0.824 [0.754, 0.886]
Pi3X	reprojection consistency	1	0.478 [0.435, 0.518]	0.929 [0.899, 0.955]
Pi3X	fill-trained per-image control	1	1.000 [0.999, 1.000]	0.000 [0.000, 0.001]
Pi3X	fill-trained support head	1	0.999 [0.999, 1.000]	0.001 [0.000, 0.003]

Stress tests. Section 5.2 of the main paper summarises this table.

Table S6. **Stress tests on DTU.** 18 scans $\times$ 2 mask seeds, radius 0.18, models VGGT, Pi3X, DA3. Reference rows are the matching cells of Table 1 of the paper (blur, 10 spread views, seeds 0 and 1). Last column: paired CUR difference against the reference with a sign-flip p over scans.

model	test	AUROC	CUR	CUR-ERR	AbsRel_U	CUR vs ref
VGGT-1B	reference	0.902 [0.868, 0.930]	0.259 [0.175, 0.349]	0.000	0.010	
VGGT-1B	inpaint fill	0.867 [0.821, 0.907]	0.347 [0.255, 0.443]	0.001	0.018	$+0.088$ ($p = 0.031$)
VGGT-1B	5 views	0.902	0.269 [0.173, 0.377]	0.000	0.011	$+0.010$ ($p = 0.63$)
VGGT-1B	3 views	0.899	0.259 [0.167, 0.361]	0.000	0.013	$+0.001$ ($p = 0.98$)
VGGT-1B	low parallax	0.911	0.214 [0.110, 0.334]	0.000	0.021	-0.045 ($p = 0.35$)
VGGT-1B	+ distractor	0.905	0.257 [0.179, 0.340]	0.000	0.011	-0.002 ($p = 0.90$)
Pi3X	reference	0.828 [0.781, 0.870]	0.521 [0.390, 0.650]	0.002	0.024	
Pi3X	inpaint fill	0.786 [0.731, 0.836]	0.589 [0.473, 0.702]	0.004	0.022	$+0.068$ ($p = 0.005$)
Pi3X	5 views	0.822	0.539 [0.411, 0.661]	0.006	0.024	$+0.018$ ($p = 0.44$)
Pi3X	3 views	0.840	0.497 [0.373, 0.618]	0.032	0.051	-0.024 ($p = 0.64$)
Pi3X	low parallax	0.812	0.523 [0.376, 0.671]	0.040	0.050	$+0.002$ ($p = 0.98$)
Pi3X	+ distractor	0.829	0.510 [0.368, 0.650]	0.002	0.024	-0.011 ($p = 0.66$)
DA3	reference	0.712 [0.632, 0.783]	0.679 [0.569, 0.791]	0.006	0.018	
DA3	inpaint fill	0.726	0.688 [0.605, 0.774]	0.009	0.018	$+0.008$ ($p = 0.87$)
DA3	5 views	0.697	0.785 [0.703, 0.865]	0.005	0.019	$+0.106$ ($p = 0.008$)
DA3	3 views	0.729	0.667 [0.560, 0.770]	0.018	0.031	-0.012 ($p = 0.81$)
DA3	low parallax	0.863 [0.785, 0.925]	0.372 [0.230, 0.520]	0.008	0.029	-0.307 ($p = 0.0003$)
DA3	+ distractor	0.660 [0.580, 0.734]	0.775 [0.680, 0.868]	0.003	0.019	$+0.096$ ($p = 0.0004$)

Stress tests, plotted.

Every detector on the true-visibility protocol. Table S7 lists every detector of the main paper's Table 3 with 95% cluster-bootstrap intervals over scenes, including the fill-trained heads and the linear probe trained on self-support labels.

Operating points from the per-pixel scores. Table S8 is computed from the per-pixel scores on the labelled pixels of every cell (scene, seed, view count), each cell weighing the same. AURC: area under the single-view rate of the kept pixels against coverage (oracle: supported pixels first). AbsRel of all labelled pixels and of the half with the highest score. CUR / keep: fraction of single-view pixels passing and fraction of supported pixels kept at a threshold fixed (a) on the other scenes of the same dataset so that 90% of their supported pixels pass (leave-one-scene-out), (b) on DTU and applied unchanged (frozen; the DTU row has none). Bands: fraction of pixels marked observed / abstain / imagined at the paper's fixed thresholds; the single-view rate and AbsRel inside the observed band.




Figure S7. **Stress tests.** CUR under each stress condition against the reference, with intervals. View count does nothing for VGGT and Pi3X; the inpainted fill raises leakage; DA3 alone reacts to parallax and to a distractor.

Table S7. **True-visibility protocol, every detector**, pooled over scenes and view counts as in the main paper, with 95% cluster-bootstrap intervals over scenes.

detector	DTU AUROC↑	DTU CUR↓	CO3Dv2 AUROC↑	CO3Dv2 CUR↓	ETH3D AUROC↑	ETH3D CUR↓	Photot. AUROC↑	Photot. CUR↓
VGGT-1B								
native confidence	0.772 [0.722, 0.823]	0.530 [0.443, 0.616]	0.754 [0.712, 0.793]	0.723 [0.650, 0.796]	0.715 [0.621, 0.802]	0.566 [0.430, 0.704]	0.802 [0.748, 0.850]	0.451 [0.343, 0.569]
reprojection consistency	0.954 [0.944, 0.963]	0.082 [0.067, 0.098]	0.793 [0.746, 0.839]	0.693 [0.517, 0.860]	0.975 [0.968, 0.982]	0.069 [0.034, 0.106]	0.824 [0.786, 0.869]	0.340 [0.249, 0.423]
distance to image border	0.701 [0.671, 0.731]	0.727 [0.700, 0.755]	0.454 [0.388, 0.520]	0.897 [0.834, 0.946]	0.725 [0.669, 0.780]	0.632 [0.534, 0.728]	0.730 [0.695, 0.765]	0.649 [0.606, 0.689]
depth edges	0.549 [0.519, 0.576]	0.831 [0.806, 0.855]	0.422 [0.373, 0.473]	0.943 [0.923, 0.962]	0.598 [0.503, 0.699]	0.762 [0.638, 0.857]	0.674 [0.594, 0.748]	0.619 [0.527, 0.714]
fill-trained head	0.609 [0.575, 0.646]	0.765 [0.728, 0.798]	0.451 [0.379, 0.522]	0.916 [0.880, 0.948]	0.686 [0.615, 0.760]	0.657 [0.551, 0.758]	0.704 [0.647, 0.759]	0.673 [0.594, 0.749]
fill-trained per-image control	0.744 [0.705, 0.779]	0.640 [0.586, 0.697]	0.356 [0.306, 0.410]	0.957 [0.943, 0.969]	0.619 [0.542, 0.698]	0.736 [0.641, 0.820]	0.622 [0.562, 0.686]	0.760 [0.706, 0.805]
per-image control (GT labels)	0.878 [0.845, 0.907]	0.340 [0.289, 0.394]	0.462 [0.392, 0.540]	0.878 [0.814, 0.933]	0.712 [0.649, 0.767]	0.666 [0.608, 0.731]	0.787 [0.732, 0.837]	0.530 [0.448, 0.603]
linear probe (GT labels)	0.989 [0.985, 0.992]	0.024 [0.015, 0.035]	0.913 [0.883, 0.942]	0.250 [0.165, 0.337]	0.966 [0.959, 0.975]	0.095 [0.068, 0.122]	0.894 [0.843, 0.936]	0.265 [0.158, 0.392]
support head, GT visibility labels	0.993 [0.990, 0.995]	0.015 [0.008, 0.024]	0.927 [0.903, 0.951]	0.211 [0.138, 0.287]	0.980 [0.972, 0.986]	0.055 [0.035, 0.076]	0.908 [0.863, 0.947]	0.258 [0.146, 0.391]
per-image control (self labels)	0.885 [0.851, 0.912]	0.325 [0.272, 0.383]	0.460 [0.394, 0.532]	0.892 [0.833, 0.937]	0.626 [0.538, 0.711]	0.750 [0.665, 0.830]	0.729 [0.656, 0.805]	0.681 [0.535, 0.810]
linear probe (self labels)	0.988 [0.984, 0.992]	0.022 [0.014, 0.032]	0.898 [0.861, 0.934]	0.296 [0.191, 0.402]	0.967 [0.958, 0.976]	0.084 [0.058, 0.107]	0.924 [0.903, 0.948]	0.187 [0.127, 0.243]
support head, label-free	0.992 [0.989, 0.995]	0.017 [0.010, 0.025]	0.931 [0.907, 0.953]	0.199 [0.134, 0.266]	0.980 [0.972, 0.986]	0.051 [0.033, 0.069]	0.930 [0.908, 0.954]	0.191 [0.125, 0.253]
label-free head, adapted on the target domain	–	–	0.841 [0.785, 0.891]	0.474 [0.338, 0.610]	–	–	0.926 [0.899, 0.952]	0.203 [0.132, 0.275]
support head (GT labels) × native confidence	0.986 [0.980, 0.990]	0.031 [0.018, 0.047]	0.920 [0.891, 0.947]	0.236 [0.149, 0.338]	0.954 [0.935, 0.972]	0.131 [0.071, 0.199]	0.931 [0.912, 0.952]	0.177 [0.115, 0.237]
label-free head × native confidence	0.980 [0.973, 0.986]	0.048 [0.030, 0.069]	0.920 [0.890, 0.948]	0.225 [0.144, 0.314]	0.943 [0.920, 0.965]	0.150 [0.086, 0.224]	0.930 [0.912, 0.951]	0.179 [0.118, 0.238]
Pi3X								
native confidence	0.820 [0.793, 0.845]	0.493 [0.435, 0.553]	0.697 [0.649, 0.740]	0.846 [0.803, 0.888]	0.887 [0.856, 0.918]	0.304 [0.213, 0.389]	0.839 [0.808, 0.867]	0.450 [0.365, 0.549]
reprojection consistency	0.914 [0.900, 0.929]	0.164 [0.120, 0.213]	0.885 [0.859, 0.909]	0.224 [0.164, 0.293]	0.977 [0.965, 0.986]	0.054 [0.024, 0.092]	0.814 [0.775, 0.857]	0.361 [0.287, 0.431]
distance to image border	0.701 [0.671, 0.731]	0.727 [0.700, 0.755]	0.454 [0.388, 0.520]	0.897 [0.834, 0.946]	0.725 [0.669, 0.780]	0.632 [0.534, 0.728]	0.730 [0.695, 0.765]	0.649 [0.606, 0.689]
depth edges	0.545 [0.516, 0.573]	0.835 [0.812, 0.858]	0.424 [0.377, 0.474]	0.951 [0.933, 0.967]	0.596 [0.498, 0.703]	0.761 [0.640, 0.854]	0.638 [0.570, 0.700]	0.699 [0.640, 0.762]
fill-trained head	0.713 [0.679, 0.745]	0.650 [0.596, 0.706]	0.433 [0.378, 0.491]	0.909 [0.864, 0.942]	0.647 [0.573, 0.703]	0.695 [0.643, 0.751]	0.823 [0.784, 0.863]	0.454 [0.370, 0.536]
fill-trained per-image control	0.718 [0.681, 0.751]	0.667 [0.622, 0.715]	0.391 [0.338, 0.445]	0.959 [0.948, 0.969]	0.644 [0.595, 0.695]	0.719 [0.625, 0.800]	0.681 [0.631, 0.730]	0.720 [0.657, 0.781]
per-image control (GT labels)	0.863 [0.831, 0.891]	0.375 [0.326, 0.425]	0.428 [0.359, 0.507]	0.889 [0.823, 0.941]	0.694 [0.640, 0.749]	0.685 [0.614, 0.745]	0.775 [0.722, 0.825]	0.577 [0.499, 0.651]
linear probe (GT labels)	0.985 [0.979, 0.989]	0.034 [0.021, 0.049]	0.931 [0.907, 0.954]	0.203 [0.133, 0.277]	0.956 [0.939, 0.970]	0.123 [0.074, 0.181]	0.919 [0.894, 0.944]	0.204 [0.136, 0.271]
support head, GT visibility labels	0.990 [0.986, 0.994]	0.021 [0.010, 0.035]	0.930 [0.907, 0.953]	0.221 [0.138, 0.312]	0.975 [0.964, 0.984]	0.072 [0.041, 0.107]	0.938 [0.919, 0.959]	0.176 [0.111, 0.240]
per-image control (self labels)	0.871 [0.837, 0.899]	0.363 [0.309, 0.418]	0.469 [0.400, 0.546]	0.877 [0.809, 0.928]	0.610 [0.531, 0.688]	0.776 [0.709, 0.831]	0.719 [0.643, 0.797]	0.697 [0.566, 0.821]
linear probe (self labels)	0.983 [0.977, 0.988]	0.036 [0.023, 0.051]	0.931 [0.903, 0.957]	0.192 [0.121, 0.269]	0.939 [0.918, 0.956]	0.171 [0.114, 0.241]	0.919 [0.894, 0.945]	0.200 [0.133, 0.264]
support head, label-free	0.988 [0.983, 0.993]	0.025 [0.013, 0.040]	0.939 [0.916, 0.960]	0.190 [0.118, 0.265]	0.963 [0.946, 0.976]	0.103 [0.061, 0.158]	0.940 [0.920, 0.960]	0.166 [0.105, 0.226]
label-free head, adapted on the target domain	–	–	0.964 [0.947, 0.978]	0.094 [0.054, 0.143]	–	–	0.929 [0.898, 0.958]	0.198 [0.118, 0.282]
support head (GT labels) × native confidence	0.988 [0.983, 0.993]	0.027 [0.014, 0.042]	0.928 [0.903, 0.952]	0.230 [0.144, 0.323]	0.978 [0.967, 0.987]	0.064 [0.033, 0.099]	0.935 [0.911, 0.957]	0.181 [0.109, 0.258]
label-free head × native confidence	0.986 [0.980, 0.991]	0.030 [0.017, 0.046]	0.935 [0.912, 0.958]	0.200 [0.124, 0.280]	0.967 [0.949, 0.980]	0.092 [0.051, 0.146]	0.934 [0.910, 0.957]	0.185 [0.113, 0.258]
Pi3								
native confidence	0.841 [0.815, 0.864]	0.489 [0.426, 0.553]	0.551 [0.503, 0.600]	0.882 [0.845, 0.917]	0.814 [0.756, 0.871]	0.498 [0.371, 0.618]	0.847 [0.795, 0.892]	0.447 [0.345, 0.555]
reprojection consistency	0.952 [0.943, 0.960]	0.089 [0.069, 0.112]	0.894 [0.871, 0.915]	0.205 [0.153, 0.261]	0.976 [0.965, 0.985]	0.039 [0.023, 0.058]	0.817 [0.775, 0.864]	0.345 [0.250, 0.432]
distance to image border	0.701 [0.671, 0.731]	0.727 [0.700, 0.755]	0.454 [0.388, 0.520]	0.897 [0.834, 0.946]	0.725 [0.669, 0.780]	0.632 [0.534, 0.728]	0.730 [0.695, 0.765]	0.649 [0.606, 0.689]
depth edges	0.546 [0.518, 0.574]	0.839 [0.816, 0.862]	0.424 [0.377, 0.472]	0.950 [0.932, 0.967]	0.597 [0.499, 0.704]	0.764 [0.637, 0.858]	0.652 [0.583, 0.718]	0.670 [0.598, 0.745]
per-image control (GT labels)	0.878 [0.846, 0.906]	0.345 [0.291, 0.402]	0.464 [0.393, 0.544]	0.880 [0.815, 0.935]	0.717 [0.651, 0.774]	0.661 [0.601, 0.729]	0.796 [0.744, 0.842]	0.510 [0.431, 0.583]
linear probe (GT labels)	0.985 [0.980, 0.990]	0.032 [0.019, 0.046]	0.943 [0.922, 0.962]	0.175 [0.109, 0.245]	0.938 [0.905, 0.965]	0.165 [0.091, 0.249]	0.914 [0.882, 0.944]	0.218 [0.143, 0.290]
support head, GT visibility labels	0.992 [0.988, 0.995]	0.016 [0.008, 0.026]	0.934 [0.914, 0.954]	0.203 [0.135, 0.273]	0.953 [0.926, 0.974]	0.135 [0.068, 0.214]	0.932 [0.911, 0.954]	0.201 [0.131, 0.272]
per-image control (self labels)	0.888 [0.856, 0.914]	0.320 [0.268, 0.381]	0.471 [0.402, 0.548]	0.895 [0.834, 0.942]	0.654 [0.579, 0.725]	0.750 [0.668, 0.822]	0.724 [0.645, 0.804]	0.683 [0.533, 0.820]
linear probe (self labels)	0.983 [0.977, 0.989]	0.031 [0.018, 0.046]	0.926 [0.897, 0.953]	0.235 [0.139, 0.335]	0.917 [0.885, 0.944]	0.225 [0.151, 0.308]	0.915 [0.882, 0.945]	0.209 [0.140, 0.275]
support head, label-free	0.989 [0.984, 0.994]	0.021 [0.011, 0.034]	0.930 [0.907, 0.952]	0.225 [0.145, 0.309]	0.951 [0.924, 0.971]	0.139 [0.075, 0.215]	0.931 [0.908, 0.955]	0.181 [0.121, 0.238]
label-free head × native confidence	0.985 [0.979, 0.990]	0.034 [0.021, 0.048]	0.915 [0.888, 0.942]	0.266 [0.172, 0.364]	0.943 [0.911, 0.966]	0.151 [0.088, 0.228]	0.929 [0.907, 0.953]	0.197 [0.129, 0.257]
Depth Anything 3								
native confidence	0.836 [0.815, 0.855]	0.430 [0.383, 0.481]	0.683 [0.615, 0.742]	0.743 [0.655, 0.828]	0.643 [0.557, 0.744]	0.635 [0.494, 0.757]	0.782 [0.707, 0.851]	0.512 [0.389, 0.636]
reprojection consistency	0.926 [0.912, 0.939]	0.175 [0.118, 0.241]	0.836 [0.799, 0.872]	0.463 [0.335, 0.585]	0.962 [0.942, 0.977]	0.109 [0.044, 0.176]	0.844 [0.804, 0.882]	0.332 [0.247, 0.419]
distance to image border	0.701 [0.671, 0.731]	0.727 [0.700, 0.755]	0.454 [0.388, 0.520]	0.897 [0.834, 0.946]	0.725 [0.669, 0.780]	0.632 [0.534, 0.728]	0.730 [0.695, 0.765]	0.649 [0.606, 0.689]
depth edges	0.551 [0.525, 0.576]	0.844 [0.821, 0.868]	0.408 [0.356, 0.463]	0.968 [0.953, 0.981]	0.592 [0.498, 0.695]	0.767 [0.643, 0.859]	0.645 [0.582, 0.707]	0.717 [0.651, 0.782]
per-image control (GT labels)	0.761 [0.728, 0.794]	0.586 [0.537, 0.632]	0.440 [0.373, 0.506]	0.903 [0.842, 0.947]	0.746 [0.701, 0.794]	0.620 [0.535, 0.700]	0.732 [0.688, 0.767]	0.646 [0.606, 0.684]
linear probe (GT labels)	0.973 [0.964, 0.980]	0.069 [0.048, 0.093]	0.875 [0.846, 0.902]	0.354 [0.283, 0.427]	0.969 [0.956, 0.980]	0.086 [0.050, 0.125]	0.909 [0.884, 0.937]	0.216 [0.153, 0.270]
support head, GT visibility labels	0.985 [0.978, 0.990]	0.036 [0.022, 0.053]	0.883 [0.859, 0.908]	0.329 [0.265, 0.392]	0.985 [0.981, 0.989]	0.040 [0.026, 0.054]	0.927 [0.900, 0.953]	0.188 [0.127, 0.244]
per-image control (self labels)	0.760 [0.727, 0.792]	0.598 [0.548, 0.647]	0.416 [0.349, 0.484]	0.911 [0.847, 0.956]	0.749 [0.700, 0.801]	0.610 [0.514, 0.700]	0.727 [0.683, 0.764]	0.650 [0.608, 0.691]
linear probe (self labels)	0.971 [0.961, 0.978]	0.074 [0.050, 0.102]	0.869 [0.836, 0.900]	0.371 [0.292, 0.451]	0.952 [0.933, 0.967]	0.134 [0.089, 0.189]	0.909 [0.886, 0.937]	0.230 [0.158, 0.284]
support head, label-free	0.982 [0.975, 0.988]	0.040 [0.026, 0.058]	0.879 [0.844, 0.911]	0.323 [0.249, 0.398]	0.974 [0.968, 0.980]	0.070 [0.049, 0.092]	0.925 [0.905, 0.948]	0.202 [0.141, 0.250]
label-free head × native confidence	0.977 [0.967, 0.984]	0.056 [0.033, 0.083]	0.833 [0.784, 0.875]	0.394 [0.302, 0.490]	0.919 [0.892, 0.947]	0.167 [0.115, 0.220]	0.921 [0.898, 0.948]	0.206 [0.139, 0.264]

Cross-model disagreement. Two backbones run on the same views; view by view the second depth is aligned to the first by the median ratio over all valid pixels, and minus the relative disagreement is the confidence. Table S9: on the benchmark's filled patches every pair is at chance, and on real single-view geometry (DTU, clean views) disagreement scores 0.50 to 0.63, so models also agree with one another where only one view supports the surface. Agreement between models, unlike agreement between views, carries no signal in either case.

Fill sensitivity of the invented surface. If the surface a backbone returns inside the hidden region were fixed by the prior, changing the pixels the region is filled with would not move it. For every benchmark cell (seed 0, radius 0.18) the same hidden sphere is filled three ways (gray, blur, noise), the backbone runs on each, the three depths are aligned to the blur run

Table S8. **Operating points.** See the paragraph above for the columns.

dataset	backbone	detector	AURC	AbsRel all	AbsRel top half	CUR / keep (a)	CUR / keep (b)	obs. / abst. / imag.	single-view in obs.	AbsRel in obs.
DTU	VGGT-1B	native confidence	0.077	0.007	0.004	0.63 / 0.89	–	–	–	–
DTU	VGGT-1B	reprojection	0.035	0.007	0.005	0.08 / 0.94	–	–	–	–
DTU	VGGT-1B	head, GT labels	0.025	0.007	0.004	0.01 / 0.90	–	0.82 / 0.04 / 0.15	0.007	0.005
DTU	VGGT-1B	head, label-free	0.026	0.007	0.004	0.01 / 0.90	–	0.82 / 0.03 / 0.14	0.008	0.005
DTU	Pi3X	native confidence	0.057	0.021	0.015	0.59 / 0.89	–	–	–	–
DTU	Pi3X	reprojection	0.041	0.021	0.017	0.12 / 0.91	–	–	–	–
DTU	Pi3X	head, GT labels	0.026	0.021	0.014	0.01 / 0.90	–	0.79 / 0.05 / 0.16	0.006	0.016
DTU	Pi3X	head, label-free	0.026	0.021	0.014	0.02 / 0.90	–	0.77 / 0.06 / 0.17	0.005	0.016
CO3Dv2	VGGT-1B	native confidence	0.105	0.026	0.019	0.83 / 0.90	0.00 / 0.00	–	–	–
CO3Dv2	VGGT-1B	reprojection	0.088	0.026	0.021	1.00 / 1.00	0.14 / 0.53	–	–	–
CO3Dv2	VGGT-1B	head, GT labels	0.068	0.026	0.022	0.17 / 0.82	0.03 / 0.51	0.56 / 0.13 / 0.31	0.014	0.022
CO3Dv2	VGGT-1B	head, label-free	0.070	0.026	0.022	0.16 / 0.82	0.06 / 0.57	0.64 / 0.10 / 0.26	0.034	0.022
CO3Dv2	Pi3X	native confidence	0.122	0.017	0.011	0.80 / 0.84	0.83 / 0.86	–	–	–
CO3Dv2	Pi3X	reprojection	0.065	0.017	0.013	0.18 / 0.89	0.18 / 0.89	–	–	–
CO3Dv2	Pi3X	head, GT labels	0.068	0.017	0.013	0.13 / 0.83	0.06 / 0.71	0.67 / 0.13 / 0.20	0.031	0.014
CO3Dv2	Pi3X	head, label-free	0.067	0.017	0.012	0.12 / 0.84	0.06 / 0.76	0.64 / 0.16 / 0.20	0.019	0.013
ETH3D	VGGT-1B	native confidence	0.196	0.022	0.016	0.68 / 0.89	0.00 / 0.00	–	–	–
ETH3D	VGGT-1B	reprojection	0.125	0.022	0.017	0.03 / 0.93	0.03 / 0.93	–	–	–
ETH3D	VGGT-1B	head, GT labels	0.123	0.022	0.017	0.08 / 0.91	0.00 / 0.54	0.48 / 0.09 / 0.43	0.007	0.013
ETH3D	VGGT-1B	head, label-free	0.123	0.022	0.016	0.07 / 0.90	0.01 / 0.62	0.57 / 0.07 / 0.36	0.008	0.012
ETH3D	Pi3X	native confidence	0.145	0.015	0.009	0.61 / 0.90	0.62 / 0.92	–	–	–
ETH3D	Pi3X	reprojection	0.124	0.015	0.012	0.04 / 0.96	0.04 / 0.98	–	–	–
ETH3D	Pi3X	head, GT labels	0.127	0.015	0.010	0.08 / 0.90	0.01 / 0.66	0.55 / 0.13 / 0.32	0.037	0.009
ETH3D	Pi3X	head, label-free	0.129	0.015	0.010	0.13 / 0.90	0.05 / 0.79	0.60 / 0.11 / 0.29	0.052	0.009
Photot.	VGGT-1B	native confidence	0.030	0.039	0.020	0.57 / 0.89	0.00 / 0.02	–	–	–
Photot.	VGGT-1B	reprojection	0.024	0.039	0.025	0.30 / 0.91	0.30 / 0.90	–	–	–
Photot.	VGGT-1B	head, GT labels	0.013	0.039	0.026	0.27 / 0.90	0.06 / 0.59	0.67 / 0.11 / 0.22	0.007	0.026
Photot.	VGGT-1B	head, label-free	0.012	0.039	0.023	0.20 / 0.90	0.06 / 0.61	0.72 / 0.10 / 0.18	0.007	0.024
Photot.	Pi3X	native confidence	0.020	0.041	0.021	0.63 / 0.88	0.40 / 0.71	–	–	–
Photot.	Pi3X	reprojection	0.025	0.041	0.031	0.31 / 0.90	0.33 / 0.94	–	–	–
Photot.	Pi3X	head, GT labels	0.011	0.041	0.023	0.17 / 0.90	0.13 / 0.83	0.83 / 0.09 / 0.09	0.012	0.028
Photot.	Pi3X	head, label-free	0.011	0.041	0.023	0.17 / 0.90	0.19 / 0.92	0.87 / 0.06 / 0.07	0.015	0.028

Table S9. **Cross-model disagreement as a detector.** Filled patches: DTU seed 0, blur, radius 0.18 (18 scans); CO3Dv2 blur and noise, seed 0, radius 0.18 (18 scenes). Single-view: the DTU vis protocol pooled over 3, 5 and 10 views. 95% cluster-bootstrap intervals over scenes.

pair	filled patch, DTU		filled patch, CO3Dv2		single-view, DTU	
	AUROC	CUR	AUROC	CUR	AUROC	CUR
Pi3X against DA3	0.560 [0.497, 0.624]	0.831 [0.761, 0.892]	0.563 [0.513, 0.614]	0.807 [0.740, 0.869]	–	–
Pi3X against Pi3	0.574 [0.493, 0.651]	0.794 [0.710, 0.873]	0.610 [0.557, 0.660]	0.759 [0.690, 0.821]	0.592 [0.545, 0.636]	0.733 [0.687, 0.776]
VGGT-1B against DA3	0.548 [0.461, 0.631]	0.822 [0.738, 0.893]	0.545 [0.478, 0.607]	0.831 [0.769, 0.888]	–	–
VGGT-1B against MapAnything	0.613 [0.526, 0.698]	0.779 [0.651, 0.892]	0.533 [0.459, 0.606]	0.856 [0.789, 0.910]	–	–
VGGT-1B against Pi3	0.571 [0.496, 0.641]	0.781 [0.703, 0.853]	0.564 [0.494, 0.629]	0.810 [0.745, 0.871]	0.571 [0.510, 0.628]	0.746 [0.684, 0.804]
VGGT-1B against Pi3X	0.523 [0.440, 0.602]	0.865 [0.809, 0.916]	0.527 [0.452, 0.595]	0.842 [0.779, 0.900]	0.543 [0.476, 0.606]	0.765 [0.708, 0.821]

by a per-view median ratio over the pixels outside the hidden region (the input mask, not a label), and every pixel's score is minus the relative spread of its depth over the three fills, so a pixel whose depth depends on the fill scores low. Table S10: AUROC and CUR of that score on the cell's U / S labels, the same for the blur-noise pair alone, the median relative spread inside and outside the hidden region, native confidence on the blur run of the same cells, and the single-view variant (the region refilled in view 0 only, gray and noise against blur, scored on the pixels of that view and on those of the nine untouched views). Refilling the region in a single view moves the surface in that view (AUROC 0.93 to 0.97 on its pixels, median spread 0.7 to 5.4%) and, an order of magnitude less, in the nine untouched views (0.73 to 0.88 on theirs, spread 0.1 to 0.7%): the invented surface follows the pixels of the view it is drawn in, with a weaker pull from the other views. 18 DTU scans and 18 CO3Dv2 scenes, four backbones.

Table S10. **Fill sensitivity of the invented surface.** The depth spread over three fills of the same hidden sphere as a detector, against native confidence on the same cells; the last two columns of each block refill one view only. 95% cluster-bootstrap intervals over scenes.

backbone	DTU, 18 scans								CO3Dv2, 18 scenes							
	AUROC	CUR	AUROC (blur, noise)	spread U (%)	spread S (%)	native AUROC	one view, own	one view, others	AUROC	CUR	AUROC (blur, noise)	spread U (%)	spread S (%)	native AUROC	one view, own	one view, others
VGGT-1B	0.978 [0.965, 0.987]	0.053 [0.028, 0.083]	0.934	2.0	0.1	0.915	0.969	0.882	0.910 [0.871, 0.943]	0.209 [0.135, 0.292]	0.844	1.1	0.2	0.839	0.934	0.843
Pi3X	0.918 [0.889, 0.943]	0.225 [0.152, 0.312]	0.854	1.6	0.3	0.831	0.930	0.842	0.965 [0.952, 0.976]	0.079 [0.049, 0.117]	0.903	1.1	0.1	0.778	0.935	0.823
Pi3	0.927 [0.873, 0.962]	0.174 [0.099, 0.274]	0.876	2.1	0.3	0.928	0.938	0.754	0.947 [0.930, 0.963]	0.125 [0.080, 0.177]	0.887	0.8	0.1	0.934	0.944	0.843
Depth Anything 3	0.824 [0.767, 0.875]	0.437 [0.318, 0.563]	0.806	2.0	0.6	0.714	0.960	0.729	0.620 [0.543, 0.699]	0.723 [0.604, 0.823]	0.612	1.3	0.9	0.684	0.775	0.630

The matched split. Table S11: every detector on the matched-patch protocol of the paper's Section 3 (three identical patches per scene: hidden everywhere, hidden except in an evidence set of 1, 2 or half the views, hidden only in the evidence set), DTU and CO3Dv2, blur and noise pooled, seeds 0 and 1, radius 0.18. AUROC$_m$ and CUR$_m$ score the imagined patch against the filled-but-observed one; *patch* scores clean supported pixels against the filled-but-observed ones; the evidence columns split the observed pixels by how many clean views see them (one at low or high parallax, two or more). The per-image controls are the pipeline check: they must stay near chance.

Table S11. **Matched split, every detector.**

detector	DTU						CO3Dv2					
	AUROC$_m$ ↑	CUR$_m$ ↓	patch	1 view, low	1 view, high	2+ views	AUROC$_m$ ↑	CUR$_m$ ↓	patch	1 view, low	1 view, high	2+ views
VGGT-1B												
native confidence	0.551	0.802	0.909	0.521	0.503	0.499	0.486	0.852	0.679	0.525	0.466	0.473
reprojection, own cameras	0.495	0.903	0.527	0.494	0.485	0.467	0.480	0.909	0.459	0.490	0.459	0.485
support head, label-free (clean-view labels)	0.544	0.780	0.742	0.459	0.466	0.516	0.464	0.893	0.626	0.475	0.432	0.433
matched per-image control (pipeline check)	0.587	0.694	0.999	0.577	0.610	0.581	0.575	0.743	0.987	0.573	0.578	0.590
matched linear probe	0.726	0.504	0.982	0.686	0.691	0.787	0.629	0.703	0.962	0.633	0.592	0.681
matched head, GT placement	0.763	0.430	0.993	0.725	0.727	0.825	0.656	0.616	0.965	0.649	0.648	0.712
matched per-image control, label-free	0.562	0.696	0.999	0.559	0.569	0.558	0.538	0.805	0.981	0.543	0.545	0.559
matched head, label-free	0.754	0.454	0.992	0.707	0.726	0.826	0.681	0.619	0.931	0.685	0.638	0.744
Pi3X												
native confidence	0.474	0.870	0.822	0.499	0.407	0.430	0.500	0.806	0.767	0.536	0.473	0.496
reprojection, own cameras	0.467	0.900	0.520	0.472	0.437	0.439	0.485	0.913	0.483	0.490	0.470	0.476
support head, label-free (clean-view labels)	0.481	0.820	0.693	0.398	0.437	0.452	0.502	0.845	0.481	0.516	0.437	0.475
matched per-image control (pipeline check)	0.591	0.670	0.999	0.585	0.620	0.580	0.583	0.718	0.981	0.586	0.595	0.595
matched linear probe	0.712	0.577	0.948	0.694	0.680	0.779	0.659	0.650	0.886	0.664	0.614	0.723
matched head, GT placement	0.730	0.503	0.985	0.710	0.715	0.808	0.687	0.551	0.925	0.681	0.674	0.754
matched per-image control, label-free	0.614	0.620	0.998	0.614	0.602	0.631	0.565	0.757	0.982	0.559	0.548	0.600
matched head, label-free	0.693	0.537	0.979	0.680	0.658	0.758	0.675	0.644	0.896	0.664	0.627	0.743
Pi3												
native confidence	0.495	0.828	0.925	0.495	0.494	0.484	0.494	0.808	0.905	0.518	0.521	0.492
reprojection, own cameras	0.501	0.891	0.524	0.497	0.484	0.482	0.475	0.924	0.494	0.482	0.462	0.472
matched per-image control (pipeline check)	0.585	0.694	0.999	0.572	0.601	0.579	0.571	0.748	0.988	0.570	0.580	0.588
matched head, GT placement	0.768	0.454	0.983	0.740	0.728	0.859	0.685	0.593	0.949	0.679	0.643	0.761
matched per-image control, label-free	0.592	0.683	0.999	0.578	0.588	0.578	0.570	0.756	0.981	0.578	0.566	0.584
matched head, label-free	0.772	0.448	0.988	0.748	0.729	0.855	0.678	0.627	0.946	0.691	0.616	0.740
Depth Anything 3												
native confidence	0.425	0.854	0.751	0.420	0.414	0.354	0.482	0.839	0.663	0.528	0.479	0.446
reprojection, own cameras	0.431	0.924	0.570	0.429	0.410	0.385	0.484	0.886	0.479	0.488	0.458	0.464
matched per-image control (pipeline check)	0.591	0.773	0.724	0.597	0.607	0.614	0.581	0.777	0.736	0.570	0.572	0.621
matched head, GT placement	0.703	0.548	0.996	0.701	0.678	0.817	0.622	0.654	0.976	0.649	0.624	0.679
matched per-image control, label-free	0.594	0.749	0.711	0.608	0.590	0.601	0.582	0.781	0.727	0.572	0.568	0.616
matched head, label-free	0.714	0.516	0.991	0.712	0.670	0.811	0.671	0.606	0.955	0.679	0.657	0.727

Provenance. Table S12: the provenance heads of Section 5 of the paper on the vis cells of every dataset, support AUROC and CUR of the aggregated score next to the conv head of the main table on the same cells, and the attribution columns (prov-AUROC, its in-frame variant that keeps only views whose frame contains the point, top-1) against the reprojection test with the model's own cameras read per view. Means over scene means. Figure S8 shows one scene per dataset.

Table S12. **Provenance heads.** Support score (AUROC, CUR) and attribution (prov-AUROC over every ordered pair of views, its in-frame variant, top-1 on supported pixels) per backbone and dataset.

detector	DTU					CO3Dv2					ETH3D					Photot.				
	AUROC	CUR	prov-AUROC	in-frame	top-1	AUROC	CUR	prov-AUROC	in-frame	top-1	AUROC	CUR	prov-AUROC	in-frame	top-1	AUROC	CUR	prov-AUROC	in-frame	top-1
VGGT-1B																				
support head, label-free (no attribution)	0.992	0.017	–	–	–	0.931	0.199	–	–	–	0.980	0.051	–	–	–	0.930	0.191	–	–	–
reprojection, own cameras	0.953	0.083	0.965	0.944	0.990	0.792	0.702	0.783	0.783	0.937	0.975	0.069	0.959	0.905	0.827	0.824	0.340	0.889	0.765	0.951
provenance head, GT labels	0.995	0.011	0.971	0.939	0.992	0.924	0.208	0.835	0.831	0.939	0.977	0.058	0.879	0.828	0.779	0.926	0.216	0.884	0.784	0.955
provenance head, label-free	0.993	0.014	0.958	0.921	0.988	0.926	0.195	0.829	0.826	0.940	0.970	0.079	0.828	0.832	0.766	0.932	0.177	0.853	0.776	0.938
Pi3X																				
support head, label-free (no attribution)	0.988	0.025	–	–	–	0.939	0.190	–	–	–	0.963	0.103	–	–	–	0.940	0.166	–	–	–
reprojection, own cameras	0.914	0.164	0.911	0.880	0.981	0.884	0.254	0.912	0.911	0.951	0.977	0.054	0.976	0.923	0.831	0.814	0.361	0.878	0.756	0.950
provenance head, GT labels	0.992	0.018	0.953	0.917	0.986	0.903	0.271	0.870	0.870	0.945	0.965	0.094	0.818	0.840	0.758	0.923	0.201	0.823	0.790	0.906
provenance head, label-free	0.989	0.025	0.943	0.911	0.985	0.913	0.250	0.877	0.877	0.948	0.958	0.115	0.822	0.852	0.752	0.928	0.187	0.829	0.793	0.909
Pi3																				
support head, label-free (no attribution)	0.989	0.021	–	–	–	0.930	0.225	–	–	–	0.951	0.139	–	–	–	0.931	0.181	–	–	–
reprojection, own cameras	0.952	0.089	0.941	0.924	0.987	0.894	0.205	0.930	0.929	0.953	0.976	0.039	0.972	0.937	0.831	0.817	0.345	0.887	0.761	0.950
provenance head, GT labels	0.993	0.016	0.956	0.925	0.987	0.940	0.185	0.877	0.876	0.940	0.961	0.103	0.807	0.837	0.760	0.918	0.223	0.824	0.791	0.915
provenance head, label-free	0.991	0.019	0.951	0.925	0.986	0.947	0.152	0.881	0.879	0.942	0.946	0.150	0.815	0.856	0.762	0.923	0.201	0.820	0.801	0.918
Depth Anything 3																				
support head, label-free (no attribution)	0.982	0.040	–	–	–	0.879	0.323	–	–	–	0.974	0.070	–	–	–	0.925	0.202	–	–	–
reprojection, own cameras	0.926	0.175	0.890	0.870	0.981	0.836	0.463	0.854	0.853	0.949	0.962	0.109	0.934	0.868	0.828	0.844	0.332	0.866	0.755	0.953
provenance head, GT labels	0.985	0.037	0.937	0.895	0.980	0.887	0.295	0.847	0.845	0.938	0.971	0.069	0.842	0.767	0.777	0.922	0.202	0.810	0.761	0.905
provenance head, label-free	0.982	0.044	0.930	0.892	0.980	0.887	0.301	0.850	0.848	0.941	0.966	0.084	0.841	0.798	0.793	0.924	0.202	0.797	0.770	0.902

Twenty views. With 20 clean DTU views, twice the most the heads saw in training, the visibility heads score AUROC 0.990 to 0.993 and the label-free heads 0.990 to 0.992, native confidence falls to 0.61 (VGGT) and 0.83 (Pi3X), reprojection




Figure S8. **Which view saw it, one scene per dataset** (VGGT, label-free provenance head, five input views, scenes the head never saw). Per row: the reference view with three query pixels, the ground-truth number of other views that see each pixel, the number the head attributes, and the head's probability per other input view for each query (bar colour: ground truth).

consistency scores 0.93 and 0.89, and the per-image control rises to 0.94: with twenty views the few remaining single-view pixels sit at the frame edge, and the control reads the edge.

Real occlusion against dense references: protocol. The backbone runs on N clean input views (3, 5 or 10; DTU: the spread view sets rotated by the seed; CO3Dv2, ETH3D and TUM RGB-D: adjacent frames, ETH3D and TUM RGB-D ordered by co-visibility). Every input pixel is back-projected with the predicted depth and cameras and placed in the ground-truth frame by a similarity transform: fitted on the camera centres on DTU and ETH3D, and on the input pixels that carry ground-truth depth on CO3Dv2 and TUM RGB-D, whose neighbouring video frames make a fit on camera centres degenerate (a cell then needs at least half of those pixels on the scanned surface; the measured share is 0.67 to 0.98). Each predicted

point is matched to the nearest point of the dense reference (DTU: all 49 rig views; CO3Dv2: the MVS depth of every known frame; ETH3D: the laser depth of every image; TUM RGB-D: the sensor depth of 80 frames spread evenly over the sequence, readings beyond 4 m dropped), at most 600k points, within $\tau = 1\%$ of the median depth. A reference point is *observed* when at least one input view sees it (it projects into the view onto that view's own ground-truth depth within 3%). It is *unobserved* when no input view passes that test and a z-buffer of the whole reference rendered into each input view (3×3 minimum filter, the same 3% tolerance) also finds it visible in none. A point the depth test calls unobserved and the z-buffer calls visible is *ambiguous*: it sits in a gap of that view's reference depth, and predicted points nearest to it are left out of both classes. Predicted points on an unobserved surface are the positives; the score is the detector's confidence; AUROC is computed per (scene, seed, view count) when at least 30 points are unobserved. A cell (dataset, backbone, view count) supports a detection claim when the unobserved share averages at least 0.5% and the head beats native confidence at $p < 0.05$ (paired sign-flip over scenes). The TUM RGB-D sequences, chosen by name before any detector was run: freiburg1 desk, desk2, room, plant, teddy and 360; freiburg2 desk; freiburg3 long_office_household, teddy, cabinet, large_cabinet and structure_texture_far.

Why the labels are hole-robust. The observed test needs ground-truth depth in the input view; a hole there would label a surface the camera does see as unobserved. The share of z-visible reference points that the depth test alone calls unobserved is 0.001 to 0.004 on DTU, 0.034 to 0.081 on CO3Dv2 and 0.31 to 0.35 on ETH3D, whose laser depth has gaps. The ambiguous class removes those points: it holds 0.1 to 0.4% of the predicted points on DTU, 0.9 to 2.8% on TUM RGB-D, 1.6 to 3.4% on CO3Dv2 and 1.9 to 6.7% on ETH3D, where it is several times the unobserved class. The labels are defined from geometry alone and were fixed before any detector was scored with them.

Capacity. Table S14: three heads trained on the same frozen features with the same label-free labels and schedule (1500 steps), scored with the real-occlusion protocol, plus the per-image control. Parameters: VGGT-1B: linear 2.11 M, conv 3.29 M, transformer 3.71 M; Pi3X: linear 0.53 M, conv 1.71 M, transformer 2.12 M The cross-view transformer head has two global-attention blocks over the tokens of all views (2D sinusoidal positions, a learned view embedding). It reaches a validation AUROC of 0.993 on its own labels yet is better than the conv head in none of the 12 cells.

Fused reconstruction at three views. Table S15: the fused-cloud protocol above with three input views, where real unseen geometry is most common, on the 18 DTU benchmark scans, the 22 DTU test scans and 12 ETH3D scenes, two view sets each. The head's cloud is about as accurate as native confidence's and keeps less single-view geometry in every row.

The matched head and the one-view case. On the matched split the per-image controls score 0.585 to 0.591 AUROC_m on DTU (bound 0.60), the heads 0.703 to 0.768 with ground-truth placement and 0.693 to 0.772 label-free. With one clean low-parallax view the heads reach 0.68 to 0.75; fine-tuning the VGGT heads for 1000 more steps with one-view evidence sampled at probability 0.7 leaves that case at 0.713 and 0.715, so the limit is the evidence, not the training budget.

Causal test of the support direction (details and caveats). Direction per hooked layer: mean supported token minus mean single-view token, fitted with ground-truth labels on DTU training scans 7, 8, 14, 16, 18, 19, 20, 22, 30, 31, 36 and 39 at five views; evaluation on the 18 benchmark scans at five views. VGGT: the four aggregator layers the depth head reads; Pi3 and Pi3X: the decoder tokens, edited where the point and confidence decoders read them. Mean over scans, unedited / ablated / random direction: support-head AUROC 0.994 / 0.659 / 0.994 (VGGT), 0.991 / 0.607 / 0.991 (Pi3X), 0.991 / 0.648 / 0.991 (Pi3); native-confidence AUROC 0.790 / 0.560 / 0.788, 0.830 / 0.577 / 0.830, 0.818 / 0.432 / 0.818; AbsRel on single-view pixels 0.011 / 0.141 / 0.011, 0.026 / 0.038 / 0.026, 0.020 / 0.182 / 0.020 (every ablated-against-random difference $p < 0.03$, paired sign-flip over scans; all but the two Pi3X depth differences $p < 10^{-4}$). The test was declared exploratory before the run, with both readings (read but unused; used) stated in advance. The random directions are isotropic and carry little token variance, so a second control, declared before it was run, repeats the edit along the three highest-variance principal directions of the patch tokens after the support direction is projected out. Token variance along the support direction / these three: 133 / 182, 160, 47 in the last VGGT layer (49 / 59, 40, 18 in the layer before; the two early layers carry under 4 along any of them), 10 / 21, 16, 14 on Pi3X and 13 / 20, 17, 11 on Pi3. Under these edits the support head stays at AUROC 0.991–0.994 (VGGT), 0.977–0.991 (Pi3X) and 0.982–0.991 (Pi3), and native confidence at 0.78–0.83, 0.82–0.84 and 0.77–0.82; the support direction's effect on the head is larger than each of them on each backbone ($p < 10^{-4}$, nine of nine comparisons, the criterion stated in advance). Depth is where the backbones differ: AbsRel on single-view pixels under the three matched edits is 0.027–0.039 on VGGT and 0.031–0.033 on Pi3, far below the support direction's 0.141 and 0.182, but 0.039–0.153 on Pi3X, at or above the support direction's 0.038. On Pi3X the depth effect is therefore not specific to the support direction and we do not claim it.

Causal test on ETH3D (partial transfer). The same directions, fitted on DTU training scans, are applied without refitting to the nine ETH3D scenes of the single-view table (five adjacent views). Support-head AUROC, unedited / support direction ablated / random / the three variance-matched directions: 0.981 / 0.829 / 0.981 / 0.946–0.970 (VGGT), 0.970 / 0.829 / 0.969 / 0.946–0.971 (Pi3X), 0.953 / 0.874 / 0.953 / 0.911–0.948 (Pi3). The criterion fixed before the run asked for the support direction to exceed every matched direction at $p < 0.05$ (exact paired sign-flip over nine scenes) on every backbone; it is met in six of nine comparisons (all three on Pi3X, two on VGGT, one on Pi3), so it is not met. Depth error on single-view pixels under the support direction rises from 2.6–2.8% to 8.8–9.1% on VGGT and Pi3, above every matched direction on Pi3 ($p = 0.004$) and above one of three on VGGT; on Pi3X, as on DTU, the matched directions damage depth more. We therefore state the causal result for DTU, and for ETH3D only that a direction fitted on another dataset still lowers the detector where a random one does not.

Foreign-view test (details). $K - 1$ views of a DTU benchmark scan plus one view of another benchmark scan at a seeded position; 18 scans, three seeds, 54 captures. Each detector's per-pixel score is averaged over each view; *sep* is the share of genuine views that score above the foreign one. At $K = 5$, sep for native confidence / reprojection / head: 0.880 / 0.954 / 0.991 (VGGT), 0.958 / 0.986 / 0.986 (Pi3X), 0.954 / 0.986 / 0.972 (Pi3), 0.894 / 0.963 / 1.000 (DA3); the head exceeds native confidence at $p < 0.05$ on VGGT, Pi3X and DA3 (the rule fixed in advance asked for three of four). At $K = 10$ every detector is near 1 and none differs. With a Gaussian-noise view in place of the foreign photograph, native confidence reaches sep 1.000 on Pi3 and Pi3X and the head 0.870 and 0.875 ($p < 10^{-4}$, the head is worse); on VGGT and DA3 both are at or near 1. The head was never trained on foreign or noise views.

Moving scenes, full video (rule not met). Every other experiment uses rigid scenes. We ran the DTU-trained label-free heads, unchanged, on the eight TUM RGB-D sequences with moving people (two people sitting or walking at a desk, four camera motions each) and, as a control, on five static sequences of the same camera. Each sequence is taken whole: 200 frames in temporal order, cut into 20 consecutive windows of ten frames, one forward pass per window. Labels come from sensor depth and motion-capture poses only. The sensor point of each pixel is projected into the other nine frames of its window; a pixel is *supported* if at least two frames see it, *single-view* if none does, and *moving* if at least two frames look through it (their depth is farther by more than 10% over a 3×3 neighbourhood), which cannot happen in a rigid scene. Supported and single-view pixels stay clear of every such violation, so the single-view class no longer mixes unseen surfaces with moved ones. On the static sequences every moving pixel is label noise: 0.16% of the pixels, against 5.1% on the dynamic sequences (the rule fixed in advance read the moving class only below a quarter). The unit is the sequence, with an exact paired sign-flip over the eight dynamic sequences; the rule asked for the head to exceed native confidence at $p < 0.05$ on three of four backbones.

Supported against single-view, static pixels of the dynamic sequences. AUROC for native confidence / reprojection / head: 0.556 / 0.648 / 0.700 (VGGT, $p = 0.008$), 0.749 / 0.712 / 0.780 (Pi3X, $p = 0.13$), 0.745 / 0.702 / 0.787 (Pi3, $p = 0.09$), 0.542 / 0.693 / 0.764 (DA3, $p = 0.008$). The head is the best of the three on every backbone, significantly above native confidence on two, so the rule is not met. On the static control, under the same video protocol, the head reaches 0.808 / 0.892 / 0.893 / 0.889 against 0.616 / 0.822 / 0.790 / 0.749 for native confidence: the head is about 0.1 AUROC lower on the sequences with moving people.

Supported against moving. Native confidence / reprojection / head: 0.602 / 0.830 / 0.764 (VGGT), 0.850 / 0.866 / 0.755 (Pi3X), 0.815 / 0.879 / 0.768 (Pi3), 0.616 / 0.857 / 0.783 (DA3). The head exceeds native confidence on VGGT and DA3 ($p = 0.008$) and is below it on Pi3X ($p = 0.016$) and Pi3; the rule is not met. Reprojection, which tests agreement of the predicted geometry directly, is the best detector of moving surfaces on all four backbones. The head does not tell a moved surface from an unseen one (single-view against moving: 0.42 to 0.54). Depth error (AbsRel after median scaling on supported pixels) is 0.03 to 0.07 on supported, 0.09 to 0.11 on single-view and 0.13 to 0.21 on moving pixels, so moving surfaces are where these backbones are least accurate. We therefore state the claims for rigid scenes.

HAD's hallucination scorer (no valid comparison). We ran the released scoring network of HAD (reference in the paper) on the DTU captures, giving it the ground-truth cameras it requires, and fixed in advance that its scores would count only if its own renderings of the scored views reached 15 dB. They reached 11.3 dB on three-view DTU captures, so by that rule its scores (which were at chance, AUROC 0.46 to 0.47) are not a valid measurement of the method and we claim no comparison. We then checked the wrapper without any label: the checkpoint's 365 tensors all match the model, half and full precision and four resolutions give the same renderings (8.9 to 9.2 dB on a five-view capture), a reference view rendered at its own pose reaches 24.9 dB, and neither the inverse pose convention, the OpenGL axis convention nor five scene scales raises quality above 10.4 dB. The renderings show the scene at the right viewpoint, blurred and misregistered: the convention is right and




Figure S9. **Moving scenes** (VGGT, TUM RGB-D *walking_xyz*; the three windows with the largest share of moving pixels, middle frame of each, chosen by that rule). Labels: supported (green), single-view (red), moving (purple; outlined on the score maps). Each score is shown between its 2nd and 98th percentile within the window, with the window's AUROC for supported against single-view (static) and against moving. The head is dark on the walking person and bright on the desk every frame sees; on Pi3X and Pi3 it shows no such gain over native confidence (see the paragraph above).




Figure S10. **The same window on four backbones** (TUM RGB-D *walking_xyz*, the window with the largest share of moving pixels, middle frame). Top: native confidence. Bottom: the support head. Bottom left: the labels (supported green, single-view red, moving purple; the moving class is outlined on every map). Numbers are the window's AUROC for supported against single-view (static) and against moving pixels. The head separates the static part on every backbone in this window; it is dark on the walking person on VGGT and DA3 and not on Pi3X and Pi3, where native confidence does as well or better.

the renderer does not reproduce DTU views at these baselines (cameras up to 0.87 m apart at 0.74 m depth). HAD targets generated novel views with known cameras; our setting is unposed input views.




Figure S11. **Moving scenes in numbers.** (a) Supported against single-view on the static pixels of the eight dynamic sequences: bars are means over sequences, dots are sequences, the line is the head's level on the five static sequences of the same camera. (b) Supported against moving: reprojection is the best detector on every backbone. (c) The whole *walking_xyz* video on VGGT, window by window (static part), with the share of moving pixels in each window.

Novel-view rendering from filtered points (negative result). We tested whether removing unsupported points helps a downstream renderer. Gaussian splatting is initialised from the predicted points of the input views, either all of them or without the 20% a detector trusts least (a random 20%, lowest native confidence, lowest support score, or lowest mean rank of both), with identical optimisation, and scored on eight held-out rig views of 15 DTU scans that no head and no benchmark setting used, at three and six input views on four backbones (eight settings; the rule was fixed before the run). In LPIPS the head's filter is significantly better than no filter in 4 of 8 settings (VGGT at both view counts, by 0.09 and 0.12; Pi3 and DA3 at six views), and significantly better than native confidence's filter in none; it is significantly worse in 4 (by 0.007 to 0.05). The combined rank is never better than native confidence. Rendering quality is driven by depth error, which native confidence ranks; support is a different quantity, and removing single-view points does not by itself improve a renderer.

Gaussian-splatting backbone (partial run). AnySplat (reference in the paper), a feed-forward 3D Gaussian-splatting model, was scored on the DTU configuration with its per-pixel Gaussian opacity as confidence (120 of 540 rows) and with the rendered accumulated alpha (450 of 540 rows), bf16 on one L4. Pooled over blur and noise: opacity AUROC 0.583 / CUR 0.718, rendered alpha 0.632 / 0.745, CUR-ERR 0.02 and 0.06; the noise fill drives the opacity below chance (0.36). The representation does not change the answer: a Gaussian the model places on an unseen surface is as opaque as one on an observed surface. The run stopped behind other jobs on the shared card and is reported as partial.

Table S13. **Real occlusion against dense references, every cell.** AUROC for predicted points on observed against unobserved surfaces, mean over scenes (two seeds each); paired sign-flip p over scenes. *ambiguous*: share of predicted points the hole-robust labels leave out. *claim*: yes / no where the cell qualifies (unobserved share $\geq 0.5\%$), – where the share is below 0.5%. DTU benchmark 18 scans, DTU test 22, ETH3D 12 scenes, TUM RGB-D 12 sequences, CO3Dv2 18 scenes.

dataset	backbone	views	ambiguous	unobs. share	native	head	head − native (p)	claim
DTU benchmark	VGGT-1B	3	0.44%	0.91%	0.787	0.830	+0.043 (0.070)	no
DTU benchmark	VGGT-1B	5	0.37%	0.45%	0.780	0.919	+0.139 (<0.0001)	–
DTU benchmark	VGGT-1B	10	0.20%	0.16%	0.777	0.954	+0.177 (<0.0001)	–
DTU benchmark	Pi3X	3	0.23%	0.87%	0.712	0.807	+0.095 (0.0004)	yes
DTU benchmark	Pi3X	5	0.18%	0.35%	0.731	0.855	+0.123 (0.0002)	–
DTU benchmark	Pi3X	10	0.08%	0.09%	0.731	0.929	+0.198 (0.0001)	–
DTU benchmark	Pi3	3	0.21%	0.93%	0.661	0.782	+0.121 (0.003)	yes
DTU benchmark	Pi3	5	0.22%	0.41%	0.741	0.879	+0.137 (0.0001)	–
DTU benchmark	Pi3	10	0.11%	0.09%	0.817	0.932	+0.115 (0.0004)	–
DTU benchmark	DA3	3	0.23%	1.47%	0.616	0.725	+0.109 (0.0003)	yes
DTU benchmark	DA3	5	0.22%	0.47%	0.694	0.807	+0.114 (0.0005)	–
DTU benchmark	DA3	10	0.10%	0.12%	0.757	0.914	+0.157 (0.0002)	–
DTU test	VGGT-1B	3	0.33%	0.71%	0.781	0.852	+0.071 (0.024)	yes
DTU test	VGGT-1B	5	0.32%	0.36%	0.805	0.921	+0.117 (0.0001)	–
DTU test	VGGT-1B	10	0.19%	0.11%	0.772	0.951	+0.178 (<0.0001)	–
DTU test	Pi3X	3	0.21%	0.74%	0.679	0.782	+0.102 (0.002)	yes
DTU test	Pi3X	5	0.18%	0.34%	0.735	0.855	+0.120 (<0.0001)	–
DTU test	Pi3X	10	0.09%	0.09%	0.790	0.931	+0.141 (0.0001)	–
DTU test	Pi3	3	0.27%	0.90%	0.622	0.772	+0.151 (0.0008)	yes
DTU test	Pi3	5	0.19%	0.36%	0.731	0.886	+0.155 (<0.0001)	–
DTU test	Pi3	10	0.10%	0.10%	0.811	0.931	+0.120 (<0.0001)	–
DTU test	DA3	3	0.20%	0.91%	0.589	0.769	+0.180 (<0.0001)	yes
DTU test	DA3	5	0.19%	0.37%	0.756	0.845	+0.089 (0.014)	–
DTU test	DA3	10	0.08%	0.08%	0.827	0.942	+0.115 (0.0001)	–
ETH3D	VGGT-1B	3	5.91%	0.79%	0.622	0.739	+0.116 (0.004)	yes
ETH3D	VGGT-1B	5	6.09%	0.60%	0.668	0.846	+0.178 (0.0006)	yes
ETH3D	VGGT-1B	10	3.68%	0.18%	0.709	0.872	+0.163 (0.002)	–
ETH3D	Pi3X	3	6.65%	1.35%	0.708	0.716	+0.008 (0.808)	no
ETH3D	Pi3X	5	5.95%	0.61%	0.764	0.791	+0.027 (0.292)	no
ETH3D	Pi3X	10	5.25%	0.24%	0.759	0.863	+0.103 (0.019)	–
ETH3D	Pi3	3	4.69%	0.90%	0.683	0.761	+0.078 (0.006)	yes
ETH3D	Pi3	5	4.77%	1.09%	0.695	0.826	+0.130 (0.004)	yes
ETH3D	Pi3	10	3.82%	0.26%	0.795	0.880	+0.085 (0.002)	–
ETH3D	DA3	3	3.43%	1.01%	0.512	0.753	+0.220 (0.010)	yes
ETH3D	DA3	5	4.91%	0.59%	0.627	0.831	+0.203 (0.001)	yes
ETH3D	DA3	10	1.93%	0.24%	0.601	0.772	+0.171 (0.003)	–
TUM RGB-D	VGGT-1B	3	2.16%	9.99%	0.537	0.630	+0.093 (0.005)	yes
TUM RGB-D	VGGT-1B	5	1.55%	6.92%	0.561	0.668	+0.107 (0.0008)	yes
TUM RGB-D	VGGT-1B	10	0.91%	4.52%	0.605	0.704	+0.099 (0.025)	yes
TUM RGB-D	Pi3X	3	2.55%	8.28%	0.813	0.787	−0.026 (0.136)	no
TUM RGB-D	Pi3X	5	1.92%	5.75%	0.812	0.816	+0.004 (0.778)	no
TUM RGB-D	Pi3X	10	1.05%	3.00%	0.817	0.839	+0.022 (0.222)	no
TUM RGB-D	Pi3	3	2.82%	8.17%	0.780	0.793	+0.013 (0.476)	no
TUM RGB-D	Pi3	5	2.02%	5.64%	0.804	0.830	+0.026 (0.221)	no
TUM RGB-D	Pi3	10	1.08%	2.88%	0.794	0.842	+0.048 (0.019)	yes
TUM RGB-D	DA3	3	2.68%	8.02%	0.656	0.704	+0.048 (0.057)	no
TUM RGB-D	DA3	5	2.09%	5.92%	0.659	0.751	+0.092 (0.007)	yes
TUM RGB-D	DA3	10	1.36%	3.57%	0.711	0.772	+0.061 (0.045)	yes
CO3Dv2	VGGT-1B	3	2.62%	1.12%	0.734	0.761	+0.027 (0.277)	no
CO3Dv2	VGGT-1B	5	2.27%	0.89%	0.756	0.794	+0.038 (0.128)	no
CO3Dv2	VGGT-1B	10	1.59%	0.68%	0.754	0.791	+0.036 (0.182)	no
CO3Dv2	Pi3X	3	3.35%	0.84%	0.666	0.764	+0.098 (0.027)	yes

Table S14. **Capacity on real occlusion.** AUROC observed against unobserved points, mean over scenes; last column paired sign-flip over scenes. This comparison was run before the hole-robust labels, so its ETH3D cells include the ambiguous points; on DTU alone the reading is the same.

backbone	dataset	views	native	per-image control	linear probe	conv head (ours)	transformer head	transformer − conv (p)
VGGT-1B	DTU	3	0.797	0.762	0.839	0.815	0.815	+0.001 (0.826)
VGGT-1B	DTU	5	0.797	0.818	0.895	0.897	0.894	−0.004 (0.013)
VGGT-1B	DTU	10	0.782	0.840	0.913	0.918	0.915	−0.003 (0.179)
VGGT-1B	ETH3D	3	0.550	0.541	0.602	0.616	0.576	−0.041 (0.003)
VGGT-1B	ETH3D	5	0.579	0.544	0.638	0.655	0.637	−0.018 (0.117)
VGGT-1B	ETH3D	10	0.604	0.562	0.675	0.684	0.673	−0.011 (0.167)
Pi3X	DTU	3	0.682	0.714	0.773	0.775	0.763	−0.012 (0.001)
Pi3X	DTU	5	0.697	0.774	0.818	0.821	0.816	−0.005 (0.103)
Pi3X	DTU	10	0.710	0.824	0.895	0.892	0.894	−0.002 (0.483)
Pi3X	ETH3D	3	0.636	0.537	0.634	0.639	0.631	−0.008 (0.164)
Pi3X	ETH3D	5	0.658	0.568	0.659	0.660	0.651	−0.009 (0.100)
Pi3X	ETH3D	10	0.646	0.542	0.670	0.674	0.681	+0.006 (0.591)

Table S15. **Fused point cloud at three views.** Accuracy at the given coverage, the head's accuracy and F1 change against native confidence (paired sign-flip p over scenes), and the single-view share of the kept points.

dataset	backbone	coverage	acc. native	acc. reproj.	acc. head	head − native (p)	F1 head − native	single-view native	single-view head
DTU benchmark	VGGT-1B	0.8	0.597	0.569	0.572	−0.024 (<0.0001)	−0.020	0.154	0.101
DTU benchmark	VGGT-1B	0.9	0.556	0.533	0.545	−0.011 (0.0001)	−0.009	0.156	0.131
DTU benchmark	Pi3X	0.8	0.172	0.166	0.173	+0.001 (0.695)	+0.001	0.140	0.099
DTU benchmark	Pi3X	0.9	0.161	0.156	0.159	−0.001 (0.101)	−0.001	0.150	0.128
DTU benchmark	Pi3	0.8	0.209	0.202	0.206	−0.003 (0.107)	−0.003	0.150	0.092
DTU benchmark	Pi3	0.9	0.192	0.186	0.189	−0.003 (0.001)	−0.003	0.153	0.122
DTU benchmark	DA3	0.8	0.175	0.180	0.186	+0.011 (0.449)	+0.011	0.142	0.114
DTU benchmark	DA3	0.9	0.158	0.166	0.170	+0.012 (0.372)	+0.011	0.152	0.140
DTU test	VGGT-1B	0.8	0.516	0.497	0.498	−0.018 (0.0001)	−0.017	0.160	0.104
DTU test	VGGT-1B	0.9	0.484	0.465	0.471	−0.013 (<0.0001)	−0.012	0.162	0.134
DTU test	Pi3X	0.8	0.185	0.178	0.183	−0.002 (0.063)	−0.002	0.144	0.108
DTU test	Pi3X	0.9	0.169	0.163	0.169	−0.000 (0.639)	−0.000	0.155	0.138
DTU test	Pi3	0.8	0.218	0.210	0.212	−0.006 (0.027)	−0.005	0.153	0.097
DTU test	Pi3	0.9	0.200	0.193	0.196	−0.004 (0.003)	−0.004	0.157	0.128
DTU test	DA3	0.8	0.185	0.194	0.195	+0.010 (0.185)	+0.010	0.147	0.121
DTU test	DA3	0.9	0.169	0.177	0.180	+0.011 (0.118)	+0.010	0.158	0.148
ETH3D	VGGT-1B	0.8	0.196	0.191	0.194	−0.001 (0.757)	−0.002	0.038	0.024
ETH3D	VGGT-1B	0.9	0.186	0.183	0.186	+0.000 (0.963)	−0.001	0.037	0.029
ETH3D	Pi3X	0.8	0.188	0.175	0.178	−0.010 (0.021)	−0.013	0.038	0.026
ETH3D	Pi3X	0.9	0.178	0.169	0.173	−0.004 (0.003)	−0.005	0.038	0.031
ETH3D	Pi3	0.8	0.175	0.158	0.164	−0.012 (0.011)	−0.011	0.039	0.026
ETH3D	Pi3	0.9	0.162	0.151	0.156	−0.006 (0.003)	−0.005	0.038	0.030
ETH3D	DA3	0.8	0.119	0.153	0.159	+0.040 (0.060)	+0.044	0.036	0.025
ETH3D	DA3	0.9	0.110	0.143	0.149	+0.038 (0.035)	+0.043	0.036	0.030