Status	Finished
Started	Sunday, 4 October 2026, 7:23 PM
Completed	Sunday, 4 October 2026, 7:34 PM
Duration	10 mins 21 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t = (11, 3)
x = 3 * t
print(x)
```

a. (11,3)(11,3)(11,3)

b. (11, 3, 11, 3, 11, 3) ✓

c. [11,11,11,3,3,3]

d. (11,3,11,11,3,11,11,11,3)

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. True ✓
True

b. False
True

c. False
False

d. True
False

Question **3**

Correct

Mark 1.00 out of 1.00

Choose the correct option.

a. In Python, a tuple can contain only strings as its elements.

b. In Python, a tuple can contain both integers and strings as its elements. ✓

c. In Python, a tuple can contain either string or integer but not both at a time.

d. In Python, a tuple can contain only integers as its elements.

Question **4**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. Computer

b. () ✓

c. (Computer)

d. Error

Question **5**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. TypeError: update() doesn't allow list as a argument.

b. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

c. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

d. Name Error

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a. {‘rec’, True, (‘cse’, ‘ece’)}

b. {‘rec’, 1, (‘cse’, ‘ece’)} ✓

c. Error

d. {‘rec’, 1, (‘cse’, ‘ece’),True}

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

a. {4} ✓

b. {2}

c. {1,3,4}

d. {1,3,2}

Question **8**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. True ✓

b. False

Question **9**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

- a. None of these
- b. We can change the tuple once created
- c. A tuple maintains the order of items ✓
- d. A tuple is unordered

Question **10**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

- a. {}
- b. {2,5,3,1}
- c. {2,5,1}
- d. {3} ✓

Question **11**

Correct

Mark 1.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

- a. A new set will be created with the elements of both set1 and set2 ✓
- b. Elements of set2 will get appended to set1
- c. A new set will be created with the unique elements of set1 and set2.
- d. Elements of set1 will get appended to set2

Question **12**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

- a. True
  False
- b. False
  True
- c. True ✓
  True
- d. False
  False

Question **13**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

a. tupl.sort()

b. tupl.append(2)

c. tupl1=tupl+tupl ✓

d. tupl[1]=2

Question **14**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t1 = (55, 44, 33, 22, 11)

x = [t1[i] for i in range(0, len(t1), 2)]

print(x)

a. (55,33,11)

b. [(55,33,11)]

c. ([55,33,11])

d. [55, 33, 11] ✓

Question **15**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
```

```
print type(a)
```

```

```

a. <class 'int'>

b. str

c. <class 'tuple'>

d. <class 'str'> ✓