Status	Finished
Started	Sunday, 4 October 2026, 9:05 PM
Completed	Sunday, 4 October 2026, 9:10 PM
Duration	5 mins 24 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. readline()
b. read()
c. readlist()
d. readlines() ✓

The correct answer is: readlines()

Question **2**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

a. 0
b. EOFError
c. An empty string ✓
d. None

The correct answer is: An empty string

Question **3**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

- a. null
- b. garbage
- c. 0 ✓
- d. 2
- e. 1

The correct answer is:
0

Question **4**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

- a. truncate() ✓
- b. reduce()
- c. shrink()
- d. resize()

The correct answer is: truncate()

Question **5**

Correct

Mark 1.00 out of 1.00

What is the purpose of the with statement in Python file handling?

- a. To read data from a file
- b. To write data to a file
- c. To delete a file
- d. To automatically close the file after its suite finishes ✓

The correct answer is: To automatically close the file after its suite finishes

Question **6**

Correct

Mark 1.00 out of 1.00

Which method is used to get the current file position?

a. locate()
b. tell() ✓
c. current()
d. position()

The correct answer is: tell()

Question **7**

Correct

Mark 1.00 out of 1.00

Which method is used to close a file in Python?

a. terminate()
b. finish()
c. end()
d. close() ✓

The correct answer is: close()

Question **8**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open(file = “a.txt”, “r”)
b. infile = open(file = “a.txt”, “r”)
c. infile = open(file, “a.txt”, “r”)
d. infile = open(“a.txt”, “r”) ✓

The correct answer is:
infile = open(“a.txt”, “r”)

Question **9**

Correct

Mark 1.00 out of 1.00

Which of the following is true about the readlines() method?

- a. It reads the entire file and returns it as a list of lines ✓
- b. It reads the entire file and returns it as a string
- c. It reads the file and returns it as a dictionary
- d. It reads a single line from the file

The correct answer is: It reads the entire file and returns it as a list of lines

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

- a. Hello
- b. Hello, world! ✓
- c. world
- d. An error is raised

The correct answer is: Hello, world!

Question **11**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code if the file "example.txt" contains "Python Programming"?

```
f = open("example.txt", "r")
print(f.read(6))
f.close()
```

a. Python Programming

b. Program

c. Python ✓

d. An error is raised

The correct answer is: Python

Question **12**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

a. a list of single characters

b. a list of lines ✓

c. str

d. a list of integers

The correct answer is:
a list of lines

Question **13**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

a. The encoding of the file
b. The file's read/write position
c. The buffer size for the file operations ✓
d. The access mode of the file

The correct answer is: The buffer size for the file operations

Question **14**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a.
- Move file pointer five characters behind from the current position.

b.
- Move file pointer five characters behind ahead from the end of a file.

c. Move file pointer five characters ahead from the beginning

d.
- Move file pointer five characters ahead from the current position. ✓

The correct answer is:

- Move file pointer five characters ahead from the current position.

Question **15**

Correct

Mark 1.00 out of 1.00

What does the encoding parameter in the open() function specify?

a. The buffer size
b. The size of the file
c. The encoding format of the file ✓
d. The mode of the file

The correct answer is: The encoding format of the file