

QEMU (Win)

```
Administrator: C:\Windows\system32\cmd.exe
Microsoft Windows [Version 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Users\user>ping 192.168.1.1

Pinging 192.168.1.1 with 32 bytes of data:
Reply from 192.168.1.1: bytes=32 time=1ms TTL=255
Reply from 192.168.1.1: bytes=32 time=1ms TTL=255
Reply from 192.168.1.1: bytes=32 time=1ms TTL=255
Reply from 192.168.1.1: bytes=32 time=1ms TTL=255

Ping statistics for 192.168.1.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 1ms, Average = 1ms

C:\Users\user>
```

ROUTER

```
ROUTER#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
ROUTER(config)#interface ethernet 0/0
ROUTER(config-if)#ip address 192.168.1.1 255.255.255.0
ROUTER(config-if)#exit
ROUTER(config)#exit
ROUTER#
*Jul 10 08:14:46.044: %SYS-5-CONFIG_I: Configured from console by console
ROUTER#show ip interface brief
Interface                IP-Address      OK? Method Status      Prot
-----
oob1
Ethernet0/0               192.168.1.1     YES manual up          up
Ethernet0/1               unassigned      YES TFTP  down        down
Ethernet0/2               unassigned      YES TFTP  down        down
Ethernet0/3               unassigned      YES TFTP  down        down

ROUTER#
```

Press RETURN to get started.

```
*Jul 18 08:44:58.031: %SYS-5-CONFIG_I: Configured from console by console
ROUTER#
ROUTER#s
*Jul 18 08:47:30.023: %SYS-5-CONFIG_I: Configured from console by ccna on vty0 (192.168.1.10)
ROUTER#s
% Type "show ?" for a list of subcommands
ROUTER#conf t
Enter configuration commands, one per line. End with CNTL/Z.
ROUTER(config)#ip domain-name
% Incomplete command.

ROUTER(config)#ip domain-name prajith.com
ROUTER(config)#crypto key generate rsa modulus 2048
% You already have RSA keys defined named ROUTER.prajith.com.
% They will be replaced.

% The key modulus size is 2048 bits
% Generating 2048 bit RSA keys, keys will be non-exportable...
*Jul 18 08:49:04.273: %SSH-5-DISABLED: SSH 2.0 has been disabled
[OK] (elapsed time was 2 seconds)

ROUTER(config)#
*Jul 18 08:49:06.025: %SSH-5-ENABLED: SSH 2.0 has been enabled
ROUTER(config)#ip ssh version 2
ROUTER(config)#username ccna
ROUTER(config)#privilege 15 secret ccna
^
% Invalid input detected at '^' marker.

ROUTER(config)#username ccna privilege 15 secret ccna
ROUTER(config)#line vty 0 4
ROUTER(config-line)#transport input ssh
ROUTER(config-line)#login local
ROUTER(config-line)#exit
ROUTER(config)#exit
ROUTER#
*Jul 18 08:50:58.396: %SYS-5-CONFIG_I: Configured from console by console
ROUTER#
```



