AEGIS: NETWORK TOPOLOGY MINIMUM VERTEX COVER ENGINE

A PROJECT REPORT

Submitted By

PRAJWAL PRAVEEN (Reg No: ATP24CS089)

To

the APJ Abdul Kalam Technological University

in partial fulfillment of the requirements for the award of the degree of

Bachelor of Technology in Computer Science and Engineering

Course: PCCST502 – Design And Analysis Of Algorithms



DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

Ahalia School of Engineering & Technology

Ahalia Campus, Kozhippara, Palakkad, Kerala - 678557

OCTOBER 2026

AHALIA SCHOOL OF ENGINEERING & TECHNOLOGY
ISO 9001:2015 Certified Institution. Approved by AICTE & Affiliated to A. P. J. Abdul Kalam Technological University
Ahalia Health, Heritage & Knowledge Village, Palakkad - 678557. Ph: 04923-226666, www.ahalia.ac.in

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

CERTIFICATE

This is to certify that the project work report entitled ‘Aegis: Network Topology Minimum Vertex Cover Engine’ submitted by PRAJWAL PRAVEEN (Reg No: ATP24CS089), of Fifth Semester, B.Tech in Computer Science & Engineering, has been successfully carried out under our supervision and guidance in partial fulfillment of the requirements of the project work for the subject PCCST502 – Design And Analysis Of Algorithms, prescribed by APJ Abdul Kalam Technological University (KTU), Kerala. It is further certified that this work is a bonafide record of the project work carried out by the above student during the academic year 2026–2027.

Project Guide
Ms. Happy A
Assistant Professor
Dept. of Computer Science & Engg.

Head of the Department
Dr. S Gunasekaran
Professor and Head
Dept. of Computer Science & Engg.

AHALIA SCHOOL OF ENGINEERING & TECHNOLOGY
ISO 9001:2015 Certified Institution. Approved by AICTE & Affiliated to A. P. J. Abdul Kalam Technological University
Ahalia Health, Heritage & Knowledge Village, Palakkad - 678557. Ph: 04923-226666, www.ahalia.ac.in

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

DECLARATION

I hereby declare that the project report 'AEGIS: NETWORK TOPOLOGY MINIMUM VERTEX COVER ENGINE' submitted for the partial fulfilment of the requirements of the Fifth Semester Project for the course PCCST502 – Design And Analysis Of Algorithms, prescribed by APJ Abdul Kalam Technological University, Kerala, is a bonafide work carried out by me under the guidance of Ms. HAPPY A, Assistant Professor, Department of Computer Science & Engineering, Ahalia School of Engineering & Technology. The submission represents my algorithmic designs, implementation, and empirical evaluations in my own words. Where ideas, concepts, or standard library tools of others have been utilized, they have been adequately and accurately cited.

Place : PALAKKAD
Date : 25-10-2026

COUNTERSIGNED
Ms. Happy A
Assistant Professor, Dept. of CSE

PRAJWAL PRAVEEN
(Reg No: ATP24CS089)
Student, 5th Semester B.Tech CSE

ACKNOWLEDGEMENT

First and foremost, I express my deepest gratitude to the Almighty for granting the wisdom and strength necessary to complete this work. I express sincere gratitude to Dr. P R Suresh, Ph.D., Principal, Ahalia School of Engineering and Technology, for his institutional leadership. I extend sincere thanks to Dr. Krishna Kumar Kishor, Ph.D., Vice Principal, for providing computational infrastructure. I express my profound gratitude to Dr. S. Gunasekaran, Ph.D., Professor and Head of the Department of Computer Science and Engineering, for his constant encouragement. I am immensely indebted to my Project Guide, Ms. Happy A, Assistant Professor, for her meticulous supervision, insightful guidance, and continuous technical encouragement. I also thank Mr. Nandu S Nair for his timely mentorship. Finally, I express heartfelt appreciation to my parents and friends for their unwavering moral support.

INSTITUTION VISION & MISSION

• Vision: Grow as a center of learning and research, transforming students to professionals with knowledge, skill, competence, commitment, confidence through decisive learning and contribute to the sustainable development of the society.

• Mission: To instil technical expertise to address current challenges; to foster research, innovation, and entrepreneurship; and to promote welfare of society through ethical and professional conduct.

DEPARTMENT VISION & MISSION

• Vision: To develop computer science engineers with knowledge, computing skills and empowering them to excel in their profession through performance based learning contributing to sustainability, well-being of the society and professional ethics.

• Mission: To implement effective outcome-based education that fosters competent and skilled graduates; and to provide opportunities in research and collaborative innovation.

ABSTRACT

The Aegis project is an algorithmic network defense optimization engine engineered to solve the optimal Intrusion Detection System (IDS) and firewall sensor placement problem on computer networks. Deploying deep-packet inspection sensors across every single host is economically, computationally, and logistically prohibitive. By modeling network topologies as undirected graphs G = (V, E) where devices constitute vertices and communication links represent edges, Aegis frames sensor placement as the fundamental Minimum Vertex Cover (MVC) combinatorial optimization problem.

PROJECT IDEA: To formulate network defense sensor allocation as a mathematically rigorous graph optimization problem, evaluate the computational boundaries of Karp's NP-complete vertex cover problem, and engineer high-performance exact, approximate, and heuristic solvers capable of processing both synthetic topologies and real-world Nmap network scans.

IMPLEMENTATION & METHODOLOGY: Aegis is developed in Python 3 utilizing NetworkX for graph modeling, Matplotlib for topological and empirical visualization, and python-nmap for active host discovery. The engine implements three distinct algorithmic paradigms: (1) An exact Branch-and-Bound algorithm with maximal matching lower-bound pruning and degree-1 reductions achieving optimality in O(1.465^n) time; (2) A classic polynomial-time 2-Approximation algorithm based on maximal matching guaranteeing solutions within 2*|OPT| in linear O(|E|) time; and (3) A Greedy Degree heuristic achieving an O(log Delta) approximation. Experimental evaluation demonstrates that Aegis reduces active monitoring requirements by 70% to 75% on enterprise networks while preserving 100% link coverage.

GITHUB REPOSITORY: https://github.com/prajwal-56/aegis

LIST OF CONTENTS

S.NO	TOPIC	PAGE NO
1	CHAPTER 1 - INTRODUCTION	8
1.1	Background & Cybersecurity Motivation	8
1.2	Relevance to Design and Analysis of Algorithms	8
1.3	Aim and Objectives of the Project	9
1.4	Problem Statement, Scope & Requirements	9
2	CHAPTER 2 - ALGORITHMIC FOUNDATIONS & ANALYSIS	10
2.1	Graph-Theoretic Mathematical Formulation	10
2.2	Minimum Vertex Cover & NP-Completeness Proof	10
2.3	Exact Solver: Branch-and-Bound with Pruning	11
2.4	Polynomial-Time 2-Approximation via Maximal Matching	12
2.5	Greedy Degree-Based Heuristic	12
2.6	Asymptotic Complexity Summary	12
3	CHAPTER 3 - SYSTEM ARCHITECTURE & DESIGN	13
3.1	System Pipeline Architecture	13
3.2	Modular Software Component Design	13
3.3	Network Ingestion & Subnet Anti-Clique Engine	14
3.4	Interactive Visualization & CLI Dispatcher	14
4	CHAPTER 4 - IMPLEMENTATION & WORKFLOW	15
4.1	End-to-End Execution Workflow	15
4.2	Branch-and-Bound Decision Flowchart	15
4.3	Core Algorithmic Engineering Mechanisms	16
4.4	Defensive Invariant Enforcement & Robustness	16
5	CHAPTER 5 - EXPERIMENTAL RESULTS & BENCHMARKING	17
5.1	Benchmarking Experimental Setup	17
5.2	Empirical Runtime & Scaling Analysis	17
5.3	Topological Case Studies (Enterprise & Corporate LAN)	18
5.4	Hardware Overhead & Economic Cost Savings Analysis	18
6	CHAPTER 6 - SOFTWARE TESTING & VERIFICATION	19
6.1	Testing Strategy & Canonical Graph Benchmark Verification	19
6.2	Automated Pytest Execution Matrix (10/10 Passing)	19
7	CHAPTER 7 - CONCLUSION & FUTURE ENHANCEMENTS	20
7.1	Project Summary & Key Algorithmic Takeaways	20
7.2	Future Research Roadmap & Technological References	20

LIST OF FIGURES

FIG NO	FIGURE NAME	PAGE
Figure 3.1	Aegis System Architecture & Algorithmic Pipeline	13
Figure 4.1	Branch-and-Bound Exact Solver Logic Decision Flowchart	15
Figure 5.1	Runtime Scaling Comparison (Log Scale) & Solution Quality Bounds	17
Figure 5.2	Enterprise Network Topology Optimal Vertex Cover (|OPT| = 4)	18
Figure 5.3	Mock Corporate Network Topology Optimal Sensor Placement (|OPT| = 3)	18

LIST OF TABLES

TABLE NO	TABLE NAME	PAGE
Table 2.1	Asymptotic Time & Space Complexity of Implemented Solvers	12
Table 3.1	Aegis Modular Code Architecture & Component Responsibilities	13
Table 5.1	Empirical Runtime, Solution Size, and Approximation Ratios across Network Sizes	17
Table 5.2	Network Monitoring Hardware Overhead and Cost Reduction Matrix	18
Table 6.1	Automated Test Suite Verification Matrix (10 Automated Test Cases)	19

CHAPTER 1
INTRODUCTION

1.1 Background & Cybersecurity Motivation

Modern enterprise and campus computer networks interconnect hundreds or thousands of heterogeneous networked endpoints, including core backbone routers, departmental distribution switches, database clusters, virtualization hosts, engineering workstations, and IoT hardware. In this complex, interconnected networking paradigm, securing communication channels against internal lateral movement, stealthy port scanning, unauthorized exfiltration, and zero-day malware dissemination is a paramount cybersecurity priority. Network Intrusion Detection Systems (NIDS) and packet-sniffing appliances operate by intercepting raw communication frames as they traverse physical or logical links.

However, deploying hardware inspection appliances, commercial TAP licenses, or high-overhead eBPF packet inspection engines across every single network host is economically prohibitive and introduces severe CPU overhead on lightweight endpoints. Fortunately, digital network transmission is an inherently relational process between an initiator u and a responder v over communication link (u, v). If either endpoint u OR v contains an active inspection monitor, every packet traversing that link is captured, inspected, and logged. Therefore, complete link surveillance does not require universal host instrumentation; rather, administrators require the smallest possible subset of network hosts such that every communication link touches at least one monitored host.

1.2 Relevance to Design and Analysis of Algorithms

This real-world cybersecurity challenge maps directly to the classical Minimum Vertex Cover (MVC) problem—one of Richard Karp's original 21 NP-complete problems (1972). The Aegis project provides an end-to-end pedagogical and engineering case study for core concepts of the Design and Analysis of Algorithms (DAA) curriculum (PCCST502):
1. Asymptotic Intractability: Demonstrates why brute-force exhaustive enumeration of vertex subsets suffers from exponential state explosion O(2^n · m).
2. Exact Combinatorial Optimization: Illustrates how mathematical reductions (Degree-1 absorption) and admissible matching lower-bound heuristics enable Branch-and-Bound algorithms to prune massive subtrees, running in O(1.465^n) time.
3. Approximation Algorithm Design: Explores polynomial-time approximation algorithms with provable worst-case performance ratios (2-Approximation via Maximal Matching).
4. Heuristic Analysis: Investigates greedy local search heuristics that achieve logarithmic approximation bounds O(log Delta) in practice.

1.3 Aim and Objectives of the Project

Project Aim: The overarching aim of Aegis is to bridge theoretical graph optimization with practical network security engineering. The concrete technical objectives are:

• Algorithmic Synthesis: Implement and mathematically evaluate three complementary solver paradigms: exact combinatorial Branch-and-Bound, linear-time 2-Approximation via maximal matching, and greedy degree heuristics.
• Network Ingestion: Construct an active network scanning module utilizing Nmap to discover live hosts and reconstruct realistic hierarchical topologies.
• Anti-Clique Reconstruction: Formulate an anti-clique graph normalization algorithm to eliminate artificial complete subgraphs (Kn) common in naive LAN scans.
• Empirical Benchmarking: Develop an automated benchmarking suite to capture high-precision execution timings, approximation ratios, and scaling behavior.
• Interactive Visualization: Build high-resolution graph visualization tools highlighting active monitoring nodes in crimson and monitored endpoints in slate blue.
• Rigorous Verification: Establish a comprehensive automated unit and integration test suite guaranteeing algorithmic correctness across diverse topologies.

1.4 Problem Statement, Scope & Requirements

Problem Formulation: Given an undirected graph $G = (V, E)$ representing an active computer network where V represents network hosts and E represents communication channels, find a minimum cardinality subset $C \subseteq V$ such that $\forall (u, v) \in E, (u \in C \vee v \in C)$.
Project Scope: The system encompasses active subnet discovery, synthetic topology modeling, algorithmic solving, empirical performance analysis, automated testing, and graphical topology rendering. Target hardware includes standard x86_64 Linux workstations with Python 3.10+ and Nmap.

1.5 Software & System Dependencies

• Python 3.14 / 3.10+: Core runtime environment providing high-precision performance counters (time.perf_counter).
• NetworkX (>=3.0): High-performance graph modeling library managing node attributes, adjacency matrices, and graph algorithms.
• Matplotlib (>=3.8): Scientific visualization framework generating dual-axis logarithmic benchmark plots and topological layouts.
• python-nmap (>=0.7.1) & Nmap: Network discovery suite performing ARP and ICMP host discovery across IPv4 subnets.
• Pytest (>=8.0): Industrial testing framework executing automated test matrices and verifying algorithmic invariants.

CHAPTER 2
ALGORITHMIC FOUNDATIONS & THEORETICAL ANALYSIS

2.1 Graph-Theoretic Mathematical Formulation

Let G = (V, E) be an undirected, simple, finite graph. The vertex set V with |V| = n denotes the finite set of network devices. The edge set E with |E| = m denotes communication channels between devices. A subset C ⊆ V is formally defined as a Vertex Cover of G if and only if:

$$\forall (u, v) \in E : (u \in C \vee v \in C)$$

The Minimum Vertex Cover (MVC) optimization problem seeks to find a vertex cover C* of minimum cardinality:

$$C^* = \text{argmin}_{C \subseteq V} \{ |C| : C \text{ is a vertex cover of } G \}$$

In decision form (VC-DEC), the problem asks: Given a graph G = (V, E) and an integer k ≤ |V|, does G contain a vertex cover C such that |C| ≤ k?

2.2 Computational Complexity & NP-Completeness Proof

Theorem: The Vertex Cover decision problem (VC-DEC) is NP-Complete.
Proof Overview:
1. VC-DEC ∈ NP: Given a candidate certificate C ⊆ V, a deterministic polynomial-time verifier verifies that |C| ≤ k in O(1) time and checks that for every edge (u, v) ∈ E, at least one of u or v belongs to C. This edge-checking process runs in O(|E|) time. Because the verification algorithm runs in polynomial time O(n + m), VC-DEC belongs to the complexity class NP.
2. VC-DEC is NP-Hard via Reduction from 3-SAT: The reduction proceeds from 3-SAT to Independent Set (IS), and subsequently to Vertex Cover via the fundamental duality theorem: A set S ⊆ V is an independent set of G if and only if its complement V \ S is a vertex cover of G. Since 3-SAT is proven NP-complete (Cook-Levin Theorem) and polynomial reductions compose transitively, VC-DEC is NP-Complete.
Combinatorial Barrier: For a network of n devices, the number of possible vertex subsets is 2^n. For n = 15, 2^15 = 32,768 states (solvable in milliseconds). For n = 50, 2^50 ≈ 1.12 × 10^15 states, which would require decades of compute time. This exponential growth necessitates advanced exact branch pruning and approximation.

2.3 Exact Solver: Branch-and-Bound with Pruning

To achieve mathematical optimality without succumbing to naive 2^n combinatorial explosion, Aegis implements an exact Branch-and-Bound (B&B) algorithm fortified with admissible lower-bound bounding, degree-1 reductions, and maximum-degree branching heuristics.

1. Admissible Lower Bounding via Maximal Matching: In any graph G, a matching $M \subseteq E$ is a subset of edges such that no two edges share a common vertex. Because each edge in M is mutually disjoint, no single vertex can cover more than one edge in M. Therefore, any valid vertex cover C must contain at least one distinct vertex for every edge in M. Consequently, the cardinality of ANY matching $|M|$ establishes a rigorous admissible lower bound on the remaining cover:

$$|\text{Remaining Minimum Cover}| \geq |M|$$

During recursive search, Aegis computes a greedy maximal matching M on remaining uncovered edges in $O(|E|)$ time. If $|\text{current_cover}| + |M| \geq |\text{best_known}|$, the current search subtree cannot possibly improve upon the best-known solution, and the entire branch is pruned immediately.

2. Degree-1 Vertex Reduction Rule: In sparse topologies, peripheral devices (workstations, printers) frequently possess degree 1. Let u be a degree-1 vertex connected solely to neighbor v. If u is chosen in the cover, it covers only the single edge (u, v). If neighbor v is chosen instead, v covers (u, v) in addition to all other edges incident to v. Thus, including v rather than u is always mathematically optimal or tied:

$$\deg(u) = 1 \land (u, v) \in E \implies v \in C^*$$

Aegis detects degree-1 leaves and immediately forces neighbor v into the cover without branching, shrinking the graph deterministically.

3. Maximum Degree Branching Heuristic: When no degree-1 reductions remain, the solver branches on the vertex v exhibiting the maximum remaining degree:

• Branch 1 ($v \in C$): Include v in the cover and recurse on the remaining graph G - {v}.

• Branch 2 ($v \notin C$): If v is excluded, EVERY neighbor in N(v) MUST be included in the cover to satisfy all edges incident to v. Aegis adds N(v) to the cover and recurses on $G - (N(v) \cup \{v\})$.

Recurrence Relation & Complexity: This branching rule yields the recurrence $T(n) \leq T(n - 1) + T(n - \deg(v))$. Because $\deg(v) \geq 2$, the worst-case recurrence is bounded by $T(n) \leq T(n - 1) + T(n - 3)$, which solves to $O(1.465^n)$. This reduction enables exact solving for networks of 30+ nodes in milliseconds.

2.4 Polynomial-Time 2-Approximation via Maximal Matching

When network scale exceeds 100 devices, exact algorithms become intractable. Aegis implements the classic polynomial-time 2-Approximation algorithm:
Algorithm Mechanics: (1) Initialize cover C = ∅. (2) While uncovered edges remain, pick an arbitrary edge (u, v). (3) Add BOTH endpoints u and v to C. (4) Remove all edges incident to u or v. (5) Repeat until no uncovered edges remain.
Rigorous Proof of the 2-Approximation Bound:
• Let M be the set of edges selected in Step 2. Because all edges incident to u or v are purged upon selection, no two edges in M share an endpoint; hence, M is a matching.
• Every valid vertex cover C* (including the optimal cover) must touch at least one endpoint of every edge in M. Because all edges in M are disjoint, no single vertex can cover more than one edge in M. Therefore: $|C^*| \geq |M|$.
• In our algorithm, exactly 2 vertices were added to C for each edge in M: $|C| = 2 \cdot |M|$.
• Combining the two relations: $|C| = 2 \cdot |M| \leq 2 \cdot |C^*|$.
Hence, the algorithm is mathematically guaranteed never to pick more than twice the optimal number of sensors, executing in linear O(|E|) time.

2.5 Greedy Degree-Based Heuristic

While the 2-approximation provides a provable worst-case bound of 2.0, picking both endpoints often introduces redundant sensors. Aegis implements a Greedy Degree Heuristic: at each iteration, it selects the vertex v with the maximum number of currently uncovered incident edges, adds v to C, and marks its incident edges as covered. This greedy strategy guarantees an O(log Delta) approximation factor (where Delta is the maximum degree) and empirically achieves optimal or near-optimal covers (|OPT|) on real hierarchical network topologies.

2.6 Asymptotic Complexity Summary

Algorithm	Time Complexity	Space Complexity	Approximation Factor	Optimality Guarantee
Brute-Force Enumeration	O(2^n · m)	O(n)	1.0 (Exact)	Guaranteed Minimal
Exact Branch & Bound	O(1.465^n)	O(n + m)	1.0 (Exact)	Guaranteed Minimal
2-Approximation (Matching)	O(m)	O(n + m)	2.0 (|C| <= 2*|OPT|)	Bounded Approximate
Greedy Degree Heuristic	O(m · log n)	O(n + m)	O(log Delta)	Empirical Near-Optimal

Table 2.1: Asymptotic Time & Space Complexity of Implemented Solvers

CHAPTER 3
SYSTEM ARCHITECTURE & DESIGN

3.1 System Pipeline Architecture

Aegis is engineered following a clean, layered pipeline pattern consisting of four coordinated layers: (1) Network Ingestion, (2) Topology Construction, (3) Algorithmic Solver Core, and (4) Analytics & Visualization. Figure 3.1 illustrates the architectural dataflow.




Figure 3.1: Aegis System Architecture & Algorithmic Pipeline

3.2 Modular Software Component Design

The codebase is organized into modular Python components adhering to strict separation of concerns:

Module File	Primary Responsibility	Core Classes / Functions
graph_utils.py	Graph modeling, validation, & visual rendering	is_vertex_cover(), generate_synthetic_graph(), visualize_network_cover()
exact_solver.py	Exact Minimum Vertex Cover solvers	exact_vertex_cover_branch_and_bound(), solve_exact(), _get_matching_lower_bound()
approx_solver.py	Linear-time approximation & greedy heuristics	approx_vertex_cover_2approx(), approx_vertex_cover_greedy(), solve_approx()
scan.py	Nmap active discovery & topology builder	scan_network_live(), build_network_graph(), get_local_subnet()
benchmark.py	Empirical runtime & quality evaluation suite	run_benchmark_suite(), plot_benchmark_results()
main.py	Unified CLI interface & analytics dispatcher	main(), run_pipeline(), print_summary_table()

Table 3.1: Aegis Modular Code Architecture & Component Responsibilities

3.3 Network Ingestion Engine & Subnet Anti-Clique Reconstruction

A critical engineering contribution in Aegis is solving the Subnet Clique Trap. Naive network scanners assume that all hosts on a /24 subnet communicate directly with one another, resulting in a complete graph (clique Kn). In Kn, the minimum vertex cover is mathematically trivial: MVC(Kn) = n - 1 (every device except one must be monitored). To model real networks accurately, scan.py reconstructs realistic hierarchical topologies:

1. Gateway Sniffing: Inspects the kernel routing table via /proc/net/route or `ip route show default` to identify the default gateway router IP.
2. Active Nmap Discovery: Executes `nmap -sn` (ping and ARP scan) to identify live hosts, MAC vendors, and hostnames without altering network state.
3. Hierarchical Link Synthesis: Establishes a multi-tier tree: (a) Gateway router acts as core hub; (b) Departmental switches aggregate client pools; (c) Shared servers and printers connect to multiple client groups; and (d) Individual workstations attach as leaf endpoints.
4. Mock Topology Fallback: If Nmap is uninstalled, if raw sockets are restricted, or if running offline, Aegis seamlessly loads a pre-configured 10-device realistic corporate network topology (gateway, switches, NAS, printers, workstations, and IoT cameras).

3.4 Interactive Visualization & CLI Dispatcher

Aegis provides a rich command-line interface (main.py) and a scientific visualization engine (graph_utils.py):

• Unified CLI Dispatcher: Supports flags for active scanning (--scan), mock testing (--mock), synthetic presets (--preset [enterprise|scale_free|random]), and comparative benchmarking (--benchmark).

• Color-Coded Topological Rendering: Utilizes NetworkX spring-layout algorithms to draw network graphs. Active sensor nodes selected in the cover are rendered as enlarged crimson nodes (#DE2D26), while non-monitoring client endpoints are rendered in serene slate blue (#6BAED6). Edges represent monitored communication links. Visual figures are exported at publication-grade 300 DPI to the results/ directory.

• Summary Table & Analytics: Displays ASCII summary tables comparing cover cardinality, execution latencies, approximation ratios, and percentage cost reductions across all three algorithms simultaneously.

CHAPTER 4
IMPLEMENTATION & WORKFLOW

4.1 End-to-End Execution Workflow

The end-to-end execution lifecycle of Aegis follows a deterministic, pipeline-driven control flow: (1) Argument parsing and target subnet detection; (2) Topology ingestion or synthetic graph generation; (3) Graph normalization into an undirected NetworkX graph G = (V, E); (4) Dispatching to exact, approximate, and greedy solvers; (5) Integrity verification via is_vertex_cover(); and (6) Results tabularization and visualization.

4.2 Branch-and-Bound Decision Flowchart

Figure 4.1 details the recursive decision tree executed by the Branch-and-Bound solver. The engine iteratively tests lower-bound thresholds, applies reduction rules on degree-1 endpoints, and branches across the maximum-degree neighborhood.




Figure 4.1: Branch-and-Bound Exact Solver Logic Decision Flowchart

4.3 Core Algorithmic Engineering Mechanisms

Aegis implements several high-performance algorithmic engineering techniques that optimize runtime and memory usage across all modules:

1. Dynamic Adjacency Tracking: During Branch-and-Bound search, maintaining dynamic adjacency dictionaries remaining_adj = {u: set(neighbors)} enables O(1) degree lookups and rapid degree-1 vertex detection without expensive whole-graph traversals.

2. Canonical Edge Normalization: To eliminate edge duplication in undirected graphs, edges are canonically represented as ordered 2-tuples tuple(sorted((u, v), key=str)). This ensures rapid set difference operations (remaining_edges - removed_edges) in constant time.

3. Matching Lower Bound Cache: _get_matching_lower_bound() iterates through remaining edges and greedily accumulates pairwise disjoint edge pairs, computing an admissible lower bound in $O(|E|)$ time.

4. Degree-1 Leaf Absorption: When a degree-1 leaf is detected, Aegis bypasses branching entirely, immediately adding the sole neighbor to the cover and pruning all incident edges in a single recursive step.

4.4 Defensive Invariant Enforcement & Robustness

• Algorithmic Invariant Verification: Every solver execution is cross-validated by is_vertex_cover(graph, cover). The function verifies that $\forall\ (u, v) \in E : (u \in C \vee v \in C)$, guaranteeing zero undetected links.

• Boundary Condition Stability: Solvers handle edge cases gracefully: empty graphs G(0, 0) return empty sets $\varnothing$ in O(1) time; single-edge graphs G(2, 1) return minimal covers immediately without entering recursive loops.

• Graceful Degradation: scan.py implements multi-layered fallback mechanisms: if python-nmap is uninstalled or if raw socket permissions are denied, the engine falls back to mock enterprise network topologies seamlessly, preventing fatal program crashes.

CHAPTER 5
EXPERIMENTAL RESULTS & PERFORMANCE BENCHMARKING

5.1 Benchmarking Experimental Setup

To evaluate solver execution time and solution quality, Aegis was benchmarked on synthetic Barabási–Albert scale-free networks ranging from n = 6 to n = 22 vertices (step size = 2, 3 randomized seed samples per size) on Linux x86_64 with Python 3.14.

Nodes (n)	Exact Time (s)	2-Approx Time (s)	Greedy Time (s)	Exact Size | OPT|	2-Approx Size	Greedy Size	Approx Ratio
6	0.000051	0.000008	0.000017	3.0	4.0	3.0	1.33x
8	0.000047	0.000010	0.000016	4.0	6.0	4.0	1.50x
10	0.000052	0.000008	0.000018	4.0	6.7	4.0	1.69x
12	0.000070	0.000012	0.000022	5.3	8.7	5.3	1.65x
14	0.000084	0.000015	0.000031	6.0	9.0	6.0	1.50x
16	0.000103	0.000017	0.000028	7.3	10.7	7.3	1.45x
18	0.000119	0.000019	0.000034	7.7	11.7	7.7	1.54x
20	0.000138	0.000024	0.000047	9.3	13.3	9.3	1.43x
22	0.000164	0.000026	0.000048	9.7	16.0	10.0	1.64x

Table 5.1: Empirical Runtime, Solution Size, and Approximation Ratios across Network Sizes

5.2 Runtime Scaling & Quality Analysis

Figure 5.1 presents the generated dual-benchmark plots: Left Plot shows that while Exact Branch-and-Bound exhibits steep exponential growth, 2-Approximation and Greedy scale polynomially, running up to an order of magnitude faster. Right Plot confirms that 2-Approximation never exceeds the 2*|OPT| bound, while the Greedy heuristic consistently tracks the true optimal cover |OPT|.




Figure 5.1: Runtime Scaling Comparison (Log Scale) & Solution Quality Bounds

5.3 Topological Case Studies: Enterprise & Corporate Networks

Case Study 1 (Enterprise Tree Topology, Figure 5.2): Evaluated on an enterprise network with 14 devices and 13 connections. The exact solver identified an optimal cover of |OPT| = 4 nodes [Switch-1, Switch-2, Switch-3, Switch-4], saving 71.4% in sensor deployment costs. Case Study 2 (Mock Corporate LAN, Figure 5.3): Evaluated on 10 hosts with 17 active connections (gateway, servers, printers, workstations, cameras, and phones). The solver selected 3 nodes [192.168.1.1, 192.168.1.101, 192.168.1.102], achieving 70.0% sensor reduction.




Figure 5.2: Enterprise Topology (|OPT| = 4)




Figure 5.3: Mock Corporate LAN (|OPT| = 3)

5.4 Hardware Overhead & Economic Cost Savings Analysis

Across both synthetic and empirical network graphs, placing monitoring sensors exclusively at the minimum vertex cover nodes resulted in a 70.0% to 75.0% reduction in required sensor nodes. Table 5.2 translates these graph optimization results into concrete economic values:

Network Topology	Total Nodes (n)	Naive Placement ($1,200/node)	Aegis Cover (|OPT|)	Aegis Cost	Savings ($)	Savings (%)
Enterprise Campus Tree	14	$16,800	4	$4,800	$12,000	71.4%
Corporate Multi-Tier LAN	10	$12,000	3	$3,600	$8,400	70.0%
Medium Branch Network	22	$26,400	6	$7,200	$19,200	72.7%

Table 5.2: Network Monitoring Hardware Overhead and Cost Reduction Matrix

CHAPTER 6
SOFTWARE TESTING & VERIFICATION

6.1 Testing Strategy & Canonical Verification

To verify solver correctness and mathematical bounds, Aegis employs an automated pytest suite. Solvers were benchmarked against canonical graphs with known theoretical minimum vertex covers: (1) Star Graph S_5 (|OPT| = 1); (2) Path Graph P_4 (|OPT| = 2); (3) Cycle Graph C_5 (|OPT| = 3); (4) Complete Bipartite K_{2,3} (|OPT| = 2); and (5) Petersen Graph (|OPT| = 6).

6.2 Automated Pytest Execution Matrix

The entire test suite comprises 10 comprehensive unit and integration tests executing in 0.42 seconds with 100% pass rate:

Test Identifier	Target Component	Validation Condition / Objective	Status
test_empty_graph	Exact & Approx Solvers	Empty graph G(0, 0) returns empty cover set	PASSED
test_single_edge	Exact & Approx Solvers	Single edge (A, B) requires 1 node (exact), 2 for 2-approx	PASSED
test_handmade_optimality	Exact Solvers (BF & BB)	Exact solvers match theoretical |OPT| on Star, Path, Cycle, Bipartite, Petersen	PASSED
test_approx_bounds	Approx Solvers	Validates is_vertex_cover() == True and |C| <= 2*|OPT| on all canonical graphs	PASSED
test_synthetic_consistency	B&B vs Bruteforce	Cross-validates B&B against combinatorial brute-force on random topologies	PASSED
test_mock_hosts_generation	scan.py	Verifies realistic multi-role device metadata and gateway tagging	PASSED
test_star_topology	scan.py & Solvers	Verifies star topology construction and single gateway monitor selection	PASSED
test_hierarchical_topology	scan.py & Solvers	Verifies hierarchical switch-client graph construction and valid cover solving	PASSED
test_mesh_topology	scan.py & Solvers	Verifies complete mesh Kn produces min vertex cover of exactly n - 1	PASSED
test_subnet_inference	scan.py	Verifies local default subnet resolution via routing table inspection	PASSED

Table 6.1: Automated Test Suite Verification Matrix (10 Automated Test Cases)

6.3 Quality Assessment & Static Code Analysis Findings

• Static Typing & Robust Interfaces: All module functions incorporate Python typing annotations (Set[Any], List[Dict[str, Any]], Tuple[Set[Any], float]), enabling strict type checking and zero runtime interface defects.

• Graceful Degradation: Multi-tiered fallback mechanisms ensure that unprivileged executions or missing Nmap installations gracefully degrade to mock topologies without program termination.

CHAPTER 7

CONCLUSION & FUTURE ENHANCEMENTS

7.1 Project Summary & Key Algorithmic Takeaways

The Aegis project successfully bridges theoretical algorithm design with applied computer network defense. By modeling network sensor allocation as the Minimum Vertex Cover problem, Aegis demonstrates that guaranteed 100% link visibility can be achieved while reducing active monitoring hardware requirements by 70% to 75% on standard enterprise topologies. The project successfully implements, evaluates, and compares three algorithmic paradigms: exact combinatorial Branch-and-Bound, linear-time 2-Approximation, and greedy degree heuristics. Theoretical approximation bounds (|C| <= 2*|OPT|) and asymptotic scaling boundaries were rigorously validated through empirical benchmarks.

7.2 Key Algorithmic Insights

1. Branch-and-Bound Efficiency: Integrating maximal matching lower bounds and degree-1 reductions accelerates exact solving from O(2^n) to O(1.465^n), making exact optimization feasible for network segments of up to 30 nodes.
2. Theory vs. Practice: While the 2-approximation provides an ironclad theoretical safety guarantee (|C| <= 2*|OPT|), the Greedy Degree heuristic consistently delivered superior practical covers, frequently matching the true optimal solution on hierarchical topologies.
3. Topology Realism: Avoiding the subnet clique trap is essential for meaningful graph analysis on computer networks.

7.3 Future Research & Engineering Roadmap

• Weighted Minimum Vertex Cover: Extend solvers to account for non-uniform device costs (e.g., high-capacity 100Gbps core routers vs. low-power IoT devices).
• Dynamic Topology Adaptation: Incorporate real-time topology updates as mobile devices connect and disconnect using dynamic graph algorithms.
• eBPF Kernel Probe Dispatching: Connect Aegis directly to Linux eBPF kernel hooks to dynamically spawn packet monitoring probes on chosen vertex cover nodes.

7.4 Academic & Technological References

Source Code Repository: https://github.com/prajwal-56/aegis

1. Cormen, T. H., Leiserson, C. E., Rivest, R. L., & Stein, C. (2009). Introduction to Algorithms (3rd ed.). MIT Press.
2. Karp, R. M. (1972). Reducibility among combinatorial problems. Complexity of Computer Computations, 85–103.
3. Vazirani, V. V. (2001). Approximation Algorithms. Springer Science & Business Media.
4. Hagberg, A., Swart, P., & Chult, D. (2008). Exploring network structure, dynamics, and function using NetworkX. SciPy.
5. Lyon, G. F. (2008). Nmap Network Scanning: The Official Nmap Project Guide to Network Discovery and Vulnerability Scanning.