

API Response Reference

unoStarterKit backend · for the mobile app · 5 October 2026

This document describes the exact JSON the backend returns for every endpoint under **/api**: the response envelopes, every status and error code, and a raw response body for each success and error case. The bodies were captured from the running backend and are unedited; long lines are wrapped only to fit the page.

Basics

- Base path: `/api`. Send `Accept: application/json` on every request and `Content-Type: application/json` for JSON bodies (use `multipart/form-data` only for the avatar upload).
- Authenticated endpoints need `Authorization: Bearer <access_token>`.
- **Decide success or failure from the HTTP status code.** The `status` field in the body always repeats it.
- On errors, branch on `code`, never on `message`: codes are stable, messages may be reworded. Every `message` is safe to show to the user.

Response envelopes

Success

```
{"status":200,"message":"Optional text or null","data":{" ... }}
```

`data` is an object, an array, an empty array or null depending on the endpoint.

Paginated success

```
{"status":200,"message":"...", "data":[ ... ], "meta":{"current_page":1, "last_page":2, "per_page":20, "total":22, "from":1, "to":20}}
```

- `meta` is present only on paginated endpoints (currently the notifications list).
- No more pages when `current_page == last_page`. Load the next page with `?page=N`.
- Empty result: `"data": [], "total":0, "from":null, "to":null, "last_page":1`.

Error

```
{"status":422,"code":"validation_failed","message":"The email field is required.,"errors":{"email":["The email field is required."]}}
```

- `errors` is null, except for validation and OTP errors, where it maps each field name to a list of messages. Show the first message under the field.
- `data` is added to a `403 verification_required` error and lists what the user still has to verify (see Sign-up verification).
- `debug` is added to 500 responses only when the server runs with `APP_DEBUG=true` (local development). It is never present in production.

Status and error codes

HTTP	code	When	Suggested handling
401	<code>invalid_credentials</code>	Wrong email or password on login	Show message on the login form
401	<code>unauthenticated</code>	Token missing, invalid, expired or logged out on a protected endpoint	Clear the session and show login
401	<code>token_expired</code> <code>token_invalid</code>	Reserved; not returned by the current endpoints	Clear the session and show login
403	<code>account_blocked</code>	Blocked account tries to log in or verify	Show message
403	<code>verification_required</code>	Email or mobile number not verified yet (only when sign-up verification is enabled). A new code has been sent	Open the code screen for each channel in <code>data.verification_required</code>
403	<code>account_pending_approval</code>	Unapproved account tries to log in, registers, or finishes verifying (only when approval is enabled). No token is returned	Show message
403	<code>forbidden</code>	Action not allowed, e.g. another user's notification	Show message
404	<code>not_found</code>	Unknown endpoint, record or content type	Show message or empty state
422	<code>reset_token_invalid</code>	Password reset with a <code>reset_token</code> that is wrong, expired (15 min) or already used	Show message; restart the reset flow from step 1
405	<code>method_not_allowed</code>	Wrong HTTP method	Developer error
422	<code>validation_failed</code>	Field validation failed	Show <code>errors[field][0]</code> under each field
422	<code>otp_invalid</code> <code>otp_expired</code> <code>otp_attempt_limit</code>	Wrong code / code expired / too many wrong codes	Show <code>errors.otp[0]</code> ; on expired or attempt limit offer Resend
422	<code>otp_already_verified</code> <code>otp_not_found</code>	Code already used, or the email / mobile number is already verified / no code to check	Continue to the next step / restart the flow
422	<code>otp_resend_cooldown</code> <code>otp_resend_limit</code>	Resend too soon / too many resends	Wait Retry-After seconds / restart the flow
422	<code>otp_delivery_failed</code> <code>otp_error</code>	The code could not be sent / other OTP error	Show message; let the user retry
429	<code>too_many_requests</code>	Rate limit hit	Wait Retry-After seconds
500	<code>server_error</code>	Unexpected server failure	Show a generic error; message is safe to show
503	<code>service_unavailable</code>	Maintenance mode	Show a maintenance screen and retry later

Tokens and sessions

- The login, register, verify and refresh responses include `expires_in` in seconds (3600 by default).
- Call `POST /api/auth/refresh` shortly before the token expires. Refresh needs a token that is still valid: once it has expired, the user must log in again.
- A missing, invalid, expired or logged-out token all return the same `401 unauthenticated` body. Treat it as “session ended”.
- After a password reset, every token issued before the reset returns `401 unauthenticated` on all devices.

Rate limits

- Login, register and the four password-reset endpoints allow **3 requests per 60 minutes per IP address**.
- Verifying a sign-up code allows **6 requests per minute**; resending one allows **3 requests per minute**.
- Those responses include `X-RateLimit-Limit` and `X-RateLimit-Remaining`. A 429 also includes `Retry-After` (seconds).
- Resending a reset or sign-up code is also limited to once every 60 seconds (`otp_resend_cooldown`, with `Retry-After`).

Endpoint index

Method	Path	Token	Purpose
POST	<code>/api/auth/login</code>	No	Authentication
POST	<code>/api/auth/register</code>	No	Authentication
POST	<code>/api/auth/refresh</code>	Yes	Authentication
POST	<code>/api/auth/logout</code>	Yes	Authentication
POST	<code>/api/auth/verification/verify</code>	No	Sign-up verification
POST	<code>/api/auth/verification/resend</code>	No	Sign-up verification
POST	<code>/api/auth/password/forgot</code>	No	Password reset (not logged in)
POST	<code>/api/auth/password/verify</code>	No	Password reset (not logged in)
POST	<code>/api/auth/password/resend</code>	No	Password reset (not logged in)
POST	<code>/api/auth/password/reset</code>	No	Password reset (not logged in)
GET	<code>/api/profile</code>	Yes	Profile
GET	<code>/api/user</code>	Yes	Profile
POST	<code>/api/profile</code>	Yes	Profile
POST	<code>/api/change-password</code>	Yes	Profile
POST	<code>/api/device-tokens</code>	Yes	Profile
GET	<code>/api/notifications?page=N</code>	Yes	Notifications
PATCH	<code>/api/notifications/{id}/read</code>	Yes	Notifications
PATCH	<code>/api/notifications/mark-all-as-read</code>	Yes	Notifications
GET	<code>/api/faqs</code>	No	Content and support
GET	<code>/api/{type}</code>	No	Content and support
POST	<code>/api/contact-us</code>	Optional	Content and support

Authentication

POST /api/auth/login

Token required: **No** · Returns the access token and the user. Store the token and send it as **Authorization: Bearer <token>**.

Field	Rules
email	required, email, lowercase
password	required
device_id + device_token	optional; send both to register the device for push
token_type	optional: fcm apns
platform	optional: android ios web
device_name, app_version	optional

200 success

POST /api/auth/login

```
Request body: {"email": "sample.user@example.com", "password": "Password@123", "device_id": "device-123", "device_token": "fcm-token-abc", "platform": "android"}
```

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{ "status":200,"message":null,"data":{"access_token":"eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpc3MiOiJodHRwczovLjVub3N0YXJ0ZXJraXQudG9zdC9hcGkvYXV0aC9sb2dpbiIsImhhbmRlc6MTc5MTE5MjYwMCwiZWhwdjoxNzkxMTk2MjAwLjCuYmYiojE3OTExOTI2MDAsImp0aSI6IjhucCBHNHNC1Ic0t2QLzaT2YiLCJzZWdWIoIiIiwic2giOiJ0eXoIiwiaWF0IjE5ODUyOTU5NDZmNmNyInSwibmFtciBfSJQ0bW5lZD80aGVycmlhZHM2dy9kbmtCMQ-82dIg","token_type":"bearer","expires_in":3600,"user":{"id":2,"name":"Sample User","email":"sample.user@example.com","phone":null,"avatar":null,"location":null,"subscription_type":null,"roles":["user"],"is_blocked":false,"is_approved":true,"is_email_verified":true,"is_phone_verified":false,"pending_verifications":[],"approved_at":"2026-10-05T09:30:00+00:00","email_verified_at":"2026-10-05T09:30:00+00:00","phone_verified_at":null,"blocked_at":null,"created_at":"2026-10-05T09:30:00+00:00","updated_at":"2026-10-05T09:30:00+00:00"}}}
```

401 wrong credentials

POST /api/auth/login

```
Request body: {"email": "sample.user@example.com", "password": "wrong-password"}
```

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":401,"code":"invalid_credentials","message":"Invalid email or password.","errors":null}
```

422 missing fields

```
POST /api/auth/login
```

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{
  "status": 422,
  "code": "validation_failed",
  "message": "The email field is required. (and 1 more error)",
  "errors": {
    "email": ["The email field is required."],
    "password": ["The password field is required."]
  }
}
```

422 invalid email

POST /api/auth/login

Request body: {"email": "not-an-email", "password": ""}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{
  "status": 422,
  "code": "validation_failed",
  "message": "The email field must be a valid email address. (and 1 more error)",
  "errors": {
    "email": ["The email field must be a valid email address."],
    "password": ["The password field is required."]
  }
}
```

403 blocked account

POST /api/auth/login

Request body: {"email": "blocked.user@example.com", "password": "Password@123"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":403,"code":"account_blocked","message":"Your account has been blocked.","errors":null}
```

403 email not verified (sign-up verification enabled; a new code is sent)

POST /api/auth/login

Request body: {"email": "unverified.user@example.com", "password": "Password@123"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":403,"code":"verification_required","message":"Please verify your account. We have sent a verification code to your email.","errors":null,"data":{"verification_required":["email"],"otp_length":6}}
```

403 account pending approval (approval enabled)

POST /api/auth/login

Request body: {"email": "pending.user@example.com", "password": "Password@123"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":403,"code":"account_pending_approval","message":"Your account is pending approval.","errors":null}
```

429 rate limited

POST /api/auth/login

Request body: {"email": "sample.user@example.com", "password": "wrong-password"}

Response headers: Retry-After: 3600, X-RateLimit-Limit: 3, X-RateLimit-Remaining: 0

```
{"status":429,"code":"too_many_requests","message":"Too many attempts. Please try again later.","errors":null}
```

POST /api/auth/register

Token required: **No** · Same success body as login: the new user is logged in straight away. When sign-up verification is enabled, no token is returned; see Sign-up verification. When admin approval is enabled (and verification is not), the account is created but the response is **403 account_pending_approval** with no token: show the message and let the user log in once an admin has approved them.

Field	Rules
name	required, max 255
email	required, email, lowercase, unique
password + password_confirmation	required, min 8, must match
phone	optional, Australian format (0412 345 678 or +61 2 1234 5678); required when mobile verification is enabled
device fields	optional, same as login; not saved when no token is returned, so send them again at the first login

POST /api/auth/register

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

200 verification required (email verification enabled)

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

403 account created, pending approval (approval enabled, no token)

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

422 validation errors

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

POST /api/auth/refresh

Token required: **Yes** · Returns a new token (same body as login). The current token must not have expired yet.

POST /api/auth/refresh · with Bearer token

unoStarterKit · API Response Reference

401 missing token

POST /api/auth/refresh

```
{"status":401,"code":"unauthenticated","message":"Unauthenticated.","errors":null}
```

POST /api/auth/logout

Token required: **Yes** · The token is invalidated; later calls with it return 401.

Field	Rules
device_id	required; removes this device's push token

422 missing device_id

POST /api/auth/logout · with Bearer token

```
{"status":422,"code":"validation_failed","message":"The device id field is required.","errors":{"device_id":["The device id field is required."]}}
```

200 success

POST /api/auth/logout · with Bearer token

Request body: {"device_id": "device-123"}

```
{"status":200,"message":"Successfully logged out","data":null}
```

401 token already logged out

POST /api/auth/logout · with Bearer token

Request body: {"device_id": "device-123"}

```
{"status":401,"code":"unauthenticated","message":"Unauthenticated.","errors":null}
```

Sign-up verification

Each project can require new users to verify their **email**, their **mobile number**, or both, with a one-time code before a token is issued. Both are off by default; the backend switches them on with `USER_REQUIRE_EMAIL_VERIFICATION` and `USER_REQUIRE_PHONE_VERIFICATION`. The app does not need to know the settings: it reacts to the responses below.

- **Register** returns `data.verification_required` (for example `["email"]` or `["email", "phone"]`) and `data.otp_length` instead of `access_token`. A code has been sent to each listed channel: email codes by email, mobile codes by SMS. Show one code screen per channel.
- **Verify** each channel with `POST /api/auth/verification/verify`. While another channel is still listed, the response is `200` with the remaining `verification_required`. When nothing is left, the response is the normal login body with `access_token`.
- **Login** before verifying returns `403 verification_required` with the same `data`, and a new code is sent, so go straight to the code screen.
- **Admin approval**: if the project also requires approval, finishing verification returns `403 account_pending_approval` until an admin approves the account. Without sign-up verification, register itself returns that response.
- **Profile changes**: when `POST /api/profile` changes the email or mobile number, that channel must be verified again. The response message says a code was sent and `user.pending_verifications` lists the channel; verify it with the same endpoint (the current token keeps working).
- The `user` object includes `is_email_verified`, `is_phone_verified`, `email_verified_at`, `phone_verified_at` and `pending_verifications`.

POST /api/auth/verification/verify

Token required: **No** · Checks a sign-up code and marks that channel verified. Returns the token once nothing is left to verify.

Field	Rules
<code>email</code>	required, the account email
<code>channel</code>	required: email phone
<code>otp</code>	required, the code that was sent
<code>device fields</code>	optional, same as login; used when the token is issued

422 missing fields

POST /api/auth/verification/verify

Response headers: X-RateLimit-Limit: 6, X-RateLimit-Remaining: 5

```
{"status":422,"code":"validation_failed","message":"The email field is required. (and 2 more errors)","errors":{"email":["The email field is required."],"channel":["The channel field is required."],"otp":["The otp field is required."]}}
```

422 wrong code

POST /api/auth/verification/verify

Request body: `{"email": "verify.user@example.com", "channel": "email", "otp": "000000"}`

Response headers: X-RateLimit-Limit: 6, X-RateLimit-Remaining: 5

```
{"status":422,"code":"otp_invalid","message":"The OTP is incorrect. 4 attempts remaining.","errors":{"otp":["The OTP is incorrect. 4 attempts remaining."]}}
```

200 verified (returns the token)

POST /api/auth/verification/verify

Request body: {"email": "verify.user@example.com", "channel": "email", "otp": "439268", "device_id": "device-456", "device_token": "fcm-token-def", "platform": "ios"}

Response headers: X-RateLimit-Limit: 6, X-RateLimit-Remaining: 5

```
{"status":200,"message":null,"data":{"access_token":"eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpc3MiOiJodHRwczovL3Vub3N0YXJ0ZXJraXQudGVzdC9hcGkvYXV0aC92ZXJpZmlyYXRpb24vdmVyaWZ5IiwiaWF0IjoxNzkxMTkyNjYxLjleHAiOjE3OTExOTYyNjEsIm5iZiI6MTc5MTE5MjY2MSwianRpIjoieTEJrS1JPMlhVG1uM3g4TyIsInN1YiI6IjEzIiwicHViIjoiMjZDVjODk0OWY2MDBhZGIzOWU3MDFjNDAwODcyZGI3YTU5NzZmNyIsInR2IjowfQ.8IsmB6UJ2mT_E2mjWPi0I1WJL3yKEls8_5avBgG5WI","token_type":"bearer","expires_in":3600,"user":{"id":13,"name":"Verify User","email":"verify.user@example.com","phone":null,"avatar":null,"location":null,"subscription_type":null,"roles":["user"],"is_blocked":false,"is_approved":true,"is_email_verified":true,"is_phone_verified":false,"pending_verifications":[],"approved_at":"2026-10-05T09:30:00+00:00","email_verified_at":"2026-10-05T09:31:01+00:00","phone_verified_at":null,"blocked_at":null,"created_at":"2026-10-05T09:30:00+00:00","updated_at":"2026-10-05T09:31:01+00:00"}}
```

422 already verified

POST /api/auth/verification/verify

Request body: {"email": "verify.user@example.com", "channel": "email", "otp": "439268"}

Response headers: X-RateLimit-Limit: 6, X-RateLimit-Remaining: 5

```
{"status":422,"code":"otp_already_verified","message":"Your email is already verified.","errors":{"otp":["Your email is already verified."]}}
```

200 register with email and mobile verification enabled

POST /api/auth/register

Request body: {"name": "Both User", "email": "both.user@example.com", "phone": "0412 345 678", "password": "Password@123", "password_confirmation": "Password@123"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":200,"message":"We have sent a verification code to your email and mobile number.","data":{"verification_required":["email","phone"],"otp_length":6}}
```

200 email verified, mobile number still to verify

POST /api/auth/verification/verify

Request body: {"email": "both.user@example.com", "channel": "email", "otp": "506148"}

Response headers: X-RateLimit-Limit: 6, X-RateLimit-Remaining: 5

```
{"status":200,"message":"Email verified. Please also verify your mobile number.","data":{"verification_required":["phone"],"otp_length":6}}
```

200 last channel verified (returns the token)

POST /api/auth/verification/verify

Request body: {"email": "both.user@example.com", "channel": "phone", "otp": "620745"}

Response headers: X-RateLimit-Limit: 6, X-RateLimit-Remaining: 5

```
{"status":200,"message":null,"data":{"access_token":"eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpc3MiOiJodHRwczovL3Vub3N0YXJ0ZXJraXQudGVzdC9hcGkvYXV0aC92ZXJpZmlyYXRpb24vdmVyaWZ5IiwiaWF0IjoxNzkxMTkyNjYxLjleHAiOjE3OTExOTYyNjEsIm5iZiI6MTc5MTE5MjY2MSwianRpIjoieTEJrS1JPMlhVG1uM3g4TyIsInN1YiI6IjEzIiwicHViIjoiMjZDVjODk0OWY2MDBhZGIzOWU3MDFjNDAwODcyZGI3YTU5NzZmNyIsInR2IjowfQ.LkHrjVl866D0P-rvspumF7GIsstL1qXIi83ZoIHyYPk","token_type":"bearer","expires_in":3600,"user":{"id":14,"name":"Both User","email":"both.user@example.com","phone":"0412 345 678","avatar":null,"location":null,"subscription_type":null,"roles":["user"],"is_blocked":false,"is_approved":true,"is_email_verified":true,"is_phone_verified":true,"pending_verifications":[],"approved_at":"2026-10-05T09:31:01+00:00","email_verified_at":"2026-10-05T09:31:01+00:00","phone_verified_at":"2026-10-05T09:31:01+00:00","blocked_at":null,"created_at":"2026-10-05T09:31:01+00:00","updated_at":"2026-10-05T09:31:01+00:00"}}
```

403 verified, waiting for admin approval

POST /api/auth/verification/verify

Request body: {"email": "approval.user@example.com", "channel": "email", "otp": "355434"}

Response headers: X-RateLimit-Limit: 6, X-RateLimit-Remaining: 5

```
{"status":403,"code":"account_pending_approval","message":"Your account is verified and pending approval .","errors":null}
```

POST /api/auth/verification/resend

Token required: **No** · Sends a new code to that channel. Same response for unknown or already verified accounts. Blocked for 60 seconds after each send (see Retry-After).

Field	Rules
email	required
channel	required: email phone

422 resend too soon (cooldown)

POST /api/auth/verification/resend

Request body: {"email": "verify.user@example.com", "channel": "email"}

Response headers: Retry-After: 60, X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"otp_resend_cooldown","message":"Please wait 60 seconds before requesting another OTP.","errors":{"otp":["Please wait 60 seconds before requesting another OTP."]}}
```

200 new code sent

POST /api/auth/verification/resend

Request body: {"email": "verify.user@example.com", "channel": "email"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":200,"message":"A new verification code has been sent.","data":null}
```

200 unknown email (same response, nothing sent)

POST /api/auth/verification/resend

Request body: {"email": "nobody@example.com", "channel": "email"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":200,"message":"A new verification code has been sent.","data":null}
```

422 invalid channel

POST /api/auth/verification/resend

Request body: {"email": "verify.user@example.com", "channel": "sms"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"validation_failed","message":"The selected channel is invalid.","errors":{"channel":["The selected channel is invalid."]}}
```

Password reset (not logged in)

POST /api/auth/password/forgot

Token required: **No** · Step 1: emails a verification code. The response is identical for registered and unknown emails, so the app cannot tell whether an account exists; always continue to the code screen.

Field	Rules
email	required

200 code sent (registered email)

POST /api/auth/password/forgot

Request body: {"email": "sample.user@example.com"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":200,"message":"Please check your email for a verification code.,"data":null}
```

200 unknown email (same response, nothing sent)

POST /api/auth/password/forgot

Request body: {"email": "nobody@example.com"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":200,"message":"Please check your email for a verification code.,"data":null}
```

422 missing email

POST /api/auth/password/forgot

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"validation_failed","message":"The email field is required.,"errors":{"email":["The email field is required."]}}
```

POST /api/auth/password/verify

Token required: **No** · Step 2: checks the code and returns a single-use reset_token, valid for expires_in seconds (15 minutes). Keep it in memory for step 3.

Field	Rules
email	required, the email from step 1
otp	required, the emailed code

422 missing fields

POST /api/auth/password/verify

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"validation_failed","message":"The email field is required. (and 1 more error)","errors":{"email":["The email field is required.],"otp":["The otp field is required."]}}
```

422 no reset in progress for this email

POST /api/auth/password/verify

Request body: {"email": "empty.user@example.com", "otp": "123456"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"otp_invalid","message":"The verification code is incorrect.,"errors":{"otp":["The verification code is incorrect."]}}
```

422 wrong code

POST /api/auth/password/verify

Request body: {"email": "reset.flow@example.com", "otp": "000000"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"otp_invalid","message":"The OTP is incorrect. 4 attempts remaining.","errors":{"otp":["The OTP is incorrect. 4 attempts remaining."]}}
```

200 verified (returns reset_token)

POST /api/auth/password/verify

Request body: {"email": "reset.flow@example.com", "otp": "683567"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":200,"message":"Code verified. You can now set a new password.","data":{"reset_token":"mI68tg4mfrwSEVKEDV6AYyp8q0IQXXe0hQ4ZjGTU12dzJWDNbZwKmfajOjSSci29","expires_in":900}}
```

422 code already verified

POST /api/auth/password/verify

Request body: {"email": "reset.flow@example.com", "otp": "683567"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"otp_already_verified","message":"This OTP has already been verified.","errors":{"otp":["This OTP has already been verified."]}}
```

POST /api/auth/password/resend

Token required: **No** · Sends a new code. Same response for unknown emails. Blocked for 60 seconds after each send (see Retry-After).

Field	Rules
email	required

422 resend too soon (cooldown)

POST /api/auth/password/resend

Request body: {"email": "resend.user@example.com"}

Response headers: Retry-After: 60, X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"otp_resend_cooldown","message":"Please wait 60 seconds before requesting another OTP.","errors":{"otp":["Please wait 60 seconds before requesting another OTP."]}}
```

200 new code sent

POST /api/auth/password/resend

Request body: {"email": "resend.user@example.com"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":200,"message":"A new verification code has been sent.","data":null}
```

200 unknown email (same response, nothing sent)

POST /api/auth/password/resend

Request body: {"email": "nobody@example.com"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":200,"message":"A new verification code has been sent.","data":null}
```

422 missing email

POST /api/auth/password/resend

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"validation_failed","message":"The email field is required.,"errors":{"email":["The email field is required."]}}
```

POST /api/auth/password/reset

Token required: No · Step 3: sets the new password. The reset_token works once. Afterwards every existing login token for that user returns 401, and the user logs in again with the new password.

Field	Rules
reset_token	required, from step 2
password + password_confirmation	required, min 8, must match

422 missing fields

POST /api/auth/password/reset

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"validation_failed","message":"The reset token field is required. (and 1 more error)","errors":{"reset_token":["The reset token field is required.],"password":["The password field is required."]}}
```

422 invalid or expired reset_token

POST /api/auth/password/reset

Request body: {"reset_token": "not-a-real-token", "password": "NewPassword@123", "password_confirmation": "NewPassword@123"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"reset_token_invalid","message":"Your reset session has expired. Please request a new code.,"errors":{"reset_token":["Your reset session has expired. Please request a new code."]}}
```

422 password confirmation mismatch

POST /api/auth/password/reset

Request body: {"reset_token": "mI68tg4mfrwSEVKEDV6AYyp8q0IQXXe0hQ4ZjGTU12dzJWDNbZwKmfajOjSSci29", "password": "NewPassword@123", "password_confirmation": "Different@123"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"validation_failed","message":"The password field confirmation does not match.,"errors":{"password":["The password field confirmation does not match."]}}
```

200 password reset

POST /api/auth/password/reset

Request body: {"reset_token": "mI68tg4mfrwSEVKEDV6AYyp8q0IQXXe0hQ4ZjGTU12dzJWDNbZwKmfajOjSSci29", "password": "NewPassword@123", "password_confirmation": "NewPassword@123"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":200,"message":"Your password has been reset. Please log in with your new password.,"data":null}
```

422 reset_token already used

POST /api/auth/password/reset

Request body: {"reset_token": "mI68tg4mfrwSEVKEDV6AYyp8q0IQXxe0hQ4ZjGTU12dzJWDNbZwKmfajOjSSci29", "password": "NewPassword@123", "password_confirmation": "NewPassword@123"}

Response headers: X-RateLimit-Limit: 3, X-RateLimit-Remaining: 2

```
{"status":422,"code":"reset_token_invalid","message":"Your reset session has expired. Please request a new code.","errors":{"reset_token":["Your reset session has expired. Please request a new code."]}}
```

401 token issued before the reset no longer works

GET /api/profile · with Bearer token

```
{"status":401,"code":"unauthenticated","message":"Unauthenticated.","errors":null}
```

Profile

GET /api/profile

Token required: **Yes** · The logged-in user.

200 success

GET /api/profile · with Bearer token

```
{"status":200,"message":null,"data":{"id":2,"name":"Sample User","email":"sample.user@example.com","phone":null,"avatar":null,"location":null,"subscription_type":null,"is_blocked":false,"is_approved":true,"is_email_verified":true,"is_phone_verified":false,"pending_verifications":[],"approved_at":"2026-10-05T09:30:00+00:00","email_verified_at":"2026-10-05T09:30:00+00:00","phone_verified_at":null,"blocked_at":null,"created_at":"2026-10-05T09:30:00+00:00","updated_at":"2026-10-05T09:30:00+00:00"}}
```

401 missing token

GET /api/profile

```
{"status":401,"code":"unauthenticated","message":"Unauthenticated.","errors":null}
```

GET /api/user

Token required: **Yes** · Same user object as GET /api/profile.

200 success

GET /api/user · with Bearer token

```
{"status":200,"message":null,"data":{"id":2,"name":"Sample User Updated","email":"sample.user@example.com","phone":null,"avatar":null,"location":null,"subscription_type":null,"is_blocked":false,"is_approved":true,"is_email_verified":true,"is_phone_verified":false,"pending_verifications":[],"approved_at":"2026-10-05T09:30:00+00:00","email_verified_at":"2026-10-05T09:30:00+00:00","phone_verified_at":null,"blocked_at":null,"created_at":"2026-10-05T09:30:00+00:00","updated_at":"2026-10-05T09:32:02+00:00"}}
```

POST /api/profile

Token required: **Yes** · Changing the email or mobile number while sign-up verification is enabled sends a code to the new address; verify it with POST /api/auth/verification/verify.

Field	Rules
name	required
email	required, unique
phone	optional, Australian format; required when mobile verification is enabled
avatar	optional image (jpeg, png, jpg, gif, webp, max 2 MB); send as multipart/form-data
password + password_confirmation	optional

200 success

POST /api/profile · with Bearer token

Request body: {"name": "Sample User Updated", "email": "sample.user@example.com", "phone": null}

```
{"status":200,"message":"Profile Updated Successfully","data":{"id":2,"name":"Sample User Updated","email":"sample.user@example.com","phone":null,"avatar":null,"location":null,"subscription_type":null,"roles":["user"],"is_blocked":false,"is_approved":true,"is_email_verified":true,"is_phone_verified":false,"pending_verifications":[],"approved_at":"2026-10-05T09:30:00+00:00","email_verified_at":"2026-10-05T09:30:00+00:00","phone_verified_at":null,"blocked_at":null,"created_at":"2026-10-05T09:30:00+00:00","updated_at":"2026-10-05T09:32:02+00:00"}}
```

200 email changed (email verification enabled)

POST /api/profile · with Bearer token

Request body: {"name": "Change User", "email": "changed.user@example.com"}

```
{"status":200,"message":"Profile Updated Successfully. We have sent a verification code to your new email.", "data":{"id":10,"name":"Change User", "email":"changed.user@example.com", "phone":null, "avatar":null, "location":null, "subscription_type":null, "roles":["user"], "is_blocked":false, "is_approved":true, "is_email_verified":false, "is_phone_verified":false, "pending_verifications":["email"], "approved_at":"2026-10-05T09:30:00+00:00", "email_verified_at":null, "phone_verified_at":null, "blocked_at":null, "created_at":"2026-10-05T09:30:00+00:00", "updated_at":"2026-10-05T09:32:02+00:00"}}
```

422 validation errors

POST /api/profile · with Bearer token

Request body: {"name": "", "email": "empty.user@example.com"}

```
{"status":422,"code":"validation_failed","message":"The name field is required. (and 1 more error)","errors":{"name":["The name field is required."], "email":["The email has already been taken."]}}
```

POST /api/change-password

Token required: Yes

Field	Rules
current_password	required
new_password + new_password_confirmation	required, min 8, must match

422 wrong current password

POST /api/change-password · with Bearer token

Request body: {"current_password": "wrong-password", "new_password": "Another@1234", "new_password_confirmation": "Another@1234"}

```
{"status":422,"code":"validation_failed","message":"The provided password does not match your current password.", "errors":{"current_password":["The provided password does not match your current password."]}}
```

422 validation errors

POST /api/change-password · with Bearer token

Request body: {"new_password": "short", "new_password_confirmation": "nope"}

```
{"status":422,"code":"validation_failed","message":"The current password field is required. (and 2 more errors)", "errors":{"current_password":["The current password field is required."], "new_password":["The new password field confirmation does not match."], "new_password_confirmation":["The new password field must be at least 8 characters."]}}
```

200 success

POST /api/change-password · with Bearer token

Request body: {"current_password": "Password@123", "new_password": "Another@1234", "new_password_confirmation": "Another@1234"}

```
{"status":200,"message":"Password Changed Successfully", "data":null}
```

POST /api/device-tokens

Token required: **Yes** · Registers or updates this device's push token.

Field	Rules
device_id, device_token	required
token_type	optional: fcm apns
platform	optional: android ios web
device_name, app_version	optional

200 success

POST /api/device-tokens · with Bearer token

Request body: {"device_id": "device-123", "device_token": "fcm-token-abc", "token_type": "fcm", "platform": "android", "device_name": "Pixel 8", "app_version": "1.0.0"}

```
{"status":200,"message":"Device registered for push notifications.","data":null}
```

422 validation errors

POST /api/device-tokens · with Bearer token

Request body: {"platform": "windows-phone"}

```
{"status":422,"code":"validation_failed","message":"The device id field is required. (and 2 more errors) ", "errors":{"device_id":["The device id field is required."], "device_token":["The device token field is required."], "platform":["The selected platform is invalid."]}}
```

Notifications

GET /api/notifications?page=N

Token required: **Yes** · Paginated: see the meta object. Lists the broadcasts sent to this user. Blocked accounts and accounts still waiting for approval do not receive broadcasts.

Field	Rules
page	optional query parameter, default 1; 20 items per page

200 page 1 with several items

GET /api/notifications · with Bearer token

```
{
  "status": 200,
  "message": "Notifications retrieved successfully",
  "data": [
    {
      "id": 22,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 22.",
        "data": [],
        "title": "Sample notification 22"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:30:00.000000Z",
      "updated_at": "2026-10-05T09:30:00.000000Z",
      "id": 21,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 21.",
        "data": [],
        "title": "Sample notification 21"
      },
      "read_at": "2026-10-05T09:30:00.000000Z",
      "url": null,
      "created_at": "2026-10-05T09:29:00.000000Z",
      "updated_at": "2026-10-05T09:29:00.000000Z",
      "id": 20,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 20.",
        "data": [],
        "title": "Sample notification 20"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:28:00.000000Z",
      "updated_at": "2026-10-05T09:28:00.000000Z",
      "id": 19,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 19.",
        "data": [],
        "title": "Sample notification 19"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:27:00.000000Z",
      "updated_at": "2026-10-05T09:27:00.000000Z",
      "id": 18,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 18.",
        "data": [],
        "title": "Sample notification 18"
      },
      "read_at": "2026-10-05T09:30:00.000000Z",
      "url": null,
      "created_at": "2026-10-05T09:26:00.000000Z",
      "updated_at": "2026-10-05T09:26:00.000000Z",
      "id": 17,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 17.",
        "data": [],
        "title": "Sample notification 17"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:25:00.000000Z",
      "updated_at": "2026-10-05T09:25:00.000000Z",
      "id": 16,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 16.",
        "data": [],
        "title": "Sample notification 16"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:24:00.000000Z",
      "updated_at": "2026-10-05T09:24:00.000000Z",
      "id": 15,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 15.",
        "data": [],
        "title": "Sample notification 15"
      },
      "read_at": "2026-10-05T09:30:00.000000Z",
      "url": null,
      "created_at": "2026-10-05T09:23:00.000000Z",
      "updated_at": "2026-10-05T09:23:00.000000Z",
      "id": 14,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 14.",
        "data": [],
        "title": "Sample notification 14"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:22:00.000000Z",
      "updated_at": "2026-10-05T09:22:00.000000Z",
      "id": 13,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 13.",
        "data": [],
        "title": "Sample notification 13"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:21:00.000000Z",
      "updated_at": "2026-10-05T09:21:00.000000Z",
      "id": 12,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 12.",
        "data": [],
        "title": "Sample notification 12"
      },
      "read_at": "2026-10-05T09:30:00.000000Z",
      "url": null,
      "created_at": "2026-10-05T09:20:00.000000Z",
      "updated_at": "2026-10-05T09:20:00.000000Z",
      "id": 11,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 11.",
        "data": [],
        "title": "Sample notification 11"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:19:00.000000Z",
      "updated_at": "2026-10-05T09:19:00.000000Z",
      "id": 10,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 10.",
        "data": [],
        "title": "Sample notification 10"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:18:00.000000Z",
      "updated_at": "2026-10-05T09:18:00.000000Z",
      "id": 9,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 9.",
        "data": [],
        "title": "Sample notification 9"
      },
      "read_at": "2026-10-05T09:30:00.000000Z",
      "url": null,
      "created_at": "2026-10-05T09:17:00.000000Z",
      "updated_at": "2026-10-05T09:17:00.000000Z",
      "id": 8,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 8.",
        "data": [],
        "title": "Sample notification 8"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:16:00.000000Z",
      "updated_at": "2026-10-05T09:16:00.000000Z",
      "id": 7,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 7.",
        "data": [],
        "title": "Sample notification 7"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:15:00.000000Z",
      "updated_at": "2026-10-05T09:15:00.000000Z",
      "id": 6,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 6.",
        "data": [],
        "title": "Sample notification 6"
      },
      "read_at": "2026-10-05T09:30:00.000000Z",
      "url": null,
      "created_at": "2026-10-05T09:14:00.000000Z",
      "updated_at": "2026-10-05T09:14:00.000000Z",
      "id": 5,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 5.",
        "data": [],
        "title": "Sample notification 5"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:13:00.000000Z",
      "updated_at": "2026-10-05T09:13:00.000000Z",
      "id": 4,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 4.",
        "data": [],
        "title": "Sample notification 4"
      },
      "read_at": null,
      "url": null,
      "created_at": "2026-10-05T09:12:00.000000Z",
      "updated_at": "2026-10-05T09:12:00.000000Z",
      "id": 3,
      "type": "push",
      "notifiable_type": "App\\Models\\User",
      "notifiable_id": 2,
      "data": {
        "body": "This is sample notification number 3.",
        "data": [],
        "title": "Sample notification 3"
      },
      "read_at": "2026-10-05T09:30:00.000000Z",
      "url": null,
      "created_at": "2026-10-05T09:11:00.000000Z",
      "updated_at": "2026-10-05T09:11:00.000000Z",
      "meta": {
        "current_page": 1,
        "last_page": 2,
        "per_page": 20,
        "total": 22,
        "from": 1,
        "to": 20
      }
    ]
  }
}
```

200 last page (current_page == last_page)

GET /api/notifications?page=2 · with Bearer token

```
{"status":200,"message":"Notifications retrieved successfully","data":[{"id":2,"type":"push","notifiable_type":"App\\Models\\User","notifiable_id":2,"data":{"body":"This is sample notification number 2.","data":[],"title":"Sample notification 2"},"read_at":null,"url":null,"created_at":"2026-10-05T09:10:00.000000Z","updated_at":"2026-10-05T09:10:00.000000Z"}, {"id":1,"type":"push","notifiable_type":"App\\Models\\User","notifiable_id":2,"data":{"body":"This is sample notification number 1.","data":[],"title":"Sample notification 1"},"read_at":null,"url":null,"created_at":"2026-10-05T09:09:00.000000Z","updated_at":"2026-10-05T09:09:00.000000Z"}],"meta":{"current_page":2,"last_page":2,"per_page":20,"total":22,"from":21,"to":22}}
```

200 empty result

GET /api/notifications · with Bearer token

```
{"status":200,"message":"Notifications retrieved successfully","data":[],"meta":{"current_page":1,"last_page":1,"per_page":20,"total":0,"from":null,"to":null}}
```

401 missing token

GET /api/notifications

```
{"status":401,"code":"unauthenticated","message":"Unauthenticated.","errors":null}
```

401 expired token

GET /api/notifications · with Bearer token

```
{"status":401,"code":"unauthenticated","message":"Unauthenticated.","errors":null}
```

PATCH /api/notifications/{id}/read

Token required: **Yes** · Marks one notification as read.

200 success

PATCH /api/notifications/1/read · with Bearer token

```
{"status":200,"message":"Notification marked as read","data":[]}
```

403 notification belongs to another user

PATCH /api/notifications/23/read · with Bearer token

```
{"status":403,"code":"forbidden","message":"This action is unauthorized.","errors":null}
```

404 unknown id

PATCH /api/notifications/999999999/read · with Bearer token

```
{"status":404,"code":"not_found","message":"The requested resource was not found.","errors":null}
```

PATCH /api/notifications/mark-all-as-read

Token required: **Yes**

200 success

PATCH /api/notifications/mark-all-as-read · with Bearer token

```
{"status":200,"message":"All notifications marked as read","data":[]}
```

Content and support

GET /api/faqs

Token required: **No** · All FAQs, not paginated.

200 success

GET /api/faqs

```
{"status":200,"message":null,"data":[{"id":1,"question":"How do I reset my password?","answer":"Use \"Forgot password\" on the login screen and follow the code we email you.","created_at":"2026-10-05T09:30:00.000000Z"}, {"id":2,"question":"How do I contact support?","answer":"Use the Contact Us form in the app.","created_at":"2026-10-05T09:30:00.000000Z"}]}
```

GET /api/{type}

Token required: **No** · description is HTML from the CMS editor; render it as HTML.

Field	Rules
type	terms_and_conditions privacy_policy community_guidelines

200 success

GET /api/terms_and_conditions

```
{"status":200,"message":null,"data":{"id":1,"type":"terms_and_conditions","title":"Terms & Conditions","description":"<p>These are the sample terms and conditions.</p>","updated_at":"2026-10-05T09:30:00.000000Z"}}
```

404 content not created yet

GET /api/privacy_policy

```
{"status":404,"code":"not_found","message":"Content not found.","errors":null}
```

404 unknown type

GET /api/refund_policy

```
{"status":404,"code":"not_found","message":"The requested resource was not found.","errors":null}
```

POST /api/contact-us

Token required: **Optional** · If a token is sent, the message is linked to that user.

Field	Rules
name	required
email	required
message	required, max 5000

201 success

POST /api/contact-us

Request body: {"name": "Sample User", "email": "sample.user@example.com", "message": "I need help with my account."}

Response headers: X-RateLimit-Limit: 5, X-RateLimit-Remaining: 4

```
{"status":201,"message":"Your message has been sent successfully.","data":[]}
```

422 validation errors

POST /api/contact-us

Request body: {"email": "not-an-email"}

Response headers: X-RateLimit-Limit: 5, X-RateLimit-Remaining: 4

```
{"status":422,"code":"validation_failed","message":"The name field is required. (and 2 more errors)","errors":{"name":["The name field is required."],"email":["The email field must be a valid email address."],"message":["The message field is required."]}}
```

Responses shared by every endpoint

These bodies are identical on every endpoint; the 500 and 503 samples were produced with test routes.

405 wrong method

DELETE /api/notifications · with Bearer token

```
{"status":405,"code":"method_not_allowed","message":"This method is not allowed for this endpoint.,"errors":null}
```

500 server error (production)

GET /api/__sample/server-error

```
{"status":500,"code":"server_error","message":"Something went wrong. Please try again later.,"errors":null}
```

500 server error (APP_DEBUG=true)

GET /api/__sample/server-error

```
{"status":500,"code":"server_error","message":"Something went wrong. Please try again later.,"errors":null,"debug":{"exception":"RuntimeException","message":"Sample failure for documentation","file":"E:\\unoStarterKit\\tests\\Capture\\CaptureApiReferenceTest.php","line":51}}
```

503 maintenance mode

GET /api/__sample/maintenance

```
{"status":503,"code":"service_unavailable","message":"The service is temporarily unavailable. Please try again later.,"errors":null}
```

A 401 with [unauthenticated](#) (see Profile or Notifications) and a 429 with [too_many_requests](#) (see Login) look the same on every endpoint.