

Prosafe-RS Assessment

Course Duration: 5 Days

Maximum Marks: 15

From: 16.2.26

Marks Obtained:

To : 20.2.26

Faculty Name: PRAJNAL KT

Participant's name: Kanishka S

Faculty Signature:

1. Select the appropriate answer from the given options

In the name Prosafe-RS, RS stands for

- ☒ Responsive solutions
- ☐ Retentive solution
- ☐ Reliable solution
- ☐ Restorable solution

2. Select the appropriate answer from the given options

Prosafe-RS IS

- ☐ SIL1 certified
- ☐ SIL2 certified
- ☒ SIL3 certified
- ☐ SIL4 certified

3. Fill in the Blanks

SIL stands for Safety Integrity level

SIS stands for Safety Instrumented System

4. Select the appropriate answer from the given options

Prosafe RS can be plugged on to the safety network of

- ☒ Centum VP
- ☐ Centum XL
- ☐ Micro XL

5. Select the appropriate answer from the given options

Data transmission speed of the Vnet/IP is

- 10 KBps
- 100 Mbps
- 10 Mbps
- ☒ 1 gbps

6. Select whether the given statement is True or False

Prosafe-RS system is TUV certified

- ☒ a) True
- b) False

7. The window that is used to create the Variables is,

- a. I/O wiring window
- b. Dictionary
- ☒ c. Link architecture window
- d. Hardware architecture window

8. Select whether the given statement is True or False

Instances have to be created for IO_variables for integration with CS3000.

- ☒ a) True
- b) False

9. Fill in the blanks

Offline download can be performed when the security level of the system is... Zero....

10. Select whether the given statement is True or False

At security level 1, we can perform IOM download

- a) True
- ☒ (b) False

11. The window that is used to map Prosafe-RS tags to CS3000 is,

- a. I/O wiring window
- ☒ b. Tag name Builder
- c. Link architecture window
- d. Hardware architecture window

12. Select the appropriate answer from the given options

Which window in workbench is used to Lock/Unlock the I/O MODULE?

- SCS State management
- I/O Parameter builder
- SCS taglist import
- ✓ Input/Output lock window

13. Which tool in Centum VP is used to import the SCS tags to CS3000

- ✓ SCS tag list import
- SCS test function
- Output Enable
- Linked part updating

14. IEC Standards recommended for Safety System are

- a) IEC 61508, 61511
- b) IEC 61511, 61508

15. Yokogawa Prosafe-RS system is Safety architecture



