
STRUCTURAL ENGINEERING FOR DATA

A Blueprint for Supervised Learning Algorithms


Linear & Logistic Regression | Decision Trees & Random Forests | KNN & Naive Bayes | Support Vector Machines



Gemini Notebook

BUILDING COMPLEXITY FROM THE GROUND UP

Every supervised learning algorithm is a structural solution to a specific data problem. We begin by drawing straight lines through continuous data, adapt them for classification, introduce logical branching, and ultimately learn to fold infinite spatial dimensions.



Gemini Notebook

LINEAR REGRESSION AND THE ARCHITECTURE OF LEAST SQUARES



CORE CONCEPT:

We fit a line by rotating it until the squared distances (residuals) between the data points and the line are minimised.


STRUCTURAL INSIGHT:

Squaring ensures all distances are positive and heavily penalises extreme outliers.


The perfect rotation is our optimal mathematical architecture.

Gemini Notebook

R-Squared Quantifies Structural Integrity



High Raw Variation



Significantly Reduced Variation


$$\frac{[\text{Variation Around Mean}] - [\text{Variation Around Fit}]}{[\text{Variation Around Mean}]}$$


Key Takeaway: R-Squared simply tells us how much of the original variation in the data is explained by taking a new variable into account. An R-squared of 0.60 equals a 60% reduction in variance.

Gemini Notebook

BENDING THE LINE FOR CLASSIFICATION


When predicting discrete categories, straight lines fail because they predict impossible probabilities. Logistic Regression bends the line into an S-Curve, ensuring every prediction outputs a valid probability strictly between 0 and 1.





Gemini Notebook

MAXIMUM LIKELIHOOD AS THE ENGINE




Mechanism: Logistic regression abandons Least Squares. Instead, it calculates the probability of observing each specific data point given a candidate curve.

The Goal: It multiplies all these individual probabilities together. The curve that yields the highest total product (the Maximum Likelihood) becomes our final mathematical architecture.

Gemini Notebook

DECISION TREES BUILD LOGICAL SCHEMATICS

Unlike geometric equations, trees partition chaotic data using distinct true/false thresholds.



Structural Advantage:

Naturally handles a chaotic mix of continuous (Age) and discrete (Diet) variables without needing spatial transformation.

Gemini Notebook

Gini Impurity: The Search for Purity

Gini Impurity = 0




$$\text{Gini Equation} = 1 - P(\text{yes})^2 - P(\text{no})^2$$

Mechanism: When building a tree, the algorithm tests every possible variable split. It calculates the weighted average of the Gini Impurity for the resulting leaves. The split that yields the lowest impurity (the purest separation of categories) is chosen as the structural node.

Gemini Notebook

Random Forests and the Power of the Ensemble


The Problem: Individual trees memorise training data (High Variance).



The Solution (Bagging): We create hundreds of trees using Bootstrapped datasets (allowing duplicates). Crucially, at each split, the tree can only consider a random subset of variables. This forced variation creates a highly robust forest.

Gemini Notebook

Built-In Validation: Out-of-Bag Error



Mechanism:

Because Bootstrapping relies on random sampling with replacement, roughly one-third of the original data never makes it into a given tree's training set.

Evaluation:

We run these isolated Out-of-Bag samples through the trees that did not train on them. The proportion incorrectly classified serves as a highly accurate, built-in estimate of the model's real-world error rate, without needing a separate test set.

Gemini Notebook

K-Nearest Neighbours (KNN): The Geometry of Proximity

KNN operates on the premise that similar things exist in close proximity. It categorises new data based on the majority vote of its geometric neighbours.



The Tuning Parameter (K):

A low K (e.g., K=1) creates highly rigid boundaries sensitive to noise and outliers.


A **low K** (e.g., K=1) creates highly rigid boundaries sensitive to noise and outliers.


A **high K** (e.g., K=11) smooths the decision boundary, capturing the dominant local cluster.

Gemini Notebook

Naive Bayes and the Bag of Words








Mechanism:
Naive Bayes ignores grammar and word order entirely (hence 'naive'). It treats language as an unstructured bag of words, calculating independent mathematical probabilities based on historical training data.

Bias Profile:
By ignoring structural relationships among words, it introduces high bias. However, in practice (like spam filtering), it demonstrates remarkably low variance and high reliability.

Gemini Notebook

Multiplying Likelihoods and Laplace Smoothing



The Zero Problem:

If a word (like 'Lunch') never appeared in the spam training data, its probability is 0.

Multiplying any sequence by 0 destroys the entire equation, rendering the model useless.

The Structural Fix:


Laplace Smoothing adds a baseline count (usually α = 1) to every word in the histograms.

This ensures no probability is ever zero, allowing the mathematical engine to keep running smoothly.

Gemini Notebook

Support Vector Machines: The Maximal Margin

Instead of just drawing any line between categories, we want the threshold that provides the widest possible buffer zone (the margin) between the closest data points.




The Vulnerability:

A Maximal Margin Classifier is perfectly rigid. A single outlier forces the margin to shrink drastically, making the model highly sensitive to training data (High Variance).

Gemini Notebook

The Soft Margin: Engineering for Resilience



The Trade-off:


By deliberately allowing a specific number of misclassifications (controlled by Cross-Validation), we create a 'Soft Margin'. This sacrifices perfect accuracy on the training data to build a wider, more stable boundary.

Support Vectors:

The data points sitting on the edge of, or within, this soft margin are the foundational pillars of the model. This increases bias slightly but drastically lowers variance for future predictions.

Gemini Notebook

Escaping Flatland: The Dimension Shift




The Core Magic: When data overlaps severely, we map it into a higher-dimensional space. Entangled data points stretch apart, revealing clean, flat separation boundaries.

Gemini Notebook

The Kernel Trick: Computational Illusion

Top Path:
Physical Transformation
(Computationally Crushing)





Bottom Path:
Algebraic Dot Product
(Instantaneous)

$$(a \cdot b + r)^d$$




Mechanism:
Actually transforming millions of data points into 3D, 4D, or higher dimensions requires impossible computational power.

The Trick: Kernel functions calculate the exact spatial relationship (dot product) between data points as if they were in a higher dimension, without ever moving the data at all. It is spatial manipulation through pure algebra.

Gemini Notebook

Radial Kernels and Infinite Dimensions



Mechanism:

The Radial Basis Function (RBF) Kernel behaves like a weighted nearest neighbour model, giving high influence to close points and dropping distant points to zero.

The Engine:

Underneath the hood, the RBF kernel utilises the Taylor Series expansion. Because this series extends forever, the Kernel Trick is effectively calculating data separation across an infinite number of mathematical dimensions.

Gemini Notebook

The Predictive Architect's Diagnostic Matrix

Algorithm	Core Mechanism	Key Metric	Bias / Variance	Ideal Use Case
Linear Regression	Curve Fitting	Least Squares / R-Squared	Moderate / Low	Continuous Prediction
Logistic Regression	S-Curve Boundary	Maximum Likelihood	Moderate / Low	Binary Classification
Decision Trees	Logical Rules	Gini Impurity	Low / High	Mixed Data Types
Random Forests	Ensemble Rules	OOB Error (Bagging)	Low / Low	High Accuracy Needed
K-Nearest Neighbours	Spatial Proximity	Majority Vote	Variable (K-dependent)	Localised Clustering
Naive Bayes	Probability	Likelihoods + Laplace	High / Low	Text & NLP (Bag of Words)
Support Vector Machines	Spatial Geometry	Soft Margin / Kernel Trick	Low / Low	Complex Non-Linearity

Gemini Notebook

Form Follows Function in Data Architecture

There is no single perfect algorithm. Machine learning is structural engineering. Your dataset dictates the architecture.

Whether building logical trees to parse chaotic human variables, bending logistic curves to cap probabilities, or folding space into infinite dimensions, the goal remains the same:



Takeaway: Build the structure that best reveals the underlying truth of your data.

Gemini Notebook