Status	Finished
Started	Thursday, 8 October 2026, 11:27 AM
Completed	Thursday, 8 October 2026, 11:38 AM
Duration	10 mins 47 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which of the following number can never be generated by the following code: random.randrange(0, 100)

a. 0
b. 1
c. 99
d. 100 ✓

Question **2**

Correct

Mark 1.00 out of 1.00

Fill in the line of the following Python code for calculating the factorial of a number?

```
def factorial👎 :
    if (n==1 or n==0):
       return 1
    else:
        return ——
num = 5;
print("number : ",num)
print("Factorial : ",factorial(num))
```

a. fact(n)*fact(n-1)
b. (n-1)*(n-2)
c. n*(n-1)
d. (n * factorial(n - 1)) ✓

Question **3**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def sayHello():
    print('Hello World!')
sayHello()
sayHello()
```

a. Hello World! ✓
Hello World!

b. None of the mentioned

c. 'Hello World!'
'Hello World!'

d. Hello
Hello

Question **4**

Incorrect

Mark 0.00 out of 1.00

Which of the following statement is a function call?

a. def sum

b. call sum

c. function sum ✗

d. sum

Question **5**

Correct

Mark 1.00 out of 1.00

Write the output of : print(max([1, 2, 3, 4], [4, 5, 6], [7]))

a. [7] ✓

b. [1, 2, 3, 4]

c. 7

d. [4, 5, 6]

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following function call?

```
def fun1(name, age=20):
    print(name, age)
fun1('Emma', 25)
```

a. name

b. Emma 20

c. age

d. Emma 25 ✓

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def maximum(x, y):
    if x > y:
        return x
    elif x == y:
        return 'The numbers are equal'
    else:
        return y
print(maximum(2, 3))
```

a. None of the mentioned

b. 2

c. 3 ✓

d. The numbers are equal

Question **8**

Correct

Mark 1.00 out of 1.00

The part of the program where a variable is accessible is known as the _____ of that variable

a. part

b. none of the mentioned

c. scope ✓

d. module

Question **9**

Correct

Mark 1.00 out of 1.00

The function can be called in the program by writing function name followed by _____.

- a. ( ) ✓
- b. None of the mentioned
- c. { }
- d. [ ]

Question **10**

Correct

Mark 1.00 out of 1.00

Functions which do not return any value is called _____.

- a. default function
- b. null function
- c. void function ✓
- d. zero function

Question **11**

Correct

Mark 1.00 out of 1.00

Write the output of : print(min(tuple("computer")))

- a. c ✓
- b. t
- c. u
- d. o

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following is not the scope of variable?

- a. None of the mentioned
- b. Outside ✓
- c. Local
- d. Global

Question **13**

Correct

Mark 1.00 out of 1.00

In a program, a function can be called ____ times.

- a. 3
- b. Multiple times ✓
- c. 2
- d. 5

Question **14**

Correct

Mark 1.00 out of 1.00

Choose the incorrect statement.

- a. print(pow(2.3, 3.2))
- b. None of the mentioned ✓
- c. print(pow(2, 3))
- d. print(pow(2, 3, 2))

Question **15**

Correct

Mark 1.00 out of 1.00

Which of the following is not the type of function argument?

- a. default argument
- b. Keyword argument
- c. initial argument ✓
- d. Required argument

Status	Finished
Started	Thursday, 8 October 2026, 11:42 AM
Completed	Thursday, 22 October 2026, 8:28 AM
Duration	13 days 20 hours
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 2.00 out of 2.00

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: U = 2^a * 3^b * 5^c, where a, b and c are nonnegative integers.

For example:

Test	Result
`print(checkUgly(6))`	`ugly`
`print(checkUgly(21))`	`not ugly`

Answer: (penalty regime: 0 %)

Reset answer

```
def checkUgly(n):
    if n <= 0:
        return "not ugly"

    for factor in [2, 3, 5]:
        while n % factor == 0:
            n = n // factor

    if n == 1:
        return "ugly"
    return "not ugly"

```

	Test	Expected	Got	
✓	`print(checkUgly(6))`	`ugly`	`ugly`	✓
✓	`print(checkUgly(21))`	`not ugly`	`not ugly`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **2**

Correct

Mark 2.00 out of 2.00

Write a function that returns the value of a+aa+aaa+aaaa with a given digit as the value of a.

Suppose the following input is supplied to the program:

9

Then, the output should be:

9+99+999+9999=11106

Sample Input Format:

9

Sample Output format:

11106

For example:

Test	Result
print(Summation(8))	9872

Answer: (penalty regime: 0 %)

Reset answer

```
def Summation(a):
    return a + int(str(a) * 2) + int(str(a) * 3) + int(str(a) * 4)
```

	Test	Expected	Got	
✓	print(Summation(8))	9872	9872	✓
✓	print(Summation(10))	10203040	10203040	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **3**

Correct

Mark 2.00 out of 2.00

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all

the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
print(christmasDiscount(578))	12

Answer: (penalty regime: 0 %)

Reset answer

```
def christmasDiscount(orderValue):
    total = 0

    for digit in str(orderValue):
        if digit in "2357":
            total += int(digit)

    return total


```

	Test	Expected	Got	
✓	print(christmasDiscount(578))	12	12	✓
✓	print(christmasDiscount(57))	12	12	✓
✓	print(christmasDiscount(222))	6	6	✓
✓	print(christmasDiscount(77777))	35	35	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **4**

Correct

Mark 2.00 out of 2.00

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

Example 1:

Input:

69

Output:

true

Example 2:

Input:

88

Output:

true

Example 3:

Input:

962

Output:

false

Example 4:

Input:

1

Output:

true

For example:

Test	Result
`print(Strobogrammatic(69))`	`True`
`print(Strobogrammatic(962))`	`False`

Answer: (penalty regime: 0 %)

Reset answer

```
def Strobogrammatic(num):
    num = str(num)
    mapping = {'0': '0', '1': '1', '6': '9', '8': '8', '9': '6'}
    rotated = ""

    for digit in reversed(num):
        if digit not in mapping:
            return False
        rotated += mapping[digit]

    return rotated == num
```

	Test	Expected	Got	
✓	`print(Strobogrammatic(69))`	`True`	`True`	✓
✓	`print(Strobogrammatic(88))`	`True`	`True`	✓
✓	`print(Strobogrammatic(962))`	`False`	`False`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **5**

Correct

Mark 2.00 out of 2.00

complete function to implement coin change making problem i.e. finding the minimum

number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
def coinChange(n):
    coins = [1, 2, 3, 4]
    dp = [float('inf')] * (n + 1)
    dp[0] = 0

    for i in range(1, n + 1):
        for coin in coins:
            if coin <= i:
                dp[i] = min(dp[i], dp[i - coin] + 1)

    return dp[n]
```

	Test	Expected	Got	
✓	print(coinChange(16))	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.