Enrollment No.	Name of Student
The state of the s	Name of Stadent

Motilal Nehru National Institute of Technology, Allahabad Department of Civil Engineering

B.Tech V Semester, Mid Term Exam (Odd semester 2017-18)

Course Code: CE-1502

Course Name: Transportation Engineering-I

Duration: 1.5 hours

Date: 21/09/2017

Time: 10.30 am to 12.00 pm

Max. Marks: 20

Read Instructions:

- Assume suitable data and state it clearly.
- ✓ Answers should be brief and to the point.
- ✓ Attempt all questions in serial order and write all parts of a question at one place.
- ✓ Do not write anything on your question papers except your names and enrolment number.

Q1. Write answers for the following: Aux two

(2*2=4)

- a) Discuss the factors influencing highway capacity.
- الر) Discuss the factors influencing highway geometric design.
 - c) Draw and discuss the fundamental diagrams of traffic flow.
 - d) Discuss the various mandatory and obligatory points for highway alignment.

Q2. Differentiate between:

(4*1=4)

- a) Time headway and Space headway.
- c) Overturning and Transverse skid
- b) Capacity and Level of service
- d) Ruling and Exceptional gradient

Q3. Short answers: Any two

- a) Curve Resistance
- c) Creeper lane
- b) Setback distance
 - d) 30th Hourly Volume

Q4. State True or False and correct the false statements. Justify your answers in either case:

- a) On divided highways with four or more lanes, OSD is not provided, but only SSD is sufficient.
- b) In a Distance-Time diagram of vehicle trajectories, more line between two reference lines on x-axis indicates high density.

Q5. Numerical (Any three)

(3*2=6)

- (i) A car is travelling at a speed of 90 kmph. The brakes are applied to avoid a collision with an object that is 90 m away from the point when the driver applies the brakes. Determine
 - (i) For which of the given cases the car will collide with the object, and
 - (ii) The speed of car for all cases when it collides with the object.
 - (a) Level terrain.
- (b) Upgrade of 5%
- (c) Downgrade of 5%
- (ii) Determine the length of the transition curve required for a horizontal curve on a two-lane twoway highway with a 360 m radius and 180m length in a built-up area. Also determine the distance to be kept clear from inside edge of inner lane to provide a sufficient SSD. Assume the design speed as 65 kmph.

Sunaliment No.	Name of Student

(iii) Four road links A, B, C and D are to be constructed under the NHDP project. Determine the order of priority for phasing the road construction. The utility units for the population are 0.5, and 5 and; 2, 3 and 5 units per 1000 t for agricultural, raw materials and industrial products. The negative effect of expenditure on truck transportation (on sections with slopes), required for supply of material for road construction is also to be considered for the utility analysis. Assume a factor of 5 units per Rs. 1000 spent on trucking.

Rond Length link (km)	No. of villages served w.r.t population rage			ed ige	Productivity served, t			Length of gradient route	Cost of trucking per km of	
	\$00	501- 1000	1001- 2000	>2000	Agricultural products	Raw materials	Industrial products	travelled by trucks and its Grade	graded route	
	55	30	15	10	3	4000	3000	1000	3 km for 6%	Rs. 600 for 6% grade
^ 	45	20	8	6	3	5000	1000	1600	4 km for 3%	Rs. 250 for 3% grade
B C	50	15	6	5	5	6000	2000	3200	2.5 km for 8%	Rs. 700 for 8% grade
D	50	40	4	3	2	3000	7000	2000	5 km for 2.5%	Rs. 200 for 2.5% grade
- D	30	<u>۳۳</u>	<u> </u>	3	S	2	3	S		

(iv) Design a two-phase traffic signal for an intersection with four arms by Webster's method for the following data. Take all-red time for pedestrian crossing as 12 seconds.

,	North	South	East	West
Design Hour Flow	600	400	590	460
Saturation Flow	1900	1500	2360	2000

Q6. Draw neat figures for the following: Any One

(2*1=2)

- a) All vehicular conflict points on a 2-lane 2-way 4-legged intersection.
- b) One labelled example each for Prohibitory, Mandatory, Informatory and Cautionary Traffic Signs.

##########