Marketing Platform Frontend · Project Setup

What is set up in the web app so far · November 2026

1. Core framework

- **Next.js 16.4** (App Router) with **React 19.3**, written in strict **TypeScript**.
- Builds with **Turbopack**.
- **Cache Components** and **Partial Prefetching** are on: pages are prerendered as static, and links prefetch only what they need.
- **typedRoutes** is on: a wrong route in `<Link href>` is a TypeScript error.
- **Standalone output:** `npm run build` produces a self-contained server (`.next/standalone/server.js`); a `copy-assets` script copies static files into it.

2. Styling and design system

- **Tailwind CSS v4.** All colours are design tokens in `globals.css` (`bg-card` , `text-muted-foreground` , `bg-primary-soft` ...). No raw hex colours in components.
- **Light and dark mode:** `next-themes` toggles a `.dark` class on `<html>` ; every token has a dark value.
- **Self-hosted fonts** (no Google Fonts requests):
  - Inter for body text
  - Plus Jakarta Sans for headings and the logo
  - Noto Sans Devanagari for Hindi, loaded only when Hindi text appears
  - JetBrains Mono for code
- **Animation:** CSS keyframes (`animate-pop-in` , `animate-modal-in` ...) plus the `motion` library (only `LazyMotion` + `m` , small bundle). Respects the OS "reduce motion" setting.
- **Base UI components** in `src/components/ui/` :
  - `Button` with variants and sizes via `cva`
  - `Typography` : `Heading` , `Text` , `Kpi` , `Code`
  - `DropdownMenu` , `Popover` , `Sheet` , built on `radix-ui`
- **Icons:** `lucide-react` .

3. State and data

- **TanStack Query** for server/API data (caching, retries, no retry on 4xx).
- **Zustand** for UI state only, such as the sidebar and the mobile menu (`ui-store.ts`).
- **React Hook Form + Zod** for forms (installed, not used yet).
- **API client** (`lib/api/client.ts`):
  - Cookie-based auth (tokens are never stored in JavaScript)
  - 15-second timeout
  - Typed `ApiError` on failures
- **Mock data** (`mocks/app-header.ts`) drives the app header until the real API exists.

4. Pages (routes)

- `/`: marketing home page (hero and feature cards) with the **website header**.
- `/dashboard`: app dashboard (title and 4 skeleton cards) with the **app header**.
- `/design-system`: preview page for buttons, typography and colours.
- `(marketing)` and `(app)` route groups give each area its own layout, and so its own header.

5. Website header (before login)

- **Logo:** the product name `BrandName` is defined once, in `config/brand.ts`.
- **Features, Industries, Resources** all open the same style of mega panel: items with icons and descriptions, a promo card and a footer row.
- **Pricing, Creators, Briefs, About** are plain links.
- **Theme toggle, Login, Start free** on the right.
- **Scroll:** on the home page the header is transparent until you scroll.
- **Mobile:** a full-screen menu sheet with accordions, plus "Chat on WhatsApp", Login and Start free at the bottom.
- **SEO:** all menu links are in the server-rendered HTML, so search engines can crawl them.
- **One config:** all menu data lives in `site-header/nav-config.ts`.

6. App header (after login)

- Logo and business switcher (Sharma Sweets, Starter plan).
- **Search:** opens with ⌘K / Ctrl+K, with arrow-key navigation through grouped results. On mobile the header row turns into a search bar.
- **WhatsApp credits chip:** green normally, yellow below ₹200, red at ₹0.
- **Create menu:** Post, Campaign, Broadcast, Creator brief. On mobile it becomes a round "+" button at the bottom right.
- **Other buttons:** notifications (badge shows "9+" above 9), help, theme, user menu (with Log out).
- **Mobile drawer:** business switcher, help and theme.

7. Security

- **Security headers** (`config/security-headers.ts`): CSP, HSTS, X-Frame-Options DENY, nosniff, Permissions-Policy.
- **Environment check:** variables in `.env.local` are validated with Zod (`config/env.ts`); a missing or invalid value fails the build.
- **No** `x-powered-by` header.

8. Code quality tools

- **ESLint:** Next.js, TypeScript and TanStack Query rules; zero warnings allowed.
- **Prettier:** formatting, with Tailwind classes sorted automatically.
- **Husky + lint-staged:** ESLint and Prettier run on changed files before every commit.
- **Commitlint:** commit messages must follow Conventional Commits (`feat: …`, `fix: …`).
- **Node version:** Node 24 in `.nvmrc`, with `engine-strict` on.

9. Testing

- **Vitest + Testing Library (unit tests):** 24 tests covering the button, UI store, logo, WhatsApp credits chip, notification badge and nav config.
- **Playwright (end-to-end)** on desktop and mobile:
  - Website header: menus, Esc, keyboard, mobile sheet
  - App header: search, Create menu, user menu, dark mode
  - Design-system page
- **Screenshots:** run with `SCREENSHOTS=1` to save both headers to `e2e/__screenshots__/`.

10. CI/CD (GitHub)

- **CI workflow:** on every push and PR it runs the format check, lint, typecheck, unit tests and build, then the Playwright end-to-end tests.
- **Security workflow** for separate security checks.
- **Dependabot** opens pull requests for package updates.
- **CODEOWNERS and a PR template** for reviews.

11. Commands

Command	Purpose
`npm run dev`	Development server
`npm run build` / `npm start`	Build / run the production server
`npm run lint`	Lint the code
`npm run typecheck`	TypeScript check
`npm test`	Unit tests
`npm run test:e2e`	Browser (end-to-end) tests
`npm run format`	Format the code

Still to do

- Real API data: `GET /me/header`, search, notifications.
- The WhatsApp business number.
- The full app sidebar.
- Marketing pages such as `/pricing` and `/features/*`.

> **Status:** the website and app header work is not committed yet. It will be committed once the production build and end-to-end tests run against the production server.