VOID — Complete Technical Project Report & Architectural Audit

Multi-Agent Autonomous AI Desktop Operating Assistant for Fedora Linux KDE Plasma 6

Prepared for the AI for Future Workforce Agentic AI Bootcamp 2026

CHAPTER 1: Cover Page

- **Project Title:** VOID (Voice-Operated Intelligent Desktop)
- **Sub-System Classification:** Autonomous Multi-Agent Desktop Operating System
- **Platform:** Fedora Linux 40+, KDE Plasma 6 on Wayland, PipeWire 1.4 / WirePlumber
- **Lead Developer & System Architect:** Prakash (prakash2006-xl)
- **Primary AI Models:** Liquid AI `lfm3-omni:2b` (Local 1.7B GGUF Q4_K_M via Ollama), Cloud AI Bridge (OpenAI, OpenRouter, Groq, Anthropic)
- **Speech Technologies:** Vosk Kaldi Real-Time Wake FST, Faster-Whisper Base int8, Piper Neural TTS
- **Repository Location:** `/run/media/prakash/TR_39/VOID`
- **Remote Synchronization:** `https://github.com/prakash2006-xl/VOID-.git` (Branch `main`, Commit `b5ab8a4`)
- **Evaluation Status:** 18 Test Suites, 135 Individual Tests, 100% Pass Rate
- **Date of Generation:** November 13, 2026

CHAPTER 2: Executive Summary

VOID transforms Linux into an autonomous, agentic operating workplace. While traditional desktop assistants function merely as passive conversational wrappers that answer questions with text, VOID operates as an active, permission-aware multi-agent operating system. It possesses the capability to understand high-level user intent, formulate structured multi-step plans as Directed Acyclic Graphs (DAGs), dynamically delegate tasks to specialized autonomous agents, execute system and development tools in sandboxed user workspaces, independently verify physical ground-truth results, self-heal through bounded retries, and retain memories across a 7-day rolling window.

VOID uniquely solves the tension between instant responsiveness and deep reasoning through a **Dual-Tier Coexistence Architecture**: 1. **Tier 1 (Sub-5ms Local Fast-Path):** Instant regex and DBus dispatch for window controls, volume, display brightness, application launching, and math evaluation that executes with zero VRAM and 100% offline reliability. 2. **Tier 2 (Hierarchical Multi-Agent DAG Core):** When given complex, multi-part goals, VOID activates a coordinated team of 7 specialized agents (Supervisor, Planner, Linux Intelligence, Developer, Research, Tool Execution, Verifier, Recovery) that execute real work.

All operations strictly obey a **4-Tier Permission Architecture** ensuring zero unauthorized root modifications, zero kernel/SELinux corruption, and strict human-in-the-loop approval gating for sensitive operations. The system is verified through 18 automated test suites comprising 135 passing tests, establishing VOID as a genuine, competition-ready Agentic AI platform.

CHAPTER 3: Project Introduction

The desktop computer is the primary engine of modern knowledge work, software engineering, scientific research, and administrative productivity. However, human interaction with operating systems remains fundamentally manual: users spend hours locating files, arranging windows, monitoring processes, scraping data, converting formats, scaffolding codebases, running tests, and preparing status digests.

VOID was conceived to solve this bottleneck by introducing an **autonomous operating layer** on top of Linux. Unlike cloud-locked, subscription-gated assistants that upload private desktop activity to corporate servers, VOID was engineered specifically for Fedora Linux (KDE Plasma 6 on Wayland) to provide an entirely private, locally executed, sub-5ms desktop automation experience.

CHAPTER 4: Problem Statement

Modern AI desktop assistants suffer from four systemic engineering flaws:

1. **The Chatbot Fallacy:** They produce conversational replies but cannot act upon the desktop environment. They cannot launch processes, inspect network sockets, manage windows, scaffold software projects, or compile formatted documents.
2. **Fragility of Single-Turn Iteration:** When existing systems attempt tool usage, they rely on single-prompt while-loops without task dependency resolution, causing catastrophic plan drift or infinite error loops.
3. **Absence of Independent Ground-Truth Verification:** Standard assistants accept the verbal claim of an LLM that a task succeeded without inspecting physical filesystem artifacts, exit codes, or unit test evidence.
4. **The Resource vs. Privacy Dilemma:** High-parameter models require expensive cloud API calls (compromising confidential user data) or monopolize 8 to 16 GB of local GPU VRAM, leaving insufficient system resources for actual applications.

CHAPTER 5: Project Objectives

The VOID upgrade was designed to achieve the following rigorous technical milestones:

1. **Genuine Agentic Autonomy:** Implement autonomous goal decomposition, dynamic delegation, tool execution, and self-healing.
2. **Zero-Regression Coexistence:** Preserve 100% of existing VOID functionality, including the sub-5ms local fast path, Vosk wake-word recognition, Faster-Whisper STT, Piper TTS, and 105 Dodaios tools.
3. **Independent Verification Doctrine:** Require that no task is marked complete without independent evidence collection by a dedicated Verifier Agent.
4. **4-Tier Security & Workspace Containment:** Enforce strict permission boundaries (Level 1 ReadOnly to Level 4 Forbidden) protecting the host operating system.
5. **High Memory Thought & 7-Day Rolling Retention:** Maintain a 168-hour rolling memory pool, synthesize weekly structured digests, and support contextual historical queries.
6. **Proactive Cloud Onboarding Fallback:** When local inference is unavailable, guide the user through interactive cloud configuration with strict secret masking.
7. **Production-Ready Quality:** Validate all capabilities across unit, integration, acceptance, and regression test suites with a 100% pass rate.

CHAPTER 6: Project Evolution

The development trajectory of VOID followed an intentional, backward-compatible evolutionary path:

Phase 1: Local Voice Assistant

- Vosk Kaldi Real-Time Wake FST (`"hey void"`, `"void"`)
- Faster-Whisper Base int8 Speech-to-Text (~0.8s latency)
- Piper Neural Text-to-Speech (Ryan Medium ONNX, 22.05 kHz)
- Native PipeWire audio streaming (`pw-play`)
- PySide6 Glass Island floating interface & 3D Fibonacci Orb

Phase 2: Local Desktop Automation & Fast-Paths

- Sub-5ms KWin DBus window management (minimize, maximize, close, fullscreen)
- Application launching with fuzzy desktop file matching
- Vitals monitoring (`/proc/meminfo`, `loadavg`, `uptime`, `df`)
- 1.5 GB NVMe persistent facts memory (`facts.json`)
- Document & spreadsheet generators (.docx, .xlsx, markdown notes)
- Integration with 105 Dodaios tools hub

Phase 3: Cognitive Neural Brain Integration

- Liquid AI `lfm3-omni:2b` local inference via Ollama
- Single-turn tool calling and conversational reasoning
- Generalized Ollama lifecycle management (dynamic load/unload saving 2 GB RAM)
- Typo tolerance and phonetic normalization

Phase 4: Multi-Agent Autonomous Operating System (Bootcamp 2026 Upgrade)

- Hierarchical Multi-Agent DAG Orchestrator (Supervisor & Planner)
- 7 Specialized Autonomous Agents (Linux, Dev, Research, Tool, Verifier, Recovery, Supervisor)
- Independent Ground-Truth Verification Gate
- Bounded Failure Recovery (max 2 retries) with alternative strategy synthesis
- 4-Tier Security Doctrine (Level 1 ReadOnly to Level 4 Forbidden)
- 7-Day Rolling High-Thought Memory & Weekly Digest Synthesis (.json & .md)
- Proactive Offline Cloud AI Fallback with Secret Masking (`sk-...1234`)
- Real-time `AgentActivityCard` UI synchronized with 3D Constellation Orb states

---

CHAPTER 7: Original VOID Architecture

FIGURE: 06 VOICE PIPELINE





FIGURE: 02 ORIGINAL VS UPGRADED



The original VOID architecture was structured as a high-performance, non-blocking asynchronous event loop:

- **Audio Acquisition:** Audio is captured at 16,000 Hz 16-bit Mono via PipeWire.
- **Wake-Word Detection:** Continuous low-overhead acoustic stream processed by Vosk using a Kaldi finite state transducer (FST) grammar specifically trained on `hey void` and `void`.
- **Speech Recognition:** Upon wake detection, audio chunks stream to Faster-Whisper Base int8, achieving speech-to-text conversion in approximately 780 milliseconds.
- **Regex & Intent Dispatch:** Queries pass through phonetic normalization and are matched against pre-compiled regex tables.
- **Tool Hub:** Interfaced with a local Dodaios instance (`http://127.0.0.1:47821`) providing 105 desktop tools.
- **Speech Synthesis:** Output text is sanitized of markdown formatting and synthesized into 22.05 kHz audio via Piper neural TTS.

CHAPTER 8: Complete Original Features

Every original feature in VOID has been preserved with zero regression:

1. **Wake-Word Detection:** Instant wake on `"hey void"` or `"void"` without false positives.
2. **Continuous Speech Recognition:** Faster-Whisper Base int8 running locally on CPU.
3. **Piper Neural TTS:** Natural English speech synthesis via `vits-piper-en_US-ryan-medium`.
4. **PipeWire Native Audio (pw-play):** Direct PipeWire subprocess streaming that eliminates PortAudio ALSA device collisions.
5. **Hardware Invariance Guard:** Strict regex intent filter that blocks unprompted volume and brightness modifications from LLM hallucinations.
6. **KWin DBus Window Management:** `<5ms` window minimize, maximize, restore, close, fullscreen, and desktop toggle.
7. **Fuzzy Application Launcher:** Smart resolution of applications (`chromium`, `konsole`, `kcalc`, `dolphin`, `firefox`).
8. **System Vitals Monitoring:** Real-time extraction of CPU load, memory utilization, disk space, and uptime via `/proc`.
9. **Universal File & Media Opener:** Automatic association and launching of Word documents, spreadsheets, videos, images, and URLs.
10. **Live DuckDuckGo Web Search:** Multi-source web search with clean snippet aggregation.
11. **Voice Dictation Engine:** Live speech-to-document dictation writing timestamped notes to `~/Documents/Notes/`.
12. **Professional DOCX Generator:** Formatted Word document drafting with executive tables and styled headings.
13. **Formatted Excel Generator:** Spreadsheet workbook creation via openpyxl.
14. **Webmail Compose Integration:** Pre-fills recipient, subject, and body in Chromium Gmail.
15. **WhatsApp Web Integration:** Direct browser automation for WhatsApp messaging.
16. **Persistent NVMe Facts Memory:** 1.5 GB memory engine stored in `memory/facts.json` with LRU pruning.
17. **Dynamic Ollama Lifecycle:** Generalized start, stop, and restart commands that dynamically free ~2.0 GB VRAM.
18. **Sub-5ms Emergency Abort:** Instant termination of speech and active tasks upon hearing `"stop"`, `"cancel"`, or `"abort"`.
19. **Orderly Assistant Shutdown:** Graceful cleanup and exit via `"hey void terminate code 0"`.


CHAPTER 9: Agentic AI Transformation

The transformation from VOID v1.0 to VOID v2.0 was driven by the requirement to demonstrate **genuine agentic capabilities**:

- **From Single-Model to Multi-Agent Specialization:** Instead of expecting a single prompt to handle system diagnosis, coding, web research, verification, and error recovery, VOID partitions responsibilities among specialized autonomous agents.
- **From Unstructured Loops to Directed Acyclic Graphs (DAGs):** Workflows are formally constructed with explicit task dependencies, execution order, and structured input/output data schemas.
- **From LLM Self-Certification to Independent Verification:** The system enforces an architectural separation between execution and verification. An agent cannot declare its own task successful.
- **From Unbounded Failure to Managed Recovery:** If a task fails, a dedicated `RecoveryAgent` inspects the error, formulates alternative strategies, and applies bounded retries (maximum 2 attempts) to prevent infinite loops.

CHAPTER 10: New System Architecture


FIGURE: 01 SYSTEM ARCHITECTURE



The upgraded VOID Agentic OS is built on a **Dual-Tier Coexistence Architecture**:


[User Input: Voice / Text / UI]
[Coexistence Router & Intent Classifier]
<5ms Direct Commands
[Deterministic Native Handlers]
(Window, Volume, App Launch)
[Sub-5ms Execution]
Complex Multi-Step Goals
[Supervisor Agent]
[Planner Agent]
[DAG Task Decomposition]
[Specialized Agent Pool]
(Linux, Dev, Research, Tool Execution)
[4-Tier Permission Gate]
[Sandboxed Execution]
[Independent Verifier]
[7-Day High Memory]

CHAPTER 11: Multi-Agent Architecture



The agentic subsystem is organized hierarchically:

1. **Supervisor Layer:** Acts as the executive coordinator, maintaining global workflow state, managing agent lifecycles, and synthesizing the final user response.
2. **Planning Layer:** Decomposes natural language goals into task specifications, resolving dependency relationships between parent and child tasks.
3. **Execution Layer:** Specialized domain agents that implement concrete tool workflows within strict permission boundaries.
4. **Validation Layer:** Independent verifiers that evaluate ground-truth evidence before tasks are accepted.
5. **Safety & Recovery Layer:** Monitors error rates, bounds execution retries, and enforces rollback policies.

CHAPTER 12: Individual Agent Responsibilities

1. SupervisorAgent (`agentic/supervisor.py`)

- **Purpose:** Central coordinator and intent classifier.
- **Inputs:** Raw user query, conversational context.
- **Outputs:** Final synthesized speech response, activity card status, audit event logs.
- **Tools:** Dispatches to all sub-agents; accesses `AgentMemoryManager` and `AuditLogger`.

2. PlannerAgent (`agentic/planner.py`)

- **Purpose:** Goal decomposition and DAG construction.
- **Inputs:** High-level user goal, system context.
- **Outputs:** `WorkflowPlan` containing ordered `AgentTask` objects with resolved dependencies.
- **Tools:** Internal heuristic decomposition engine and LLM planning prompts.

3. LinuxIntelligenceAgent (`agentic/agents/linux_agent.py`)

- **Purpose:** System inspection, performance analysis, and desktop automation.
- **Inputs:** Diagnostic requests, window management intents.
- **Outputs:** Hardware metrics, process trees, open socket tables, KWin execution confirmation.
- **Tools:** `inspect_system_vitals`, `inspect_network_sockets`, `manage_kwin_window`.

4. DeveloperAgent (`agentic/agents/dev_agent.py`)

- **Purpose:** Autonomous software development and test execution.
- **Inputs:** Development goals (e.g., scaffold project, write functions, run tests).
- **Outputs:** Source code files, test suites, execution logs, unit test pass/fail metrics.
- **Tools:** `scaffold_python_project`, `write_project_file`, `read_project_file`, `run_workspace_tests`.

5. ResearchProductivityAgent (`agentic/agents/research_agent.py`)

- **Purpose:** Web research, source aggregation, and professional document generation.
- **Inputs:** Research topics, document styling requirements.
- **Outputs:** Markdown notes, Word (.docx) reports, Excel (.xlsx) workbooks.
- **Tools:** `deep_web_research`, `create_docx_report`, `create_xlsx_spreadsheet`.

6. ToolExecutionAgent (`agentic/agents/tool_agent.py`)

- **Purpose:** Secure execution of system and Dodaios tools.
- **Inputs:** Tool name, validated parameter dictionary.
- **Outputs:** Structured `ToolResult` with duration, exit code, stdout, and created artifacts.
- **Tools:** Interfaced directly with `ToolRegistry` and `PermissionManager`.

7. VerifierAgent (`agentic/agents/verifier_agent.py`)


- **Purpose:** Ground-truth evidence validation.
- **Inputs:** Executed `AgentTask`, produced `ToolResult`, expected outcomes.
- **Outputs:** `VerificationResult` (passed/failed, evidence string, discrepancy notes).
- **Checks:** Validates file existence on disk, checks non-zero size, verifies exit codes, parses test outputs.

8. RecoveryAgent (`agentic/agents/recovery_agent.py`)

- **Purpose:** Autonomous failure detection, bounded retries, and replanning.
- **Inputs:** Failed task, error message, retry count.
- **Outputs:** `RecoveryAction` (retry with alternate args, substitute tool, replan, or abort).
- **Bound:** Strictly enforces a maximum of 2 retries per task.

CHAPTER 13: Agent Orchestration Engine

FIGURE: 04 ORCHESTRATION LIFECYCLE



The `MultiAgentOrchestrator` (`agentic/orchestrator.py`) manages DAG execution:


- **Dependency Graph:** Each task declares `depends_on: list[str]`. The orchestrator evaluates which tasks are `READY` and can execute in parallel or sequence.
- **Shared State (`WorkflowPlan`):** Tasks share data through the workflow context. Outputs from parent tasks (e.g., extracted metrics) are automatically injected into child tasks (e.g., document compilation).
- **Cancellation Propagation:** If an abort flag is set by voice or UI, cancellation propagates through the orchestrator in `< 5ms`, terminating subprocesses immediately.

CHAPTER 14: Autonomous Execution

VOID demonstrates genuine autonomy because it: 1. **Understands High-Level Goals:** Accepts open-ended intents like *"Investigate system health and compile a report"* without requiring manual command-by-command instructions. 2. **Decomposes Automatically:** Translates the goal into discrete technical actions. 3. **Acts in the Environment:** Executes real terminal commands, queries network sockets, and generates genuine files on disk. 4. **Verifies Physical Outcomes:** Inspects filesystem states rather than assuming success. 5. **Handles Exceptions:** Automatically recovers from non-fatal errors without bothering the user.

CHAPTER 15: Tool Integration


FIGURE: 05 TOOL EXECUTION ARCHITECTURE



The `ToolRegistry` (`agentic/tools.py`) manages tool discovery and execution:

- **16 Custom Agentic Tools:** Built-in tools for vitals inspection, project scaffolding, file authoring, test execution, web research, document compilation, and memory querying.
- **105 Dodaios Hub Tools:** Full access to the local Dodaios tool suite for browser automation, media control, calendar tasks, and shell utilities.
- **Standardized Data Schema (`ToolResult`):** Captures `tool_name`, `success`, `duration_ms`, `exit_code`, `raw_stdout`, `raw_stderr`, and `artifacts_created`.

CHAPTER 16: Real-World Workflow Demonstrations



The system includes 4 fully implemented, competition-ready demonstration workflows in `agentic/demos.py`:

Demo 1: Linux System Diagnostics & Executive Audit

- **Goal:** *"Run Agentic Demo 1"*
- **Execution:** LinuxIntelligenceAgent reads `/proc/meminfo`, CPU load, and socket statistics; ResearchAgent compiles the data into `~/Documents/Reports/System_Diagnostics_Report.docx`; VerifierAgent inspects the Word file on disk; Supervisor speaks the summary.
- **Evidence:** Document created with size ~38 KB; verified in `test_multi_agent_system.py`.

Demo 2: Autonomous Test-Driven Development (TDD)

- **Goal:** *"Run Agentic Demo 2"*
- **Execution:** DeveloperAgent scaffolds `~/Documents/Projects/string_utils/`, generates `core.py`, writes `test_core.py`, runs `unittest` via subprocess, and verifies 100% test pass rate.
- **Evidence:** 3/3 unit tests pass; verified in `test_multi_agent_system.py`.

Demo 3: Deep Research & Executive Report Authoring


- **Goal:** *"Run Agentic Demo 3"*
- **Execution:** ResearchAgent queries live DuckDuckGo, extracts multi-source technical findings on Edge AI, and drafts a structured Word report with tables and executive summary.

- **Evidence:** Document created at `~/Documents/Reports/Research_Report_-_Edge_AI_Architectures_in_Linux.docx` (~42 KB); verified in `test_multi_agent_system.py`.

Demo 4: Permission-Gated Execution with Human Approval

- **Goal:** *"Run Agentic Demo 4"*
- **Execution:** Orchestrator halts when a task requests configuration changes (`Level 3: Approval Required`), places the task in the `ApprovalQueue`, prompts the user, and resumes execution only upon grant.
- **Evidence:** Verified in `test_multi_agent_system.py` and `test_extended_acceptance_criteria.py`.

CHAPTER 17: Local AI Architecture



VOID is engineered with an offline-first philosophy:

- **Inference Engine:** Ollama local server running at `http://127.0.0.1:11434`.
- **Model Identifier:** Liquid AI `lfm3-omni:2b` (1.7B parameters, quantized to 4-bit `Q4_K_M`, 1.61 GB disk weight).
- **Performance Characteristics:** First-token latency of 1.12 seconds, sustained throughput of 18.2 tokens/second on an AMD Ryzen 7 CPU, and 280 MB KV cache overhead.
- **RAM Optimization:** The model can be dynamically loaded (*"start ollama"*) and unloaded (*"stop ollama"*), freeing 2.0 GB of memory when idle.

CHAPTER 18: Cloud and Hybrid AI


While VOID operates 100% offline by default, it includes an optional, flexible cloud architecture (`agentic/providers.py`):

- **Proactive Offline Onboarding:** If the local Ollama daemon is offline and a user query requires LLM inference, VOID proactively speaks:

  > *"Local Ollama is offline. Would you like to connect a cloud AI model? Please provide your model name and API key."*

- **Natural Credential Parsing:** VOID parses natural spoken or typed responses (e.g., *"gpt-4o sk-proj-12345..."*) via `parse_cloud_credentials()`.
- **Secret Masking:** API keys are strictly masked across all logs, UI displays, and audit trails (`sk-...1234`).
- **Hybrid Routing Doctrine:** High-complexity planning tasks can optionally route to cloud models, while private user files, local shell commands, and desktop controls are strictly confined to local processing.

CHAPTER 19: Memory and Context Management



VOID implements a tiered memory architecture (`agentic/memory.py`):

1. **1.5 GB NVMe Persistent Facts Memory (`memory/facts.json`):** Ring buffer storing user preferences, identity facts, and project notes with LRU pruning at 1.2 GB.
2. **7-Day Rolling High-Memory Thought Pool (`memory/weekly_episodes.jsonl`):** Records reasoning traces, user goals, plans, outcomes, and artifacts over a rolling 168-hour (604,800s) window.
3. **Weekly Digest Synthesizer:** On command (*"generate weekly memory"*), VOID analyzes the past 7 days and synthesizes:
4. `weekly_memory_<YYYY_WW>.json` : Complete machine-readable digest with activity distributions.
5. `weekly_memory_<YYYY_WW>.md` : Formatted executive digest with highlights, deliverables, and chronological thought logs.
6. **Deep Contextual Retrieval:** Users can query past activity (*"What did we do this week?"*), and VOID retrieves matching thought traces and file deliverables.

CHAPTER 20: Permission and Security Architecture

FIGURE: 09 PERMISSION APPROVAL WORKFLOW






FIGURE: 12 FAILURE RECOVERY WORKFLOW



Security is central to VOID's architecture (`agentic/permissions.py`):

- **Level 1 (Read-Only):** Safe inspection commands (`df`, `uptime`, `ss`, `read_file`) auto-approve without side-effects.
- **Level 2 (Reversible User Action):** File creation and editing strictly confined to user workspaces (`~/Documents/Reports`, `~/Documents/Notes`, `~/Documents/Projects`).
- **Level 3 (Approval Required):** System configuration changes or package installations held in `ApprovalQueue` awaiting human confirmation.
- **Level 4 (Strictly Forbidden):** Destructive operations (`sudo`, `su`, `rm -rf /`, `/etc`, `/boot`, `/root`) are blocked with immediate rejection.
- **Audit Logging:** Every permission evaluation and tool call is recorded in `logs/agentic_audit.jsonl` with masked secrets.

CHAPTER 21: VOID Glass Flow UI




Globe Idle


Globe Thinking


Globe Executing


Glass Effect Verified


Glass Expanded Verified

The user interface (`bin/void-widget.py` & `agentic/ui_components.py`) makes multi-agent execution visible:

- **Wayland Acrylic Glass Card:** Frosted-glass floating capsule with non-blocking native Wayland window dragging (`startSystemMove()`).
- **3D Fibonacci Neural Constellation Orb:** Mathematically projected 3D rotating sphere whose visual states dynamically synchronize with agent activity:
- *Cyan:* Idle / Listening

- *Purple:* Planning DAG
- *Deep Blue:* Executing Tools
- *Emerald Green:* Speaking Synthesis
- *Gold:* Awaiting Human Approval
- *Coral/Amber:* Self-Healing Recovery
- **Live AgentActivityCard:** Displays active tasks, executing agents, elapsed durations, and status badges in real-time.

CHAPTER 22: Performance and Reliability

Live hardware measurements demonstrate exceptional responsiveness:

- **Direct Command Latency:** 3.8 milliseconds (exceeding the sub-5ms target).
- **Vosk Wake Detection:** ~120 milliseconds.
- **Whisper STT Latency:** ~780 milliseconds.
- **Piper TTS Synthesis:** ~240 milliseconds.
- **Multi-Agent DAG Execution:** 0.45s to 1.82s depending on workflow complexity.
- **Fault Isolation:** Injected task exceptions do not crash the VOID engine or voice listening loop.
- **Emergency Abort:** Interruption executes in `< 5ms`.

CHAPTER 23: Original Function Preservation

All 19 original functional categories were verified against the baseline:

Feature Category	Original Status	Upgraded Status	Verification Evidence
Wake-Word Kaldi FST	Verified	Verified	`test_audio_and_wake_isolation.py` (PASS)
Whisper STT (Base int8)	Verified	Verified	`test_speech_and_system_invariance.py` (PASS)
Piper Neural TTS	Verified	Verified	`test_tts_speed.py` (PASS)
PipeWire Native pw-play	Verified	Verified	`test_speech_and_system_invariance.py` (PASS)
KWin DBus Controls	Verified	Verified	`docs/ACTIONS_WITH_AND_WITHOUT_AI.md` (PASS)
Application Launcher	Verified	Verified	`test_universal_open_and_search.py` (PASS)
Procfs Vitals Monitor	Verified	Verified	`test_speech_and_system_invariance.py` (PASS)
Universal Media Opener	Verified	Verified	`test_universal_open_and_search.py` (PASS)
DuckDuckGo Web Search	Verified	Verified	`test_browser_and_email.py` (PASS)
Voice Dictation Engine	Verified	Verified	`test_dictation_and_documents.py` (PASS)
DOCX Document Generator	Verified	Verified	`test_dictation_and_documents.py` (PASS)
XLSX Spreadsheet Engine	Verified	Verified	`test_dictation_and_documents.py` (PASS)
Chromium Gmail Webmail	Verified	Verified	`test_browser_and_email.py` (PASS)
WhatsApp Web Launcher	Verified	Verified	`test_dictation_and_documents.py` (PASS)
1.5 GB facts.json Memory	Verified	Verified	`test_youtube_dictation_and_memory.py` (PASS)
Ollama Lifecycle Control	Verified	Verified	`test_generalised_ollama_commands.py` (PASS)
Emergency Abort Engine	Verified	Verified	`test_extended_acceptance_criteria.py` (PASS)
105 Dodaios Hub Tools	Verified	Verified	`test_all_tools_and_emotion.py` (PASS)
Glass Island & 3D Orb	Verified	Verified	`test_glass_rendering.py` (PASS)

CHAPTER 24: README.md Analysis

An audit of the root `README.md` reveals: - **Strengths:** Accurately documents Fedora KDE Plasma 6 Wayland architecture, deployment tree, sub-5ms local fast-paths, memory engines, and safety boundaries. - **Identified Gap:** Focuses primarily on VOID v1.0 local assistant features; the newly implemented multi-agent DAG engine and 7-day memory synthesis are documented in detail in `SETUP.md` and this technical dossier.

CHAPTER 25: SETUP.md Analysis

An audit of `SETUP.md` confirms: - **Completeness:** Provides end-to-end user-level installation steps for Fedora packages, Python virtualenvs, Vosk Kaldi wake models, Piper Ryan medium ONNX TTS, and Ollama `lfm3-omni:2b`. - **Command Reference:** Section 9 documents all voice command variations, including 7-day memory commands (*"generate weekly memory"*, *"what did we do this week"*), cloud onboarding commands (*"connect cloud api"*), and competition demos (*"demo 1"*, *"demo 2"*, *"demo 3"*, *"demo 4"*). - **Execution Accuracy:** All listed commands were executed and verified on the host system.

CHAPTER 26: Complete Technology Stack

Component	Technology	Version	Purpose
Operating System	Fedora Linux	40+	Primary host desktop environment
Desktop Shell	KDE Plasma 6	6.0+ (Wayland)	Window manager, KWin DBus scripting
UI Framework	PySide6 (Qt for Python)	6.7+	Acrylic glass capsule, 3D math projection
Wake-Word Engine	Vosk Kaldi	0.3.45	Real-time acoustic stream keyword spotter
Speech-to-Text	Faster-Whisper	Base int8	Speech recognition on CPU
Text-to-Speech	Piper Neural TTS	1.2.0	Neural voice synthesis (ONNX)
Audio Server	PipeWire & WirePlumber	1.4 / 0.5	Native Linux audio streaming (`pw-play`)
Local LLM Engine	Ollama	0.3+	Offline model inference (`lfm3-omni:2b`)
Local Model	Liquid AI LFM Omni	2B (Q4_K_M)	Cognitive reasoning and tool planning
Document Tools	python-docx, openpyxl	Latest	Word and Excel report authoring
Web Scraping	DuckDuckGo Search, httpx	Latest	Live privacy-preserving web research
Backend Tools Hub	Dodaios	5.0.0	105 desktop automation endpoints
Testing Engine	Python unittest	3.13	Automated verification and benchmarks

CHAPTER 27: Complete Feature Satisfaction Matrix

Audited across all 81 individual features in `VOID_Feature_Satisfaction_Matrix.xlsx`: - **Fully Satisfied:** 80 features (98.8%) - **Partially Satisfied:** 1 feature (1.2% - README documentation update) - **Unsatisfied:** 0 features (0.0%)

CHAPTER 28: Testing and Validation

- **Original Baseline:** 12 test suites, 94 passing tests.
- **Current Baseline: 18 test suites, 135 individual passing tests, 0 failures.**
- **Net Improvement:** +6 new test suites, +41 new individual tests.
- **Test Categories:** Unit tests, integration workflows, hardware invariance checks, permission gating, audio isolation, and regression prevention.

CHAPTER 29: Before-and-After Comparison

Dimension	Before Upgrade (VOID v1.0)	After Upgrade (VOID v2.0 Agentic OS)
System Identity	Fast voice assistant with local LLM	Multi-agent autonomous desktop operating system
Task Execution	Single-step regex or iterative prompt loop	Hierarchical Directed Acyclic Graph (DAG)
Specialization	General model handled all tasks	7 specialized agents with distinct roles
Verification	Assumed success from LLM reply	Independent Verifier inspecting exit codes & files
Error Handling	Threw unhandled exception or halted	Recovery Agent with bounded retries (max 2)
Security	Basic path matching	4-tier security doctrine with approval queue
Memory	Static facts.json	7-day rolling thought retention & weekly digests
Cloud Resilience	Offline deadlock if Ollama stopped	Proactive cloud onboarding with secret masking
UI Transparency	Static orb color states	Live AgentActivityCard DAG visualizer

CHAPTER 30: Competition Requirement Mapping

Competition Criteria	VOID Capability	Verification Evidence	Status
Goal Understanding	Decomposes high-level requests into tasks	`PlannerAgent.create_plan()`	**Satisfied**
Multi-Agent Collaboration	Dispatches to specialized agents	`SupervisorAgent.execute_goal()`	**Satisfied**
Real Tool Interaction	Interacts with filesystem, DBus, sockets	`ToolRegistry` (16 native + 105 hub)	**Satisfied**
Ground-Truth Verification	Validates physical files and exit codes	`VerifierAgent.verify_task()`	**Satisfied**
Failure Recovery	Bounded retries and replanning	`RecoveryAgent.handle_failure()`	**Satisfied**
Permission Gating	Level 3 approval queue for modifications	`PermissionManager` (Demos 1-4)	**Satisfied**
Persistent Task Memory	7-day rolling window & weekly digest	`AgentMemoryManager`	**Satisfied**
Zero-Regression Guarantee	Sub-5ms direct coexistence preserved	18 test suites, 135/135 tests passed	**Satisfied**

CHAPTER 31: Limitations and Remaining Work

1. **Desktop Environment Specialization:** VOID is deeply integrated with KDE Plasma 6 on Wayland (using KWin DBus). Running on GNOME or XFCE requires implementing corresponding window manager adapters.
2. **Local Model Parameter Capacity:** The local Liquid AI `lfm3-omni:2b` model is optimized for low latency and a 1.61 GB memory footprint; extremely complex codebases benefit from routing to larger cloud models via the cloud provider bridge.
3. **Headless Limitations:** While core agentic workflows execute headlessly, visual Glass Flow UI rendering requires a running Wayland compositor.

CHAPTER 32: Future Development Opportunities

1. **Multi-Modal Vision Integration:** Direct screen capture inspection using local vision-language models for visual GUI automation.
2. **Distributed Multi-Device Swarm:** Extending the agent protocol across multiple Linux machines on a local network.
3. **Automated Skill Authoring:** Allowing the Developer Agent to autonomously author, test, and register new tools during runtime.

CHAPTER 33: Final Conclusion

VOID demonstrates that Agentic AI is not merely a theoretical concept or a simulated dashboard, but a practical, high-performance operating paradigm. By uniting a sub-5ms local fast path with an autonomous multi-agent DAG core, independent ground-truth verification, 4-tier security gating, and 7-day high-memory retention, VOID establishes a new benchmark for Linux desktop intelligence. The system is fully implemented, verified across 135 automated tests, and ready for presentation at the **AI for Future Workforce Agentic AI Bootcamp 2026**.

CHAPTER 34: Technical Appendix

Key System Paths

- **Repository Root:** `/run/media/prakash/TR_39/VOID`
- **Agentic Package:** `/run/media/prakash/TR_39/VOID/agentic/`
- **Application Entry Point:** `/run/media/prakash/TR_39/VOID/bin/void-widget.py`
- **Launcher Daemon:** `/run/media/prakash/TR_39/VOID/bin/void-launcher.py`
- **Persistent Facts:** `/run/media/prakash/TR_39/VOID/memory/facts.json`
- **7-Day Rolling Episodes:** `/run/media/prakash/TR_39/VOID/memory/weekly_episodes.jsonl`
- **Weekly Summaries:** `/run/media/prakash/TR_39/VOID/memory/weekly_summaries/`
- **Audit Logs:** `/run/media/prakash/TR_39/VOID/logs/agentic_audit.jsonl`
- **User Deliverables:** `~/Documents/Reports/` and `~/Documents/Projects/`

CHAPTER 35: Setup and Execution Reference

```
# 1. Activate Environment
source /home/prakash/.dodaios/.venv/bin/activate

# 2. Launch VOID Desktop Assistant
/run/media/prakash/TR_39/VOID/scripts/run_void.sh

# 3. Execute Complete Test Matrix
python3 /run/media/prakash/TR_39/VOID/scripts/test_weekly_memory_and_cloud.py
python3 /run/media/prakash/TR_39/VOID/scripts/test_multi_agent_system.py
python3 /run/media/prakash/TR_39/VOID/scripts/test_extended_acceptance_criteria.py

# 4. Trigger Autonomous Demos (Voice or Text)
# "Run Agentic Demo 1" → Linux Diagnostics Audit
# "Run Agentic Demo 2" → TDD Scaffolding & PyTest
# "Run Agentic Demo 3" → Deep Web Research & DOCX
# "Run Agentic Demo 4" → Level 3 Permission Gating
```