



SOFTWARE REQUIREMENTS SPECIFICATION

# TravelPort

Goibibo-Inspired Full-Stack Travel Booking Portal

---

| DOCUMENT VERSION | DATE     | STATUS | CLASSIFICATION |
|------------------|----------|--------|----------------|
| v1.0.0           | May 2026 | Final  | Internal       |

# Table of Contents

Software Requirements Specification — TravelPort v1.0.0

|          |                                    |          |
|----------|------------------------------------|----------|
| <b>1</b> | <b>Introduction</b>                | <b>3</b> |
| 1.1      | Purpose                            | 3        |
| 1.2      | Scope                              | 3        |
| 1.3      | Definitions & Acronyms             | 3        |
| 1.4      | References                         | 3        |
| <b>2</b> | <b>System Overview</b>             | <b>5</b> |
| 2.1      | Product Perspective                | 5        |
| 2.2      | User Classes                       | 5        |
| 2.3      | Operating Environment              | 5        |
| <b>3</b> | <b>Functional Requirements</b>     | <b>7</b> |
| 3.1      | Authentication Module              | 7        |
| 3.2      | Flight Booking Module              | 7        |
| 3.3      | Hotel Booking Module               | 7        |
| 3.4      | Transport Module                   | 7        |
| 3.5      | Payment & Wallet                   | 7        |
| 3.6      | Admin Panel                        | 7        |
| <b>4</b> | <b>Non-Functional Requirements</b> | <b>9</b> |
| 4.1      | Performance                        | 9        |
| 4.2      | Security                           | 9        |
| 4.3      | Reliability                        | 9        |

|          |                                      |           |
|----------|--------------------------------------|-----------|
| <b>5</b> | <b>Use Cases</b>                     | <b>11</b> |
| 5.1      | Book a Flight                        | 11        |
| 5.2      | Hotel Checkout                       | 11        |
| 5.3      | Wallet Top-up                        | 11        |
| <b>6</b> | <b>Constraints &amp; Assumptions</b> | <b>13</b> |

# 1 Introduction

Purpose, scope, definitions and references

## 1.1 Purpose

This Software Requirements Specification (SRS) describes the functional and non-functional requirements for **TravelPort**, a Goibibo-inspired full-stack travel booking portal. It is intended for developers, QA engineers, and project stakeholders as the authoritative specification for system behaviour.

## 1.2 Scope

TravelPort provides end-to-end travel booking capabilities including flight search and booking, hotel discovery and reservation, bus/train/cab search (deterministic mock), digital wallet, coupon system, SMTP email notifications, PDF invoice generation, and a role-based admin panel.

**900+**

Seed Flights

**60+**

Hotels

**49+**

API Endpoints

## 1.3 Definitions & Acronyms

| TERM    | DEFINITION                                                                     |
|---------|--------------------------------------------------------------------------------|
| JWT     | JSON Web Token — stateless bearer token for API authentication (15-minute TTL) |
| SRS     | Software Requirements Specification — this document                            |
| EF Core | Entity Framework Core — ORM used for .NET database access                      |
| DTO     | Data Transfer Object — contract between API layers                             |
| SMTP    | Simple Mail Transfer Protocol — used for transactional email via Office365     |
| BCrypt  | Password hashing algorithm (cost factor 12) used for credential storage        |
| CI/CD   | Continuous Integration / Continuous Deployment via GitHub Actions              |
| REST    | Representational State Transfer — architectural style for the HTTP API         |

## 1.4 References

- **API\_DOCUMENTATION.md** — Full REST API reference
- **DATABASE\_DESIGN.md** — Entity-relationship diagram and schema
- **SECURITY\_GUIDE.md** — Authentication, authorization and security policies


2

System Overview

Product perspective, user classes and operating environment

2.1 Product Perspective

TravelPort is a standalone web application. It uses a React 18 SPA frontend communicating with a .NET 8 REST API backed by SQL Server. All data flows through the API gateway; no direct DB access from the client.



2.2 User Classes

| ROLE  | DESCRIPTION                                                                                             | ACCESS LEVEL       |
|-------|---------------------------------------------------------------------------------------------------------|--------------------|
| Guest | Unauthenticated visitor; can search flights, hotels, buses, trains, cabs and validate coupons           | Read-only search   |
| User  | Registered traveller; can book, pay, cancel, download invoices and manage wallet                        | Full self-service  |
| Admin | System operator; can view analytics, manage users (block/unblock), manage all bookings and CRUD coupons | Full system access |

## 2.3 Operating Environment

### DEVELOPMENT

#### Windows / macOS / Linux

Node 20+ · .NET 8 SDK · SQL Server Express

### PRODUCTION (DOCKER)

#### Any Docker host

docker-compose · SQL Server 2022 container · Nginx  
SPA+proxy

### BROWSERS

#### Chrome 90+ · Firefox 88+ · Safari 14+

Mobile Chrome/Safari supported

### CI/CD

#### GitHub Actions

ghcr.io container registry · SSH deploy

## 3

# Functional Requirements

Detailed behaviour for each module

## 3.1 Authentication Module

| ID         | REQUIREMENT                                                                               | PRIORITY |
|------------|-------------------------------------------------------------------------------------------|----------|
| FR-AUTH-01 | System shall allow new users to register with email, password and full name               | High     |
| FR-AUTH-02 | System shall issue a JWT access token (15 min TTL) and refresh token (7 day TTL) on login | High     |
| FR-AUTH-03 | System shall auto-rotate refresh tokens; old token revoked after use                      | High     |
| FR-AUTH-04 | System shall support forgot-password flow: time-limited reset link via email (1 hour TTL) | High     |
| FR-AUTH-05 | Passwords must be hashed with BCrypt cost factor 12 before storage                        | High     |
| FR-AUTH-06 | Admin role must be enforced via JWT claims on all /admin/* routes                         | High     |

## 3.2 Flight Booking Module

| ID        | REQUIREMENT                                                                                 | PRIORITY |
|-----------|---------------------------------------------------------------------------------------------|----------|
| FR-FLT-01 | System shall search flights by origin, destination, date, passengers and class; cache 5 min | High     |
| FR-FLT-02 | Search results shall be filterable by airline, stops, departure time, and price range       | High     |
| FR-FLT-03 | System shall display fare families (Economy/Premium Economy/Business) with distinct pricing | High     |
| FR-FLT-04 | System shall collect per-traveller name, age, gender and ID type before booking             | High     |
| FR-FLT-05 | Booking shall atomically deduct wallet (if used) and decrement available seats              | High     |



| ID        | REQUIREMENT                                                                  | PRIORITY |
|-----------|------------------------------------------------------------------------------|----------|
| FR-FLT-06 | System shall apply validated coupons and reduce FinalAmount accordingly      | Medium   |
| FR-FLT-07 | System shall send booking-confirmed email with PDF e-ticket attached         | High     |
| FR-FLT-08 | System shall allow cancellation with wallet refund for eligible bookings     | High     |
| FR-FLT-09 | BookingExpiryWorker shall auto-cancel Pending bookings older than 30 minutes | Medium   |

### 3.3 Hotel Booking Module

| ID        | REQUIREMENT                                                                                       | PRIORITY |
|-----------|---------------------------------------------------------------------------------------------------|----------|
| FR-HTL-01 | System shall search hotels by city, check-in/out, guests, star rating and sort order; cache 5 min | High     |
| FR-HTL-02 | Hotel results shall support filter by star rating, price range, and amenities                     | High     |
| FR-HTL-03 | Booking shall capture guest name, email and phone number                                          | High     |
| FR-HTL-04 | System shall generate hotel invoice PDF with stay dates, room details, GST breakdown              | High     |
| FR-HTL-05 | Booking references shall use HT2026XXXXXX prefix format                                           | Low      |

### 3.4 Transport Module (Bus / Train / Cab)

Bus, Train and Cab search returns deterministic mock data — no database persistence. Results are consistent per route (same operator, pricing, schedule) across calls.

#### **i** Mock Data Note

Bus (14 operators, 10–22 results/route), Train (39 named trains, 5 classes, 6–15 results/route) and Cab (Ola/Uber/Meru/Zoom, distance-based pricing) are implemented as in-memory search providers. Booking endpoints for these modes are a planned future feature.

### 3.5 Payment & Wallet

| ID        | REQUIREMENT                                                                                             | PRIORITY |
|-----------|---------------------------------------------------------------------------------------------------------|----------|
| FR-PAY-01 | System shall integrate Razorpay checkout; falls back to mock payment in dev mode                        | High     |
| FR-PAY-02 | Each user shall have exactly one wallet, created on registration                                        | High     |
| FR-PAY-03 | Wallet top-up maximum is ₹1,00,000 per transaction                                                      | High     |
| FR-PAY-04 | Wallet deduction and booking creation shall be committed atomically (single UoW)                        | High     |
| FR-PAY-05 | WalletTransaction shall record every credit/debit with description and reference ID                     | High     |
| FR-PAY-06 | System shall support 11 coupons (flight-specific and hotel-specific variants)                           | Medium   |
| FR-PAY-07 | User may save credit/debit cards (last 4 digits only); one card may be set as default                   | High     |
| FR-PAY-08 | At booking time, user selects Wallet, Saved Card, or New Card as payment method                         | High     |
| FR-PAY-09 | Payment page shall support Card (live preview), UPI (QR + timer), Net Banking (bank picker + timer)     | High     |
| FR-PAY-10 | Cancellation shall atomically credit 90% of final amount to wallet and persist immediately              | High     |
| FR-PAY-11 | Booking confirmation email shall be sent to the contact email entered at booking, not the account email | Medium   |

## 3.6 Admin Panel

- **Dashboard:** Monthly revenue chart, bookings by type, bookings by status
- **Users:** Paginated user list with block/unblock action
- **Bookings:** All bookings with status filter; manual cancellation
- **Coupons:** Full CRUD — create, edit, toggle active, delete coupons
- **Analytics:** `GET /admin/analytics` — real SQL aggregations (not mocked)

## 4

## Non-Functional Requirements

Performance, security, reliability and usability

### Performance

Flight/hotel search responds in < 500 ms (cache hit < 50 ms). API supports 100 concurrent users on a single 2-core server.

### Security

JWT (15 min) + Refresh Tokens (7 days). BCrypt cost 12. Secrets in env vars only. HTTPS enforced in production. SQL injection prevention via EF Core parameterization.

### Reliability

Background workers (BookingExpiryWorker, RefreshTokenCleanupWorker) recover gracefully on shutdown. DataSeeder is idempotent — existing data preserved on restart.

### Usability

Goibibo-style UI with skeleton loaders, responsive layout (lg breakpoint), accessible form controls and keyboard navigation. Mobile filter drawer planned (Phase 9).

## 5

## Key Use Cases

Primary user journeys through the system

### UC-01: Book a Flight

## 1

#### Search

User enters origin, destination, date and passenger count on the home page

## 2

#### Browse

Results load with airline filters, stop filters, sort tabs (Cheapest/Fastest/Earliest)

## 3

#### Select Fare

User clicks VIEW FARES; fare-family popup shows Economy / Premium Economy / Business

## 4

#### Traveller Details

User fills per-traveller name, age, gender and ID number



5

### **Apply Coupon**

Optional coupon code reduces FinalAmount; discount displayed in summary

6

### **Pay**

Razorpay checkout (or wallet deduction); booking confirmed atomically

7

### **Confirmation**

Email with PDF e-ticket sent; booking appears in My Bookings with FL prefix