



API REFERENCE

TravelPort

Complete REST API Documentation — 53+ Endpoints

BASE URL (DEV)	BASE URL (DOCKER)	AUTH	FORMAT
<code>http://localhost:5000</code>	<code>http://localhost/api</code>	Bearer JWT	JSON · UTF-8



Global API Conventions

Response wrapper, error format and authentication

Response Wrapper

All endpoints wrap their response in `ApiResponse<T>`:

```
// Success
{
  "success": true,
  "data": { /* typed payload */ },
  "message": "Operation completed",
  "statusCode": 200
}

// Error
{
  "success": false,
  "data": null,
  "message": "Validation failed",
  "errors": ["Email is required", "Password too short"],
  "statusCode": 400
}
```

Authentication

Protected endpoints require an `Authorization: Bearer {token}` header. Tokens expire in 15 minutes. Use `POST /auth/refresh` to obtain a new access token.

i Swagger UI

Interactive API explorer: `http://localhost:5000/swagger` (dev) · `http://localhost/api/swagger` (Docker).
Click "Authorize" and enter `Bearer {your-token}` to test protected endpoints.

HTTP Status Codes

CODE	MEANING
200 OK	Success
201 Created	Resource created

CODE	MEANING
401 Unauthorized	Missing or expired JWT
403 Forbidden	Authenticated but insufficient role (Admin required)
404 Not Found	Resource does not exist
409 Conflict	Duplicate resource (e.g. email already registered)
500 Internal Server Error	Unhandled server error — check API logs

1

Authentication

5 endpoints

POST

/api/v1/auth/register

Public

Register new user account

REQUEST BODY / QUERY

{ email, password, fullName }

RESPONSE DATA

{ token, refreshToken, user }

POST

/api/v1/auth/login

Public

Login and obtain JWT tokens

REQUEST BODY / QUERY

{ email, password }

RESPONSE DATA

{ token, refreshToken, user }

POST

/api/v1/auth/refresh

Public

Exchange refresh token for new access token

REQUEST BODY / QUERY

{ refreshToken }

RESPONSE DATA

{ token, refreshToken }

POST

/api/v1/auth/forgot-password

Public

Send password reset email link

REQUEST BODY / QUERY

{ email }

RESPONSE DATA

{ message }

POST

/api/v1/auth/reset-password

Public

Reset password using token from email

REQUEST BODY / QUERY

{ token, newPassword }

RESPONSE DATA

{ message }

2

Flights

2 endpoints

GET

/api/v1/flights/search

Public

Search available flights

REQUEST BODY / QUERY

```
Query: origin, destination, date, passengers,
class
```

RESPONSE DATA

```
{ flights[] }
```

POST

/api/v1/flights/book

Auth Required

Book a flight

REQUEST BODY / QUERY

```
{ flightId, passengers, fareClass,
couponCode?, useWallet, travellers[] }
```

RESPONSE DATA

```
{ booking }
```

3

Hotels

2 endpoints

GET

/api/v1/hotels/search

Public

Search hotels by city and dates

REQUEST BODY / QUERY

```
Query: city, checkIn, checkOut, guests,
minStars, sortBy
```

RESPONSE DATA

```
{ hotels[] }
```

POST

/api/v1/hotels/book

Auth Required

Book a hotel room

REQUEST BODY / QUERY

```
{ hotelId, roomTypeId, checkIn, checkOut,
guests, couponCode?, useWallet, guestName,
guestEmail, guestPhone }
```

RESPONSE DATA

```
{ booking }
```

4

Transport (Search Only)

3 endpoints

GET

/api/v1/buses/search

Public

Search bus routes (deterministic mock)

REQUEST BODY / QUERY

Query: origin, destination, date, passengers

RESPONSE DATA

{ buses[] }

GET

/api/v1/trains/search

Public

Search train routes (deterministic mock)

REQUEST BODY / QUERY

Query: origin, destination, date, passengers,
class

RESPONSE DATA

{ trains[] }

GET

/api/v1/cabs/search

Public

Search cab options (deterministic mock)

REQUEST BODY / QUERY

Query: pickup, dropoff, date

RESPONSE DATA

{ cabs[] }

5

Bookings

4 endpoints

GET

/api/v1/bookings

Auth Required

Get all bookings for authenticated user (paginated)

REQUEST BODY / QUERY

Query: page, pageSize

RESPONSE DATA

{ bookings[], total }

GET

/api/v1/bookings/{id}

Auth Required

Get a single booking by ID

REQUEST BODY / QUERY

–

RESPONSE DATA

{ booking }

POST

/api/v1/bookings/{id}/cancel

Auth Required

Cancel a booking and refund wallet

REQUEST BODY / QUERY

–

RESPONSE DATA

{ booking }

GET

/api/v1/bookings/{id}/invoice

Auth Required

Download PDF invoice / e-ticket

REQUEST BODY / QUERY

–

RESPONSE DATA

application/pdf

6

Payments

2 endpoints

POST

`/api/v1/payments/initiate` Auth Required

Create Razorpay order for booking

REQUEST BODY / QUERY

`{ bookingId }`

RESPONSE DATA

`{ orderId, amount, currency }`

POST

`/api/v1/payments/verify` Auth Required

Verify Razorpay payment signature

REQUEST BODY / QUERY

`{ orderId, paymentId, signature }`

RESPONSE DATA

`{ success }`

7

Users

8 endpoints

GET

/api/v1/users/profile

Auth Required

Get authenticated user profile

REQUEST BODY / QUERY

–

RESPONSE DATA

{ user }

PUT

/api/v1/users/profile

Auth Required

Update user profile

REQUEST BODY / QUERY

{ fullName, phone }

RESPONSE DATA

{ user }

GET

/api/v1/users/wallet

Auth Required

Get wallet balance and recent transactions

REQUEST BODY / QUERY

–

RESPONSE DATA

{ balance, recentTransactions[] }

POST

/api/v1/users/wallet/topup

Auth Required

Add funds to wallet (max ₹1,00,000)

REQUEST BODY / QUERY

{ amount }

RESPONSE DATA

{ wallet }

GET

/api/v1/users/cards

Auth Required

List saved payment cards (last 4 digits only)

REQUEST BODY / QUERY

–

RESPONSE DATA

{ cards[] }

POST

/api/v1/users/cards

Auth Required

Save a new card (stores last 4 digits only)

```
{ cardHolderName, cardNumber, expiryMonth,
expiryYear, cardType, nickName?, setAsDefault?
}
```

```
{ card }
```

DELETE /api/v1/users/cards/{id}

 Auth Required

Remove a saved card

REQUEST BODY / QUERY

–

RESPONSE DATA

```
{ success }
```

PUT /api/v1/users/cards/{id}/default

 Auth Required

Set a card as the default payment card

REQUEST BODY / QUERY

–

RESPONSE DATA

```
{ card }
```

8

Coupons

1 endpoint

POST

/api/v1/coupons/validate

Public

Validate a coupon code and get discount

REQUEST BODY / QUERY

```
{ code, orderAmount, couponType }
```

RESPONSE DATA

```
{ discount, finalAmount }
```

9

Admin (Admin Role Required)

9 endpoints

GET /api/v1/admin/dashboard

Auth Required

Get dashboard stats (revenue, users, bookings)

REQUEST BODY / QUERY

—

RESPONSE DATA

```
{ stats }
```

GET /api/v1/admin/analytics

Auth Required

Get monthly revenue + bookings-by-type charts

REQUEST BODY / QUERY

—

RESPONSE DATA

```
{ analytics }
```

GET /api/v1/admin/users

Auth Required

Paginated user list

REQUEST BODY / QUERY

Query: page, search

RESPONSE DATA

```
{ users[], total }
```

POST /api/v1/admin/users/{id}/block

Auth Required

Block or unblock a user account

REQUEST BODY / QUERY

```
{ block: boolean }
```

RESPONSE DATA

```
{ user }
```

GET /api/v1/admin/bookings

Auth Required

All bookings with status filter

REQUEST BODY / QUERY

Query: status, page

RESPONSE DATA

```
{ bookings[], total }
```

GET /api/v1/admin/coupons

Auth Required

List all coupons

—

{ coupons[] }

POST

/api/v1/admin/coupons

 Auth Required

Create a new coupon

REQUEST BODY / QUERY

```
{ code, discountType, discountValue,
  minOrderValue, couponType }
```

RESPONSE DATA

```
{ coupon }
```

PUT

/api/v1/admin/coupons/{id}

 Auth Required

Update an existing coupon

REQUEST BODY / QUERY

```
{ ...coupon fields }
```

RESPONSE DATA

```
{ coupon }
```

DELETE

/api/v1/admin/coupons/{id}

 Auth Required

Delete a coupon

REQUEST BODY / QUERY

—

RESPONSE DATA

```
{ success }
```