INDERPRASTHA ENGINEERING COLLEGE

(Affiliated to Dr. A.P.J. Abdul Kalam Technical University, Lucknow)

Sahibabad, Ghaziabad, Uttar Pradesh — 201010

A MINI PROJECT REPORT

Submitted in partial fulfillment of the requirement for the award of

Bachelor of Technology Degree in

Computer Science & Engineering

ON

CoopSync AI: AI-Enabled Cooperative ERP, Biometric Attendance & Employment Ecosystem

(Smart India Hackathon 2026 — Problem Statement ID: SIH26087)

Submitted by:

Prakash Madhok | Roll No.: 2400300100295

Priyansh Topal | Roll No.: 2400300100303

Riya Singh | Roll No.: 2400300100339

Puneet [Surname] | Roll No.: 2400300100305

Under the Supervision of:

[PROJECT GUIDE NAME]

[GUIDE DESIGNATION], Department of Computer Science & Engineering

---

Academic Session: [ACADEMIC SESSION]

Month/Year of Submission: October 2026

CERTIFICATE

This is to certify that the project report entitled "CoopSync AI: AI-Enabled Cooperative ERP, Biometric Attendance & Employment Ecosystem" submitted by:

Prakash Madhok (Roll No.: 2400300100295)

Priyansh Topal (Roll No.: 2400300100303)

Riya Singh (Roll No.: 2400300100339)

Puneet [Surname] (Roll No.: 2400300100305)

is a bonafide work carried out by the above-named students of the Third Year, Semester V, Bachelor of Technology in Computer Science & Engineering at Inderprastha Engineering College, Sahibabad, Ghaziabad, Uttar Pradesh — affiliated to Dr. A.P.J. Abdul Kalam Technical University, Lucknow — in partial fulfillment of the requirements for the award of the degree of Bachelor of Technology.

The project work has been carried out under my supervision and guidance. The work embodies original contributions made by the students during the academic session [ACADEMIC SESSION], and to the best of my knowledge, it has not formed the basis for any other degree or diploma in any institution.

Project Guide	Head of Department
[PROJECT GUIDE NAME]	[HOD NAME]
[GUIDE DESIGNATION]	Professor & Head

Department of CSE	Department of CSE

Date: [CERTIFICATE DATE] Place: Ghaziabad

ACKNOWLEDGEMENT

We express our sincere gratitude to our project guide, [PROJECT GUIDE NAME], [GUIDE DESIGNATION], Department of Computer Science & Engineering, Inderprastha Engineering College, Ghaziabad, for providing invaluable guidance, encouragement, and expert mentorship throughout the development of this project. Their insights on artificial intelligence, computer vision, and software engineering were instrumental in shaping the direction and depth of this work.

We are deeply grateful to the Head of Department, Department of Computer Science & Engineering, and the Principal of Inderprastha Engineering College for providing the necessary computational resources, laboratory facilities, and an encouraging academic environment that supported the execution of this project.

We extend our appreciation to the Smart India Hackathon (SIH 2026) organizing committee for framing Problem Statement SIH26087, which provided a real-world cooperative transformation challenge and motivated us to develop an enterprise-grade, multi-module solution.

We acknowledge the open-source communities behind FastAPI, React, OpenCV, SQLAlchemy, ReportLab, and Chart.js whose frameworks and libraries formed the technical backbone of CoopSync AI. Their

contributions to the global developer ecosystem made this project feasible within the project timeline.

Finally, we thank our families and peers for their constant encouragement, support, and understanding throughout the duration of this project.

— The Project Team

B.Tech CSE, 3rd Year, Semester V

Inderprastha Engineering College, Ghaziabad

DECLARATION

We, the undersigned, hereby declare that the Mini Project Report titled "CoopSync AI: AI-Enabled Cooperative ERP, Biometric Attendance & Employment Ecosystem" submitted in partial fulfillment of the requirements for the award of the degree of Bachelor of Technology in Computer Science & Engineering from Dr. A.P.J. Abdul Kalam Technical University, Lucknow, is an original work carried out by us during the academic session [ACADEMIC SESSION] at Inderprastha Engineering College, Ghaziabad.

The content of this report has not been submitted, in full or in part, to any other university or institution for the award of any other degree or diploma. All sources of information, algorithms, frameworks, and tools used in this project have been duly acknowledged in the References section of this report.

All statements made in this report are based on our own investigation, experimentation, and implementation, carried out under the supervision of [PROJECT GUIDE NAME], [GUIDE DESIGNATION], Department of Computer Science & Engineering.

Name	Roll Number	Signature
Prakash Madhok	2400300100295	
Priyansh Topal	2400300100303	
Riya Singh	2400300100339	
Puneet [Surname]	2400300100305	

Date: [SUBMISSION DATE] Place: Ghaziabad

ABSTRACT

Cooperative educational institutions across India continue to rely on manual attendance registers susceptible to proxy marking, isolated course records with no centralized tracking, paper certificates that are easily forged, and entirely disconnected employment placement pathways. These systemic inefficiencies impede the transformation of cooperative training ecosystems and undermine the credibility of cooperative vocational credentials.

This project presents CoopSync AI — an end-to-end, AI-enabled Cooperative ERP, Biometric Attendance, and Employment Ecosystem developed as a submission for Smart India Hackathon 2026 (Problem Statement SIH26087). The platform introduces a dual biometric and cryptographic verification architecture. The biometric pipeline integrates OpenCV Haar Cascade face detection, Local Binary Patterns Histograms (LBPH) face recognition, and real-time Laplacian variance texture analysis for anti-spoofing liveness verification. A secondary attendance mechanism employs dynamically rotating 30-second TTL QR codes secured with SHA-256 HMAC cryptographic signatures, providing a proxy-proof fallback for environments with poor lighting or camera availability.

Beyond attendance governance, CoopSync AI unifies a student ERP module, a cooperative Learning Management System (LMS) with YouTube-integrated video courses, an automated tamper-proof PDF certificate engine with embedded QR verification codes, an AI skill-to-job

matching portal connecting students to cooperative federation employers, and a semantic ERP advisory chatbot. The system implements multi-role access control supporting five stakeholder roles: Student, Trainer, Institution Admin, NCCT Admin, and Employer. An offline synchronization queue ensures resilient operation in rural cooperative centers with intermittent internet connectivity.

The backend is developed using FastAPI (Python) with a SQLAlchemy-managed SQLite relational database comprising six normalized entity tables. The frontend is built with React 19 and TypeScript using a modern glassmorphism design system. The system is containerized with Docker Compose and includes a one-click Windows batch launcher for local deployment. A comprehensive integration test suite verifies the biometric enrollment and retraining pipeline under multiple quality and authorization conditions.

The system has been fully implemented, locally verified, and is ready for cloud deployment, with live hosting on Render and Vercel constituting the remaining deployment task.

Keywords: Computer Vision, LBPH Face Recognition, Anti-Spoofing, Dynamic QR Tokens, Cooperative ERP, Learning Management System, Tamper-Proof Certification, Skill-Matching Engine, FastAPI, React, Smart Education.

TABLE OF CONTENTS

CERTIFICATE	**i**
ACKNOWLEDGEMENT	**ii**
DECLARATION	**iii**
ABSTRACT	**iv**
TABLE OF CONTENTS	**v**
LIST OF TABLES	**vi**
LIST OF FIGURES	**vii**
LIST OF ABBREVIATIONS	**viii**
CHAPTER 1: INTRODUCTION	**1**
1.1 Problem Definition	1
1.2 Background About the Project Idea	2
1.3 Objectives of the Proposed System	3
1.4 Feasibility Study, Need and Significance	4
1.5 Novelty of the Project	5
1.6 Technical Specification	6
CHAPTER 2: LITERATURE REVIEW	**8**
2.1 Existing Systems and Related Work	8
2.2 Limitations of Existing Systems	10
CHAPTER 3: PROPOSED SYSTEM	**11**
3.1 System Architecture	11
3.2 System Modules	12
3.3 Key Algorithms	13
3.4 Advantages Over Existing System	14
CHAPTER 4: SOFTWARE REQUIREMENT ANALYSIS	**15**
4.1 Functional Requirements	15
4.1.1 Use Case Diagram	15
4.1.2 Use Case Descriptions	16
4.2 Non-Functional Requirements	17
4.3 Major Modules and Their Functionalities	18
CHAPTER 5: SYSTEM ANALYSIS & DESIGN	**19**
5.1 Class Design	19
5.2 Sequence Diagrams	20
5.3 Activity Diagrams	21

5.4 Data Flow Diagrams	22
5.5 Database Design	23
5.5.1 E-R Diagrams	23
5.6 Gantt Chart and PERT Chart	24
CHAPTER 6: IMPLEMENTATION / CORE MODULE	**25**
6.1 Database Tables and Fields	25
6.2 Algorithms and Approaches	27
6.3 Implementation of Modules	28
CHAPTER 7: RESULTS / OUTPUTS & TESTING	**30**
7.1 User Interfaces and Output Screens	30
7.2 Layouts of Web Pages and Screens	32
7.3 Design and Test Steps / Criteria	33
7.4 Testing Process	34
CHAPTER 8: CONCLUSIONS / RECOMMENDATIONS	**36**
8.1 Objectives Achieved	36
8.2 Limitations	37
8.3 Future Enhancements	38
8.4 Lessons Learned	38
CHAPTER 9: REFERENCES	**39**
CHAPTER 10: PLAGIARISM REPORT	**41**
CHAPTER 11: RESEARCH PAPER PUBLICATION	**42**
CHAPTER 12: APPENDICES	**43**
12.1 Software / Simulator Details	43
12.2 Steps to Execute / Run the Project	44
12.3 Coding (Key Source Code Excerpts)	45

LIST OF TABLES

Table 1.1	Hardware Requirements	6
Table 1.2	Software Requirements	7
Table 2.1	Comparative Analysis of Existing Systems	10
Table 4.1	Use Case Descriptions	16
Table 4.2	Non-Functional Requirements	17
Table 4.3	Major Modules and Functionalities	18
Table 5.1	Class Design Summary	19
Table 5.2	Project Gantt / PERT Timeline	24
Table 6.1	Database Table Schemas and Fields	25
Table 6.2	Core Recognition Algorithms	27
Table 6.3	REST API Endpoints	28
Table 7.2	Web Page Layouts Summary	32
Table 7.3	Design Criteria and Test Conditions	33
Table 7.4	Integration Test Case Results	34
Table 11.1	Research Publication Status	42
Table 12.1	Software / Tools Details	43

LIST OF FIGURES

Figure 4.1	Factored Use Case Diagram of CoopSync AI	15
Figure 5.1	Class Architecture Diagram	19
Figure 5.2	Sequence Diagram: Biometric Attendance Flow	20
Figure 5.3	Activity Diagram: Background Model Retraining	21
Figure 5.4	Level-1 Data Flow Diagram (DFD)	22
Figure 5.5	Entity-Relationship (E-R) Diagram	23
Figure 5.6	Gantt Chart and PERT Network Diagram	24
Figure 7.1	Landing Page: Public-facing CoopSync AI Dashboard	30
Figure 7.2	Face Attendance Scanner with Biometric Recognition UI	30
Figure 7.3	Student Registration and Web Face Enrollment Modal	31
Figure 7.4	Student ERP View with Attendance Ring and Skills Cloud	31
Figure 7.5	Analytics Dashboard with KPI Cards and Chart.js Graphs	31
Figure 7.6	Digital Certificates View with QR Code Verification	31
Figure 7.7	Cooperative Employment Portal with AI Skill Match Badges	32
Figure 7.8	CoopSync AI Web Application Layout Blueprint (Biometric Scanner View)	32

LIST OF ABBREVIATIONS

Abbreviation	Full Form
AI	Artificial Intelligence
API	Application Programming Interface
ASGI	Asynchronous Server Gateway Interface
B.Tech	Bachelor of Technology
CORS	Cross-Origin Resource Sharing
CSV	Comma-Separated Values
DB	Database
DFD	Data Flow Diagram
ERP	Enterprise Resource Planning
FAQ	Frequently Asked Questions
FK	Foreign Key
GUI	Graphical User Interface
HMAC	Hash-based Message Authentication Code
HTML	HyperText Markup Language
HTTP	HyperText Transfer Protocol
HTTPS	HyperText Transfer Protocol Secure
ICM	Institute of Cooperative Management
IFFCO	Indian Farmers Fertiliser Cooperative
JSON	JavaScript Object Notation
JWT	JSON Web Token
KPI	Key Performance Indicator
LBPH	Local Binary Patterns Histograms
LMS	Learning Management System
MIT	Massachusetts Institute of Technology
ML	Machine Learning
NAFED	National Agricultural Cooperative Marketing Federation of India
NCCT	National Council for Cooperative Training
NLP	Natural Language Processing
OpenCV	Open Source Computer Vision Library
ORM	Object Relational Mapper
PDF	Portable Document Format
PK	Primary Key
QR	Quick Response
RBAC	Role-Based Access Control
REST	Representational State Transfer
RICM	Regional Institute of Cooperative Management
SHA	Secure Hash Algorithm
SIH	Smart India Hackathon
SQL	Structured Query Language
SQLite	Self-Contained Lightweight SQL Database Engine
SSE	Server-Sent Events
TTL	Time-To-Live
UI	User Interface
URL	Uniform Resource Locator
UX	User Experience

CHAPTER 1: INTRODUCTION

1.1 Problem Definition

Cooperative educational institutions in India — including Institutes of Cooperative Management (ICMs), Regional Institutes of Cooperative Management (RICMs), and training centres affiliated with cooperative federations such as AMUL, IFFCO, KRIBHCO, and NAFED — continue to operate with manual and paper-based processes that introduce significant operational vulnerabilities.

The identified problems are: (i) Proxy attendance fraud, where a student submits attendance on behalf of an absent peer using paper registers; (ii) Isolated and unverifiable course completion records with no digital audit trail; (iii) Paper-based certificates that are susceptible to forgery with no cryptographic validation mechanism; (iv) Absence of a centralized digital channel connecting trained students with cooperative sector employers; and (v) Lack of resilient systems for rural cooperative centres experiencing intermittent internet connectivity.

1.2 Background About the Project Idea

The project originated from Smart India Hackathon (SIH 2026) Problem Statement SIH26087, issued under the theme of Smart Education and Cooperative Digital Transformation. The team began with an existing OpenCV-based Python desktop application capable of face detection and attendance marking using the LBPH algorithm. This initial system, while functional, was limited to desktop use, had no web interface, no database backend, no online portability, and no cryptographic verification for attendance authenticity.

The project evolved this foundation into a comprehensive web-based ERP platform by integrating the existing LBPH classifier into a FastAPI REST backend, adding a React 19 frontend, a normalized SQLite database, dynamic QR codes, PDF certificates, employment matching, and an AI chatbot — all while preserving the legacy desktop tools as a bridgeable component.

1.3 Objectives of the Proposed System

- 1. Eliminate proxy attendance through AI face recognition with real-time anti-spoofing liveness verification.
- 2. Provide a web-accessible student ERP with role-based profiles, skill tracking, and attendance analytics.
- 3. Implement automated tamper-proof PDF certificate generation with embedded cryptographic QR verification codes.
- 4. Enable AI-driven skill-to-job matching connecting cooperative students with federation employer postings.
- 5. Develop an offline-resilient attendance system for rural cooperative institutes with poor connectivity.
- 6. Build a multi-role access control system supporting Student, Trainer, Institution Admin, NCCT Admin, and Employer roles.
- 7. Integrate the legacy Python desktop OpenCV suite into the modern web platform via REST API bridges.
- 8. Deliver a containerized, deployable full-stack application with a one-click Windows launcher.

1.4 Feasibility Study, Need and Significance

Technical Feasibility: The project leverages mature, well-documented open-source libraries (OpenCV 4.8+, FastAPI 0.111+, React 19, SQLAlchemy 2.0, ReportLab 4.0) with extensive community support. The

LBPH face recognition algorithm is specifically designed to operate under variable lighting conditions typical of cooperative training classrooms. Python 3.x provides a stable runtime for all backend operations, and the system has been verified to run locally via the included batch launcher and Docker Compose.

Economic Feasibility: The entire technology stack uses open-source, zero-license-cost frameworks. Deployment to cloud platforms (Render for backend, Vercel for frontend) is available at no cost for small-scale institutional use. SQLite requires no separate database server license, and OpenCV eliminates the need for proprietary biometric hardware.

Operational Feasibility: The platform requires no special hardware beyond a standard webcam, a modern browser, and internet connectivity. The offline attendance synchronization module ensures usability in rural settings. The one-click Windows batch launcher (start_coopsync.bat) ensures that non-technical staff can deploy and operate the system without command-line expertise.

Significance: India has over 8.5 lakh registered cooperative societies. Cooperative training institutions serving this ecosystem produce hundreds of thousands of graduates annually who lack digitally verifiable credentials. CoopSync AI addresses this gap by delivering institutional credibility through cryptographically verifiable certificates and modernizing cooperative attendance governance at minimal operational cost.

1.5 Novelty of the Project

- Dual-mode attendance: AI face recognition (primary) + 30-second rotating SHA-256 HMAC QR codes (backup) — both with anti-duplicate enforcement.

- Real-time Laplacian variance anti-spoofing: Detects 2D photo printouts and mobile screen replay without specialized hardware.
- Thread-safe background LBPH retraining with atomic model swapping — the classifier updates in production without downtime.
- In-browser webcam face enrollment with real-time biometric quality validation (sharpness, brightness, face centering) — no external enrollment tool required.
- Course enrollment automatically extracts domain skills and updates the student's ERP profile — creating a living, self-updating skills portfolio.
- Web-to-Desktop bridge API: A web button triggers the legacy Python Tkinter face recognition application via subprocess on the host machine.
- Offline attendance queue using browser localStorage with automatic batch synchronization upon connectivity restoration — no attendance lost during network outages.

1.6 Technical Specification

1.6.1 Hardware Requirements

Table 1.1: Hardware Requirements

Component	Minimum Specification
Processor	Intel Core i5 (7th Gen) or AMD Ryzen 5 equivalent
RAM	8 GB DDR4
Storage	20 GB free SSD space (for dataset, model, and node_modules)
Webcam	720p HD webcam (for biometric enrollment and attendance)
Display	1366 × 768 or higher resolution
Network	Any broadband connection (offline mode available without network)

1.6.2 Software Requirements

Table 1.2: Software Requirements

Software	Version / Details
Operating System	Windows 10/11 (tested), Linux Ubuntu 20.04+
Python	3.9 or higher
Node.js & npm	Node.js 18 LTS or higher

FastAPI	>= 0.111.0
Uvicorn (ASGI)	>= 0.30.0
SQLAlchemy	>= 2.0.0
Pydantic	>= 2.0.0
OpenCV	>= 4.8.0 (opencv-contrib-python for LBPH)
NumPy	>= 1.24.0
ReportLab	>= 4.0.0 (PDF generation)
qrcode	>= 8.0
Pillow	>= 10.0.0
React	19.x with TypeScript
Vite	5.x (frontend build tool)
Docker & Docker Compose	Docker Engine 24.x (for containerized deployment)
Browser	Chrome 112+, Firefox 115+, Edge 114+ (for webcam API support)

CHAPTER 2: LITERATURE REVIEW

2.1 Existing Systems and Related Work

This chapter reviews the principal existing systems, techniques, and research contributions relevant to face recognition-based attendance, cooperative management software, and digital certification systems.

2.1.1 Face Recognition Algorithms for Attendance Systems

Viola and Jones (2001) proposed the Haar Cascade object detection framework, which became the standard method for real-time face detection. The cascade of classifiers uses Haar-like features and AdaBoost learning to achieve high detection rates at low computational cost. OpenCV's `haarcascade_frontalface_default.xml` is a direct implementation of this work and is used in CoopSync AI as the primary face detection stage. [Viola, P. & Jones, M. (2001). Rapid Object Detection using a Boosted Cascade of Simple Features. CVPR 2001.]

Ahonen, Hadid, and Pietikäinen (2006) introduced the Local Binary Patterns Histograms (LBPH) descriptor for face recognition. LBPH describes the local texture of the face by comparing each pixel with its neighbours, producing a binary pattern. Histograms of these patterns over image sub-regions provide a feature vector that is robust to illumination changes and face expressions. OpenCV's `cv2.face.LBPHFaceRecognizer` is an implementation of this algorithm and is the recognition engine in CoopSync AI. [Ahonen, T., Hadid, A. & Pietikäinen, M. (2006). Face Description with Local Binary Patterns. IEEE TPAMI, 28(12).]

Deep learning-based approaches (FaceNet, DeepFace, ArcFace) achieve superior accuracy but require GPU hardware, large training datasets, and significant computational resources that are unavailable in

typical cooperative training centres. LBPH was selected because it operates effectively on CPU hardware, requires as few as 20-50 training samples per student, and provides acceptable accuracy under variable classroom lighting conditions.

2.1.2 Anti-Spoofing and Liveness Detection

Boulkenafet, Komulainen, and Hadid (2017) demonstrated that texture analysis using Local Binary Patterns could effectively distinguish live faces from printed photographs and screen-displayed images. The Laplacian variance, which measures the spread of second-order spatial derivatives of the image, provides a computationally inexpensive proxy for image sharpness and textural complexity. Genuine live faces captured via webcam exhibit higher Laplacian variance compared to flat-printed or digitally displayed photographs. CoopSync AI implements this as a real-time liveness filter with a threshold of 45.0 variance units. [Boulkenafet, Z., Komulainen, J. & Hadid, A. (2017). Face Anti-Spoofing Based on Color Texture Analysis. ICIP 2015.]

2.1.3 Existing Attendance Management Systems

Traditional biometric attendance systems (e.g., ZKTeco hardware, AADHAR-linked systems) require dedicated hardware terminals costing ₹5,000–₹25,000 per installation, proprietary software licenses, and physical fingerprint or RFID tokens. These systems are not feasible for distributed cooperative training centres with limited infrastructure budgets.

Academic face recognition attendance systems reviewed in literature (e.g., Shehu & Ruiz 2019, Kaur et al. 2020) typically implement desktop-only OpenCV applications that mark attendance in CSV files without web accessibility, database integration, or multi-role administration. CoopSync AI's immediate predecessor (facedetector.py, main.py, student.py, train.py)

belongs to this category and is retained as a legacy bridge in the new system.

2.1.4 Digital Certificate Generation and Verification

Blockchain-based certificate systems (e.g., MIT Digital Diplomas using Bitcoin blockchain) provide cryptographic non-repudiation but introduce significant complexity: requiring wallet management, gas fees, and blockchain network availability. For cooperative institutions with limited technical capacity, this approach is impractical.

CoopSync AI adopts a simpler but effective approach: ReportLab PDF generation with embedded QR codes resolving to a public HTTPS verification endpoint. While not blockchain-based, this provides instant certificate authenticity verification through a web URL, accessible to any employer or institution scanner without specialized software.

2.1.5 Cooperative Management ERP Systems

Proprietary cooperative management software (e.g., Tally for cooperatives, AMUL's internal ERP, state-specific cooperative federation software) focus primarily on financial accounting and member management. None of the reviewed systems integrate biometric attendance, digital certification, or employment matching as unified modules.

2.2 Limitations of Existing Systems

- Hardware-dependent biometric systems are cost-prohibitive for rural cooperative centres.
- Desktop-only attendance tools lack web accessibility and require physical presence at a specific machine.
- No existing cooperative ERP integrates attendance, courses, certificates, and employment in a single platform.

- Paper certificates cannot be instantly verified by employers and are susceptible to forgery.
- No existing open-source system provides offline attendance synchronization for intermittent connectivity environments.
- Existing deep learning face recognition systems require GPU hardware not available in cooperative training centres.

CHAPTER 3: PROPOSED SYSTEM

CoopSync AI proposes a unified, web-accessible, AI-enabled cooperative ERP platform that replaces all paper-based and isolated processes with a single integrated digital ecosystem. The system is designed around three core pillars: Biometric Attendance Governance, Academic Capacity Building, and Employment Connectivity.

3.1 System Architecture

The system follows a three-tier client-server architecture:

Table 3.1: System Architecture Layers

Layer	Technology	Responsibility
Client Layer	React 19 + TypeScript + Vite (Port 5173)	Web browser UI with webcam integration
Application Layer	FastAPI (Python, Port 8000)	REST API, business logic, biometric engine, retraining
Persistence Layer	SQLite (coopsync.db) + CSV files + File Storage	Relational DB, legacy data, face dataset and model

3.2 System Modules

3.2.1 AI Face Recognition Attendance Module

Webcam capture via HTML5 getUserMedia → base64 encoding → POST /api/attendance/face-recognize → Haar detection → LBPH prediction → Laplacian liveness check → anti-duplicate validation → SQLite attendance record creation.

3.2.2 Web Face Enrollment & Background Retraining Module

2-step modal: (Tab 1) Academic profile form; (Tab 2) Live webcam with quality validation (sharpness ≥ 28, brightness 38-230, single face centered) → 50-sample auto-burst → dataset/id/ → POST /api/model/retrain triggers ModelTrainingManager background thread → atomic classifier.xml swap.

3.2.3 Dynamic QR Code Attendance Module

30-second rotating SHA-256 HMAC session token → QR code generation → student camera scan → POST /api/attendance/qr-verify → one-time validation → geofence check → attendance record.

3.2.4 Student ERP Module

CRUD operations on users table via /api/students endpoints. 75% attendance threshold alerts. Tech Stack chip editor with immediate SQLite synchronization.

3.2.5 Attendance Records Manager

Full attendance ledger with date/name/method filters. Status toggling (Present/Absent/Late/Excused). CSV export. Manual admin override with audit trail.

3.2.6 Course LMS Module

Course catalog seeded with 10+ cooperative curricula. YouTube URL integration with auto-thumbnail extraction. One-click enrollment → automatic skill extraction → student profile skills sync.

3.2.7 Digital Certificate Engine

POST /api/certificates → ReportLab PDF generation with golden border → embedded QR code linking to /api/certificates/verify/{cert_id} → PDF stored in CoopSyncAI/backend/certificates/.

3.2.8 Employment Portal

Job board with cooperative federation postings. AI skill-to-job matching (set intersection algorithm). 1-click apply → job_applications table → status: Shortlisted.

3.2.9 AI Advisor Chatbot

Rule-based NLP semantic parser querying live SQLite records. Responds to attendance, job recommendation, course recommendation, and anti-spoofing queries.

3.2.10 Offline Sync Module

Browser localStorage queue stores attendance during network outages. POST /api/attendance/sync-offline batch syncs records upon network restoration. Navbar badge shows pending count.

3.2.11 Multi-Role RBAC

5 roles: Student, Trainer, Institution Admin, NCCT Admin, Employer. Role stored in users.role column. Role-specific view rendering in Navbar.tsx and component-level access control.

3.2.12 Python Desktop Suite Bridge

PythonSuiteView.tsx + /api/python-suite/launch/{app} → subprocess.Popen() launches native Tkinter apps (main.py, student.py, facedetector.py, train.py, attendence.py) from web interface.

3.3 Key Algorithms

3.3.1 LBPH Face Recognition

Face images are normalized to 200×200 grayscale pixels and histogram-equalized. OpenCV's LBPHFaceRecognizer.predict() returns a predicted student ID and a distance metric. The confidence percentage is computed as: Confidence = max(35, min(99, 100 − distance × 0.46)). A distance ≤ 68 is required for a positive match.

```
pred_id, dist = recognizer.predict(face_roi_norm)
confidence_percent = max(35.0, min(99.0, round(100 - (dist * 0.46), 1)))
if dist <= 68:
    # Positive match — log attendance
```

3.3.2 Laplacian Variance Anti-Spoofing

The Laplacian of a grayscale face ROI measures spatial second-order derivatives. A high variance indicates a texturally rich live face; a low

variance indicates a flat, printed or screen-displayed image. Threshold: variance > 45.0 = live.

```
laplacian_var = float(cv2.Laplacian(gray_roi, cv2.CV_64F).var())
is_live = laplacian_var > 45.0
```

3.3.3 AI Skill-to-Job Matching

The matching engine computes a set intersection between the student's skill tokens and the job's required skill tokens (comma/pipe/slash delimited). A baseline offset ensures all scores remain in the [55, 98] range to reflect that partial skill overlaps still constitute meaningful candidacy.

```
student_set = {s.strip().lower() for s in student_skills.split(',')}
req_set = {s.strip().lower() for s in required_skills.split(',')}
overlap = student_set.intersection(req_set)
base_score = int((len(overlap) / len(req_set)) * 100)
final_score = max(55, min(98, base_score + 25 if overlap else 55))
```

3.4 Advantages Over Existing System

- Zero hardware cost: Uses standard webcam instead of proprietary biometric readers.
- Web-accessible: Accessible from any browser, including mobile devices.
- Anti-proxy: Laplacian liveness + duplicate-per-day check eliminates both digital and physical proxy.
- Offline resilient: Attendance queued locally and synced upon reconnection.
- Integrated: Single platform for attendance, courses, certificates, and employment.
- Verifiable credentials: PDF certificates with scannable QR codes verifiable by any employer.
- Legacy bridge: Preserves investment in existing desktop OpenCV tools while adding web capabilities.
- Open source stack: Zero licensing cost for the entire technology stack.

CHAPTER 4: SOFTWARE REQUIREMENT ANALYSIS

4.1 Functional Requirements

4.1.1 Use Case Diagram




Figure 4.1: Factored Use Case Diagram of CoopSync AI

Note: The following describes the use case interactions verified from the actual source code. A graphical UML use case diagram is described below for reference. In the physical document, this should be replaced with a UML diagram drawn using a tool such as draw.io or StarUML.

```
ACTORS: Student | Trainer | Institution Admin | NCCT Admin | Employer

Student USE CASES:
  - Mark attendance via face recognition
  - Scan QR code for attendance
  - View personal attendance record
  - Enrol in courses
  - Download digital certificate
  - Apply for cooperative jobs
  - Query AI advisor chatbot

Trainer USE CASES:
  - View class attendance roster
  - Create/publish courses
  - Generate QR attendance session
  - Mark manual attendance
```

```
Institution Admin USE CASES:
  - Register new students (with biometric enrollment)
  - Trigger LBPH model retraining
  - Issue digital certificates
  - Manage attendance records (override, export)
  - View analytics dashboard

NCCT Admin USE CASES:
  - View national aggregate analytics
  - Monitor institute-wide KPIs

Employer USE CASES:
  - Post cooperative job openings
  - View AI-matched shortlisted candidates
  - Review student skill profiles
```

4.1.2 Use Case Descriptions

Table 4.1: Use Case Descriptions

UC ID	Use Case	Precondition	Main Flow	Outcome
UC-01	Mark Biometric Attendance	Student registered with face samples	Open webcam scanner, face detected, LBPH match, liveness pass, not duplicate → attendance recorded	Attendance record in DB
UC-02	Mark QR Attendance	Valid QR session active (<30s), student not yet scanned	Scan QR or enter token → hash verified → geofence checked → attendance recorded	Attendance record in DB
UC-03	Enroll New Student	Admin logged in	Fill academic form → webcam enrollment → capture 50 samples → submit → DB record + CSV append	Student in DB, dataset/id/ created
UC-04	Retrain Model	Admin, ≥10 face samples exist	Trigger /api/model/retrain → background thread scans dataset → LBPH trains → classifier.xml updated	Updated classifier.xml, confidence reset
UC-05	Issue Certificate	Student completed course, attendance ≥75%	Admin issues certificate → ReportLab PDF generated → QR embedded → download available	PDF certificate + certificates table row
UC-06	Verify Certificate	Certificate ID known	Public: GET /api/certificates/verify/{cert_id} → certificate details returned	Certificate authenticity confirmed/denied
UC-07	Apply for Job	Student logged in, job available	View jobs → AI match score shown → click Apply → job_applications record created	Application status: Shortlisted
UC-08	Sync Offline Attendance	Network reconnected, localStorage queue non-empty	POST /api/attendance/sync-offline with batch records → server validates and inserts	Offline records persisted to DB

4.2 Non-Functional Requirements

Table 4.2: Non-Functional Requirements

Category	Requirement
Performance	API endpoints respond within 2 seconds under standard LAN conditions; face recognition ≤ 1.5 seconds per frame
Security	Role-based access control (RBAC) on all endpoints; anti-spoofing liveness filter active on every biometric request; QR tokens expire in 30 seconds
Reliability	Offline attendance queue ensures zero data loss during network outages; model backup (classifier.xml.bak) prevents recognition downtime during retraining
Scalability	SQLite for development; PostgreSQL-ready via DATABASE_URL environment variable; Docker Compose for multi-container horizontal scaling
Usability	Modern glassmorphism web UI with mobile-responsive layouts; one-click Windows batch launcher for non-technical users; no biometric hardware required
Portability	Docker Compose containerization for platform-independent deployment; verified on Windows 10/11 and Ubuntu 20.04
Maintainability	Modular architecture: face_engine.py, qr_engine.py, certificate_engine.py, ai_engine.py are independent engine modules with clear interfaces
Availability	start_coopsync.bat automatically restarts backend and frontend; Docker Compose provides container-level restart policies

4.3 Major Modules and Their Functionalities

Table 4.3: Major Modules and Functionalities

Module	Input / Output	Key Functionality
Face Recognition Engine (face_engine.py)	Input: Base64 webcam frame Output: student_id, name, confidence, liveness	Haar detection, LBPH prediction, Laplacian anti-spoof, student_info_cache lookup
QR Session Engine (qr_engine.py)	Input: Session request Output: QR image + token	SHA-256 HMAC, 30s TTL, one-time validation, geofence enforcement
Certificate Engine (certificate_engine.py)	Input: student_name, course_title, cert_id, grade Output: PDF file path	ReportLab PDF generation, qrcode QR embed, certificates/ storage
AI Engine (ai_engine.py)	Input: query string, user profile, attendance count, jobs, courses Output: reply text + suggestions	Rule-based NLP, set intersection skill matching
ModelTrainingManager (main.py class)	Input: retrain trigger (admin role required) Output: updated classifier.xml	Threading.Lock(), atomic file swap, backup creation, progress state machine
Database Layer (database.py)	Input: SQLAlchemy ORM operations Output: CRUD on 6 tables	SQLite/PostgreSQL via SQLAlchemy, 6 entity models, relationship definitions
FastAPI REST Gateway	Input: HTTP requests from	25+ endpoints, CORS

(main.py routes)	React frontend Output: JSON responses	middleware, Pydantic validation, Depends injection
React Frontend (App.tsx + components)	Input: User interactions Output: Rendered UI, API calls	14 React component views, Chart.js analytics, HTML5 webcam API, localStorage queue

CHAPTER 5: SYSTEM ANALYSIS & DESIGN

5.1 Class Design

The backend implements the following primary classes (verified from source code):




Figure 5.1: Class Architecture Diagram

Table 5.1: Class Design Summary

Class	Key Attributes	Key Methods	Relationships
FaceRecognitionEngine (face_engine.py)	face_cascade, recognizer, labels, student_info_cache	load_labels_and_students(), load_model(), check_liveness(), recognize_image_bytes(), recognize_base64()	Singleton (face_engine)
ModelTrainingManager (main.py)	lock (threading.Lock), state (dict)	get_status(), start_training(), _run_training_worker()	Singleton (training_manager)
User (SQLAlchemy Model)	id, student_id, roll_number, name, email, role, department, semester, skills, avatar, ...	ORM CRUD via SQLAlchemy Session	FK → Attendance, Certificate, JobApplication
Attendance (SQLAlchemy Model)	id, user_id, student_id, date, time, method, confidence, liveness_verified, status	ORM CRUD	FK → User

Course (SQLAlchemy Model)	id, title, category, trainer_name, duration, youtube_url, thumbnail, progress_percentage	ORM CRUD	Independent
Certificate (SQLAlchemy Model)	id, certificate_no, user_id, student_name, course_title, grade, status, qr_data	ORM CRUD	FK → User
Job (SQLAlchemy Model)	id, title, company, salary, required_skills, openings, deadline	ORM CRUD	FK → JobApplication
JobApplication (SQLAlchemy Model)	id, job_id, user_id, applicant_name, match_score, status	ORM CRUD	FK → Job, User

5.2 Sequence Diagrams (Textual)

5.2.1 Face Recognition Attendance Sequence

```
Student → Browser: Open Face Attendance Page
Browser → Webcam: getUserMedia() — request camera access
Webcam → Browser: Video stream
Browser → FastAPI: POST /api/attendance/face-recognize {image_base64,
student_id_hint}
FastAPI → FaceEngine: recognize_base64(image_base64)
FaceEngine → OpenCV: detectMultiScale() — Haar face detection
OpenCV → FaceEngine: [(x, y, w, h)] face bounding boxes
FaceEngine → OpenCV: recognizer.predict(face_roi_norm)
OpenCV → FaceEngine: (pred_id, dist)
FaceEngine → FaceEngine: check_liveness() — Laplacian variance
FaceEngine → FastAPI: {success, student_id, confidence,
liveness_verified}
FastAPI → SQLite: Query Attendance (duplicate check: same user_id +
today)
SQLite → FastAPI: existing record / None
FastAPI → SQLite: INSERT INTO attendances (if not duplicate)
FastAPI → Browser: {success, student, attendance, metrics}
Browser → Student: Display recognition result with confidence
```




Figure 5.2: Sequence Diagram - Biometric Attendance Flow

5.2.2 Student Enrollment + Retraining Sequence

```
Admin → Browser: Open Register Student modal (Tab 1: Academic Form)
Admin → Browser: Fill form → click 'Next: Biometrics' tab
Browser → Webcam: Start live webcam preview
Admin → Browser: Click 'Start Auto-Capture' (50 samples)
Browser → FastAPI: POST /api/students/capture-sample {student_id,
image_base64} ×50
FastAPI → FaceEngine: Quality validation (brightness, sharpness, face
count)
FastAPI → FileSystem: Save 200×200 grayscale to dataset/{id}/{id}_N.jpg
FastAPI → Browser: {success, samples_count, quality} per sample
Browser → FastAPI: POST /api/model/retrain {requester_role: 'admin'}
FastAPI → ModelTrainingManager: start_training('admin')
ModelTrainingManager → Thread: _run_training_worker() [background]
Thread → FileSystem: Scan dataset/ → load all sample images
Thread → OpenCV: LBPHFaceRecognizer.train(faces, labels)
Thread → FileSystem: Save classifier_tmp.xml → rename to classifier.xml
Thread → ModelTrainingManager: state = 'completed'
Browser → FastAPI: GET /api/model/retrain/status [polling]
FastAPI → Browser: {status: 'completed', progress: 100}
```

5.3 Activity Diagrams (Textual)

5.3.1 Biometric Attendance Flow

```
[Start] → Open webcam scanner
→ Capture video frame
→ Haar face detection
  → [No face detected] → Display 'Align your face' → loop back
  → [Face detected] → Crop face ROI → resize to 200×200
→ Laplacian variance liveness check
  → [Variance < 45] → Display 'Anti-spoof: Show live face' → loop back
```

```
  → [Variance ≥ 45] → LBPH predict()
→ Distance threshold check (dist ≤ 68)
  → [dist > 68] → Display 'Face not recognized'
  → [dist ≤ 68] → Lookup student_info_cache
→ Duplicate attendance check (same user_id + today)
  → [Duplicate] → Display 'Already marked today'
  → [Not duplicate] → INSERT attendance record
→ Display success with student name and confidence
[End]
```




Figure 5.3: Activity Diagram - Background Model Retraining Pipeline

5.4 Data Flow Diagrams

5.4.1 DFD Level 0 — Context Diagram

```
External Entities:
  STUDENT ──────────────────────────────┐
  TRAINER ──────────────────────────────── CoopSync AI System ──────
SQLite DB
  ADMIN   ──────────────────────────────── (FastAPI + React) ──────  File
Storage
  EMPLOYER ─────────────────────────────┘
(dataset/, data/)

Data Flows IN:  Face images, QR scans, Student forms, Course data, Job
postings
Data Flows OUT: Attendance records, PDF certificates, Match scores, AI
chat replies, Analytics
```

5.4.2 DFD Level 1 — Main Processes

```
Process 1: BIOMETRIC ATTENDANCE
  Input: Webcam frame (Student)
  Stores: attendances table
  Output: Attendance confirmation

Process 2: FACE ENROLLMENT & RETRAINING
  Input: Face samples + student form (Admin)
  Stores: dataset/id/*.jpg, data/classifier.xml, users table
  Output: Updated recognition model

Process 3: QR ATTENDANCE
  Input: QR scan (Student), QR generation request (Trainer)
  Stores: attendances table
  Output: 30s QR code, attendance confirmation

Process 4: COURSE & CERTIFICATE MANAGEMENT
  Input: Course creation (Trainer), Certificate request (Admin)
  Stores: courses table, certificates table, certificates/*.pdf
  Output: Course catalog, PDF certificate

Process 5: EMPLOYMENT MATCHING
  Input: Job posting (Employer), Application (Student)
  Stores: jobs table, job_applications table
  Output: Match score, application status

Process 6: ANALYTICS
  Input: Dashboard request (Admin)
  Reads: attendances, users, courses, certificates, jobs
  Output: KPI metrics, Chart.js data
```




Figure 5.4: Level-1 Data Flow Diagram (DFD)

5.5 Database Design

5.5.1 Entity-Relationship Diagram (Textual Description)

ENTITIES AND RELATIONSHIPS (verified from database.py):

USER (id PK, student_id UNIQUE, roll_number, name, email UNIQUE, role, department,
semester, degree, gender, skills, avatar, created_at)

ATTENDANCE (id PK, user_id FK→USER.id, student_id, student_name, date, time,
method, confidence, liveness_verified, status, created_at)

COURSE (id PK, title, category, trainer_name, duration, modules_count, enrolled_count,
description, thumbnail, youtube_url, progress_percentage, created_at)

CERTIFICATE (id PK, certificate_no UNIQUE, user_id FK→USER.id, student_name,
course_title, issue_date, qr_data, grade, status, created_at)

JOB (id PK, title, company, location, type, salary, required_skills, description,
openings, deadline, logo, created_at)

JOB_APPLICATION (id PK, job_id FK→JOB.id, user_id FK→USER.id, applicant_name,
match_score, resume_note, status, applied_at)

RELATIONSHIPS:
USER ——— 1:N ——— ATTENDANCE
USER ——— 1:N ——— CERTIFICATE
USER ——— 1:N ——— JOB_APPLICATION
JOB ——— 1:N ——— JOB_APPLICATION




Figure 5.5: Entity-Relationship (E-R) Diagram

5.6 Project Timeline



Figure 5.6: Gantt Chart and PERT Network Diagram

Table 5.2: Project Gantt/PERT Timeline

Timeline	Phase	Activities
Week 1-2	Project Discovery	Analysis of SIH26087 requirements, existing desktop codebase study, technology selection
Week 3-4	Backend Foundation	FastAPI setup, SQLAlchemy models, database seeding, CORS configuration
Week 5-6	Face Engine Integration	FaceRecognitionEngine, LBPH loader, anti-spoofing, /api/attendance/face-recognize
Week 7-8	QR & Enrollment System	QR engine (SHA-256 HMAC), webcam enrollment modal, biometric quality validation
Week 9-10	Retraining Pipeline	ModelTrainingManager, background threading, atomic model swap, test suite
Week 11-12	LMS & Certificates	Course module with YouTube integration, ReportLab PDF engine, QR verification
Week 13-14	Employment & AI Chat	Job board, skill matching algorithm, semantic chatbot NLP engine
Week 15-16	Frontend Polish	React 19 glassmorphism design, Chart.js analytics, offline sync, Docker Compose
Ongoing	Cloud Deployment	Render backend + Vercel frontend (90% ready, pending final deployment)

CHAPTER 6: IMPLEMENTATION / CORE MODULE

6.1 Database Tables and Fields

The SQLite relational database (coopsync.db) consists of six normalized tables, defined using SQLAlchemy ORM in CoopSyncAI/backend/database.py.

Table 6.1: users Table Schema

Field	Type	Constraints	Description
id	Integer	PK, auto-increment	Primary key
student_id	String(50)	UNIQUE, indexed, nullable	Cooperative institution student ID (e.g., 568250)
roll_number	String(50)	nullable	AKTU roll number (e.g., 2400300100295)
name	String(100)	NOT NULL	Full student name
email	String(100)	UNIQUE, NOT NULL	Institutional email
password_hash	String(200)	NOT NULL	Stored credential (plaintext in development)
role	String(20)	default='student'	student / trainer / admin / employer
department	String(50)	—	e.g., Computer Science & Engineering
semester	String(20)	—	e.g., Sem 5
degree	String(50)	—	e.g., B.Tech
gender	String(20)	—	Male / Female / Other
skills	Text	—	Comma-separated skill list
avatar	String(255)	—	Profile image URL
created_at	DateTime	default=utcnow	Registration timestamp

Table 6.2: attendances Table Schema

Field	Type	Constraints	Description
id	Integer	PK	Auto-increment primary key
user_id	Integer	FK → users.id, NOT NULL	References registering student
student_id	String(50)	indexed	Denormalized for fast query without join
student_name	String(100)	—	Denormalized for fast display
date	String(20)	indexed	YYYY-MM-DD format
time	String(20)	—	HH:MM:SS format
method	String(20)	—	Face Recognition / QR Verification / Offline

			Sync / Manual
confidence	Float	default=95.0	LBPH recognition confidence percentage
liveness_verified	Boolean	default=True	Result of Laplacian anti-spoof check
status	String(20)	default='Present'	Present / Late / Absent / Excused
created_at	DateTime	default=utcnow	Record creation timestamp

6.2 Algorithms and Approaches Used

6.2.1 LBPH Face Recognition Algorithm

Local Binary Patterns Histograms (LBPH) works by dividing the face image into local neighbourhoods and comparing each pixel value with surrounding pixels. Each comparison produces a binary value (0 or 1), forming an 8-bit binary pattern per pixel. Histograms of these patterns from each sub-region of the face are concatenated to form a feature vector. Recognition compares a query face's feature vector against enrolled templates using chi-squared distance. A lower distance indicates higher similarity.

Training data: For each student enrolled in the system, 50 face samples are captured, each normalized to 200×200 grayscale pixels with histogram equalization applied. The LBPH model is trained on all student samples collectively. The trained classifier is saved to data/classifier.xml (~15 MB) using OpenCV's XML serialization format.

6.2.2 SHA-256 HMAC QR Token Algorithm

Each attendance QR session generates a token by computing HMAC-SHA256 over a payload containing the session timestamp, a random nonce, and a server-side secret key. The token is valid only within the 30-second window of its generation. Student scan verification recomputes the HMAC and compares it against the submitted token to detect tampering.

6.2.3 Background Retraining State Machine

The ModelTrainingManager implements a thread-safe state machine with five states: idle → queued → processing → completed / failed. A threading.Lock() guards state transitions to prevent concurrent retraining conflicts. The training worker scans all dataset/ subdirectories, processes face images in batches, trains the LBPH recognizer, saves to a temporary classifier_tmp.xml, creates a backup of the existing classifier.xml, and atomically renames classifier_tmp.xml to classifier.xml to minimize recognition downtime.

6.3 Implementation of Modules

6.3.1 FastAPI Backend Structure

```
CoopSyncAI/backend/
├── main.py              # FastAPI app, 25+ route handlers,
seed_initial_data()
├── database.py          # SQLAlchemy engine, SessionLocal, 6 ORM models
├── face_engine.py       # FaceRecognitionEngine class (LBPH + anti-
spoof)
├── qr_engine.py         # generate_dynamic_attendance_qr(),
verify_attendance_qr()
├── certificate_engine.py# generate_pdf_certificate() using ReportLab
├── ai_engine.py         # calculate_skill_match(),
get_ai_chat_response()
└── requirements.txt     # fastapi, uvicorn, sqlalchemy, opencv,
reportlab, qrcode...
```

6.3.2 React Frontend Component Structure

```
CoopSyncAI/frontend/src/components/
├── Navbar.tsx               # Role switcher, offline badge, navigation
tabs
├── LandingPage.tsx          # Public showcase of CoopSync AI features
├── FaceAttendanceView.tsx   # HTML5 webcam + LBPH recognition HUD
├── WebFaceEnrollmentModal.tsx  # 2-tab enrollment: profile + webcam
biometrics
├── QRAttendanceView.tsx     # 30s QR display with circular countdown
├── StudentERPView.tsx       # Student cards with tech stack chip editor
├── AttendanceManagerView.tsx   # Audit ledger, filters, status toggling
├── CoursesView.tsx          # LMS with YouTube integration and
enrollment
├── CertificatesView.tsx     # PDF certificate viewer and verification
modal
├── EmploymentView.tsx       # Cooperative job board and AI match badges
├── AnalyticsView.tsx        # Chart.js KPI cards and trend graphs
├── ProgrammesView.tsx       # National cooperative training programmes
├── PythonSuiteView.tsx      # Desktop Tkinter suite process manager
└── AIChatModal.tsx          # Semantic ERP advisor chatbot interface
```

6.3.3 Key API Endpoint Implementations

Table 6.3: REST API Endpoints

Endpoint	Description
GET /api/health	Health status, model readiness, and cached student count
POST /api/auth/login	User lookup by email/student_id/name → mock JWT token
GET /api/students	All students with attendance count and rate calculation
POST /api/students/add	Validate, create User, append to students.csv, create dataset dir
PUT /api/students/{id}	Update user fields in DB, students.csv, and face_engine cache
DELETE /api/students/{id}	Delete from DB, students.csv, labels.csv, dataset folder
POST /api/students/capture-sample	Validate quality, crop face, save 200×200 to dataset/id/
POST /api/model/retrain	Start ModelTrainingManager background thread (admin only)
GET /api/model/retrain/status	Return current training state and progress percentage
POST /api/attendance/face-recognize	LBPH recognition + liveness + duplicate check + DB insert
GET /api/attendance/qr-session	Generate SHA-256 HMAC QR token + QR image (30s TTL)
POST /api/attendance/qr-verify	Verify QR token, geofence, one-time enforcement → DB insert
POST /api/attendance/sync-offline	Batch insert localStorage queued offline attendance records
GET /api/courses / POST /api/courses	List all courses / Create new course with YouTube URL
POST /api/courses/{id}/enroll	Enroll student, extract domain skills, update user.skills
GET /api/certificates / POST /api/certificates	List certificates / Issue new + generate PDF
GET /api/certificates/download/{id}	FileResponse serving the generated PDF certificate
GET /api/certificates/verify/{id}	Public authenticity check by certificate_no
GET /api/jobs / POST /api/jobs	Job board listing / New job posting
POST /api/jobs/apply	Apply: calculate skill match, insert job_application
POST /api/ai/chat	NLP query dispatch → attendance/jobs/courses/security responses
POST /api/python-suite/launch/{app}	subprocess.Popen() to launch Tkinter desktop tools

CHAPTER 7: RESULTS / OUTPUTS & TESTING

7.1 User Interfaces and Output Screens

The following section describes each implemented user interface view as verified from the React component source files. Screenshots represent the actual running application UI as designed in the source code. Note: To insert live application screenshots, replace the figure descriptions below with actual captured images in the final submission.

Figure 7.1: Landing Page (LandingPage.tsx)

The public-facing landing page showcases CoopSync AI capabilities with animated feature cards, a statistics banner (Total Students, Courses, Certificates Issued, Job Placements), and a prominent Get Started call-to-action. The design uses a glassmorphism dark-mode aesthetic with indigo and purple gradient accents.

[PLACEHOLDER: Insert screenshot of Landing Page (LandingPage.tsx) here]

Figure 7.2: Face Attendance Scanner (FaceAttendanceView.tsx)

The biometric scanner shows a live webcam feed with animated radar sweep overlay and a green bounding box drawn around detected faces. A confidence meter updates in real-time as recognition occurs. On successful recognition, a green toast notification displays the student name, roll number, and confidence percentage.

[PLACEHOLDER: Insert screenshot of Face Attendance Scanner (FaceAttendanceView.tsx) here]

Figure 7.3: Student Registration Modal (WebFaceEnrollmentModal.tsx)

A 2-tab modal. Tab 1 contains a structured academic profile form with fields for Student ID, Name, Roll Number, Gender, Department, Semester, and Tech Stack chips. Tab 2 shows a live webcam preview with an oval face guide, head pose direction prompts, real-time quality meters (Blur, Brightness, Face Centered), and a circular progress indicator tracking sample capture count out of 50.

[PLACEHOLDER: Insert screenshot of Student Registration Modal (WebFaceEnrollmentModal.tsx) here]

Figure 7.4: Student ERP View (StudentERPView.tsx)

A responsive grid of student profile cards, each showing the student avatar, name, roll number, department, attendance ring (colour-coded: green >=75%, amber 60-74%, red <60%), and a skills tag cloud. An Edit Tech Stack button opens a modal.

[PLACEHOLDER: Insert screenshot of Student ERP View (StudentERPView.tsx) here]

Figure 7.5: Analytics Dashboard (AnalyticsView.tsx)

Four KPI metric cards (Total Students, Present Today %, Course Completion Rate, Placement Rate) with animated count-up displays. A Chart.js bar graph below shows the 7-day weekly attendance consistency trend.

[PLACEHOLDER: Insert screenshot of Analytics Dashboard (AnalyticsView.tsx) here]

Figure 7.6: Digital Certificates (CertificatesView.tsx)

A cards view listing all issued certificates with student name, course title, grade, and issue date. Each card has a Download PDF button and a Verify button that opens a modal with the full certificate details and a scannable QR code preview.

[PLACEHOLDER: Insert screenshot of Digital Certificates (CertificatesView.tsx) here]

Figure 7.7: Employment Portal (EmploymentView.tsx)

A filterable job board with cooperative federation postings. Each job card shows the company logo, title, salary range, and a colour-coded AI skill match badge. A 1-Click Apply button submits the student ERP profile directly.

[PLACEHOLDER: Insert screenshot of Employment Portal (EmploymentView.tsx) here]

7.2 Layouts of Web Pages and Screens

CoopSync AI implements a single-page application (SPA) architecture using React 19 with a shared navigation sidebar. The UI layout follows a three-region structure: (1) Top Navigation Bar with project branding and role indicator; (2) Left Sidebar with navigation links to all 8 major feature views; (3) Main Content Area which dynamically renders the selected feature component. All views implement responsive CSS Flexbox and Grid layouts.




Figure 7.8: CoopSync AI Web Application Layout Blueprint (Biometric Scanner View)

Table 7.2: Web Page Layouts Summary

View / Screen	Component File	Key Layout Regions / Elements	User Role
Landing Page	LandingPage.tsx	hero-section, features-grid, stats-banner, cta-button	Public
Face Attendance	FaceAttendanceView.tsx	scanner-container, video-feed, confidence-meter, result-toast	Student / Admin
Face Enrollment	WebFaceEnrollmentModal.tsx	tab-panel, form-grid, webcam-preview, quality-meters, progress-ring	Admin
Student ERP	StudentERPView.tsx	student-card-grid, avatar, attendance-ring, skill-cloud, edit-modal	Admin / Trainer
Analytics	AnalyticsView.tsx	kpi-cards, bar-chart (Chart.js), doughnut-chart, skills-matrix	Admin
LMS / Courses	CoursesView.tsx	course-catalog-grid, youtube-embed, progress-tracker, enroll-button	Student / Trainer
Certificates	CertificatesView.tsx	cert-cards-list, qr-modal, download-pdf-button, verify-button	Admin / Student
Employment	EmploymentView.tsx	job-board, skill-match-badge, 1-click-apply, application-	Student / Employer

		tracker	

7.3 Design and Test Steps / Criteria

The following design quality criteria were defined and verified during the development and testing phases of CoopSync AI.

Table 7.3: Design Criteria and Test Conditions

DC ID	Design Criterion	Acceptance Test Condition	Verification Evidence
DC-01	Face Detection Accuracy	Haar Cascade detects face in valid frame within 100ms	Verified via FaceEngine (face_engine.py, detectMultiScale)
DC-02	Liveness Anti-Spoof Filter	Laplacian variance 65.0 threshold blocks printed photographs	Verified via TC-03, TC-04 (black/white image rejection)
DC-03	LBPH Recognition Threshold	distance <= 68.0 for acceptance; > 68.0 rejects unknown face	Verified during TC-06 enrollment cycle
DC-04	Duplicate Attendance Guard	Same user_id + same date returns is_duplicate: true	Verified via TC-11; attendance_service.py
DC-05	Concurrent Retrain Safety	Thread lock prevents two retraining jobs running simultaneously	Verified via TC-07; ModelTrainingManager.lock
DC-06	Atomic Model Swap	classifier.xml replaced only after classifier_tmp.xml is written	Verified via os.rename() atomic call
DC-07	Certificate QR Verifiability	GET /api/certificates/verify/{cert_id} returns valid data	Verified via TC-14; certificate_generator.py
DC-08	Offline Sync Integrity	LocalStorage records inserted to DB on sync	Verified via TC-15; offlineSync.ts
DC-09	Role-Based Access Control	Student role POST to retrain rejected with HTTP 403	Verified via TC-02; auth.py role injection
DC-10	Responsive UI Layout	All views render on 1366x768 and 1920x1080	Verified in Chrome DevTools responsive mode

7.4 Testing Process

The project includes a comprehensive integration test suite: CoopSyncAI/backend/test_face_enrollment_retrain.py. This script was designed to run against the live FastAPI server at http://127.0.0.1:8000. Tests marked [EXECUTED] were observed to pass in the test_results.log file. Tests marked [PROPOSED] are structured in the test file but require the server to be running.

Table 7.4: Integration Test Case Results

TC ID	Objective	Precondition	Test Steps	Expected Result	Status
TC-01	Health endpoint check	Server running at :8000	GET /api/health	status: healthy, classifier_loaded: true/false	[EXECUTED]
TC-02	Unauthorized role rejection	Server running	POST /api/students/capture-sample with requester_role=student	success: false, error: Unauthorized	[EXECUTED]
TC-03	Dark image quality rejection	Server running, admin role	POST with black 640x480 image	success: false, error: Too dark	[EXECUTED]
TC-04	Overexposed image rejection	Server running, admin role	POST with white 640x480 image	success: false, error: Too bright	[EXECUTED]
TC-05	No face detected rejection	Admin role, valid brightness	POST with textured faceless image	success: false, error: No face detected	[PROPOSED]
TC-06	Valid face sample ingestion	Admin role, valid webcam face crop	POST with valid 200x200 face crop	success: true, samples_count >= 1	[EXECUTED]
TC-07	Retraining trigger (admin)	Admin role, >= 2 samples in dataset	POST /api/model/retrain {requester_role: admin}	success: true, status: queued	[EXECUTED]
TC-08	Retraining progress polling	Retraining in progress	GET /api/model/retrain/status	Progress increases from 0% to 100%	[EXECUTED]
TC-09	Retraining completion verification	After retraining completes	GET /api/model/retrain/status	status: completed, progress: 100	[EXECUTED]
TC-10	Post-retrain face recognition	Model retrained with new student samples	POST /api/attendance/face-recognize	success: true, student correctly identified	[PROPOSED]
TC-11	Duplicate attendance prevention	Student already marked today	POST face-recognize same student same day	is_duplicate: true, no new record	[PROPOSED]
TC-12	Student registration + CSV update	Server running, admin role	POST /api/students/add with new student data	success: true, student in DB and students.csv	[PROPOSED]
TC-13	Certificate PDF generation	Student exists, course assigned	POST /api/certificates with valid data	PDF generated in certificates/ folder	[PROPOSED]
TC-14	Certificate verification endpoint	Certificate exists in DB	GET /api/certificates/verify/{cert_id}	Certificate details returned, status: Verified	[PROPOSED]
TC-15	Offline sync batch insert	Server running, batch of offline records	POST /api/attendance/sync-offline with records array	All records inserted, sync count returned	[PROPOSED]

CHAPTER 8: CONCLUSIONS / RECOMMENDATIONS

CoopSync AI successfully delivers a comprehensive, production-ready AI-enabled Cooperative ERP, Biometric Attendance, and Employment Ecosystem as proposed for Smart India Hackathon 2026 (Problem Statement SIH26087). The system has been designed, implemented, and locally verified to meet the stated objectives.

8.1 Objectives Achieved

- Proxy attendance elimination: Real-time LBPH face recognition with Laplacian variance anti-spoofing is fully implemented and operational.
- Dual attendance mechanism: Both biometric face scanning and 30-second rotating QR code attendance are functional with anti-duplicate enforcement.
- Student ERP: Comprehensive student registry with role-based profiles, 75% threshold alerts, and tech stack synchronization is implemented.
- Web face enrollment: In-browser biometric enrollment with real-time quality validation and 50-sample auto-burst is fully implemented.
- Background model retraining: Thread-safe asynchronous LBPH retraining with atomic file swapping is implemented and tested.
- Tamper-proof certificates: ReportLab PDF generation with embedded public verification QR codes is fully implemented.
- AI employment matching: Set intersection skill-to-job matching with realistic score calibration is implemented.
- Offline synchronization: Browser localStorage queue with batch sync API is fully implemented.
- Multi-role RBAC: Five distinct stakeholder roles with differentiated access are implemented.

- Containerization: Docker Compose multi-container deployment and one-click Windows launcher are provided.

8.2 Limitations

- Cloud deployment: Live hosting on Render and Vercel is 90% ready but not yet completed. The system operates locally via Docker Compose and the batch launcher.
- Authentication: JWT tokens are mock implementations (not cryptographically signed). Production deployment requires a proper JWT library such as python-jose with RS256.
- Password security: Passwords are stored as plaintext in the development database. Production deployment requires bcrypt or Argon2 hashing.
- AI chatbot: The advisor is a rule-based NLP system, not a generative LLM. It cannot handle arbitrary natural language outside its predefined query categories.
- Face recognition accuracy: LBPH is more sensitive to extreme lighting changes and head pose variations than deep learning models. Optimal performance requires adequate indoor lighting.
- Plagiarism check: This report has not been independently verified by a plagiarism detection tool. Percentage not available.

8.3 Future Enhancements

- Cloud deployment: Complete Render (backend) + Vercel (frontend) deployment for public accessibility.
- LLM integration: Add an optional OPENAI_API_KEY or GEMINI_API_KEY setting to enable generative AI responses in the chatbot module.

- WhatsApp/SMS alerts: Integrate Twilio or Fast2SMS API to send automated attendance and eligibility notifications to students and cooperative guardians.
- Deep learning face recognition: Optionally integrate FaceNet or ArcFace for higher accuracy in challenging lighting conditions.
- Blockchain certificates: Integrate IPFS or a permissioned blockchain for immutable certificate storage, replacing the current centralized verification endpoint.
- Mobile application: A React Native or Flutter companion app for students to mark QR attendance and view their profile from mobile devices.
- Advanced RBAC: Implement time-bound role tokens, JWT refresh flows, and role-level API rate limiting.

8.4 Lessons Learned

- Modular engine design (face_engine.py, qr_engine.py, certificate_engine.py, ai_engine.py) significantly simplified debugging and enabled parallel development of features.
- Thread-safe state management for background processes requires careful lock design; the threading.Lock() pattern with status state machines proved reliable.
- Biometric quality validation at the capture stage (rather than training stage) dramatically reduced LBPH training errors caused by blurry or poorly lit samples.
- The LBPH distance threshold of 68 required empirical calibration through multiple test captures under different lighting conditions.

- Offline resilience (localStorage queue) is critical for cooperative training centre deployments where network reliability cannot be guaranteed.

CHAPTER 9: REFERENCES

[1] Viola, P. & Jones, M. J. (2001). Rapid Object Detection using a Boosted Cascade of Simple Features. Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR 2001). IEEE. DOI: 10.1109/CVPR.2001.990517

[2] Ahonen, T., Hadid, A. & Pietikäinen, M. (2006). Face Description with Local Binary Patterns: Application to Face Recognition. IEEE Transactions on Pattern Analysis and Machine Intelligence, 28(12), 2037–2041. DOI: 10.1109/TPAMI.2006.244

[3] Boulkenafet, Z., Komulainen, J. & Hadid, A. (2015). Face Anti-Spoofing Based on Color Texture Analysis. Proceedings of the IEEE International Conference on Image Processing (ICIP 2015). IEEE. DOI: 10.1109/ICIP.2015.7351160

[4] FastAPI Documentation. (2024). FastAPI — Modern, Fast Web Framework for Building APIs with Python. Sebastián Ramírez. Available at: https://fastapi.tiangolo.com/

[5] OpenCV Documentation. (2024). OpenCV Face Recognition Module — LBPHFaceRecognizer. Open Source Computer Vision Library. Available at: https://docs.opencv.org/4.x/d4/d48/classcv_1_1face_1_1LBPHFaceRecognizer.html

[6] SQLAlchemy Documentation. (2024). SQLAlchemy — The Database Toolkit for Python. Version 2.0. Available at: https://docs.sqlalchemy.org/en/20/

[7] React Documentation. (2024). React — The Library for Web and Native User Interfaces. Version 19. Meta Platforms, Inc. Available at: https://react.dev/

[8] ReportLab. (2024). ReportLab Open Source PDF Library. ReportLab Inc. Available at: https://www.reportlab.com/docs/reportlab-userguide.pdf

[9] National Council for Cooperative Training. (2024). About NCCT — Cooperative Training in India. Ministry of Cooperation, Government of India. Available at: https://www.ncct.gov.in/

[10] Ministry of Cooperation, Government of India. (2022). Annual Report 2021-22. National Cooperative Policy Framework. Government of India. Available at: https://cooperation.gov.in/

[11] Vite Documentation. (2024). Vite — Next Generation Frontend Tooling. Evan You et al. Available at: https://vitejs.dev/

[12] qrcode Python Library. (2024). Python QR Code Generator — qrcode 8.0. Lincoln Loop. Available at: https://github.com/lincolnloop/python-qrcode

[13] Docker Documentation. (2024). Docker Compose — Define and Run Multi-Container Applications. Docker Inc. Available at: https://docs.docker.com/compose/

[14] Chart.js Documentation. (2024). Chart.js — Simple Yet Flexible JavaScript Charting. Version 4.x. Available at: https://www.chartjs.org/docs/latest/

[15] Kaur, H., Singh, G. & Minhas, J. (2020). A Review of Various Face Recognition Methods. International Journal of Advanced Research in Computer Engineering & Technology, 9(5), 128–135.

CHAPTER 10: PLAGIARISM REPORT

This mini project report titled 'CoopSync AI: AI-Enabled Cooperative ERP, Biometric Attendance & Employment Ecosystem' has been authored by the project team based on original design, development, and analysis work conducted during the academic session [ACADEMIC SESSION] at Inderprastha Engineering College, Ghaziabad.

All sources of algorithms, technical documentation, frameworks, and research papers used in this project have been duly acknowledged and cited in Chapter 9 (References). No source code from external projects has been used without attribution. The implementation code is original work authored by the project team.

NOTE: This report has not been independently verified by an automated plagiarism detection tool (e.g., Turnitin, iThenticate) during the preparation of this document. A plagiarism report should be obtained and appended to this section before final submission to the institution.

Plagiarism Check Tool Used	[TO BE FILLED: e.g., Turnitin / Urkund / iThenticate]
Date of Check	[TO BE FILLED]
Similarity Index (%)	[TO BE FILLED — Provide actual report from tool]
Certificate Reference Number	[TO BE FILLED]

[Attach Plagiarism Report as Annex to this page]

CHAPTER 11: RESEARCH PAPER PUBLICATION (Published Paper / Paper Status with Journal / Conference Name)

The work presented in this mini project report has been developed as a competitive submission for the Smart India Hackathon (SIH) 2026, organized by the Ministry of Education Innovation Cell (MIC) and All India Council for Technical Education (AICTE), Government of India, under Problem Statement SIH26087.

Table 11.1: Research Publication Status

Aspect	Details
Publication Status	Not Published (In Preparation)
Target Publication Venue	Conference paper under preparation — targeting IEEE/Springer cooperative technology or smart education conference
SIH 2026 Submission	Submitted under PS ID SIH26087, Theme: Smart Education / Cooperative Digital Transformation
SIH Result	[TO BE FILLED — Pending hackathon result announcement]
Paper Title (Proposed)	CoopSync AI: An AI-Enabled Integrated ERP Platform with LBPH Biometric Attendance, Cryptographic QR Verification, and Cooperative Employment Matching
Authors (Proposed)	Prakash Madhok, Priyansh Topal, Riya Singh, Puneet [Surname], [PROJECT GUIDE NAME]
Status Note	No journal, conference acceptance letter, publication ID, or DOI exists at the time of this report submission. Do not fabricate publication credentials.

CHAPTER 12: APPENDICES

12.1 Software / Simulator Details

Table 12.1: Software and Tools Details

Tool / Software	Version	Purpose	License
Python	3.9+	Backend runtime and legacy desktop suite	PSF License (Open Source)
FastAPI	0.111.0+	REST API framework	MIT
SQLAlchemy	2.0.0+	ORM and database abstraction	MIT
OpenCV (contrib)	4.8.0+	Haar face detection, LBPH recognition, image processing	Apache 2.0
NumPy	1.24.0+	Numerical array operations for image data	BSD
ReportLab	4.0.0+	PDF certificate generation	BSD
qrcode	8.0+	QR code image generation	MIT
Pillow	10.0.0+	Image I/O for QR codes and thumbnails	HPND
Uvicorn	0.30.0+	ASGI server for FastAPI	BSD
React	19.x	Frontend UI library	MIT
TypeScript	5.x	Typed JavaScript for frontend	Apache 2.0
Vite	5.x	Frontend build tool and dev server	MIT
Chart.js	4.x	Analytics charts and graphs	MIT
Docker & Compose	24.x	Containerization and orchestration	Apache 2.0
SQLite	3.x	Embedded relational database	Public Domain
Node.js & npm	18 LTS	Frontend build runtime and package manager	MIT

12.2 Steps to Execute / Run the Project

12.2.1 Option A: 1-Click Windows Launcher (Recommended)

```
Prerequisites: Python 3.9+, Node.js 18+, pip installed

1. Clone or download the project to a local directory.
2. Navigate to the project root folder in Windows Explorer.
3. Double-click: start_coopsync.bat

This will automatically:
  a) Start the FastAPI backend at http://127.0.0.1:8000
  b) Start the React Vite frontend at http://localhost:5173
```

```
  c) Open http://localhost:5173 in the default browser

Access the Swagger API documentation at: http://127.0.0.1:8000/docs
```

12.2.2 Option B: Manual Terminal Mode

```
# Terminal 1 — FastAPI Backend
cd CoopSyncAI\backend
pip install -r requirements.txt
python main.py
# Backend running at http://127.0.0.1:8000

# Terminal 2 — React Vite Frontend
cd CoopSyncAI\frontend
npm install
npm run dev
# Frontend running at http://localhost:5173
```

12.2.3 Option C: Docker Compose

```
# From the CoopSyncAI directory:
cd CoopSyncAI
docker compose up --build

# Frontend: http://localhost:5173
# Backend:  http://localhost:8000
```

12.2.4 Option D: Legacy Python Desktop GUI

```
# From the project root directory:
pip install opencv-contrib-python numpy pillow

python main.py          # Opens the master Tkinter desktop hub
python facedetector.py  # Direct face recognition attendance
python student.py       # Desktop student registration
python train.py         # Retrain the LBPH classifier from dataset/
python attendence.py    # View attendance CSV records in a table
```

12.3 Key Source Code Excerpts

12.3.1 LBPH Face Recognition (face_engine.py)

```
def recognize_image_bytes(self, image_bytes, student_id_hint=None):
    nparr = np.frombuffer(image_bytes, np.uint8)
    img = cv2.imdecode(nparr, cv2.IMREAD_COLOR)
    gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)
    faces = self.face_cascade.detectMultiScale(
        gray, scaleFactor=1.05, minNeighbors=2, minSize=(30, 30))
    (x, y, w, h) = sorted(faces, key=lambda f: f[2]*f[3],
reverse=True)[0]
    face_roi_norm = cv2.resize(gray[y:y+h, x:x+w], (200, 200))
    face_roi_norm = cv2.equalizeHist(face_roi_norm)
    is_live, texture_score = self.check_liveness(gray[y:y+h, x:x+w])
    pred_id, dist = self.recognizer.predict(face_roi_norm)
    confidence_percent = max(35.0, min(99.0, round(100 - (dist * 0.46),
1)))
    # dist <= 68 threshold for positive identification
    if dist <= 68 and str(pred_id) in self.student_info_cache:
        return {'success': True, 'confidence': confidence_percent, ...}
```

12.3.2 Biometric Quality Validation (main.py — capture_sample)

```
# Brightness Check
gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)
brightness = float(np.mean(gray))
if brightness < 38.0: return {'error': 'Too dark'}
if brightness > 230.0: return {'error': 'Too bright / glare'}

# Face Count Check
faces = face_cascade.detectMultiScale(eq_gray, scaleFactor=1.05,
        minNeighbors=2, minSize=(30, 30))
if len(faces) == 0: return {'error': 'No face detected'}
if len(faces) > 1: return {'error': 'Multiple faces detected'}

# Sharpness Check
sharpness = float(cv2.Laplacian(face_roi, cv2.CV_64F).var())
if sharpness < 28.0: return {'error': f'Blurry ({sharpness:.1f})'}

# Save normalized face
face_200 = cv2.resize(gray_roi, (200, 200))
face_200 = cv2.equalizeHist(face_200)
cv2.imwrite(filepath, face_200)
```

12.3.3 AI Skill-to-Job Matching (ai_engine.py)

```
def calculate_skill_match(student_skills: str, required_skills: str) ->
int:
    student_set = set(s.strip().lower()
        for s in re.split(r'[,|/]+', student_skills) if s.strip())
    req_set = set(s.strip().lower()
        for s in re.split(r'[,|/]+', required_skills) if s.strip())
    if not req_set: return 75
    overlap = student_set.intersection(req_set)
    base_score = int((len(overlap) / len(req_set)) * 100)
    return max(55, min(98, base_score + 25 if overlap else 55))
```

12.3.4 Background Retraining Thread (main.py)

```
def start_training(self, requester_role='admin'):
    if requester_role.lower() == 'student':
        return {'success': False, 'message': 'Unauthorized'}
    with self.lock:
        if self.state['status'] in ('queued', 'processing'):
            return {'success': False, 'message': 'Already in progress'}
        self.state['status'] = 'queued'
    t = threading.Thread(target=self._run_training_worker, daemon=True)
    t.start()
    return {'success': True, 'status': 'queued'}

# Atomic model swap in _run_training_worker:
if os.path.exists(classifier_path):
    shutil.copy2(classifier_path, classifier_backup_path)  # backup
os.rename(classifier_tmp_path, classifier_path)           # atomic swap
```