

Java String Functions

Method • Example • Output

Method	Example	Output
<code>length()</code>	<code>"Java".length()</code>	4
<code>charAt(i)</code>	<code>"Java".charAt(2)</code>	v
<code>substring(start)</code>	<code>"Java".substring(2)</code>	va
<code>substring(start,end)</code>	<code>"Java".substring(1,3)</code>	av
<code>equals()</code>	<code>"abc".equals("abc")</code>	true
<code>equalsIgnoreCase()</code>	<code>"JAVA".equalsIgnoreCase("java")</code>	true
<code>compareTo()</code>	<code>"abc".compareTo("abd")</code>	-1
<code>contains()</code>	<code>"Hello".contains("ell")</code>	true
<code>startsWith()</code>	<code>"Java".startsWith("Ja")</code>	true
<code>endsWith()</code>	<code>"Java".endsWith("va")</code>	true
<code>indexOf()</code>	<code>"banana".indexOf('a')</code>	1
<code>lastIndexOf()</code>	<code>"banana".lastIndexOf('a')</code>	5
<code>replace()</code>	<code>"Java".replace('a','o')</code>	Jovo
<code>replaceAll()</code>	<code>"a1b2".replaceAll("\\d","")</code>	ab
<code>toUpperCase()</code>	<code>"java".toUpperCase()</code>	JAVA
<code>toLowerCase()</code>	<code>"JAVA".toLowerCase()</code>	java
<code>trim()</code>	<code>" Java ".trim()</code>	"Java"
<code>isEmpty()</code>	<code>"".isEmpty()</code>	true
<code>concat()</code>	<code>"Hi".concat(" All")</code>	Hi All
<code>split()</code>	<code>"a,b,c".split(",")</code>	["a","b","c"]
<code>toCharArray()</code>	<code>"Java".toCharArray()</code>	['J','a','v','a']
<code>valueOf()</code>	<code>String.valueOf(123)</code>	"123"
<code>join()</code>	<code>String.join("-", "A","B","C")</code>	A-B-C

Method	Example	Output
<code>repeat()</code>	<code>"Hi".repeat(3)</code>	HiHiHi

24 common `java.lang.String` methods | Strings are immutable — these methods return a new value.