

Introduction to Programming and Computational Physics

Lecture 8

Strings
Structures

Char and string

A char is a one byte integer data type:

```
char ch; //declaring a char
```

```
ch = 'h'; //the corresponding ASCII code is stored
```

```
printf("%c", ch); //the character is printed
```

h

```
printf("%d", ch); //the ASCII code is printed
```

104

An array of char is called string:

```
char str[10]; str[0] = 'X'; str[1] = '6';
```

```
printf("%c", str[0]);
```

The ASCII code

0	Ctrl-@	32	Space	64	@	96	`
1	Ctrl-A	33	!	65	A	97	a
2	Ctrl-B	34	"	66	B	98	b
3	Ctrl-C	35	#	67	C	99	c
4	Ctrl-D	36	\$	68	D	100	d
5	Ctrl-E	37	%	69	E	101	e
6	Ctrl-F	38	&	70	F	102	f
7	Ctrl-G	39	'	71	G	103	g
8	Backspace	40	(72	H	104	h
9	Tab	41)	73	I	105	i
10	Ctrl-J	42	*	74	J	106	j
11	Ctrl-K	43	+	75	K	107	k
12	Ctrl-L	44	,	76	L	108	l
13	Return	45	-	77	M	109	m
14	Ctrl-N	46	.	78	N	110	n
15	Ctrl-O	47	/	79	O	111	o
16	Ctrl-P	48	0	80	P	112	p
17	Ctrl-Q	49	1	81	Q	113	q
18	Ctrl-R	50	2	82	R	114	r
19	Ctrl-S	51	3	83	S	115	s
20	Ctrl-T	52	4	84	T	116	t
21	Ctrl-U	53	5	85	U	117	u
22	Ctrl-V	54	6	86	V	118	v
23	Ctrl-W	55	7	87	W	119	w
24	Ctrl-X	56	8	88	X	120	x
25	Ctrl-Y	57	9	89	Y	121	y
26	Ctrl-Z	58	:	90	Z	122	z
27	Escape	59	;	91	[123	{
28	Ctrl-\	60	<	92	\	124	
29	Ctrl-]	61	=	93]	125	}
30	Ctrl-^	62	>	94	^	126	~
31	Ctrl-_	63	?	95	_	127	Delete

String

If we define:

```
char stat[] = "hallo world";
```

The dimension of the array will be given by the number of characters plus one, the null char `\0` (it corresponds to the value 0 of ASCII code).

The two statements:

```
char d = 'r'; //a char
```

```
char d[] = "r"; //a string made of 2 char (r and \0)
```

are not equivalent

A fast way to print a string is using `printf` as:

```
printf(str);
```

String printing

```
#include <stdio.h>

int main()
{
    char ch[] = "C++ is a programming language.\n";
    int i=0;
    while (ch[i]!='\0')
    {
        printf("%c",ch[i]);
        i++;
    }
    return 0;
}
```

printf and sprintf

The function `printf` takes a string as input (and prints it to the screen):

```
printf("hallo world\n");
```

is equivalent to:

```
char stat[] = "hallo world\n";
```

```
printf(stat);
```

If the content of the string is not specified when we declare the array we have to specify its dimension and then use the `sprintf` function:

```
char stat[20];
```

```
sprintf(stat, "hallo world\n");
```

```
printf(stat);
```

usage of sprintf

```
#include <stdio.h>

int main()
{
    char stat[100];
    int day = 20;
    char month[] = "April";
    int year = 2010;
    sprintf(stat, "Hallo, today is %d %s %d.\n", day, month, year);
    printf(stat);
    return 0;
}
```

A summary of all input/output commands

```
int a;  
char string[100];  
FILE *filepointer;
```

Input:

```
scanf ("%d", &a);           // reads from the keyboard  
  
fscanf (filepointer, "%d", &a); // reads from a file  
  
sscanf (string, "%d", &a);   // reads from a string
```

Output:

```
printf ("%d\n", a);         // prints on the screen  
  
fprintf (filepointer, "%d\n", a); // prints into a file  
  
sprintf (string, "%d\n", a);  // prints into a string
```


Structures

A structure is a *customizable* data type formed by a collection of variables of different types. The content of a structure is defined by the user.

```
struct nameStruct
{
    typeMember1 nameMember1;
    typeMember2 nameMember2;
    ...
    typeMemberN nameMemberN;
};
```

```
struct nameStruct nameVar;
```

Declaration of a structure of
nameStruct data type

Access to the elements of the structure

```
struct date{  
    int day;  
    char* month;  
    int year;  
};
```

Once that a structure is declared, we can access its members using the expression: `structName.structMember`

```
struct date today;  
today.day = 14;  
today.month = "April";  
today.year = 2015;
```

Structures as I/O parameters

```
struct point{  
    float x;  
    float y;  
}
```

```
struct point Middle(struct point p1, struct point p2){  
    struct point mid;  
    mid.x = (p1.x + p2.x)/2.;  
    mid.y = (p1.y + p2.y)/2.;  
    return mid;  
}
```

Line crossing 2 points

```
#include<stdio.h>

struct point{
    float x;
    float y;
};

struct line{ //y=Ax+B
    float A;
    float B;
};

struct line CalcAB(struct point, struct point);


int main() {
    struct point p1,p2;
    struct line l12;
    printf("Enter the first point    x = ");
    scanf("%f",&(p1.x));
    printf("                                y = ");
    scanf("%f",&(p1.y));
    printf("Enter the second point  x = ");
    scanf("%f",&(p2.x));
    printf("                                y = ");
    scanf("%f",&(p2.y));
    if((p1.x==p2.x)&&(p1.y==p2.y)) {
        printf("it's the same point...\n");
        return 0;
    }
    l12 = CalcAB(p1,p2);
    printf("The line crossing p1 and p2 is y=%fx+%f\n",l12.A,l12.B);
    return 0;
}

struct line CalcAB(struct point p1, struct point p2) {
    struct line l12;
    l12.A = (p2.y-p1.y)/(p2.x-p1.x);
    l12.B = p1.y - l12.A*p1.x;
    return l12;
}
```

The typedef instruction

The C gives the possibility to define an "alias" for the types with the `typedef` command. For instance, if you define:

```
typedef int integernumber;
```



The following declarations are equivalent:

```
int a;
```

```
integernumber a;
```

where `int` is the usual type for integer numbers and `integernumber` is a new type name.

Sometimes it is very useful to customize your program and make it more easy to read.

typedef and the structures

typedef is very useful with structures because it makes easier their definition. The following three declarations are completely equivalent:

```
struct point{  
    float x;  
    float y;  
};
```

The struct point structure is defined.

The variable A is allocated as struct point type.


```
struct point A;
```

```
struct point{  
    float x;  
    float y;  
};  
typedef struct point point;
```

The struct point structure is defined, then the struct point type is redefined as point type.

The variable A is allocated as point type.

```
point A;
```



```
typedef struct {  
    float x;  
    float y;  
} point;
```

The point type is immediately defined.

The variable A is allocated as point type.

```
point A;
```

Line crossing 2 points

```
#include<stdio.h>

typedef struct {
    float x;
    float y;
} point;

typedef struct { //y=Ax+B
    float A;
    float B;
} line;

line CalcAB(point, point);

int main() {
    point p1,p2;
    line l12;
    printf("Enter the first point   x = ");
    scanf("%f",&(p1.x));
    printf("                           y = ");
    scanf("%f",&(p1.y));
    printf("Enter the second point x = ");
    scanf("%f",&(p2.x));
    printf("                           y = ");
    scanf("%f",&(p2.y));
    if((p1.x==p2.x)&&(p1.y==p2.y)) {
        printf("it's the same point...\n");
        return 0;
    }
    l12 = CalcAB(p1,p2);
    printf("The line crossing p1 and p2 is y=%fx+%f\n",l12.A,l12.B);
    return 0;
}

line CalcAB(point p1, point p2) {
    line l12;
    l12.A = (p2.y-p1.y)/(p2.x-p1.x);
    l12.B = p1.y - l12.A*p1.x;
    return l12;
}
```

Array of structures

An array of structure can be defined in the following way:

```
typedef struct{  
    float x;  
    float y;  
} point;  
point p[10];
```

The following loop initializes all the elements to zero:

```
int i;  
for (i=0;i<10;i++){  
    p[i].x = 0.;  
    p[i].y = 0.;  
}
```


Pointers to structures

As for any other data type, it is possible to define pointers to structures.

```
typedef struct{  
    float x;  
    float y;  
} point;  
  
point p1, p2, *pp1, *pp2;  
pp1 = &p1; pp2 = &p2;
```

And we may access the elements of p1 using the pointer:

```
(*pp1).x = 5.3;  (*pp1).y = -3.4;
```

Since the usage of pointers to structure is widely used in C language a new operator is introduced to make the procedure faster:

```
pp1->x = 5.3;  pp2->y = -3.4;
```