

```
praks@praks: ~  
GNU nano 8.7.1 program7.c  
#include <stdio.h>  
#include <stdlib.h>  
  
int global = 100;  
static int s = 50;  
  
int main()  
{  
    int stack = 10;  
    int *heap = (int *)malloc(sizeof(int));  
  
    printf("Code Segment : %p\n", (void *)main);  
    printf("Global Segment : %p\n", (void *)&global);  
    printf("Static Segment : %p\n", (void *)&s);  
    printf("Heap Segment : %p\n", (void *)heap);  
    printf("Stack Segment : %p\n", (void *)&stack);  
  
    free(heap);  
  
    return 0;  
}
```

```
praks@praks:~$ ps  
  PID TTY          TIME CMD  
  349 pts/0        00:00:00 bash  
  529 pts/0        00:00:00 ps
```

```
praks@praks: ~  
praks@praks:~$ nano program7.c  
praks@praks:~$ gcc program7.c -o program7  
praks@praks:~$ ./program7  
Code Segment : 0x5e33542d81a9  
Global Segment : 0x5e33542db010  
Static Segment : 0x5e33542db014  
Heap Segment : 0x5e3391aa5010  
Stack Segment : 0x7ffeddbf4e8c  
praks@praks:~$ |
```