

```
praks@praks:~$ nano week4
praks@praks:~$ nano week4.c
praks@praks:~$ gcc week4.c -o week4
praks@praks:~$ ./week4
Child 1: PID = 2273
Child 2: PID = 2274
Parent waiting using wait()
Child 3: PID = 2275
Child 1 completed
One child completed using wait()
Parent waiting using waitpid()
Child 2 completed
Child 3 completed
Specified child completed using waitpid()
praks@praks:~$ |
```

praks@praks: ~



GNU nano 8.7.1

week4.c *

```
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

int main()
{
    int i;
    pid_t pid;

    for (i = 0; i < 3; i++)
    {
        pid = fork();

        if (pid == 0)
        {
            printf("Child %d: PID = %d\n", i + 1, getpid());
            sleep(i + 1);
            printf("Child %d completed\n", i + 1);
            return 0;
        }
    }

    printf("Parent waiting using wait()\n");
    wait(NULL);

    printf("One child completed using wait()\n");
    printf("Parent waiting using waitpid()\n");
    waitpid(pid, NULL, 0);

    printf("Specified child completed using waitpid()\n");
    return 0;
}
```

^G Help
^X Exit

^O Write Out
^R Read File

^F Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify