







#### Basic idea:


- Exploration of state space by generating successors of already-explored states (a.k.a.~expanding states).
- Every states is evaluated: is it a goal state?


# Tree search example






# Tree search example





### Tree search example



function TREE-SEARCH(problem, strategy) returns a solution, or failure initialize the search tree using the initial state of problem loop do


if there are no candidates for expansion then return failure choose a leaf node for expansion according to *strategy*if the node contains a goal state then return the corresponding solution else expand the node and add the resulting nodes to the search tree

#### Best-first search

- Idea: use an evaluation function f(n) for each node
  - f(n) provides an estimate for the total cost.
  - → Expand the node n with smallest f(n).

Implementation:
 Order the nodes in fringe increasing order of cost.

# Romania with straight-line dist.



c
366
0
160
242
161
176
77
151
226
244
241
234
380
10
193
253
329
80
199
374

#### A\* search

- Idea: avoid expanding paths that are already expensive
- Evaluation function f(n) = g(n) + h(n)
- $g(n) = \cos t \sin t \cos r = \cosh n$
- h(n) = estimated cost from n to goal
- f(n) = estimated total cost of path through n to goal
- Best First search has f(n)=h(n)
- Uniform Cost search has f(n)=g(n)

#### Admissible heuristics

- A heuristic h(n) is admissible if for every node n, h(n) ≤ h\*(n), where h\*(n) is the true cost to reach the goal state from n.
- An admissible heuristic never overestimates the cost to reach the goal, i.e., it is optimistic
- Example: h<sub>SLD</sub>(n) (never overestimates the actual road distance)
- Theorem: If h(n) is admissible, A\* using TREE-SEARCH is optimal

#### Dominance

- If  $h_2(n) \ge h_1(n)$  for all n (both admissible)
- then  $h_2$  dominates  $h_1$
- $h_2$  is better for search: it is guaranteed to expand less or equal nr of nodes.
- Typical search costs (average number of nodes expanded):
- IDS = 3,644,035 nodes  $A^*(h_1) = 227$  nodes  $A^*(h_2) = 73$  nodes
- d=24 IDS = too many nodes  $A^*(h_1) = 39,135$  nodes  $A^*(h_2) = 1,641$  nodes

# Relaxed problems

- A problem with fewer restrictions on the actions is called a relaxed problem
- The cost of an optimal solution to a relaxed problem is an admissible heuristic for the original problem
- If the rules of the 8-puzzle are relaxed so that a tile can move anywhere, then h₁(n) gives the shortest solution
- If the rules are relaxed so that a tile can move to any adjacent square, then h₂(n) gives the shortest solution

#### Consistent heuristics

 A heuristic is consistent if for every node n, every successor n' of n generated by any action α,

$$h(n) \le c(n, a, n') + h(n')$$


If h is consistent, we have

$$f(n') = g(n') + h(n')$$
 (by def.)  
=  $g(n) + c(n,a,n') + h(n')$  ( $g(n')=g(n)+c(n.a.n')$ )  
 $\geq g(n) + h(n) = f(n)$  (consistency)  
 $f(n') \geq f(n)$ 


i.e., f(n) is non-decreasing along any path.




Theorem:
If h(n) is consistent, A\* using GRAPH-SEARCH is optimal in memory to avoid repeated
states










Straight-line distan	ce
to Bucharest	
Arad	36
Bucharest	
Craiova	16
Dobreta	24
Eforie	16
Fagaras	17
Giurgiu	7
Hirsova	15
Iasi	22
Lugoj	24
Mehadia	24
Neamt	23
Oradea	38
Pitesti	1
Rimnicu Vilcea	19
Sibiu	25
Timisoara	32
Urziceni	8
Vaslui	19
Zerind	37







Straight-line distance to Bucharest Arad 366 Bucharest 0 Crajova 160 Dobreta 242 Eforie 161 **Fagaras** 176 Giurgiu 77 Hirsova 151 226 Lugoj 244 Mehadia 241 Neamt 234 Oradea 380 Pitesti 10 Rimnicu Vilcea 193 Sibiu 253 Timisoara 329 Urziceni 80 Vaslui 199 Zerind 374








Straight-line distance	
to Bucharest	
Arad	366
Bucharest	0
Craiova	160
Dobreta	242
Eforie	161
Fagaras	176
Giurgiu	77
Hirsova	151
Iasi	226
Lugoj	244
Mehadia	241
Neamt	234
Oradea	380
Pitesti	10
Rimnicu Vilcea	193
Sibiu	253
Timisoara	329
Urziceni	80
Vaslui	199
Zerind	374















# Properties of A\*

- Complete? Yes (unless there are infinitely many nodes with  $f \le f(G)$ , i.e. step-cost  $> \varepsilon$ )
- <u>Time/Space?</u> Exponential:  $b^d$  except if:  $|h(n) h^*(n)| \le O(\log h^*(n))$
- Optimal? Yes
- Optimally Efficient: Yes (no algorithm with the same heuristic is guaranteed to expand fewer nodes)

# Memory Bounded Heuristic Search: Recursive BFS


- How can we solve the memory problem for A\* search?
- Idea: Try something like depth first search, but let's not forget everything about the branches we have partially explored.
- We remember the best f-value we have found so far in the branch we are deleting.



RBFS changes its mind very often in practice.

This is because the f=g+h become more accurate (less optimistic) as we approach the goal. Hence, higher level nodes have smaller f-values and will be explored first.

Problem: We should keep in memory whatever we can.



# Simple Memory Bounded A\*

- This is like A\*, but when memory is full we delete the worst node (largest f-value).
- Like RBFS, we remember the best descendent in the branch we delete.
- If there is a tie (equal f-values) we delete the oldest nodes first.
- simple-MBA\* finds the optimal reachable solution given the memory constraint.
- Time can still be exponential.

A Solution is not reachable if a single path from root to goal does not fit into memory