

EXPERIMENT 17:

The screenshot shows the uVision IDE interface for the exp617 project. The Disassembly window displays the following code:

```

23: EA = 1; // Enable Global Interrupt
24: while(1);
25: void main()
26: {
27:     TMOD = 0x20; // Timer1 Mode2 (8-bit auto reload)
28:     TH1 = 0xFD; // 9600 baud for 11.0592MHz crystal
29:     TL1 = 0xFD; // Load Timer1
30:     SCON = 0x50; // UART Mode1, REN=1
31:     TR1 = 1; // Start Timer1
32:     ES = 1; // Enable Serial Interrupt
33:     EA = 1; // Enable Global Interrupt
34: }

```

The Serial Channel window is configured with the following settings:

- Mode: 8-Bit Shift Register
- SCON: 0x00, SBUF: 0x00
- Baudrate: 2000000
- SMOD: 0, TI: 0, RI: 0

The Interrupt System window shows the selected interrupt as EA.

The screenshot shows the uVision IDE interface for the exp617 project. The Disassembly window displays the following code:

```

6: P1 = SBUF; // Copy received data to Port 1
7: RI = 0; // Clear receive interrupt flag
8: void main()
9: {
10:     TMOD = 0x20; // Timer1 Mode2 (8-bit auto reload)
11:     TH1 = 0xFD; // 9600 baud for 11.0592MHz crystal
12:     TL1 = 0xFD; // Load Timer1
13:     SCON = 0x50; // UART Mode1, REN=1
14:     TR1 = 1; // Start Timer1
15: }

```

The Serial Channel window is configured with the following settings:

- Mode: 8-Bit var Baudrate
- SCON: 0x52, SBUF: 0x61
- Baudrate: 2000000
- SMOD: 0, TI: 0, RI: 0

The Interrupt System window shows the selected interrupt as EA.