

Query with Sub Query& Correlated Query

```
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create database collegedb;
Query OK, 1 row affected (0.07 sec)

mysql> use collegedb;
Database changed
mysql> create table student(regno bigint primary key,stuname varchar(30),course varchar(20),marks int);
Query OK, 0 rows affected (0.20 sec)

mysql> insert into student values (191711341,'sonu','DBMS',85), (191711342,'pranathi','Java',90), (191711343,'roops','Python',75), (191711344,'abhighna','DBMS',88), (191711345,'tabassum','Java',95), (191711346,'krithika','Python',80);
Query OK, 6 rows affected (0.05 sec)
Records: 6 Duplicates: 0 Warnings: 0

mysql> select*from student;
+-----+-----+-----+-----+
| regno | stuname | course | marks |
+-----+-----+-----+-----+
| 191711341 | sonu | DBMS | 85 |
| 191711342 | pranathi | Java | 90 |
| 191711343 | roops | Python | 75 |
| 191711344 | abhighna | DBMS | 88 |
| 191711345 | tabassum | Java | 95 |
| 191711346 | krithika | Python | 80 |
+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

```
mysql> select*from student where marks>(select avg(marks) from student);
+-----+-----+-----+-----+
| regno | stuname | course | marks |
+-----+-----+-----+-----+
| 191711342 | pranathi | Java | 90 |
| 191711344 | abhighna | DBMS | 88 |
| 191711345 | tabassum | Java | 95 |
+-----+-----+-----+-----+
3 rows in set (0.05 sec)

mysql> select*from student s1 where marks=(select max(marks) from student s2 where s1.course=s2.course);
+-----+-----+-----+-----+
| regno | stuname | course | marks |
+-----+-----+-----+-----+
| 191711344 | abhighna | DBMS | 88 |
| 191711345 | tabassum | Java | 95 |
| 191711346 | krithika | Python | 80 |
+-----+-----+-----+-----+
3 rows in set (0.04 sec)

mysql> select*from student where marks=(select max(marks) from student);
+-----+-----+-----+-----+
| regno | stuname | course | marks |
+-----+-----+-----+-----+
| 191711345 | tabassum | Java | 95 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

mysql> select*from student s1 where marks>(select avg(marks) from student s2 where s1.course=s2.course);
+-----+-----+-----+-----+
| regno | stuname | course | marks |
+-----+-----+-----+-----+
| 191711344 | abhighna | DBMS | 88 |
| 191711345 | tabassum | Java | 95 |
| 191711346 | krithika | Python | 80 |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```