

## DDL Commands using CREATE, ALTER , TRUNCATE and DROP

```
mysql> use studentdb;
Database changed
mysql> create table student(stu_id int(4),stu_name varchar(20),course varchar(20),marks int(3));
Query OK, 0 rows affected, 2 warnings (0.11 sec)
```

```
mysql> desc student;
```

| Field    | Type        | Null | Key | Default | Extra |
|----------|-------------|------|-----|---------|-------|
| stu_id   | int         | YES  |     | NULL    |       |
| stu_name | varchar(20) | YES  |     | NULL    |       |
| course   | varchar(20) | YES  |     | NULL    |       |
| marks    | int         | YES  |     | NULL    |       |

```
4 rows in set (0.05 sec)
```

```
mysql> alter table student modify stu_name varchar(30);
Query OK, 0 rows affected (0.02 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc student;
```

| Field    | Type        | Null | Key | Default | Extra |
|----------|-------------|------|-----|---------|-------|
| stu_id   | int         | YES  |     | NULL    |       |
| stu_name | varchar(30) | YES  |     | NULL    |       |
| course   | varchar(20) | YES  |     | NULL    |       |
| marks    | int         | YES  |     | NULL    |       |

```
4 rows in set (0.00 sec)
```

```
mysql> alter table student add address varchar(30);
Query OK, 0 rows affected (0.12 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc student;
```

| Field    | Type        | Null | Key | Default | Extra |
|----------|-------------|------|-----|---------|-------|
| stu_id   | int         | YES  |     | NULL    |       |
| stu_name | varchar(30) | YES  |     | NULL    |       |
| course   | varchar(20) | YES  |     | NULL    |       |
| marks    | int         | YES  |     | NULL    |       |
| address  | varchar(30) | YES  |     | NULL    |       |

```
5 rows in set (0.00 sec)
```

```
mysql> alter table student add address varchar(30);
Query OK, 0 rows affected (0.12 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc student;
```

| Field    | Type        | Null | Key | Default | Extra |
|----------|-------------|------|-----|---------|-------|
| stu_id   | int         | YES  |     | NULL    |       |
| stu_name | varchar(30) | YES  |     | NULL    |       |
| course   | varchar(20) | YES  |     | NULL    |       |
| marks    | int         | YES  |     | NULL    |       |
| address  | varchar(30) | YES  |     | NULL    |       |

```
5 rows in set (0.00 sec)
```

```
mysql> truncate table student;
Query OK, 0 rows affected (0.08 sec)
```

```
mysql> drop table student;
Query OK, 0 rows affected (0.12 sec)
```