

DDL Commands with Constraints – PRIMARY, FOREIGN KEY, UNIQUE, CHECK, DEFAULT, NOT NULL

```
Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create database college;
Query OK, 1 row affected (0.02 sec)

mysql> use college;
Database changed
mysql> create table department(deptno int,deptname varchar(30));
Query OK, 0 rows affected (0.10 sec)

mysql> alter table department
-> add primary key(deptno);
Query OK, 0 rows affected (0.09 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> create table faculty(facno int,facname varchar(30),gender char(1),salary int,deptno int);
Query OK, 0 rows affected (0.08 sec)

mysql> alter table faculty
-> add primary key(facno);
Query OK, 0 rows affected (0.20 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> alter table faculty
-> modify facname varchar(30) not null;
Query OK, 0 rows affected (0.18 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> alter table faculty
-> add unique(facname);
Query OK, 0 rows affected (0.12 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> alter table faculty
-> add constraint chk_gender
-> check(gender in ('M','F'));
Query OK, 0 rows affected (0.17 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> alter table faculty
-> modify salary int default 25000;
Query OK, 0 rows affected (0.07 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> alter table faculty
-> add constraint fk_dept
-> foreign key(deptno)
-> references department(deptno);
Query OK, 0 rows affected (0.19 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc faculty;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| facno | int | NO | PRI | NULL | |
| facname | varchar(30) | NO | UNI | NULL | |
| gender | char(1) | YES | | NULL | |
| salary | int | YES | | 25000 | |
| deptno | int | YES | MUL | NULL | |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.06 sec)

mysql> insert into department values(101,'CSE'),(102,'ECE'),(103,'EEE');
Query OK, 3 rows affected (0.02 sec)
Records: 3 Duplicates: 0 Warnings: 0

mysql> insert into faculty values
-> (1,'sonu','M',30000,101),
-> (2,'Pranathi','F',35000,102),
-> (3,'Roops','F',25000,103);
Query OK, 3 rows affected (0.05 sec)
Records: 3 Duplicates: 0 Warnings: 0

mysql> select*from faculty
-> ;
+-----+-----+-----+-----+-----+
| facno | facname | gender | salary | deptno |
+-----+-----+-----+-----+-----+
| 1 | sonu | M | 30000 | 101 |
| 2 | Pranathi | F | 35000 | 102 |
| 3 | Roops | F | 25000 | 103 |
+-----+-----+-----+-----+-----+
3 rows in set (0.05 sec)
```