

1. Create a table name STUDENT with following structure.

```
MySQL 8.0 Command Line C# x
+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+
| regno | int       | YES  |     | NULL    |       |
| name  | varchar(20) | YES  |     | NULL    |       |
| gender | char(1)   | YES  |     | NULL    |       |
| DOB   | date      | YES  |     | NULL    |       |
+-----+
4 rows in set (0.01 sec)

mysql> alter table student add (mobilen int(10),city varchar(15));
Query OK, 0 rows affected, 1 warning (0.04 sec)
Records: 0 Duplicates: 0 Warnings: 1

mysql> alter table student drop DOB;
Query OK, 0 rows affected (0.05 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> truncate table student;
Query OK, 0 rows affected (0.03 sec)

mysql> desc student;
+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+
| regno | int       | YES  |     | NULL    |       |
| name  | varchar(20) | YES  |     | NULL    |       |
| gender | char(1)   | YES  |     | NULL    |       |
| mobilen | int(10)  | YES  |     | NULL    |       |
| city  | varchar(15) | YES  |     | NULL    |       |
+-----+
5 rows in set (0.00 sec)
```

2. Create a table name FACULTY with following structure.

```
mysql> create table faculty;
ERROR 4028 (HY000): A table must have at least one visible column.
mysql> drop table faculty;
ERROR 1051 (42S02): Unknown table 'student.faculty'
mysql> create database faculty;
Query OK, 1 row affected (0.01 sec)

mysql> use faculty;
Database changed
mysql> create table faculty(facno int(4),
-> facname varchar(20), gender char(1),DOB date,DOJ date, mobilen int(10));
Query OK, 0 rows affected, 2 warnings (0.03 sec)

mysql> desc faculty;
+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+
| facno | int       | YES  |     | NULL    |       |
| facname | varchar(20) | YES  |     | NULL    |       |
| gender | char(1)   | YES  |     | NULL    |       |
| DOB   | date      | YES  |     | NULL    |       |
| DOJ   | date      | YES  |     | NULL    |       |
| mobilen | int       | YES  |     | NULL    |       |
+-----+
6 rows in set (0.01 sec)
```

3. Create a table name DEPARTMENT with following structure.

```
mysql> create table department(depno varchar(4),deptname varchar(15), depthead varchar(4));
Query OK, 0 rows affected (0.03 sec)

mysql> desc department;
+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+
| depno | varchar(4) | YES  |     | NULL    |       |
| deptname | varchar(15) | YES  |     | NULL    |       |
| depthead | varchar(4) | YES  |     | NULL    |       |
+-----+
3 rows in set (0.01 sec)
```

4. Create a table name COURSE with following structure.

```
mysql> create table course(courseno varchar(3), coursedesc varchar(14), coursetype char(1), semno char(1), hallno varchar(4), facno varchar(4));
Query OK, 0 rows affected (0.03 sec)

mysql> desc course;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| courseno | varchar(3) | YES | | NULL | |
| coursedesc | varchar(14) | YES | | NULL | |
| coursetype | char(1) | YES | | NULL | |
| semno | char(1) | YES | | NULL | |
| hallno | varchar(4) | YES | | NULL | |
| facno | varchar(4) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

5. Modify the table FACULTY by adding a column name Dept of datatype VARCHAR(10)

```
mysql> use faculty;
Database changed
mysql> alter table faculty add dept char(10);
Query OK, 0 rows affected (0.04 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> desc faculty;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| facno | int | YES | | NULL | |
| facname | varchar(20) | YES | | NULL | |
| gender | char(1) | YES | | NULL | |
| DOB | date | YES | | NULL | |
| DOJ | date | YES | | NULL | |
| mobileno | int | YES | | NULL | |
| dept | char(10) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)
```