

CONTROL STATEMENTS

```
mysql> create database collegedb;
Query OK, 1 row affected (0.06 sec)

mysql> use collegedb;
Database changed
mysql> delimiter //
mysql> create function student_grade(marks int) returns varchar(10) deterministic begin declare grade varchar(10);if marks >= 90 then set grade = 'A';elseif m
arks >= 75 then set grade = 'B';elseif marks >= 60 then set grade = 'C';elseif marks >= 40 then set grade = 'D';else set grade = 'F';end if;return grade;end //
Query OK, 0 rows affected (0.01 sec)

mysql> delimiter ;
mysql> select student_grade(95) as Grade;
+-----+
| Grade |
+-----+
| A      |
+-----+
1 row in set (0.08 sec)

mysql> select student_grade(82) as Grade;
+-----+
| Grade |
+-----+
| B      |
+-----+
1 row in set (0.00 sec)

mysql> select student_grade(65) as Grade;
+-----+
| Grade |
+-----+
| C      |
+-----+
1 row in set (0.00 sec)

mysql> select student_grade(50) as Grade;
+-----+
| Grade |
+-----+
| D      |
+-----+
1 row in set (0.00 sec)

mysql> select student_grade(30) as Grade;
+-----+
| Grade |
+-----+
| F      |
+-----+
1 row in set (0.00 sec)
```