

# Modulation Classification using Convolutional Neural Network based on Deep Learning

COEN 6331

**Pranav K. Jha**

Submitted to:  
**Dr. K. Khorasani**

April 28, 2022

- Deep learning has not been well explored in many areas of Wireless communications.
- Modulation classification is one of the domain in communications where we can use deep learning to improve the performance of the network.
- The problem of recognizing the modulations correctly is a challenging task.

In this work, a Convolutional Neural Network (CNN) based on Deep learning (DL) technique has been designed to classify different types of modulation schemes.

## ■ Digital Modulations

- Binary phase shift keying (BPSK)
- Quadrature PSK (QPSK)
- 8-ary PSK (8-PSK)
- 16-ary Quadrature amplitude modulation (16-QAM)
- 64-ary QAM (64-QAM)
- 4-ary Pulse amplitude modulation (4-PAM)
- Gaussian frequency shift keying (GFSK)
- Continuous phase FSK (CPFSK)

## ■ Analog Modulations

- Broadcast FM (B-FM)
- Double sideband amplitude modulation (DSB-AM)
- Single sideband amplitude modulation (SSB-AM)

- Number of frames: 10,000 for each modulation
  - Training: 70%
  - Validation: 15%
  - Testing: 15%
- Training phase consists of training and validation.
- The test frames provides the classification accuracy.
- The number of samples in each frame are  $2^{10}$  with a sampling rate of 0.2 MHz.
- For digital modulation, the number of samples per frame are 8 and the center frequency is 900 MHz.
- For analog modulation, the center frequency is 100 MHz.

- Each of the generated frame is passed through Additive white gaussian noise (AWGN) channel with Rician multipath fading and a clock offset.
- The AWGN channel adds an SNR of 25 dB.
- The communications toolbox of matlab is used to implement this into the network.
- The Rician multipath fading channel has a delay profile of [0 1.6 3.2] samples with their corresponding path gains of [0 -3 -9].
- The K-factor<sup>1</sup> value is considered as 4 and the maximum Doppler shift<sup>2</sup> is considered as 3 Hz.
- The network is implemented with a clock offset<sup>3</sup> of 4.
- Frequency offset<sup>4</sup> and sampling rate offset<sup>5</sup> have also been applied for every frame.
- In this network, the decision is entirely based on single frame

---


<sup>1</sup>K-factor is the ratio of signal power in dominant component over the scattered, reflected power.

<sup>2</sup>The rate of change in observed wavelength, or frequency, is known as the Doppler shift.

<sup>3</sup>Offset of the clock is a delay of a given clock source

<sup>4</sup>An intentional slight shift of broadcast radio frequency (RF), to reduce interference with other transmitters.

<sup>5</sup>It is the relative offset between the sample rate of transmitter and receiver.




**Fig. (a)** Time domain representations of signal waveforms, and **(b)** Corresponding spectrograms<sup>6</sup>

<sup>6</sup>A spectrogram is a visual way of representing the signal strength, or “loudness”, of a signal over time at various frequencies present in a particular waveform.

- CNN consists of 6 convolutional layers and one fully connected layer.
- Each convolution layer except the last layer is followed by a batch normalization layer, rectified linear unit (ReLU) activation layer, and max pooling layer.
- In the last convolution layer, the max pooling layer is replaced with an average pooling layer.
- The output layer has softmax activation.
- The stochastic gradient descent with momentum (SGDM) solver has been configured with a batch size of 256.
- Maximum number of epochs are set to 12.
- Initial learning rate is set to  $2 \times 10^{-2}$  and for every 9 epochs, the learning rate decreases by a factor of 10 modclass.


The network converges in about 12 epochs and the accuracy is 92.88%.



**Fig.** Training of the CNN



Test accuracy: 93.5%



**Fig.** Confusion matrix for test data

- The network confuses 16-QAM and 64-QAM frames.
  - This problem is expected since each frame carries only 128 symbols and 16-QAM is a subset of 64-QAM.
- The network also confuses QPSK and 8-PSK frames.
  - This is based on the fact that the constellations of these modulation types look similar once phase-rotated due to the fading channel and frequency offset.
- The CNN network also confuses between DSB-AM and SSB-AM.
  - This problem arises since the DSB-SC has the same BW as AM and SSB has half of the bandwidth as AM.
- To test the performance of the trained network with over-the-air signals in Matlab, we must have dedicated SDRs for transmission and reception.
- Communications toolbox support package for analog radio devices is required which is unavailable in our lab computers.

- This project has used a CNN based DL model to classify modulations.
- Several waveforms have been generated and used for training and testing purposes.
- CNN based DL approach avoids manual feature selections and provide a higher classification accuracy.
- The CNN based DL network is successful in classifying modulations by 93.5% of accuracy.

- 1 <https://www.mathworks.com/help/deeplearning/ug/modulation-classification-with-deep-learning.html>
- 2 Peng, S., Jiang, H., Wang, H., Alwageed, H., Zhou, Y., Sebdani, M. M., & Yao, Y. D. (2018). Modulation classification based on signal constellation diagrams and deep learning. *IEEE transactions on neural networks and learning systems*, 30(3), 718-727.
- 3 O'Shea, T. J., Corgan, J., & Clancy, T. C. (2016, September). Convolutional radio modulation recognition networks. In *International conference on engineering applications of neural networks* (pp. 213-226). Springer, Cham.
- 4 O'Shea, T. J., Roy, T., & Clancy, T. C. (2018). Over-the-air deep learning based radio signal classification. *IEEE Journal of Selected Topics in Signal Processing*, 12(1), 168-179.
- 5 Liu, X., Yang, D., & El Gamal, A. (2017, October). Deep neural network architectures for modulation classification. In *2017 51st Asilomar Conference on Signals, Systems, and Computers* (pp. 915-919). IEEE.