

# Rajalakshmi Engineering College

Name: Pranav Narayanan  
Email: 240701393@rajalakshmi.edu.in  
Roll no:  
Phone: 9500579427  
Branch: REC  
Department: I CSE FD  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_PAH\_modified

Attempt : 1  
Total Mark : 5  
Marks Obtained : 5

#### Section 1 : Coding

##### 1. Problem Statement

Emily is developing a program to manage a singly linked list. The program should allow users to perform various operations on the linked list, such as inserting elements at the beginning or end, deleting elements from the beginning or end, inserting before or after a specific value, and deleting elements before or after a specific value. After each operation, the updated linked list should be displayed.

Your task is to help Emily in implementing the same.

##### ***Input Format***

The first line contains an integer choice, representing the operation to perform:

- For choice 1 to create the linked list. The next lines contain space-separated

integers, with -1 indicating the end of input.

- For choice 2 to display the linked list.
- For choice 3 to insert a node at the beginning. The next line contains an integer data representing the value to insert.
- For choice 4 to insert a node at the end. The next line contains an integer data representing the value to insert.
- For choice 5 to insert a node before a specific value. The next line contains two integers: value (existing node value) and data (value to insert).
- For choice 6 to insert a node after a specific value. The next line contains two integers: value (existing node value) and data (value to insert).
- For choice 7 to delete a node from the beginning.
- For choice 8 to delete a node from the end.
- For choice 9 to delete a node before a specific value. The next line contains an integer value representing the node before which deletion occurs.
- For choice 10 to delete a node after a specific value. The next line contains an integer value representing the node after which deletion occurs.
- For choice 11 to exit the program.

### ***Output Format***

For choice 1, print "LINKED LIST CREATED".

For choice 2, print the linked list as space-separated integers on a single line. If the list is empty, print "The list is empty".

For choice 3, 4, 5, and 6, print the updated linked list with a message indicating the insertion operation.

For choice 7, 8, 9, and 10, print the updated linked list with a message indicating the deletion operation.

For any operation that is not possible print an appropriate error message such as "Value not found in the list".

For choice 11 terminate the program.

For any invalid option, print "Invalid option! Please try again".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

5

3

7

-1

2

11

Output: LINKED LIST CREATED

5 3 7

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* next;  
};
```

```
struct Node* head = NULL;
```

```
void createLinkedList() {  
    int data;  
    while (1) {  
        scanf("%d", &data);  
        if (data == -1) break;
```

```
        struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
        newNode->data = data;  
        newNode->next = NULL;
```

```
        if (head == NULL) {  
            head = newNode;  
        } else {  
            struct Node* temp = head;  
            while (temp->next != NULL) {  
                temp = temp->next;  
            }  
            temp->next = newNode;  
        }
```

```

    }
    printf("LINKED LIST CREATED\n");
}

```

```

void displayLinkedList() {
    if (head == NULL) {
        printf("The list is empty\n");
        return;
    }

```

```

    struct Node* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}

```

```

void insertAtBeginning(int data) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;
    newNode->next = head;
    head = newNode;
    printf("The linked list after insertion at the beginning is:\n");
    displayLinkedList();
}

```

```

void insertAtEnd(int data) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;
    newNode->next = NULL;

    if (head == NULL) {
        head = newNode;
    } else {
        struct Node* temp = head;
        while (temp->next != NULL) {
            temp = temp->next;
        }
        temp->next = newNode;
    }
    printf("The linked list after insertion at the end is:\n");
}

```

```

    displayLinkedList();
}

void insertBeforeValue(int value, int data) {
    if (head == NULL) {
        printf("Value not found in the list\n");
        printf("The linked list after insertion before a value is:\n");
        displayLinkedList();
        return;
    }

    if (head->data == value) {
        insertAtBeginning(data);
        return;
    }

    struct Node* prev = NULL;
    struct Node* curr = head;

    while (curr != NULL && curr->data != value) {
        prev = curr;
        curr = curr->next;
    }

    if (curr == NULL) {
        printf("Value not found in the list\n");
        printf("The linked list after insertion before a value is:\n");
        displayLinkedList();
        return;
    }

    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;
    newNode->next = curr;
    prev->next = newNode;

    printf("The linked list after insertion before a value is:\n");
    displayLinkedList();
}

void insertAfterValue(int value, int data) {
    if (head == NULL) {

```

```
    printf("Value not found in the list\n");
    printf("The linked list after insertion after a value is:\n");
    displayLinkedList();
    return;
}
```

```
struct Node* temp = head;
while (temp != NULL && temp->data != value) {
    temp = temp->next;
}
```

```
if (temp == NULL) {
    printf("Value not found in the list\n");
    printf("The linked list after insertion after a value is:\n");
    displayLinkedList();
    return;
}
```

```
struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
newNode->data = data;
newNode->next = temp->next;
temp->next = newNode;
```

```
printf("The linked list after insertion after a value is:\n");
displayLinkedList();
}
```

```
void deleteFromBeginning() {
    if (head == NULL) {
        printf("The list is empty\n");
        return;
    }
}
```

```
struct Node* temp = head;
head = head->next;
free(temp);
```

```
printf("The linked list after deletion from the beginning is:\n");
displayLinkedList();
}
```

```
void deleteFromEnd() {
```

```

if (head == NULL) {
    printf("The list is empty\n");
    return;
}

if (head->next == NULL) {
    free(head);
    head = NULL;
} else {
    struct Node* prev = NULL;
    struct Node* curr = head;

    while (curr->next != NULL) {
        prev = curr;
        curr = curr->next;
    }

    prev->next = NULL;
    free(curr);
}

printf("The linked list after deletion from the end is:\n");
displayLinkedList();
}

void deleteBeforeValue(int value) {
    if (head == NULL || head->next == NULL) {
        printf("Deletion not possible\n");
        return;
    }

    if (head->next->next != NULL && head->next->next->data == value) {
        struct Node* temp = head;
        head = head->next;
        free(temp);
        printf("The linked list after deletion before a value is:\n");
        displayLinkedList();
        return;
    }

    struct Node* prevPrevPrev = NULL;
    struct Node* prevPrev = NULL;

```

```

struct Node* prev = head;
struct Node* curr = head->next;

while (curr != NULL && curr->data != value) {
    prevPrevPrev = prevPrev;
    prevPrev = prev;
    prev = curr;
    curr = curr->next;
}

if (curr == NULL) {
    printf("Value not found in the list\n");
    return;
}

if (prevPrev == NULL) {
    printf("Deletion not possible\n");
    return;
}

if (prevPrevPrev == NULL) {
    head = prev;
    free(prevPrev);
} else {
    prevPrevPrev->next = prev;
    free(prevPrev);
}

printf("The linked list after deletion before a value is:\n");
displayLinkedList();
}

void deleteAfterValue(int value) {
    if (head == NULL) {
        printf("The list is empty\n");
        return;
    }

    struct Node* temp = head;
    while (temp != NULL && temp->data != value) {
        temp = temp->next;
    }

```



```

    if (temp == NULL || temp->next == NULL) {
        printf("Deletion not possible\n");
        return;
    }

    struct Node* nodeToDelete = temp->next;
    temp->next = nodeToDelete->next;
    free(nodeToDelete);

    printf("The linked list after deletion after a value is:\n");
    displayLinkedList();
}

int main() {
    int choice, data, value;

    while (1) {
        scanf("%d", &choice);

        switch (choice) {
            case 1:
                createLinkedList();
                break;
            case 2:
                displayLinkedList();
                break;
            case 3:
                scanf("%d", &data);
                insertAtBeginning(data);
                break;
            case 4:
                scanf("%d", &data);
                insertAtEnd(data);
                break;
            case 5:
                scanf("%d %d", &value, &data);
                insertBeforeValue(value, data);
                break;
            case 6:
                scanf("%d %d", &value, &data);
                insertAfterValue(value, data);

```

```

        break;
    case 7:
        deleteFromBeginning();
        break;
    case 8:
        deleteFromEnd();
        break;
    case 9:
        scanf("%d", &value);
        deleteBeforeValue(value);
        break;
    case 10:
        scanf("%d", &value);
        deleteAfterValue(value);
        break;
    case 11:
        exit(0);
    default:
        printf("Invalid option! Please try again\n");
    }
}

return 0;
}

```

**Status :** Correct

**Marks :** 1/1

## 2. Problem Statement

Bharath is very good at numbers. As he is piled up with many works, he decides to develop programs for a few concepts to simplify his work. As a first step, he tries to arrange even and odd numbers using a linked list. He stores his values in a singly-linked list.

Now he has to write a program such that all the even numbers appear before the odd numbers. Finally, the list is printed in such a way that all even numbers come before odd numbers. Additionally, the even numbers should be in reverse order, while the odd numbers should maintain their original order.

Example

Input:

6

3 1 0 4 30 12

Output:

12 30 4 0 3 1

Explanation:

Even elements: 0 4 30 12

Reversed Even elements: 12 30 4 0

Odd elements: 3 1

So the final list becomes: 12 30 4 0 3 1

### ***Input Format***

The first line consists of an integer n representing the size of the linked list.

The second line consists of n integers representing the elements separated by space.

### ***Output Format***

The output prints the rearranged list separated by a space.

The list is printed in such a way that all even numbers come before odd numbers and the even numbers should be in reverse order, while the odd numbers should maintain their original order.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 6

3 1 0 4 30 12

Output: 12 30 4 0 3 1

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
};
```

```
struct Node* newNode(int data) {
    struct Node* node = (struct Node*)malloc(sizeof(struct Node));
    node->data = data;
    node->next = NULL;
    return node;
}
```

```
void append(struct Node** head, int data) {
    struct Node* new_node = newNode(data);
    if (*head == NULL) {
        *head = new_node;
        return;
    }
    struct Node* temp = *head;
    while (temp->next != NULL) {
        temp = temp->next;
    }
    temp->next = new_node;
}
```

```
struct Node* reverse(struct Node* head) {
    struct Node* prev = NULL;
    struct Node* current = head;
    struct Node* next = NULL;
    while (current != NULL) {
        next = current->next;
        current->next = prev;
        prev = current;
        current = next;
    }
```

```

    }
    return prev;
}

void printList(struct Node* head) {
    struct Node* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}

int main() {
    int n;
    scanf("%d", &n);

    struct Node *evenList = NULL, *oddList = NULL;
    int num;

    for (int i = 0; i < n; i++) {
        scanf("%d", &num);
        if (num % 2 == 0) {
            append(&evenList, num);
        } else {
            append(&oddList, num);
        }
    }

    evenList = reverse(evenList);

    printList(evenList);
    printList(oddList);

    return 0;
}

```

**Status :** Correct

**Marks :** 1/1

### 3. Problem Statement

Write a program to manage a singly linked list. The program should allow users to perform various operations on the linked list, such as inserting elements at the beginning or end, deleting elements from the beginning or end, inserting before or after a specific value, and deleting elements before or after a specific value. After each operation, the updated linked list should be displayed.

### ***Input Format***

The first line contains an integer choice, representing the operation to perform:

- For choice 1 to create the linked list. The next lines contain space-separated integers, with -1 indicating the end of input.
- For choice 2 to display the linked list.
- For choice 3 to insert a node at the beginning. The next line contains an integer data representing the value to insert.
- For choice 4 to insert a node at the end. The next line contains an integer data representing the value to insert.
- For choice 5 to insert a node before a specific value. The next line contains two integers: value (existing node value) and data (value to insert).
- For choice 6 to insert a node after a specific value. The next line contains two integers: value (existing node value) and data (value to insert).
- For choice 7 to delete a node from the beginning.
- For choice 8 to delete a node from the end.
- For choice 9 to delete a node before a specific value. The next line contains an integer value representing the node before which deletion occurs.
- For choice 10 to delete a node after a specific value. The next line contains an integer value representing the node after which deletion occurs.
- For choice 11 to exit the program.

### ***Output Format***

For choice 1, print "LINKED LIST CREATED".

For choice 2, print the linked list as space-separated integers on a single line. If the list is empty, print "The list is empty".

For choice 3, 4, 5, and 6, print the updated linked list with a message indicating the insertion operation.

For choice 7, 8, 9, and 10, print the updated linked list with a message indicating the deletion operation.

For any operation that is not possible print an appropriate error message such as "Value not found in the list".

For choice 11 terminate the program.

For any invalid option, print "Invalid option! Please try again".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

5

3

7

-1

2

11

Output: LINKED LIST CREATED

5 3 7

### ***Answer***

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* next;  
};
```

```
struct Node* head = NULL;
```

```
void createLinkedList() {  
    int data;  
    while (1) {  
        scanf("%d", &data);  
        if (data == -1) break;
```

```
        struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
```

```

newNode->data = data;
newNode->next = NULL;

if (head == NULL) {
    head = newNode;
} else {
    struct Node* temp = head;
    while (temp->next != NULL) {
        temp = temp->next;
    }
    temp->next = newNode;
}
}
printf("LINKED LIST CREATED\n");
}

void displayLinkedList() {
    if (head == NULL) {
        printf("The list is empty\n");
        return;
    }

    struct Node* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}

void insertAtBeginning(int data) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;
    newNode->next = head;
    head = newNode;
    printf("The linked list after insertion at the beginning is:\n");
    displayLinkedList();
}

void insertAtEnd(int data) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;

```



```

newNode->next = NULL;

if (head == NULL) {
    head = newNode;
} else {
    struct Node* temp = head;
    while (temp->next != NULL) {
        temp = temp->next;
    }
    temp->next = newNode;
}
printf("The linked list after insertion at the end is:\n");
displayLinkedList();
}

void insertBeforeValue(int value, int data) {
    if (head == NULL) {
        printf("Value not found in the list\n");
        printf("The linked list after insertion before a value is:\n");
        displayLinkedList();
        return;
    }

    if (head->data == value) {
        insertAtBeginning(data);
        return;
    }

    struct Node* prev = NULL;
    struct Node* curr = head;

    while (curr != NULL && curr->data != value) {
        prev = curr;
        curr = curr->next;
    }

    if (curr == NULL) {
        printf("Value not found in the list\n");
        printf("The linked list after insertion before a value is:\n");
        displayLinkedList();
        return;
    }
}

```

```

    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;
    newNode->next = curr;
    prev->next = newNode;

    printf("The linked list after insertion before a value is:\n");
    displayLinkedList();
}

```

```

void insertAfterValue(int value, int data) {
    if (head == NULL) {
        printf("Value not found in the list\n");
        printf("The linked list after insertion after a value is:\n");
        displayLinkedList();
        return;
    }
}

```

```

    struct Node* temp = head;
    while (temp != NULL && temp->data != value) {
        temp = temp->next;
    }
}

```

```

    if (temp == NULL) {
        printf("Value not found in the list\n");
        printf("The linked list after insertion after a value is:\n");
        displayLinkedList();
        return;
    }
}

```

```

    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;
    newNode->next = temp->next;
    temp->next = newNode;

    printf("The linked list after insertion after a value is:\n");
    displayLinkedList();
}

```

```

void deleteFromBeginning() {
    if (head == NULL) {
        printf("The list is empty\n");
    }
}

```

```

    return;
}

struct Node* temp = head;
head = head->next;
free(temp);

printf("The linked list after deletion from the beginning is:\n");
displayLinkedList();
}

```

```

void deleteFromEnd() {
    if (head == NULL) {
        printf("The list is empty\n");
        return;
    }

    if (head->next == NULL) {
        free(head);
        head = NULL;
    } else {
        struct Node* prev = NULL;
        struct Node* curr = head;

        while (curr->next != NULL) {
            prev = curr;
            curr = curr->next;
        }

        prev->next = NULL;
        free(curr);
    }

    printf("The linked list after deletion from the end is:\n");
    displayLinkedList();
}

```

```

void deleteBeforeValue(int value) {
    if (head == NULL || head->next == NULL) {
        printf("Deletion not possible\n");
        return;
    }
}

```

```

// Special case: value is in third node (delete first node)
if (head->next->next != NULL && head->next->next->data == value) {
    struct Node* temp = head;
    head = head->next;
    free(temp);
    printf("The linked list after deletion before a value is:\n");
    displayLinkedList();
    return;
}

struct Node* prevPrevPrev = NULL; // three nodes back
struct Node* prevPrev = NULL;    // two nodes back
struct Node* prev = head;        // one node back
struct Node* curr = head->next;   // current node

while (curr != NULL && curr->data != value) {
    prevPrevPrev = prevPrev;
    prevPrev = prev;
    prev = curr;
    curr = curr->next;
}

if (curr == NULL) {
    printf("Value not found in the list\n");
    return;
}

// Now delete the node two positions before curr (which is prevPrev)
if (prevPrev == NULL) {
    printf("Deletion not possible\n");
    return;
}

if (prevPrevPrev == NULL) {
    // Deleting the head node
    head = prev;
    free(prevPrev);
} else {
    prevPrevPrev->next = prev;
    free(prevPrev);
}

```

```

    printf("The linked list after deletion before a value is:\n");
    displayLinkedList();
}
void deleteAfterValue(int value) {
    if (head == NULL) {
        printf("The list is empty\n");
        return;
    }

    struct Node* temp = head;
    while (temp != NULL && temp->data != value) {
        temp = temp->next;
    }

    if (temp == NULL || temp->next == NULL) {
        printf("Deletion not possible\n");
        return;
    }

    struct Node* nodeToDelete = temp->next;
    temp->next = nodeToDelete->next;
    free(nodeToDelete);

    printf("The linked list after deletion after a value is:\n");
    displayLinkedList();
}

int main() {
    int choice, data, value;

    while (1) {
        scanf("%d", &choice);

        switch (choice) {
            case 1:
                createLinkedList();
                break;
            case 2:
                displayLinkedList();
                break;
            case 3:

```

```

        scanf("%d", &data);
        insertAtBeginning(data);
        break;
    case 4:
        scanf("%d", &data);
        insertAtEnd(data);
        break;
    case 5:
        scanf("%d %d", &value, &data);
        insertBeforeValue(value, data);
        break;
    case 6:
        scanf("%d %d", &value, &data);
        insertAfterValue(value, data);
        break;
    case 7:
        deleteFromBeginning();
        break;
    case 8:
        deleteFromEnd();
        break;
    case 9:
        scanf("%d", &value);
        deleteBeforeValue(value);
        break;
    case 10:
        scanf("%d", &value);
        deleteAfterValue(value);
        break;
    case 11:
        exit(0);
    default:
        printf("Invalid option! Please try again\n");
    }
}

return 0;
}

```

**Status :** Correct

**Marks :** 1/1

#### 4. Problem Statement

Imagine you are managing the backend of an e-commerce platform. Customers place orders at different times, and the orders are stored in two separate linked lists. The first list holds the orders from morning, and the second list holds the orders from the evening.

Your task is to merge the two lists so that the final list holds all orders in sequence from the morning list followed by the evening orders, in the same order

##### ***Input Format***

The first line contains an integer  $n$ , representing the number of orders in the morning list.

The second line contains  $n$  space-separated integers representing the morning orders.

The third line contains an integer  $m$ , representing the number of orders in the evening list.

The fourth line contains  $m$  space-separated integers representing the evening orders.

##### ***Output Format***

The output should be a single line containing space-separated integers representing the merged order list, with morning orders followed by evening orders.

Refer to the sample output for formatting specifications.

##### ***Sample Test Case***

```
Input: 3
101 102 103
2
104 105
Output: 101 102 103 104 105
```

### Answer

```
#include<stdio.h>
#include<stdlib.h>
typedef struct Node{
    int data;
    struct Node* next;
}Node;

Node* append(Node* tail,int val){
    Node* node=(Node*)malloc(sizeof(Node));
    node->data=val;
    node->next=NULL;
    if(tail) tail->next=node;
    return node;
}

void print(Node* head){
    while(head){
        printf("%d ",head->data);
        head=head->next;
    }
}

int main(){
    int n,m,x;
    Node* head=NULL,*tail=NULL;
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        scanf("%d",&x);
        tail=append(tail,x);
        if(!head) head=tail;
    }
    scanf("%d",&m);
    for(int i=0;i<m;i++){
        scanf("%d",&x);
        tail=append(tail,x);
        if(!head) head=tail;
    }
    print(head);
    return 0;
}
```

Status : Correct

Marks : 1/1



## 5. Problem Statement

John is working on evaluating polynomials for his math project. He needs to compute the value of a polynomial at a specific point using a singly linked list representation.

Help John by writing a program that takes a polynomial and a value of  $x$  as input, and then outputs the computed value of the polynomial.

Example

Input:

2

13

12

11

1

Output:

36

Explanation:

The degree of the polynomial is 2.

Calculate the value of  $x^2$ :  $13 * 12 = 13$ .

Calculate the value of  $x^1$ :  $12 * 11 = 12$ .

Calculate the value of  $x^0$ :  $11 * 10 = 11$ .

Add the values of  $x^2$ ,  $x^1$  and  $x^0$  together:  $13 + 12 + 11 = 36$ .

### ***Input Format***

The first line of input consists of the degree of the polynomial.

The second line consists of the coefficient  $x^2$ .

The third line consists of the coefficient of  $x^1$ .

The fourth line consists of the coefficient x0.

The fifth line consists of the value of x, at which the polynomial should be evaluated.

### ***Output Format***

The output is the integer value obtained by evaluating the polynomial at the given value of x.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 2

13

12

11

1

Output: 36

### ***Answer***

```
#include<stdio.h>
#include<stdlib.h>
#include<math.h>
typedef struct node{
    int coeff,power;
    struct node* next;
}node;

node* insert(node* head,int coeff,int power){
    node* newnode = (node*)malloc(sizeof(node));
    newnode->coeff=coeff;
    newnode->power=power;
    newnode->next=head;
    return newnode;
}

int evaluate(node* head,int x){
    int sum=0;
    while(head){
```

```
        sum+=head->coeff * pow(x,head->power);
        head=head->next;
    }
    return sum;
}
int main(){
    int degree,coeff,x;
    scanf("%d",&degree);
    node*poly=NULL;
    for(int i=degree;i>=0;i--){
        scanf("%d",&coeff);
        poly=insert(poly,coeff,i);
    }
    scanf("%d",&x);
    printf("%d\n",evaluate(poly,x));
    return 0;
}
```

**Status :** Correct

**Marks :** 1/1