

Lab Exercise 8- Create POD in Kubernetes

Objective:

- Understand the basic structure and syntax of a Kubernetes Pod definition file (YAML).
- Learn to create, inspect, and delete a Pod in a Kubernetes cluster.

Prerequisites

- Kubernetes Cluster: You need a running Kubernetes cluster. You can set up a local cluster using tools like Minikube or kind, or use a cloud-based Kubernetes service.
- kubectl: Install and configure kubectl to interact with your Kubernetes cluster.
- Basic Knowledge of YAML: Familiarity with YAML format will be helpful as Kubernetes resource definitions are written in YAML.

Step-by-Step Guide

Step 1: Create a YAML File for the Pod

We'll create a Pod configuration file named **pod-example.yaml**

```
apiVersion: v1
kind: Pod
metadata:
  name: my-pod
  labels:
    app: web
spec:
  containers:
    - name: my-container
      image: nginx:latest
```

Explanation of the YAML File

- **apiVersion:** Specifies the version of the Kubernetes API to use. For Pods, it's typically v1.
- **kind:** The type of object being created. Here it's a Pod.
- **metadata:** Provides metadata about the object, including name and labels. The name must be unique within the namespace, and labels help in identifying and organizing Pods.
- **spec:** Contains the specifications of the Pod, including:
 - **containers:** Lists all containers that will run inside the Pod. Each container needs:
 - **name:** A unique name within the Pod.
 - **image:** The Docker image to use for the container.
 - **ports:** The ports that this container exposes.
 - **env:** Environment variables passed to the container.

Step 2: Apply the YAML File to Create the Pod

Use the `kubectl apply` command to create the Pod based on the YAML configuration file.

```
kubectl apply -f pod-example.yaml
```

This command tells Kubernetes to create a Pod as specified in the `pod-example.yaml` file.

Step 3: Verify the Pod Creation

To check the status of the Pod and ensure it's running, use:


```
kubectl get pods
```

```
PS C:\Users\Devanshi\Desktop\lab_8> kubectl apply -f pod-example.yaml
pod/my-pod created
PS C:\Users\Devanshi\Desktop\lab_8> kubectl get pods
NAME      READY   STATUS    RESTARTS   AGE
my-pod    1/1     Running   0           20s
```

This command lists all the Pods in the current namespace, showing their status, restart count, and other details.

You can get detailed information about the Pod using:

`kubectl describe pod my-pod`



```
my-pod 1/1 Running 0 20s
PS C:\Users\Devanshi\Desktop\lab_8> kubectl describe pod my-pod
Name:          my-pod
Namespace:     default
Priority:       0
Service Account: default
Node:          desktop-worker/172.19.0.2
Start Time:    Mon, 09 Feb 2026 10:32:46 +0530
Labels:        app=web
Annotations:    <none>
Status:        Running
IP:            10.244.1.2
IPs:
  IP: 10.244.1.2
Containers:
  my-container:
    Container ID:  containerd://4bc182097d2888fd9222bfff5c53b2d79c4938fe79884c4b7db74b79ff28c24fa
    Image:         nginx:latest
    Image ID:      docker.io/library/nginx@sha256:c881927c4077710ac4b1da63b83aa163937fb47457950c267d92f7e4dedf4aec
    Port:          <none>
    Host Port:     <none>
    State:         Running
      Started:     Mon, 09 Feb 2026 10:32:51 +0530
    Ready:         True
    Restart Count:  0
    Environment:   <none>
    Mounts:
      /var/run/secrets/kubernetes.io/serviceaccount from kube-api-access-7wbfb (ro)
Conditions:
  Type              Status
```

This command provides detailed information about the Pod, including its events, container specifications, and resource usage.

Step 4: Interact with the Pod

You can interact with the running Pod in various ways, such as accessing the logs or executing commands inside the container.

View Logs: To view the logs of the container in the Pod:**kubectl logs my-pod**

```

PS C:\Users\Devanshi\Desktop\lab_8> kubectl logs my-pod
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: info: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: info: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Sourcing /docker-entrypoint.d/15-local-resolvers.envsh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/30-tune-worker-processes.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
2026/02/09 05:02:51 [notice] 1#1: using the "epoll" event method
2026/02/09 05:02:51 [notice] 1#1: nginx/1.29.4
2026/02/09 05:02:51 [notice] 1#1: built by gcc 14.2.0 (Debian 14.2.0-19)
2026/02/09 05:02:51 [notice] 1#1: OS: Linux 6.6.87.2-microsoft-standard-WSL2
2026/02/09 05:02:51 [notice] 1#1: getrlimit(RLIMIT_NOFILE): 1048576:1048576
2026/02/09 05:02:51 [notice] 1#1: start worker processes
2026/02/09 05:02:51 [notice] 1#1: start worker process 32
2026/02/09 05:02:51 [notice] 1#1: start worker process 33
2026/02/09 05:02:51 [notice] 1#1: start worker process 34
2026/02/09 05:02:51 [notice] 1#1: start worker process 35
2026/02/09 05:02:51 [notice] 1#1: start worker process 36
2026/02/09 05:02:51 [notice] 1#1: start worker process 37
2026/02/09 05:02:51 [notice] 1#1: start worker process 38
2026/02/09 05:02:51 [notice] 1#1: start worker process 39
2026/02/09 05:02:51 [notice] 1#1: start worker process 40
2026/02/09 05:02:51 [notice] 1#1: start worker process 41
2026/02/09 05:02:51 [notice] 1#1: start worker process 42
2026/02/09 05:02:51 [notice] 1#1: start worker process 43
2026/02/09 05:02:51 [notice] 1#1: start worker process 44
2026/02/09 05:02:51 [notice] 1#1: start worker process 45

```

Execute a Command: To run a command inside the container:**kubectl exec -it my-pod -- /bin/bash**

```

2026/02/09 05:02:51 [notice] 1#1: start worker process 47
PS C:\Users\Devanshi\Desktop\lab_8> kubectl exec -it my-pod -- /bin/bash
root@my-pod:/# echo "hello"
hello

```

The `-it` flag opens an interactive terminal session inside the container, allowing you to run commands.

Step 5: Delete the Pod

To clean up and remove the Pod when you're done, use the following command:

```
kubectl delete pod my-pod
```

```
PS C:\Users\Devanshi\Desktop\lab_8> kubectl delete pod my-pod  
pod "my-pod" deleted
```

This command deletes the specified Pod from the cluster.