AI ASSISTED CODING (ASSIGNMENT-11.1)

Name: U.Pranav Dev

Roll No: 2503A52694

Batch: 24

#Q1

Task: Use AI to generate a Stack class with push, pop, peek, and is_empty methods.

Sample Input Code:

class Stack:

pass

Prompt: generate a code on Stack class with push, pop, peek, and is_empty methods.

Code:

```
class Stack:
    def __init__(self):
        self.items = []
    def push(self, item):
        self.items.append(item)
    def pop(self):
        if self.is_empty():
            return None
        return self.items.pop()
    def peek(self):
        if self.is_empty():
            return None
```

```
        return self.items[-1]


    def is_empty(self):
        return len(self.items) == 0
stack = Stack()
stack.push(10)
stack.push(20)
print("Top element:", stack.peek())
print("Popped element:", stack.pop())
print("Is stack empty?", stack.is_empty())
```

Output:

```
PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDriv
e/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/T11.py"
Top element: 20
Popped element: 20
Is stack empty? False
PS C:\Users\chait\OneDrive\Desktop\AIAC>
```

#Q2

Task: Use AI to implement a Queue using Python lists.

Sample Input Code:

```
class Queue:
pass
```

Prompt: generate a code to implement a Queue using python list.

Code:

```
class Queue:
    def __init__(self):
        self._items = []
    def enqueue(self, item):
        """Add an item to the rear of the queue."""
        self._items.append(item)
    def dequeue(self):
```

```
        if self.is_empty():
            return None
        return self._items.pop(0)
    def peek(self):
        if self.is_empty():
            return None
        return self._items[0]
    def is_empty(self):
        return len(self._items) == 0
if __name__ == "__main__":
    queue = Queue()
    print("Is queue empty?", queue.is_empty())
    queue.enqueue(10)
    queue.enqueue(20)
    queue.enqueue(30)
    print("Queue after enqueueing 10, 20, 30:", queue._items)
    print("Front item:", queue.peek())
    print("Dequeued item:")
    print(queue.dequeue())
    print("Front item after dequeue:", queue.peek())
    print("Is queue empty?", queue.is_empty())
```

output:

```
PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDriv
e/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t11.2.py"
Is queue empty? True
Queue after enqueueing 10, 20, 30: [10, 20, 30]
Front item: 10
Dequeued item:
10
Front item after dequeue: 20
Is queue empty? False
PS C:\Users\chait\OneDrive\Desktop\AIAC>
```

#Q3

Task: Use AI to generate a Singly Linked List with insert and display

methods.

Sample Input Code:

```
class Node:
pass
class LinkedList:
pass
```

Prompt: generate a code on singly linked list with insert and display methods.

Code:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None
class LinkedList:
    def __init__(self):
        self.head = None
    def insert(self, data):
        new_node = Node(data)
        if self.head is None:
            self.head = new_node
            return
        current = self.head
        while current.next is not None:
            current = current.next
        current.next = new_node
    def display(self):
        current = self.head
        values = []

        while current is not None:
```

```
            values.append(str(current.data))
            current = current.next
        print(" -> ".join(values) if values else "The list is empty.")
if __name__ == "__main__":
    linked_list = LinkedList()
    linked_list.insert(10)
    linked_list.insert(20)
    linked_list.insert(30)
    print("Linked list:")
    linked_list.display()
```

ouput:

```
PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDrive/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t11.3.py"
Linked list:
10 -> 20 -> 30
PS C:\Users\chait\OneDrive\Desktop\AIAC>
```

#Q4

Task: Use AI to create a BST with insert and in-order traversal methods.

Sample Input Code:

```
class BST:
pass
```

Prompt: generate a code on BST with insert and in-order traversal methods.

Code:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.left = None
        self.right = None
class BST:
    def __init__(self):
        self.root = None
```

```
    def insert(self, data):
        """Insert a value into the tree."""
        self.root = self._insert(self.root, data)
    def _insert(self, node, data):
        if node is None:
            return Node(data)
        if data < node.data:
            node.left = self._insert(node.left, data)
        elif data > node.data:
            node.right = self._insert(node.right, data)
        return node
    def in_order(self):
        values = []
        self._in_order(self.root, values)
        return values
    def _in_order(self, node, values):
        if node is not None:
            self._in_order(node.left, values)
            values.append(node.data)
            self._in_order(node.right, values)
if __name__ == "__main__":
    bst = BST()
    for value in (50, 30, 70, 20, 40, 60, 80):
        bst.insert(value)
    print("In-order traversal:", bst.in_order())
```

output:

```
PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDriv
e/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t11.4.py"
In-order traversal: [20, 30, 40, 50, 60, 70, 80]
PS C:\Users\chait\OneDrive\Desktop\AIAC>
```

#Q5

Task: Use AI to implement a priority queue using Python's heapq module.

Sample Input Code:

```
class PriorityQueue:
pass
```

Prompt: generate a code to implement a priority queue using Python's heapq module.

Code:

```
import heapq

class PriorityQueue:
    def __init__(self):
        self._items = []

    def insert(self, item):
        """Add an item to the priority queue."""
        heapq.heappush(self._items, item)

    def remove(self):
        """Remove and return the item with the highest priority."""
        return heapq.heappop(self._items)

    def peek(self):
        """Return the highest-priority item without removing it."""
        return self._items[0]

    def is_empty(self):
        return len(self._items) == 0
```

```
if __name__ == "__main__":
    queue = PriorityQueue()
    for item in (5, 1, 3, 2, 4):
        queue.insert(item)

    print("Priority order:", end=" ")
    while not queue.is_empty():
        print(queue.remove(), end=" ")
```

output:

```
PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDrive/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t11.5.py"
Priority order: 1 2 3 4 5
PS C:\Users\chait\OneDrive\Desktop\AIAC>
```

#Q6

Task: Use AI to implement a double-ended queue using collections.deque.

Sample Input Code:

```
class DequeDS:
```

prompt: generate a code to implement a double-ended queue using collections.deque.

code:

```
from collections import deque
class DoubleEndedQueue:
    """A double-ended queue (deque)."""

    def __init__(self):
        """Create an empty deque."""
        self._items = deque()

    def add_front(self, item):
        """Add an item to the front of the deque."""
```

```
        self._items.appendleft(item)

    def add_rear(self, item):
        """Add an item to the rear of the deque."""
        self._items.append(item)

    def remove_front(self):
        """Remove and return the front item, or None if empty."""
        if self.is_empty():
            return None
        return self._items.popleft()

    def remove_rear(self):
        """Remove and return the rear item, or None if empty."""
        if self.is_empty():
            return None
        return self._items.pop()

    def is_empty(self):
        """Return True when the deque has no items."""
        return len(self._items) == 0

if __name__ == "__main__":
    queue = DoubleEndedQueue()

    queue.add_rear(10)
    queue.add_rear(20)
    queue.add_front(5)
    print("Deque after adding 10, 20 at the rear and 5 at the front:", queue._items)
```

```
print("Removed from front:", queue.remove_front())
print("Removed from rear:", queue.remove_rear())
print("Deque after removals:", queue._items)
print("Is deque empty?", queue.is_empty())
```

output:

```
PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDriv
e/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t6.py"
Deque after adding 10, 20 at the rear and 5 at the front: deque([5, 10, 20])
Removed from front: 5
Removed from rear: 20
Deque after removals: deque([10])
Is deque empty? False
PS C:\Users\chait\OneDrive\Desktop\AIAC>
```

Q7

Task: Real-Time Application Challenge – Choose the Right Data Structure

Scenario:

Your college wants to develop a Campus Resource Management System that handles:

1. Student Attendance Tracking – Daily log of students entering/exiting the campus.
2. Event Registration System – Manage participants in events with quick search and removal.
3. Library Book Borrowing – Keep track of available books and their due dates.

4. Bus Scheduling System – Maintain bus routes and stop connections.
5. Cafeteria Order Queue – Serve students in the order they arrive.

Student Task:

 For each feature, select the most appropriate data structure from the list below:

o Stack

o Queue

o Priority Queue

o Linked List

o Binary Search Tree (BST)

o Graph

o Hash Table

o Deque

 Justify your choice in 2–3 sentences per feature.

 Implement one selected feature as a working Python program with

AI-assisted code generation.

Expected Output:

 A table mapping feature → chosen data structure → justification.

 A functional Python program implementing the chosen feature

with comments and docstrings.

Prompt: Create a simple Python Event Registration System using a Hash Table (dictionary). Include student registration, searching, deleting, and displaying records using Student ID. Add comments, docstrings, and sample output. Keep the code beginner-friendly and menu-driven.

Code:

```
"""Simple event registration system backed by a hash table (dictionary)."""


registrations = {}


def register():
    """Register or update a student's event registration."""
    student_id = input("Enter Student ID: ").strip()
    if not student_id:
        print("Student ID cannot be empty.")
        return
```

```
    name = input("Enter Student Name: ").strip()
    event = input("Enter Event Name: ").strip()
    registrations[student_id] = [name, event]
    print("Registration successful!")

def search():
    """Search for a student using Student ID."""
    student_id = input("Enter Student ID: ").strip()
    if student_id in registrations:
        name, event = registrations[student_id]
        print("Name:", name)
        print("Event:", event)
    else:
        print("Student not found.")

def remove():
    """Remove a student's registration."""
    student_id = input("Enter Student ID: ").strip()
    if student_id in registrations:
        del registrations[student_id]
        print("Registration removed!")
    else:
        print("Student not found.")

def display():
    """Display all registered students."""
    if not registrations:
        print("No registrations found.")
        return
```

```
    for student_id, (name, event) in registrations.items():
        print(student_id, name, event)


def main():
    """Run the event registration menu."""
    while True:
        print("\n1. Register")
        print("2. Search")
        print("3. Remove")
        print("4. Display")
        print("5. Exit")

        choice = input("Enter choice: ").strip()
        if choice == "1":
            register()
        elif choice == "2":
            search()
        elif choice == "3":
            remove()
        elif choice == "4":
            display()
        elif choice == "5":
            print("Thank you!")
            break
        else:
            print("Invalid choice")

if __name__ == "__main__":
```

main()

output:



Q8

Task: Smart E-Commerce Platform – Data Structure Challenge

An e-commerce company wants to build a Smart Online Shopping System with:

1. Shopping Cart Management – Add and remove products dynamically.

2. Order Processing System – Orders processed in the order they are placed.

3. Top-Selling Products Tracker – Products ranked by sales count.

4. Product Search Engine – Fast lookup of products using product ID.

5. Delivery Route Planning – Connect warehouses and delivery

locations.

Student Task:

 For each feature, select the most appropriate data structure from

the list below:

o Stack

o Queue

o Priority Queue

o Linked List

o Binary Search Tree (BST)

o Deque

 Justify your choice in 2–3 sentences per feature.

 Implement one selected feature as a working Python program with

AI-assisted code generation.

Expected Output:

 A table mapping feature → chosen data structure → justification.

 A functional Python program implementing the chosen feature

with comments and docstrings.

Prompt: Create a simple Python Smart E-Commerce System using suitable data structures. Implement shopping cart, order processing, top-selling products, product search, and delivery planning. Add comments, docstrings, and sample output.

Code:

```
# Smart E-Commerce System
# Data Structure: Deque

from collections import deque

cart = deque()
```

```
def add_product(product):
    """Add a product to the shopping cart."""
    cart.append(product)
    print(product, "added to cart.")


def remove_product():
    """Remove the last product from the shopping cart."""
    if cart:
        product = cart.pop()
        print(product, "removed from cart.")
    else:
        print("Cart is empty.")


def display_cart():
    """Display all products in the cart."""
    print("Shopping Cart:", list(cart))


# Main program
add_product("Laptop")
add_product("Headphones")
add_product("Mouse")

display_cart()

remove_product()
```

display_cart()

output:

