

Server.

```
sai_pranavi@LAPTOP-RVOHSPKQ:~$ nano server.c
sai_pranavi@LAPTOP-RVOHSPKQ:~$ nano socket.c
sai_pranavi@LAPTOP-RVOHSPKQ:~$ gcc socket.c -o socket
socket.c: In function 'main':
socket.c:16:6: error: 'Server_fd' undeclared (first use in this function); did you mean 'server_fd'?
   16 | bind(Server_fd,(struct sockaddr *)&address, sizeof(address));
      |      ^~~~~~
      |      server_fd
socket.c:16:6: note: each undeclared identifier is reported only once for each function it appears in
sai_pranavi@LAPTOP-RVOHSPKQ:~$ nano server.c
sai_pranavi@LAPTOP-RVOHSPKQ:~$ nano socket.c
sai_pranavi@LAPTOP-RVOHSPKQ:~$ gcc socket.c -o socket
sai_pranavi@LAPTOP-RVOHSPKQ:~$ ./socket
Server waiting...
Message from client: Hello Server
```

```
GNU nano 8.7.1 socket.c
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>
#define SOCKET_PATH "/tmp/my_socket"
int main()
{
    int server_fd, client_fd;
    struct sockaddr_un address;
    char buffer[100];
    server_fd = socket(AF_UNIX, SOCK_STREAM, 0);
    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);
    unlink(SOCKET_PATH);
    bind(server_fd,(struct sockaddr *)&address, sizeof(address));
    listen(server_fd, 5);
    printf("Server waiting...\n");
    client_fd = accept(server_fd, NULL, NULL);
    read(client_fd, buffer, sizeof(buffer));
    printf("Message from client: %s\n", buffer);
    close(client_fd);
    close(server_fd);
    unlink(SOCKET_PATH);
    return 0;
}
```

Client

```
sai_pranavi@LAPTOP-RVOHSPKQ:~$ nano clientt.c
sai_pranavi@LAPTOP-RVOHSPKQ:~$ gcc client.c -o client
sai_pranavi@LAPTOP-RVOHSPKQ:~$ gcc clientt.c -o clientt
clientt.c:1:10: fatal error: Stdio.h: No such file or directory
  1 | #include <Stdio.h>
    |             ^~~~~~
compilation terminated.
sai_pranavi@LAPTOP-RVOHSPKQ:~$ nano clientt.c
sai_pranavi@LAPTOP-RVOHSPKQ:~$ gcc clientt.c - clientt
clientt.c:2:10: fatal error: unist.h: No such file or directory
  2 | #include <unist.h>
    |             ^~~~~~
compilation terminated.
gcc: error: -E or -x required when input is from standard input
sai_pranavi@LAPTOP-RVOHSPKQ:~$ nano clientt.c
sai_pranavi@LAPTOP-RVOHSPKQ:~$ gcc clientt.c -o clientt
sai_pranavi@LAPTOP-RVOHSPKQ:~$ ./clientt
Message sent to server.
sai_pranavi@LAPTOP-RVOHSPKQ:~$
```

```
GNU nano 8.7.1 clientt.c
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>
#define SOCKET_PATH "/tmp/my_socket"
int main()
{
    int client_fd;
    struct sockaddr_un address;
    client_fd = socket(AF_UNIX, SOCK_STREAM, 0);
    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);
    connect(client_fd, (struct sockaddr *)&address, sizeof(address));
    write(client_fd, "Hello Server", 12);
    printf("Message sent to server.\n");
    close(client_fd);
    return 0;
}
```