



OFFICIAL CLIENT LIBRARIES

[read more](#)**GETTING STARTED**

Authentication
JSON Response
IP Address Parameter
HTTPS/ SSL
Rate Limits
Filtering Responses
JSONP/ CORS Requests
IPv6 API Endpoint

DATA TYPES

Geolocation Data
ASN Data
Privacy Data
Carrier Data
Company Data
Hosted Domains Data
Abuse Contact Data
IP Type Data

OTHER APIS

ASN API
Ranges API
Hosted Domains API
IP Whois API

RESPONSES

Lite API
Core Plan
Standard Plan
Business Plan
Enterprise Plan

ADVANCED USAGE

Batching Requests
Command Line Interface (CLI)

DATABASE DOWNLOAD

Getting Started
Database Operations
Cloud Data Delivery
Ecosystem Integrations

IPinfo Developer Resource

The quickest and easiest way to get started with IPinfo is to use one of our [official libraries](#), which are available for many popular programming languages and frameworks. If you'd like to write your own library or interact directly with our API, then the documentation below can help you.

Authentication

Your API token is used to authenticate you with our API and can be provided either as an HTTP Basic Auth username, a bearer token, or alternatively as a token URL parameter.

```
# With Basic Auth
$ curl -u ca7bf6e0463fc8: ipinfo.io

# With Bearer token
$ curl -H "Authorization: Bearer ca7bf6e0463fc8" ipinfo.io

# With token query parameter
$ curl ipinfo.io?token=ca7bf6e0463fc8
```

JSON Response

We try to automatically detect if someone wants to view our website, and then we send back the appropriate JSON response rather than HTML. We do this based on the user agent for known popular programming

Do you need any help with API integration or want to chat with us about the use case you have?

[Drop us a message](#)



Database Guides
Database Filename Reference

DATABASE TYPES

IP To Geolocation
Privacy Detection
IP To Company
ASN Database
IP To Mobile Carrier
Hosted Domains
IP To Residential Proxy
Abuse Contact
IPinfo Lite
IPinfo Core
IPinfo Plus
IP WHOIS
IP To Geolocation Extended
Privacy Detection Extended

INTEGRATIONS

Snowflake
Google Cloud / BigQuery

LIBRARIES

OPENAPI SPEC

GUIDES

DATA

Developer Resource - IPinfo.io

languages, tools, and frameworks.

However, there are a couple of other ways to force a JSON response when it doesn't happen automatically.

One is to append `/json` at the end of any request:

```
$ curl ipinfo.io/json
$ curl ipinfo.io/8.8.8.8/json
```

The other is to set the `Accept` header to `application/json`:

```
$ curl -H "Accept: application/json"
ipinfo.io
$ curl -H "Accept: application/json"
ipinfo.io/8.8.8.8
```

IP Address Parameter

The API supports passing in a single IPv4 or IPv6 IP address. Alternatively, if you do not pass in any IP address, we'll return details for the calling address. This allows you to look up your own (or a visitor to your site) IP address details without knowing the IP address in advance.

```
# Get details for 8.8.8.8
$ curl ipinfo.io/8.8.8.8?
token=ca7bf6e0463fc8

# Get details for
2001:4860:4860::8888
$ curl
ipinfo.io/2001:4860:4860::8888?
token=ca7bf6e0463fc8

# Get details for your own IP
address, which'll be included in the
response
$ curl ipinfo.io?
token=ca7bf6e0463fc8
```

HTTPS/ SSL

Our API is available over a secure HTTPS connection for all users. Simply add

<https://> to the request URLs to make the requests secure.

```
# Get details for your own IP
address over HTTPS
$ curl https://ipinfo.io?
token=ca7bf6e0463fc8
```

Rate Limits

Our free plan offers unlimited access to our API.

Paid plans include monthly request limits with configurable alerts to help you stay in control. If you exceed your plan's limit, you'll receive a 429 HTTP status code—but with metered billing, you can automatically extend your usage without interruptions.

[Paid plans](#) come with higher monthly limits, and configurable alerts.

Filtering Responses

You can filter the API response down to specific fields or objects by adding the field or object name to the URL. In the case of a field you'll get it returned in plaintext, and an object will get returned as JSON.

```
# Get json the org field as
plaintext
$ curl ipinfo.io/8.8.8.8/org?
token=ca7bf6e0463fc8
AS15169 Google Inc.

# Get just the city as plaintext
$ curl ipinfo.io/8.8.8.8/city?
token=ca7bf6e0463fc8
Mountain View

# Get country ISO code as plaintext
$ curl ipinfo.io/8.8.8.8/country?
token=ca7bf6e0463fc8
US
```

JSONP/ CORS Requests

JSONP and CORS are supported, allowing you to use ipinfo.io entirely in client-side code. For JSONP you just need to specify the callback parameter, e.g.

`http://ipinfo.io/?
callback=callback&token=ca7bf6e0463fc8.`

Request visitor data using Fetch API (Promise)

```
fetch("https://ipinfo.io/json?  
token=ca7bf6e0463fc8").then(  
  (response) => response.json()  
)  
.then(  
  (jsonResponse) =>  
    console.log(jsonResponse.ip,  
      jsonResponse.country)  
)
```

Request visitor data using Fetch API (Async/Await)

```
const request = await  
fetch("https://ipinfo.io/json?  
token=ca7bf6e0463fc8")  
const jsonResponse = await  
request.json()  
  
console.log(jsonResponse.ip,  
  jsonResponse.country)
```

Request visitor data using JSONP

```
<script>  
  function recordData (data) {  
    console.log(data.ip,  
      data.country)  
  }  
</script>  
<script src="https://ipinfo.io/json?  
callback=recordData"></script>
```

IPv6 API endpoint

IPinfo's API ensures seamless support for both IPv4 and IPv6 connection. However, for technical reasons, we use distinct API endpoints:

- **IPv4 connection:** ipinfo.io

- **IPv6 connection:** v6.ipinfo.io

If you're on an IPv6 address, use the v6.ipinfo.io API endpoint, which functions identically to the standard IPv4 API. All API parameters and arguments are supported as usual.

Example:

```
curl https://v6.ipinfo.io
```

Our website, however, is fully dual-stacked, supporting both IPv4 and IPv6 natively through the ipinfo.io domain. Our IP data download product always includes both IPv4 and IPv6 IP addresses in each individual database download. If you are looking up IPv6 addresses as an API parameter or input, you can do so simply as well. Usage of v6.ipinfo.io only applies to IPv6 traffic visiting our API service.

Why Separate API Endpoints?

By separating the API endpoints, we prevent unintended behavior when tools default to IPv6 (via AAAA records). This ensures you receive the expected address type for your query. Because if we have A and AAAA records for the domain (supporting both v4 and v6), the users would get their v6 address back when they go to ipinfo.io's API (internet services usually default to v6 if it's available), which is not usually what they expect.

Database Downloads

IP Geolocation Database

Abuse Contact Database

IP to Company Database

IP to Privacy Detection Database

[IP to Mobile Carrier Database](#)

[IP to Hosted Domains Database](#)

[IP to ASN Database](#)

[IP Whois Database](#)

[Free IP to Country + ASN](#)

API Products

[IP Geolocation API](#)

[IP Ranges API](#)

[Privacy Detection API](#)

[IP to Company](#)

[ASN API](#)

[Hosted Domains API](#)

[IP to Mobile Carrier](#)

[Abuse Contact API](#)

[IP Whois API](#)

Data

[Our data](#)

[My IP Address](#)

[Tools](#)

[Country Internet Data](#)

[Global Geolocation Accuracy](#)

[IP Address Tags](#)

[Hosted domains by ASNs](#)

[IP Ranges](#)

[Open access](#)

Resources

[Documentation](#)

[Libraries](#)

[Help Centre](#)

[Blog](#)

[E-books](#)

[Use cases](#)

[Integrations](#)

[What is an IP address?](#)



Company

About

Careers

Community

Customers

Contact Support



Copyright © 2024 IPinfo® | [Terms & Conditions](#) · [Privacy Policy](#)

Consent
Preferences ^