Context-Window Degradation and Its Impact on Long-Document Research Synthesis: A Review of Failure Modes, Evaluation, and Mitigation

PRANAV KUMAR GUPTA, Indian Institute of Information Technology Allahabad, India

Large language models (LLMs) increasingly accept very long input contexts, creating the expectation that books, code repositories, legal collections, and scientific literature can be processed in a single inference step. A growing body of empirical work, however, shows that nominal context capacity does not guarantee reliable use of information throughout that context. This review synthesizes research on context-window degradation, with particular attention to the "lost in the middle" phenomenon, long-context evaluation, retrieval-augmented generation (RAG), adaptive context selection, and training-based mitigation. The review organizes the literature into four interacting layers: architectural capacity, positional utilization, evaluation methodology, and mitigation strategy. We compare representative studies by problem formulation, method, evaluation setting, principal finding, and limitation. The synthesis shows that simple retrieval tests can overestimate long-context competence because literal lexical matching can make evidence unusually easy to locate, whereas evaluations that require latent association or multi-step reasoning expose stronger degradation. RAG reduces the amount of distractor context but can fragment global coherence; adaptive retrieval reduces unnecessary tokens but does not by itself solve holistic synthesis; and training-based approaches target positional bias more directly. We conclude by identifying research needs around task-aware evaluation, evidence coverage, global-local context integration, reproducible effective-context measurements, and hybrid memory architectures.

CCS Concepts: • **Computing methodologies** → **Natural language processing**; *Machine learning*; • **Information systems** → *Information retrieval*.

Additional Key Words and Phrases: long-context language models, context-window degradation, lost in the middle, retrieval-augmented generation, long-context evaluation, adaptive retrieval, effective context window

1 Introduction

Transformer-based language models derive their ability to model relationships across tokens from attention mechanisms [9]. As context limits have expanded, a natural assumption has emerged: if a model can technically accept a very large number of tokens, it should be able to use information distributed across that entire input. The literature reviewed here shows that this assumption is incomplete. Long-context capability has at least two distinct dimensions: *capacity*, meaning how many tokens can be accepted, and *effective utilization*, meaning how reliably the model can retrieve and reason over relevant information at different positions and levels of abstraction.

The distinction matters for research synthesis. A long scholarly document is not simply a large collection of independent facts. A useful synthesis may require locating evidence, connecting claims across sections, resolving terminology, comparing methods, and preserving relationships between findings. A model can therefore succeed on a short retrieval probe while failing on a multi-document synthesis task.

Liu et al. [5] provided influential evidence for positional degradation: on multi-document question answering and key-value retrieval, performance can fall when relevant information is moved toward the middle of a long input. NoLiMa later challenged the sufficiency of literal-match evaluation by constructing retrieval conditions with minimal lexical overlap between questions and target information; under those conditions, performance degradation became more

Author's Contact Information: Pranav Kumar Gupta, Indian Institute of Information Technology Allahabad, Prayagraj, India, MHM2026012.

2026. Manuscript submitted to ACM




Fig. 1. Review synthesis workflow used in this manuscript. The loop indicates that identified gaps can motivate refinement of the literature scope.

pronounced as context length increased [6]. These studies motivate a broader question: *what does it mean for a model to genuinely use a long context?*

This review addresses that question through five objectives:

(1) distinguish nominal context capacity from effective information utilization;
(2) synthesize evidence for positional, distractor, and reasoning-related degradation;
(3) compare direct long-context processing with RAG and adaptive context-selection approaches;
(4) organize current mitigation strategies into a taxonomy; and
(5) identify research gaps that remain after existing retrieval and training interventions.

The remainder of the paper is organized as follows. Section 2 describes the review scope. Section 3 establishes technical foundations. Section 4 presents a taxonomy of degradation mechanisms and responses. Section 5 discusses evaluation methodology. Section 7 compares representative studies. Sections 8 and 9 synthesize limitations and research directions, followed by the conclusion in Section 11.

2 Review Scope and Synthesis Method

This manuscript is a focused narrative review rather than a systematic meta-analysis. It develops the previously submitted manuscript around a defined set of representative publications covering the Transformer foundation, RAG, positional degradation, long-context evaluation, adaptive retrieval, and training-based mitigation. The core literature includes the six references already used in the submitted draft, supplemented with foundational and closely related peer-reviewed/archival publications to strengthen the comparative synthesis.

The review uses four analytical dimensions:

Problem What failure or capability does the study investigate?
Method What architectural, retrieval, evaluation, or training intervention is used?
Evidence What task, benchmark, dataset, or measurement supports the claims?
Limitation What does the method leave unresolved for long-document synthesis?

Figure 1 summarizes the resulting review workflow. This structure deliberately separates evidence reported by individual studies from the synthesis performed in this review.

3 Technical Foundations

3.1 Attention and the Cost of Long Context

The Transformer architecture computes attention relationships between tokens [9]. In a standard self-attention layer, the attention matrix contains pairwise interactions whose storage and computation grow approximately quadratically with sequence length. A simplified asymptotic expression is

$$C_{\text{attn}}(n) = O(n^2), \tag{1}$$

where n is the number of tokens. Equation 1 describes computational scaling; it does *not* by itself imply that a model will fail at long contexts. Degradation is an empirical utilization problem involving attention distribution, learned positional behavior, distractors, and task complexity.

3.2 Nominal Capacity Versus Effective Utilization

A useful conceptual distinction is between the marketed or configured maximum context window and the range over which task performance remains acceptable. Paulsen's discussion of the Maximum Effective Context Window (MECW) formalizes this distinction for real-world use [7]. In this review, effective utilization is represented conceptually as

$$U(L, T) = \frac{P(L, T)}{P(L_0, T)}, \tag{2}$$

where $P(L, T)$ denotes performance on task T at context length L, and L_0 is a shorter reference context. Equation 2 is an analytical normalization proposed for comparison in this review, not a new empirical result. It emphasizes that context capability should be reported together with task, context length, evidence position, and performance.

4 Taxonomy of Context-Window Degradation

The reviewed literature can be organized into four interacting layers, shown in Figure 2. The first concerns the model's capacity and attention architecture. The second concerns how evidence is positioned and represented. The third concerns how long-context ability is evaluated. The fourth concerns mitigation through retrieval, context selection, calibration, or training.

4.1 Architectural and Attention-Level Factors

The Transformer foundation provides flexible token-to-token interaction but does not guarantee uniform information use [9]. Liu et al. [5] empirically observed that relevant information can be easier to access near the beginning or end of an input than in its middle. Hsieh et al. [3] connect this behavior to an intrinsic U-shaped positional attention bias and propose a calibration mechanism to reduce it.

The evidence suggests that context degradation should not be described as a single failure mode. Architecture influences what is computationally possible, but training and inference behavior determine how available capacity is actually used.

4.2 Position, Distractors, and Representation

The "lost in the middle" effect is fundamentally positional: the same relevant information can produce different outcomes when moved through a long context [5]. DENIAHL further examines how the placement and density of in-context features influence needle-in-a-haystack performance [1]. This indicates that context length alone is insufficient as




Fig. 2. Taxonomy of the main dimensions used to synthesize the reviewed long-context literature.

an evaluation variable. A meaningful test should also specify where evidence occurs, how much irrelevant material surrounds it, and whether the query shares vocabulary with the target evidence.

4.3 Recall Versus Reasoning

Long-context retrieval and long-context reasoning are related but not identical. NoLiMa reduces the usefulness of literal lexical matching by requiring models to infer latent associations between the question and relevant information [6]. Its results show that a model can appear strong under simple retrieval conditions while degrading substantially when the retrieval problem requires more semantic inference.

This distinction is especially important for research synthesis. Scientific review requires evidence aggregation rather than the recovery of one isolated sentence. Therefore, benchmarks that only ask whether a single fact can be retrieved may not predict synthesis quality.

5 Evaluation of Long-Context Capability

5.1 Needle-in-a-Haystack and Its Extensions

Needle-in-a-Haystack (NIAH) tests insert a target fact into a long distractor context and measure whether the model can recover it. NIAH is useful because it permits controlled manipulation of context length and target position. However, literal overlap between the query and target can simplify retrieval. NoLiMa addresses this issue by reducing lexical overlap and requiring latent associations [6].

DENIAHL complements this perspective by varying the placement and density of relevant features [1]. Together, these works suggest that evaluation should move from a single “needle found/not found” outcome toward a multidimensional description of evidence accessibility.

5.2 Multi-Document Question Answering

Multi-document QA is closer to research synthesis because the answer can depend on multiple pieces of evidence. Liu et al. [5] used multi-document QA and key-value retrieval to show that positional changes can alter model performance. He et al. [2] address the same family of problems through Position-Agnostic Multi-step QA, decomposing information seeking and answer aggregation.

5.3 What Should a Long-Context Benchmark Report?

Based on the reviewed studies, a useful benchmark should report at least:

(1) context length;
(2) position of relevant evidence;
(3) distractor density and semantic similarity;
(4) lexical overlap between query and evidence;
(5) whether one or multiple evidence pieces are required;
(6) retrieval accuracy separately from final answer accuracy; and
(7) computational/token cost where retrieval or context selection is used.

This reporting structure makes results more comparable across studies and reduces the risk of treating nominal context length as a complete measure of long-context capability.

6 Mitigation Approaches

6.1 Retrieval-Augmented Generation

RAG combines a language model with external non-parametric memory, retrieving relevant passages before generation [4]. Its central advantage for long-context tasks is selective exposure: the model need not process every available document at the same time. However, standard chunking can disrupt document-level coherence.

LongRAG explicitly targets this global-local tension by combining longer retrieval units with mechanisms for preserving global information while retrieving factual details [10]. The approach illustrates a broader design principle: retrieval should reduce irrelevant context without discarding the relationships needed for synthesis.

6.2 Adaptive Context Selection

Fixed-k retrieval assumes that every query needs the same number of passages. Taguchi et al. [8] propose Adaptive-k, which selects a query-specific number of passages using similarity-score distributions. Their experiments report matching or exceeding fixed-k baselines while using substantially fewer tokens, including up to 10 times fewer tokens than full-context input in the reported evaluation.

Adaptive selection therefore addresses efficiency and distractor reduction. It does not, however, eliminate the need for global synthesis when relevant evidence is distributed across distant parts of a document.

6.3 Training and Positional Calibration

Training-based methods attempt to change the model rather than only changing the input. Hsieh et al. [3] use calibration to reduce positional attention bias, while He et al. [2] introduce position-agnostic decompositional training. These approaches are complementary to retrieval: retrieval changes *what* enters the context, while training can change *how* the model uses that context.

Table 1. Comparative synthesis of representative long-context studies.

Study	Primary problem	Method / setting	Main reported evidence	Limitation relevant to synthesis
Liu et al. [5]	Positional utilization	Multi-document QA; key-value retrieval	Performance often declines when relevant information is moved to the middle of long contexts	Focuses on controlled retrieval/access tasks rather than full scholarly synthesis
Dai et al. [1]	Feature placement and density	DENIAHL needle-in-a-haystack evaluation	In-context feature placement and density affect retrieval ability	Needle-style tasks remain narrower than holistic document understanding
Modarressi et al. [6]	Literal-match shortcuts	NoLiMa with low lexical overlap	Many evaluated models degrade strongly as context grows; at 32K, most tested models fell below 50% of strong short-context baselines	Evaluation is still primarily retrieval-oriented
Zhao et al. [10]	RAG/global-context trade-off	LongRAG for long-context QA	Reported gains over long-context LLMs, advanced RAG, and vanilla RAG on multi-hop datasets	Gains are task/dataset dependent; global synthesis remains challenging
Taguchi et al. [8]	Retrieval budget selection	Single-pass Adaptive-k	Reported up to 10× token reduction versus full-context input while retaining relevant passages	Dynamic selection does not guarantee complete evidence coverage
Hsieh et al. [3]	Positional attention bias	Calibration of attention behavior	Reports improved middle-position utilization and downstream RAG performance	Requires model-specific calibration and does not address all long-context failure modes
He et al. [2]	Long-context QA retrieval and aggregation	Position-Agnostic Multi-step QA training	Reports improvements on shuffled and passage-retrieval settings	Training data and task design may not transfer uniformly across domains

7 Comparative Analysis

Table 1 synthesizes representative studies along the dimensions defined in Section 2. The table is intentionally comparative rather than ranking methods, because different studies target different failure modes.

A second comparison is useful at the system-design level. Table **??** distinguishes the principal trade-offs without assigning an overall winner.

8 Discussion: What the Literature Establishes

Three conclusions emerge from the comparison.

Table 2. Taxonomy of long-context limitations in literature synthesis.

Limitation category	Primary cause	Synthesis failure mode	Illustrative evidence
Positional bias	Attention decay and positional encoding limitations in mid-context	Key findings located in the middle of long papers are ignored or downweighted	Liu et al. [5], Hsieh et al. [3]
Lexical shortcut reliance	Over-reliance on exact word matches during retrieval	Failure to synthesize semantically related but differently phrased arguments	Modarressi et al. [6]
Feature density	Information overload across high-density context windows	Missing subtle relationships across multiple high-density sections	Dai et al. [1]
Retrieval-synthesis gap	Disconnect between local chunk retrieval and global document context	Fragmented summaries that miss paper-wide logical arcs	Zhao et al. [10], Taguchi et al. [8]




Fig. 3. Conceptual illustration of a U-shaped positional utilization pattern associated with "lost in the middle." The curve is schematic and is not a new empirical measurement.

First, *context capacity is not equivalent to context competence.* The repeated observation of positional degradation means that a context window should be treated as an available resource rather than a guarantee of uniform information access [3, 5].

Second, *evaluation design changes the apparent severity of the problem.* Literal-match NIAH tasks can test whether a model can locate a recognizable target. NoLiMa shows why stronger tests should remove lexical shortcuts and require latent associations [6]. For research synthesis, the gap is even larger because multiple pieces of evidence may need to be connected.

Third, *mitigation methods solve different parts of the problem.* RAG reduces the amount of irrelevant material; adaptive selection controls the retrieval budget; LongRAG-style designs attempt to preserve global context; and training-based methods directly target positional utilization [2, 3, 8, 10]. These approaches should therefore be viewed as complementary components rather than interchangeable alternatives.

Figure 3 illustrates the conceptual distinction between nominal capacity and effective utilization. It is a schematic, not a measured curve from a particular model.




Fig. 4. Proposed evaluation framework synthesized from the reviewed literature. It combines position, distractor, reasoning, system strategy, and efficiency dimensions.

9 Research Gaps and Future Directions

9.1 Gap 1: From Retrieval to Holistic Synthesis

Existing benchmarks provide strong evidence for retrieval degradation, but research synthesis requires more than locating a target. Future benchmarks should require models to combine evidence distributed across multiple positions and documents, while separately reporting evidence retrieval and final synthesis quality.

9.2 Gap 2: Evidence Coverage as a First-Class Metric

A generated answer may be correct while omitting important evidence, or it may cite retrieved passages without integrating them correctly. Future work should measure evidence coverage, evidence consistency, and claim-level attribution in addition to answer accuracy.

9.3 Gap 3: Reproducible Effective Context Windows

MECW-like measurements are valuable because they convert an abstract context limit into a task-dependent performance profile [7]. However, the effective window depends on model, task, evidence position, distractor distribution, and evaluation threshold. A standardized reporting protocol could define the test task, baseline context, acceptable performance loss, and confidence interval rather than reporting one universal context length.

9.4 Gap 4: Global–Local Context Integration

RAG and adaptive retrieval reduce irrelevant information, but aggressive selection can omit cross-document relationships. LongRAG demonstrates one attempt to retain both global information and local evidence [10]. Future systems should make the global/local trade-off explicit, possibly through hierarchical representations or iterative evidence aggregation.

9.5 Gap 5: Architecture–Training–Retrieval Co-Design

The literature currently contains architectural, training, and retrieval solutions that are often evaluated separately. A promising direction is a unified system in which the retrieval policy, memory representation, positional calibration, and reasoning procedure are jointly optimized. Such a system should be evaluated under both retrieval-heavy and synthesis-heavy workloads.

10 Recommended Evaluation Framework

Based on the reviewed evidence, a practical evaluation protocol for long-document research synthesis can be organized into five stages, as shown in Figure 4.

The key principle is that no single score should stand in for long-context competence. Results should be reported as a profile across context length, evidence position, task complexity, retrieval strategy, and cost. Equation 2 can be used as one normalized view, while raw task performance should remain available for interpretation.

11 Conclusion

The reviewed literature establishes a consistent distinction between the ability of an LLM to accept a long context and its ability to use that context reliably. Positional degradation, distractor sensitivity, and the gap between literal retrieval and semantic reasoning all complicate the assumption that a larger context window automatically enables better long-document synthesis.

The literature also shows that mitigation is multidimensional. RAG limits the amount of irrelevant information exposed to the model; LongRAG-style systems attempt to retain global and local evidence; adaptive retrieval controls the number of retrieved passages; and training or calibration methods target positional utilization more directly [2–4, 8, 10]. These approaches address different failure modes and should be evaluated under common task conditions rather than reduced to a single performance ranking.

For research-oriented applications, the central open problem is therefore not simply "how many tokens can the model read?" but "how reliably can the model locate, connect, reason over, and cite the evidence it needs across that context?" Progress will require evaluation protocols that measure these capabilities separately, together with system designs that integrate global memory, targeted retrieval, positional robustness, and evidence-aware reasoning.

Acknowledgments

This manuscript was prepared as a course submission using LaTeX and BibTeX. The review expands a previously prepared manuscript on context-window degradation and reorganizes it to satisfy the current assignment requirements for comparative synthesis, figures, tables, equations, and cross-referencing.

References

[1] Hui Dai, Dan Pechi, Xinyi Yang, Garvit Banga, and Raghav Mantri. 2024. DENIAHL: In-Context Features Influence LLM Needle-In-A-Haystack Abilities. *arXiv preprint arXiv:2411.19360* (2024). doi:10.48550/arXiv.2411.19360

[2] Junqing He, Kunhao Pan, Xiaoqun Dong, Zhuoyang Song, Yibo Liu, Qianguo Sun, Yuxin Liang, Hao Wang, Enming Zhang, and Jiaxing Zhang. 2024. Never Lost in the Middle: Mastering Long-Context Question Answering with Position-Agnostic Decompositional Training. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, 13628–13642. doi:10.18653/v1/2024.acl-long.736

[3] Cheng-Yu Hsieh, Yung-Sung Chuang, Chun-Liang Li, Zifeng Wang, Long Le, Abhishek Kumar, James Glass, Alexander Ratner, Chen-Yu Lee, Ranjay Krishna, and Tomas Pfister. 2024. Found in the Middle: Calibrating Positional Attention Bias Improves Long Context Utilization. In *Findings of the Association for Computational Linguistics: ACL 2024*. https://aclanthology.org/2024.findings-acl.890/

[4] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Kuttler, Mike Lewis, Wen-tau Yih, Tim Rocktaschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. In *Advances in Neural Information Processing Systems*, Vol. 33. https://proceedings.neurips.cc/paper/2020/hash/6b493230205f780e1bc26945df7481e5-Abstract.html

[5] Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the Middle: How Language Models Use Long Contexts. *Transactions of the Association for Computational Linguistics* 12 (2024), 157–173. doi:10.1162/tacl_a_00638

[6] Ali Modarressi, Hanieh Deilamsalehy, Franck Dernoncourt, Trung Bui, Ryan A. Rossi, Seunghyun Yoon, and Hinrich Schuetze. 2025. NoLiMa: Long-Context Evaluation Beyond Literal Matching. *arXiv preprint arXiv:2502.05167* (2025). doi:10.48550/arXiv.2502.05167

[7] Norman Paulsen. 2025. Context Is What You Need: The Maximum Effective Context Window for Real World Limits of LLMs. *arXiv preprint arXiv:2509.21361* (2025). Published version: Advances in Artificial Intelligence and Machine Learning, 6(1), 4853–4878 (2026), DOI 10.54364/AAIML.2026.61268. doi:10.48550/arXiv.2509.21361

[8] Chihiro Taguchi, Seiji Maekawa, and Nikita Bhutani. 2025. Efficient Context Selection for Long-Context QA: No Tuning, No Iteration, Just Adaptive-k. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 20105–20130. doi:10.18653/v1/2025.emnlp-main.1017

[9] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention Is All You Need. In *Advances in Neural Information Processing Systems*, Vol. 30. https://arxiv.org/abs/1706.03762

[10] Qingfei Zhao, Ruobing Wang, Yukuo Cen, Daren Zha, Shicheng Tan, Yuxiao Dong, and Jie Tang. 2024. LongRAG: A Dual-Perspective Retrieval-Augmented Generation Paradigm for Long-Context Question Answering. *arXiv preprint arXiv:2410.18050* (2024). doi:10.48550/arXiv.2410.18050