



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

Experiment No. 9
To create and train an Object Detector
Date of Performance:
Date of Submission:
Name: Pranav Maurya



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

Aim: To Creating and Training an Object Detector

Objective: Bag of Words BOW in computer vision Detecting cars in a scene.

Theory :

Creating and Training an object detector:-

Using built-in features makes it easy to come up with a quick prototype for an application. and we're all very grateful to the OpenCV developers for making great features, such as face detection or people detection readily available (truly, we are). However, whether you are a hobbyist or a computer vision professional, it's unlikely that you will only deal with people and faces:

Bag-of –words:-

Bag-of-words (BOW) is a concept that was not initially intended for computer vision, rather, we use an evolved version of this concept in the context of computer vision. So, let's first talk about its basic version, which-as you may have guessed-originally belongs to the field of language analysis and information retrieval. BOW is the technique by which we assign a count weight to each word in a series of documents; we then represent these documents with vectors that represent these

set of counts. Let's look at an example:

Document 1: like OpenCV and I like Python

Document 2: like C++ and Python

Document 3: don't like artichokes

BOW in Computer Vision :-

We are by now familiar with the concept of image features. We've used feature extractors, such as SIFT, and SURF, to extract features from images so that we could match these features in another image. We've also familiarized ourselves with the concept of codebook, and we know about SVM, a model that can be fed a set of features and utilizes complex algorithms to classify train data, and can predict the classification of new data. So, the implementation of a BOW approach will involve the following steps:



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

1. Take a sample dataset.
2. For each image in the dataset, extract descriptors (with SIFT, SURF, and so on).
3. Add each descriptor to the BOW trainer.
4. Cluster the descriptors to k clusters (okay, this sounds obscure, but bear with me) whose centers (centroids) are our visual words.

Detecting cars

There is no virtual limit to the type of objects you can detect in your images and videos. However, to obtain an acceptable level of accuracy, you need a sufficiently large dataset containing train images that are identical in size. This would be a time-consuming operation if we were to do it all by ourselves.

Example – car detection in a scene

We are now ready to apply all the concepts we learned so far to a real-life example, and create a car detector application that scans an image and draws rectangles around cars.

Let's summarize the process before diving into the code:

1. Obtain a train dataset.
2. Create a BOW trainer and create a visual vocabulary.
3. Train an SVM with the vocabulary.
4. Attempt detection using sliding windows on an image pyramid of a test image.
5. Apply non-maximum suppression to overlapping boxes.
6. Output the result.



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

Code :-

```
import cv2

import numpy as np

import os

if not os.path.isdir('CarData'):

    exit(1)

BOW_NUM_TRAINING_SAMPLES_PER_CLASS = 10

SVM_NUM_TRAINING_SAMPLES_PER_CLASS = 110

BOW_NUM_CLUSTERS = 40

sift = cv2.SIFT_create()

FLANN_INDEX_KDTREE = 1

index_params = dict(algorithm=FLANN_INDEX_KDTREE, trees=5)

search_params = dict(checks=50)

flann = cv2.FlannBasedMatcher(index_params, search_params)

bow_kmeans_trainer = cv2.BOWKMeansTrainer(BOW_NUM_CLUSTERS)

bow_extractor = cv2.BOWImgDescriptorExtractor(sift, flann)

def get_pos_and_neg_paths(i):

    pos_path = 'CarData/TrainImages/pos-%d.pgm' % (i+1)

    neg_path = 'CarData/TrainImages/neg-%d.pgm' % (i+1)

    return pos_path, neg_path

def add_sample(path):

    img = cv2.imread(path, cv2.IMREAD_GRAYSCALE)
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

```
keypoints, descriptors = sift.detectAndCompute(img, None)

if descriptors is not None:

    bow_kmeans_trainer.add(descriptors)

for i in range(BOW_NUM_TRAINING_SAMPLES_PER_CLASS):

    pos_path, neg_path = get_pos_and_neg_paths(i)

    add_sample(pos_path)

    add_sample(neg_path)

voc = bow_kmeans_trainer.cluster()

bow_extractor.setVocabulary(voc)

def extract_bow_descriptors(img):

    features = sift.detect(img)

    return bow_extractor.compute(img, features)

training_data = []

training_labels = []

for i in range(SVM_NUM_TRAINING_SAMPLES_PER_CLASS):

    pos_path, neg_path = get_pos_and_neg_paths(i)

    pos_img = cv2.imread(pos_path, cv2.IMREAD_GRAYSCALE)

    pos_descriptors = extract_bow_descriptors(pos_img)

    if pos_descriptors is not None:

        training_data.extend(pos_descriptors)

        training_labels.append(1)

    neg_img = cv2.imread(neg_path, cv2.IMREAD_GRAYSCALE)

    neg_descriptors = extract_bow_descriptors(neg_img)
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

```
if neg_descriptors is not None:

    training_data.extend(neg_descriptors)

    training_labels.append(-1)

svm = cv2.ml.SVM_create()

svm.train(np.array(training_data), cv2.ml.ROW_SAMPLE,

          np.array(training_labels))

for test_img_path in ['CarData/TestImages/test-0.pgm',

                      'CarData/TestImages/test-1.pgm','images/car.jpg','images/haying.jpg',]:

    img = cv2.imread(test_img_path)

    gray_img = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)

    descriptors = extract_bow_descriptors(gray_img)

    prediction = svm.predict(descriptors)

    if prediction[1][0][0] == 1.0:

        text = 'car'

        color = (0, 255, 0)

    else:

        text = 'not car'

        color = (0, 0, 255)

    cv2.putText(img, text, (10, 30), cv2.FONT_HERSHEY_SIMPLEX, 1, color, 2,

cv2.LINE_AA)

    cv2.imshow(test_img_path, img)

cv2.waitKey(0)
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

OUTPUT :-

Input :-



Output:-

No Car





Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

Input :-



Output:-

Car



Conclusion :-

Object recognition is steps to collect the related data for identifying object in digital organization.

BOM model create a histogram of Bow model creates a visual wordy that return an image then this histogram is used to train.