

1: map the localhost to domain name in centos

A:

```
l>[pranay@localhost ~]cat /etc/hosts
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.localdomain4
::1         localhost localhost.localdomain localhost6 localhost6.localdomain6
127.0.0.1    www.google.com
192.168.56.101 www.mysamplesite.com
```

2: do curl

A:

```
[pranay@localhost ~]$ curl http://www.mysamplesite.com
<!doctype html><html lang="en"><head><meta charset="utf-8"><meta name="viewport" content="width=device-width,initial-scale=1,maximum-scale=1,user-scalable=0"><meta name="robots" content="noindex, nofollow"><meta name="referrer" content="no-referrer"><title>Mattermost</title><meta name="mobile-web-app-capable" content="yes"><meta name="application-name" content="Mattermost"><meta name="format-detection" content="telephone=no"><link rel="icon" type="image/png" href="/static/images/favicon/favicon-default-16x16.png" sizes="16x16"><link rel="icon" type="image/png" href="/static/images/favicon/favicon-default-24x24.png" sizes="24x24"><link rel="icon" type="image/png" href="/static/images/favicon/favicon-default-32x32.png" sizes="32x32"><link rel="icon" type="image/png" href="/static/images/favicon/favicon-default-64x64.png" sizes="64x64"><link rel="icon" type="image/png" href="/static/images/favicon/favicon-default-96x96.png" sizes="96x96"><link rel="stylesheet" class="code_theme"><style>.error-screen{font-family:'Helvetica Neue', Helvetica, Arial, sans-serif;padding-top:50px;max-width:750px;font-size:14px;color:#333;margin:auto;display:none;line-height:1.5}.error-screen h2{font-size:30px;font-weight:400;line-height:1.2}.error-screen ul{padding-left:15px;line-height:1.7;margin-top:0;margin-bottom:10px}.error-screen hr{color:#ddd;margin-top:20px;margin-bottom:20px;border:0;border-top:1px solid #eee}.error-screen-visible{display:block}</style><meta http-equiv="Content-Security-Policy" content="script-src 'self' cdn.rudderlabs.com/ js.stripe.com/v3"><script defer="defer" src="/static/main.54a384511ae531961ca5.js"></script><link href="/static/main.d4d4065a633f175eb096.css" rel="stylesheet"><meta name="apple-mobile-web-app-title" content="Mattermost" /><meta name="apple-mobile-web-app-capable" content="yes" /><meta name="apple-mobile-web-app-status-bar-style" content="default" /><link rel="apple-touch-icon" sizes="76x76" href="/static/icon_76x76.png" /><link rel="apple-touch-icon" sizes="72x72" href="/static/icon_72x72.png" /><link rel="apple-touch-icon" sizes="60x60" href="/static/icon_60x60.png" /><link rel="apple-touch-icon" sizes="57x57" href="/static/icon_57x57.png" /><link rel="apple-touch-icon" sizes="152x152" href="/static/icon_152x152.png" /><link rel="apple-touch-icon" sizes="144x144" href="/static/icon_144x144.png" /><link rel="apple-touch-icon" sizes="120x120" href="/static/icon_120x120.png" /><link rel="manifest" href="/static/manifest.json" /></head><body class="font--open_sans enable-animations"><div id="root"><div class="error-screen"><h2>Cannot connect to Mattermost</h2><hr><p>We're having trouble connecting to Mattermost. If refreshing this page (Ctrl+R or Command+R) does not work, please verify that your computer is connected to the internet.</p></div><div class="loading-screen" style="position:relative"><div class="loading__content"><div class="round round-1"></div><div class="round round-2"></div><div class="round round-3"></div></div></div><div id="root-portal"></div></div><noscript>To use Mattermost, please enable JavaScript.</noscript></body></html>
```

3: make entry in windows host file of the domain

A:

```
# This is a sample HOSTS file used by Microsoft TCP/IP for Windows.
#
# This file contains the mappings of IP addresses to host names.
# Each
# entry should be kept on an individual line. The IP address should
# be placed in the first column followed by the corresponding host
# name.
# The IP address and the host name should be separated by at least
# one
# space.
#
# Additionally, comments (such as these) may be inserted on
# individual
# lines or following the machine name denoted by a '#' symbol.
#
# For example:
#
#       102.54.94.97       rhino.acme.com          # source server
#       38.25.63.10       x.acme.com              # x client host
#
# localhost name resolution is handled within DNS itself.
#
#       127.0.0.1         localhost
#       ::1               localhost
#       192.168.56.101    www.sampleinsite.com
```

4: domainname.com

A:

